

Gforth

for version 0.7.9'20250604, June 04, 2025

Neal Crook
Anton Ertl
David Kuehling
Bernd Paysan
Jens Wilke
Gerald Wodni

This manual is for Gforth (version 0.7.9'20250604, June 04, 2025), a fast and portable implementation of the Standard Forth language. It serves as reference manual, but it also contains an introduction to Forth and a Forth tutorial.

Authors: Bernd Paysan, Anton Ertl, Gerald Wodni, Neal Crook, David Kuehling, Jend Wilke Copyright © 1995, 1996, 1997, 1998, 2000, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 2023, 2024 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with no Invariant Sections, with the Front-Cover texts being “A GNU Manual,” and with the Back-Cover Texts as in (a) below. A copy of the license is included in the section entitled “GNU Free Documentation License.”

(a) The FSF’s Back-Cover Text is: “You have freedom to copy and modify this GNU Manual, like GNU software. Copies published by the Free Software Foundation raise funds for GNU development.”

Table of Contents

Preface

This manual documents Gforth. Some introductory material is provided for readers who are unfamiliar with Forth or who are migrating to Gforth from other Forth compilers. However, this manual is primarily a reference manual.

1 Goals of Gforth

The goal of the Gforth Project is to develop a standard model for Standard Forth. This can be split into several subgoals:

- Gforth should conform to the Forth Standard.
- It should be a model, i.e. it should define all the implementation-dependent things.
- It should become standard, i.e. widely accepted and used. This goal is the most difficult one.

To achieve these goals Gforth should be

- Similar to previous models (fig-Forth, F83)
- Powerful. It should provide for all the things that are considered necessary today and even some that are not yet considered necessary.
- Efficient. It should not get the reputation of being exceptionally slow.
- Free.
- Available on many machines/easy to port.

Have we achieved these goals?

Gforth conforms to the Forth-94 (ANS Forth) and Forth-2012 standards.

We have changed some of the internal data structures (in particular, the headers) over time, so Gforth does not provide the stability of implementation details that we originally aimed for; they were too constraining for a long-term project like Gforth. However, we still aim for a high level of stability.

Gforth is quite popular and is treated by some like a de-facto standard.

It has some similarities to and some differences from previous models.

It has powerful features, and the version 1.0 indicates that it can do everything (and more) that we originally envisioned. That does not mean that we will stop development.

We certainly have achieved and exceeded our execution speed goals (see [\[Performance\]](#), page [\[Performance\]](#))¹.

Gforth is free and available on many platforms.

1.1 Stability Goals

Programs that work on earlier versions of Gforth should also work on newer versions. However, there are some caveats:

Internal data structures (including the representation of code) of Gforth may change between versions, unless they are documented.

Moreover, we only feel obliged to keep standard words (i.e., with standard wordset names) and words documented as stable Gforth extensions (with wordset name `gforth` or `gforth-<version>`, see [\[Notation\]](#), page [\[Notation\]](#)). Other words may be removed in newer releases.

¹ However, in 1998 the bar was raised when the major commercial Forth vendors switched to native code compilers.

In particular, you may find a word by using `locate` or otherwise inspecting Gforth's source code. You can see the wordset in a comment right after the stack-effect comment. E.g., in

```
: execute-parsing ( ... addr u xt -- ... ) \ gforth
the wordset is gforth.
```

If there is no wordset for a word, it is an internal factor and may be removed in a future version. If the wordset is `gforth-experimental`, `gforth-internal`, or `gforth-obsolete`, the word may also be removed in a future version. In particular, `gforth-experimental` indicates that this is a supported word that we do not consider stable yet; `gforth-obsolete` indicates an intent to remove the word in the next version; and `gforth-internal` (or no wordset) indicates that we may remove the word as soon as we no longer use it in Gforth.

If you want to use a particular word that is not marked as stable, please let us know, and we will consider to add the word as stable word (or we may suggest an alternative to using this word).

2 Gforth Environment

Note: ultimately, the Gforth man page will be auto-generated from the material in this chapter.

For related information about the creation of images see [\[Image Files\]](#), page [\[undefined\]](#).

2.1 Invoking Gforth

Gforth is made up of two parts; an executable “engine” (named `gforth` or `gforth-fast`) and an image file. To start it, you will usually just say `gforth` – this automatically loads the default image file `gforth.fi`. In many other cases the default Gforth image will be invoked like this:

```
gforth [file | -e forth-code] ...
```

This interprets the contents of the files and the Forth code in the order they are given.

In addition to the `gforth` engine, there is also an engine called `gforth-fast`, which is faster, but gives less informative error messages (see [\[Error messages\]](#), page [\[undefined\]](#)) and may catch some errors (in particular, stack underflows and integer division errors) later or not at all. You should use it for debugged, performance-critical programs.

Moreover, there is an engine called `gforth-itc`, which is useful in some backwards-compatibility situations (see [\[Direct or Indirect Threaded?\]](#), page [\[undefined\]](#)).

In general, the command line looks like this:

```
gforth[-fast] [engine options] [image options]
```

The engine options must come before the rest of the command line. They are:

`--image-file file`

`-i file` Loads the Forth image *file* instead of the default `gforth.fi` (see [\[Image Files\]](#), page [\[undefined\]](#)).

`--apl-image file`

Loads the image *file* and leaves all further command-line arguments to the image (instead of processing them as engine options). This is useful for building executable application images on Unix, built with `gforthmi --application`

`--no-0rc` Do not load `~/config/gforthrc0` nor the file specified by `GFORTH_ENV`.

`--path path`

`-p path` Uses *path* for searching the image file and Forth source code files instead of the default in the environment variable `GFORTHPATH` or the path specified at installation time and the working directory `.` (e.g., `/usr/local/share/gforth/0.2.0:.`). A path is given as a list of directories, separated by `‘:’` (previous versions had `‘;’` for other OSes, but since Cygwin now only accepts `/cygdrive/<letter>`, and we dropped support for OS/2 and MS-DOS, it is `‘:’` everywhere).

```

--dictionary-size size
-m size      Allocate size space for the Forth dictionary space instead of using the default
               specified in the image (default: 8M). The size specification for this and subse-
               quent options consists of an integer and a unit (e.g., 1G). The unit can be one
               of b (bytes), e (element size, in this case Cells), k (kilobytes), M (Megabytes), G
               (Gigabytes), and T (Terabytes). If no unit is specified, e is used.

--data-stack-size size
-d size      Allocate size space for the data stack instead of using the default specified in
               the image (default: 16K).

--return-stack-size size
-r size      Allocate size space for the return stack instead of using the default specified in
               the image (default: 15K).

--fp-stack-size size
-f size      Allocate size space for the floating point stack instead of using the default
               specified in the image (default: 15.5K). In this case the unit specifier e refers
               to floating point numbers.

--locals-stack-size size
-l size      Allocate size space for the locals stack instead of using the default specified in
               the image (default: 14.5K).

--map_32bit
               Allocate the dictionary and some other areas in the lower 2GB of the address
               space, if possible. The purpose of this option is debugging convenience.

--vm-commit
               Normally, Gforth tries to start up even if there is not enough virtual memory
               for the dictionary and the stacks (using MAP_NORESERVE on OSs that support
               it); so you can ask for a really big dictionary and/or stacks, and as long as you
               don't use more virtual memory than is available, everything will be fine (but if
               you use more, processes get killed). With this option you just use the default
               allocation policy of the OS; for OSs that don't overcommit (e.g., Solaris), this
               means that you cannot and should not ask for as big dictionary and stacks, but
               once Gforth successfully starts up, out-of-memory won't kill it.

--help
-h           Print a message about the command-line options

--version
-v           Print version and exit

--diag
-D           Checks for and reports some performance problems.

--debug
             Print some information useful for debugging on startup.

--debug-mcheck
             Try to find and report erroneous usage of allocate, free, and the C functions
             malloc(), free(), etc.

```


- offset-image**
Start the dictionary at a slightly different position than would be used otherwise (useful for creating data-relocatable images, see [\[Data-Relocatable Image Files\]](#), page [\[undefined\]](#)).
- no-offset-im**
Start the dictionary at the normal position.
- clear-dictionary**
Initialize all bytes in the dictionary to 0 before loading the image (see [\[Data-Relocatable Image Files\]](#), page [\[undefined\]](#)).
- die-on-signal [number]**
Normally Gforth handles most signals (e.g., the user interrupt SIGINT, or the segmentation violation SIGSEGV) by translating it into a Forth **THROW**. With this option, Gforth exits if it receives such a signal. This option is useful when the engine and/or the image might be severely broken (such that it causes another signal before recovering from the first); this option avoids endless loops in such cases. The optional number set the number of signals to be handled; only the last one will cause Gforth to exit.
- ignore-async-signals**
Ignore asynchronous signals (e.g., SIGINT generated with **Ctrl-c**).

2.1.1 Code generation options

- no-dynamic**
- dynamic**
Disable or enable dynamic superinstructions with replication (see [\[Dynamic Superinstructions\]](#), page [\[undefined\]](#)). Default enabled.
- no-dynamic-image**
Disable dynamic native-code generation when loading the Gforth image, but generate dynamic native code afterwards. This option is useful when debugging Gforth's code generator.
- no-super**
Disable dynamic superinstructions, use just dynamic replication; this is useful if you want to patch threaded code (see [\[Dynamic Superinstructions\]](#), page [\[undefined\]](#)).
- ss-number=*N***
Use only the first *N* static superinstructions compiled into the engine (default: use them all; note that only **gforth-fast** has any). This option is useful for measuring the performance impact of static superinstructions.
- ss-min-codesize**
- ss-min-ls**
- ss-min-lsu**
- ss-min-nexts**
Use specified metric for determining the cost of a primitive or static superinstruction for static superinstruction selection. **Codesize** is the native code size

of the primitive or static superinstruction, **ls** is the number of loads and stores, **lsu** is the number of loads, stores, and updates, and **nexts** is the number of dispatches (not taking dynamic superinstructions into account), i.e. every primitive or static superinstruction has cost 1. Default: **codesize** if you use dynamic code generation, otherwise **nexts**.

--ss-greedy

This option is useful for measuring the performance impact of static superinstructions. By default, an optimal shortest-path algorithm is used for selecting static superinstructions. With **--ss-greedy** this algorithm is modified to assume that anything after the static superinstruction currently under consideration is not combined into static superinstructions. With **--ss-min-nexts** this produces the same result as a greedy algorithm that always selects the longest superinstruction available at the moment. E.g., if there are superinstructions AB and BCD, then for the sequence A B C D the optimal algorithm will select A BCD and the greedy algorithm will select AB C D.

--opt-ip-updates=n

Set the level of IP-update optimization (default: 31 (7+3*8)). *n* is computed as $n1 + 8 * n2$.

n1 indicates the use of IP-update optimization in straight-line code: 0 means no IP-update optimization, 1 combines IP-update optimizations of primitives without inline arguments, 2 also eliminates the dead IP updates of **;s**, **execute-s** and *fast-throw*, >2 eliminates the IP updates in front of several frequently-used primitives with inline arguments.

n2 is the number of ip-updates that can replace a load in a backwards or unconditional branch; for conditional forward branches only *n2*/2 ip-updates replace a load (to avoid too many additional updates in the fall-through path).

--code-block-size=size

Size of native-code blocks (default: 2M). Gforth allocates as many blocks of this size as necessary.

--print-metrics

On exit from Gforth: Print some metrics used during static superinstruction selection: **code size** is the actual size of the dynamically generated code. **Metric codesize** is the sum of the codesize metrics as seen by static superinstruction selection; there is a difference from **code size**, because not all primitives and static superinstructions are compiled into dynamically generated code, and because of markers. The other metrics correspond to the **ss-min-...** options. This option is useful for evaluating the effects of the **--ss-...** options.

--print-prims

When exiting GforthL: Print the primitives with static usage counts. E.g., one line might look like:

```
?branch      1-1  0   21 1575   73 0x5573e4048c33 len= 4+ 25+ 3 send=0■
```

The columns are, from left to right: name of the primitive, stack-caching state transition (from a state with 1 stack item in a register to the same state in the example), IP offset for this version of the primitive (0 for most primitives,

but, e.g., for `?branch` there are also versions with 0-zero offset), index of the primitive, index of the corresponding branch-to-IP variant (in case of a branch), static number of occurrences of the primitive in the loaded/compiled code, address of the code of the primitive (or `(nil)` if the primitive is not relocatable), length of the parts of this code: `ip-update+main+dispatch`, and whether the primitive ends a superblock (i.e., an unconditional branch or the like).

`--print-nonreloc`

When starting Gforth: Print the non-relocatable primitives.

`--print-sequences`

When loading the image: For each superblock in the image, print the sequence of primitives.

`--tpa-noautomaton`

`--tpa-noequiv`

These options are about using an automaton for speeding up startup and compilation, in particular the shortest-path algorithm used for selecting static superinstructions and stack caching variants; `tpa` stands for “tree-parsing automaton” (although we only have sequences, not trees). In the `gforth` engine the default is to use an automaton with state equivalence (state equivalence reduces the number of states compared to having one state for every sequence prefix), which is the fastest option and requires the least memory.

With static superinstructions the automaton does not work correctly, so Gforth falls back to `--tpa-noautomaton` in that case unless you ask for `--tpa-noequiv` (`gforth-fast` uses static superinstructions and therefore `--tpa-noautomaton` by default).

`--tpa-noequiv` turns off state equivalence, which costs memory and compiles a little slower than using an automaton.

`--tpa-noautomaton` turns off using the automaton. This consumes quite a bit more compile time, and should in theory use less memory than using an automaton, but apparently there is a bug in Gforth, and it consumes more memory.

The following shows the startup speed and memory consumption of Gforth 0.7.9_20240821 run with `gforth-fast -e bye` (plus the options given in the table) on a Core-i5 6600K (Skylake):

cycles	instructions	KB(RSS)	other options
23_309_239	43_534_167	9228	<code>--ss-number=0</code>
26_399_456	51_895_687	11316	<code>--ss-number=0 --tpa-noequiv</code>
40_427_672	93_709_354	10988	<code>--ss-number=0 --tpa-noautomaton</code>
27_599_969	53_126_621	11320	
27_732_944	53_128_381	11320	<code>--tpa-noequiv</code>
42_960_520	95_466_840	11044	<code>--tpa-noautomaton</code>

`--tpa-trace`

This option produces data about the number of states generated during startup and compilation.

As explained above, the image-specific command-line arguments for the default image `gforth.fi` consist of a sequence of filenames and `-e forth-code` options that are interpreted in the sequence in which they are given. The `-e forth-code` or `--evaluate forth-code` option evaluates the Forth code. This option takes only one argument; if you want to evaluate more Forth words, you have to quote them or use `-e` several times. To exit after processing the command line (instead of entering interactive mode) append `-e bye` to the command line. You can also process the command-line arguments with a Forth program (see [\(undefined\)](#) [OS command line arguments], page [\(undefined\)](#)).

If you have several versions of Gforth installed, `gforth` will invoke the version that was installed last. `gforth-<version>` invokes a specific version. If your environment contains the variable `GFORTH_PATH`, you may want to override it by using the `--path` option.

On startup, before processing any of the image option, the user initialization file is included, if it exists. The user initialization file is `~/.config/gforthrc0`, or, if the environment variable `GFORTH_ENV` is set, it contains the name of the user initialization file. You can suppress loading this file with by setting `GFORTH_ENV` to `off`, or with the option `--no-0rc`.

After processing all the image options and just before printing the boot message, the user initialization file `~/.config/gforthrc` from your home directory is included, unless the option `--no-rc` is given.

Warning levels can be set with

- `-W` Turn off warnings
- `-Won` Turn on warnings (level 1)
- `-Wall` Turn on beginner warnings (level 2)
- `-Wpedantic` Turn on pedantic warnings (level 3)
- `-Werror` Turn warnings into errors (level 4)

2.2 Leaving Gforth

You can leave Gforth by typing `bye` or `Ctrl-d` (at the start of a line) or (if you invoked Gforth with the `--die-on-signal` option) `Ctrl-c`. When you leave Gforth, all of your definitions and data are discarded. For ways of saving the state of the system before leaving Gforth see [\(undefined\)](#) [Image Files], page [\(undefined\)](#).

`bye` (-) tools-ext “bye”

Exit Gforth (with exit status 0).

2.3 Help on Gforth

Gforth has a simple, text-based online help system.

`help` ("rest-of-line" -) gforth-1.0 “help”

If no name is given, show basic help. If a documentation node name is given followed by `::`, show the start of the node. If the name of a word is given, show the documentation of the word if it exists, or its source code if not. If something else is given that is recognized,

shows help on the recognizer. You can then use the same keys and commands as after using `locate` (see [\[Locating source code definitions\]](#), page [\[undefined\]](#)).

`authors (-) gforth-1.0 “authors”`

show the list of authors

`license (-) gforth-0.2 “license”`

print the license statement

2.4 Command-line editing

Gforth maintains a history file that records every line that you type to the text interpreter. This file is preserved between sessions, and is used to provide a command-line recall facility; if you type `Ctrl-P` repeatedly you can recall successively older commands from this (or previous) session(s). The full list of command-line editing facilities is:

- `Ctrl-p` (“previous”) (or up-arrow) to recall successively older lines from the history buffer.
- `Ctrl-n` (“next”) (or down-arrow) to recall successively newer lines from the history buffer. If you moved to an older line earlier and gave it to Gforth for text-interpretation, asking for the next line as the first editing command gives you the next line after the one you selected last time.
- `Ctrl-f` (or right-arrow) to move the cursor right, non-destructively.
- `Ctrl-b` (or left-arrow) to move the cursor left, non-destructively.
- `Ctrl-h` (backspace) to delete the character to the left of the cursor, closing up the line.
- `Ctrl-k` to delete (“kill”) from the cursor to the end of the line.
- `Ctrl-a` to move the cursor to the start of the line.
- `Ctrl-e` to move the cursor to the end of the line.
- `RET` (`Ctrl-m`) or `LFD` (`Ctrl-j`) to submit the current line.
- `TAB` to step through all possible full-word completions of the word currently being typed.
- `Ctrl-d` on an empty line to terminate Gforth (gracefully, using `bye`).
- `Ctrl-x` (or `Ctrl-d` on a non-empty line) to delete the character under the cursor.

When editing, displayable characters are inserted to the left of the cursor position; the line is always in “insert” (as opposed to “overstrike”) mode.

On Unix systems, the history file is `$HOME/.local/share/gforth/history` by default¹. You can find out the name and location of your history file using:

```
history-file type \ Unix-class systems
```

```
history-file type \ Other systems
```

```
history-dir type
```

If you enter long definitions by hand, you can use a text editor to paste them out of the history file into a Forth source file for reuse at a later time.

Gforth never trims the size of the history file, so you should do this periodically, if necessary.

¹ i.e. it is stored in the user’s home directory.

2.5 Environment variables

Gforth uses these environment variables:

- **GFORTHIST** – (Unix systems only) specifies the path for the history file `.gforth-history`. Default: `$HOME/.local/share/gforth/history`.
- **GFORTHPATH** – specifies the path used when searching for the gforth image file and for Forth source-code files (usually `.`, the current working directory). Path separator is `:`, a typical path would be `/usr/local/share/gforth/1.0:..`
- **LANG** – see **LC_CTYPE**
- **LC_ALL** – see **LC_CTYPE**
- **LC_CTYPE** – If this variable contains “UTF-8” on Gforth startup, Gforth uses the UTF-8 encoding for strings internally and expects its input and produces its output in UTF-8 encoding, otherwise the encoding is 8bit (see `<undefined> [Xchars and Unicode]`, page `<undefined>`). If this environment variable is unset, Gforth looks in **LC_ALL**, and if that is unset, in **LANG**.
- **GFORTHSYSTEMPREFIX** – specifies what to prepend to the argument of `system` before passing it to C’s `system()`. Default: `./$COMSPEC /c` on Windows, `""` on other OSs. The prefix and the command are directly concatenated, so if a space between them is necessary, append it to the prefix.
- **GFORTH** – used by `gforthmi`, See `<undefined> [gforthmi]`, page `<undefined>`.
- **GFORTHD** – used by `gforthmi`, See `<undefined> [gforthmi]`, page `<undefined>`.
- **TMP, TEMP** - (non-Unix systems only) used as a potential location for the history file.

All the Gforth environment variables default to sensible values if they are not set.

2.6 Gforth files

When you install Gforth on a Unix system, it installs files in these locations by default:

- `/usr/local/bin/gforth`
- `/usr/local/bin/gforthmi`
- `/usr/local/man/man1/gforth.1` - man page.
- `/usr/local/info` - the Info version of this manual.
- `/usr/local/lib/gforth/<version>/...` - Gforth `.fi` files.
- `/usr/local/share/gforth/<version>/TAGS` - Emacs TAGS file.
- `/usr/local/share/gforth/<version>/...` - Gforth source files.
- `.../emacs/site-lisp/gforth.el` - Emacs gforth mode.

You can select different places for installation by using `configure` options (listed with `configure --help`).

2.7 Gforth in pipes

Gforth can be used in pipes created elsewhere (described in the following). It can also create pipes on its own (see `<undefined> [Pipes]`, page `<undefined>`).

If you pipe into Gforth, your program should read with `read-file` or `read-line` from `stdin` (see `<undefined> [General files]`, page `<undefined>`). `Key` does not recognize the end

of input. Words like **accept** echo the input and are therefore usually not useful for reading from a pipe. You have to invoke the Forth program with an OS command-line option, as you have no chance to use the Forth command line (the text interpreter would try to interpret the pipe input).

You can output to a pipe with **type**, **emit**, **cr** etc.

When you write to a pipe that has been closed at the other end, Gforth receives a SIGPIPE signal (“pipe broken”). Gforth translates this into the exception **broken-pipe-error**. If your application does not catch that exception, the system catches it and exits, usually silently (unless you were working on the Forth command line; then it prints an error message and exits). This is usually the desired behaviour.

If you do not like this behaviour, you have to catch the exception yourself, and react to it.

Here’s an example of an invocation of Gforth that is usable in a pipe:

```
gforth -e ": foo begin pad dup 10 stdin read-file throw dup while \
  type repeat ; foo bye"
```

This example just copies the input verbatim to the output. A very simple pipe containing this example looks like this:

```
cat startup.fs |
gforth -e ": foo begin pad dup 80 stdin read-file throw dup while \
  type repeat ; foo bye"|
head
```

Pipes involving Gforth’s **stderr** output do not work.

2.8 Startup speed

If Gforth is used for CGI scripts or in shell scripts, its startup speed may become a problem. On a 3GHz Core 2 Duo E8400 under 64-bit Linux 2.6.27.8 with libc-2.7, **gforth-fast -e bye** takes 13.1ms user and 1.2ms system time (**gforth -e bye** is faster on startup with about 3.4ms user time and 1.2ms system time, because it subsumes some of the options discussed below).

If startup speed is a problem, you may consider the following ways to improve it; or you may consider ways to reduce the number of startups (for example, by using Fast-CGI). Note that the first steps below improve the startup time at the cost of run-time (including compile-time), so whether they are profitable depends on the balance of these times in your application.

An easy step that influences Gforth startup speed is the use of a number of options that increase run-time, but decrease image-loading time.

The first of these that you should try is **--ss-number=0 --ss-states=1** because this option buys relatively little run-time speedup and costs quite a bit of time at startup. **gforth-fast --ss-number=0 --ss-states=1 -e bye** takes about 2.8ms user and 1.5ms system time.

The next option is **--no-dynamic** which has a substantial impact on run-time (about a factor of 2-4 on several platforms), but still makes startup speed a little faster: **gforth-fast --ss-number=0 --ss-states=1 --no-dynamic -e bye** consumes about 2.6ms user and 1.2ms system time.

If the script you want to execute contains a significant amount of code, it may be profitable to compile it into the image to avoid the cost of compiling it at startup time.

3 Forth Tutorial

The difference of this chapter from the Introduction (see [\[Introduction\]](#), page [\[undefined\]](#)) is that this tutorial is more fast-paced, should be used while sitting in front of a computer, and covers much more material, but does not explain how the Forth system works.

This tutorial can be used with any Standard-compliant Forth; any Gforth-specific features are marked as such and you can skip them if you work with another Forth. This tutorial does not explain all features of Forth, just enough to get you started and give you some ideas about the facilities available in Forth. Read the rest of the manual when you are through this.

The intended way to use this tutorial is that you work through it while sitting in front of the console, take a look at the examples and predict what they will do, then try them out; if the outcome is not as expected, find out why (e.g., by trying out variations of the example), so you understand what's going on. There are also some assignments that you should solve.

This tutorial assumes that you have programmed before and know what, e.g., a loop is.

3.1 Starting Gforth

You can start Gforth by typing its name:

```
gforth
```

That puts you into interactive mode; you can leave Gforth by typing `bye`. While in Gforth, you can edit the command line and access the command line history with cursor keys, similar to `bash`.

3.2 Syntax

A *word* is a sequence of arbitrary characters (except white space). Words are separated by white space. E.g., each of the following lines contains exactly one word:

```
word
!@#$$%^&*()
1234567890
5!a
```

A frequent beginner's error is to leave out necessary white space, resulting in an error like `'Undefined word'`; so if you see such an error, check if you have put spaces wherever necessary.

```
." hello, world" \ correct
."hello, world" \ gives an "Undefined word" error
```

Gforth and most other Forth systems ignore differences in case (they are case-insensitive), i.e., `'word'` is the same as `'Word'`. If your system is case-sensitive, you may have to type all the examples given here in upper case.

3.3 Crash Course

Forth does not prevent you from shooting yourself in the foot. Let's try a few ways to crash Gforth:

```
0 0 !
here execute
' catch >body 20 erase abort
' (quit1) >body 20 erase
```

The last two examples are guaranteed to destroy important parts of Gforth (and most other systems), so you better leave Gforth afterwards (if it has not finished by itself). On some systems you may have to kill gforth from outside (e.g., in Unix with `kill`).

You will find out later what these lines do and then you will get an idea why they produce crashes.

Now that you know how to produce crashes (and that there's not much to them), let's learn how to produce meaningful programs.

3.4 Stack

The most obvious feature of Forth is the stack. When you type in a number, it is pushed on the stack. You can display the contents of the stack with `.s`.

```
1 2 .s
3 .s
```

`.s` displays the top-of-stack to the right, i.e., the numbers appear in `.s` output as they appeared in the input.

You can print the top element of the stack with `..`

```
1 2 3 . . .
```

In general, words consume their stack arguments (`.s` is an exception).

Assignment: What does the stack contain after `5 6 7 .?`

3.5 Arithmetics

The words `+`, `-`, `*`, `/`, and `mod` always operate on the top two stack items:

```
2 2 .s
+ .s
.
2 1 - .
7 3 mod .
```

The operands of `-`, `/`, and `mod` are in the same order as in the corresponding infix expression (this is generally the case in Forth).

Parentheses are superfluous (and not available), because the order of the words unambiguously determines the order of evaluation and the operands:

```
3 4 + 5 * .
3 4 5 * + .
```

Assignment: What are the infix expressions corresponding to the Forth code above? Write $6-7*8+9$ in Forth notation¹.

To change the sign, use **negate**:

```
2 negate .
```

Assignment: Convert $-(-3)*4-5$ to Forth.

/mod performs both **/** and **mod**.

```
7 3 /mod . .
```

Reference: [\[Arithmetic\]](#), page [\[undefined\]](#).

3.6 Stack Manipulation

Stack manipulation words rearrange the data on the stack.

```
1 .s drop .s
1 .s dup .s drop drop .s
1 2 .s over .s drop drop drop
1 2 .s swap .s drop drop
1 2 3 .s rot .s drop drop drop
```

These are the most important stack manipulation words. There are also variants that manipulate twice as many stack items:

```
1 2 3 4 .s 2swap .s 2drop 2drop
```

Two more stack manipulation words are:

```
1 2 .s nip .s drop
1 2 .s tuck .s 2drop drop
```

Assignment: Replace **nip** and **tuck** with combinations of other stack manipulation words.

Given:	How do you get:
1 2 3	3 2 1
1 2 3	1 2 3 2
1 2 3	1 2 3 3
1 2 3	1 3 3
1 2 3	2 1 3
1 2 3 4	4 3 2 1
1 2 3	1 2 3 1 2 3
1 2 3 4	1 2 3 4 1 2
1 2 3	
1 2 3	1 2 3 4
1 2 3	1 3

```
5 dup * .
```

Assignment: Write 17^3 and 17^4 in Forth, without writing 17 more than once. Write a piece of Forth code that expects two numbers on the stack (a and b , with b on top) and computes $(a-b)(a+1)$.

Reference: [\[Stack Manipulation\]](#), page [\[undefined\]](#).

¹ This notation is also known as Postfix or RPN (Reverse Polish Notation).

3.7 Using files for Forth code

While working at the Forth command line is convenient for one-line examples and short one-off code, you probably want to store your source code in files for convenient editing and persistence. You can use your favourite editor (Gforth includes Emacs support, see [\[Emacs and Gforth\]](#), page [\[undefined\]](#)) to create *file.fs* and use

```
s" file.fs" included
```

to load it into your Forth system. The file name extension I use for Forth files is `‘.fs’`.

You can easily start Gforth with some files loaded like this:

```
gforth file1.fs file2.fs
```

If an error occurs during loading these files, Gforth terminates, whereas an error during `INCLUDED` within Gforth usually gives you a Gforth command line. Starting the Forth system every time gives you a clean start every time, without interference from the results of earlier tries.

I often put all the tests in a file, then load the code and run the tests with

```
gforth code.fs tests.fs -e bye
```

(often by performing this command with `C-x C-e` in Emacs). The `-e bye` ensures that Gforth terminates afterwards so that I can restart this command without ado.

The advantage of this approach is that the tests can be repeated easily every time the program is changed, making it easy to catch bugs introduced by the change.

Reference: [\[undefined\]](#) [\[Forth source files\]](#), page [\[undefined\]](#).

3.8 Comments

```
\ That's a comment; it ends at the end of the line
( Another comment; it ends here: ) .s
```

`\` and `(` are ordinary Forth words and therefore have to be separated with white space from the following text.

```
\This gives an "Undefined word" error
```

The first `)` ends a comment started with `(`, so you cannot nest `(`-comments; and you cannot comment out text containing a `)` with `(...)2`.

I use `\`-comments for descriptive text and for commenting out code of one or more line; I use `(`-comments for describing the stack effect, the stack contents, or for commenting out sub-line pieces of code.

The Emacs mode `gforth.el` (see [\[undefined\]](#) [\[Emacs and Gforth\]](#), page [\[undefined\]](#)) supports these uses by commenting out a region with `C-x \`, uncommenting a region with `C-u C-x \`, and filling a `\`-commented region with `M-q`.

Reference: [\[undefined\]](#) [\[Comments\]](#), page [\[undefined\]](#).

² therefore it's a good idea to avoid `)` in word names.

3.9 Colon Definitions

are similar to procedures and functions in other programming languages.

```
: squared ( n -- n^2 )
    dup * ;
5 squared .
7 squared .
```

: starts the colon definition; its name is **squared**. The following comment describes its stack effect. The words **dup *** are not executed, but compiled into the definition. **;** ends the colon definition.

The newly-defined word can be used like any other word, including using it in other definitions:

```
: cubed ( n -- n^3 )
    dup squared * ;
-5 cubed .
: fourth-power ( n -- n^4 )
    squared squared ;
3 fourth-power .
```

Assignment: Write colon definitions for **nip**, **tuck**, **negate**, and **/mod** in terms of other Forth words, and check if they work (hint: test your tests on the originals first). Don't let the 'redefined'-Messages spook you, they are just warnings.

Reference: [⟨undefined⟩ \[Colon Definitions\]](#), page [⟨undefined⟩](#).

3.10 Decompilation

You can decompile colon definitions with **see**:

```
see squared
see cubed
```

In Gforth **see** shows you a reconstruction of the source code from the executable code. Informations that were present in the source, but not in the executable code, are lost (e.g., comments).

You can also decompile the predefined words:

```
see .
see +
```

3.11 Stack-Effect Comments

By convention the comment after the name of a definition describes the stack effect: The part in front of the **--** describes the state of the stack before the execution of the definition, i.e., the parameters that are passed into the colon definition; the part behind the **--** is the state of the stack after the execution of the definition, i.e., the results of the definition. The stack comment only shows the top stack items that the definition accesses and/or changes.

You should put a correct stack effect on every definition, even if it is just **(--)**. You should also add some descriptive comment to more complicated words (I usually do this in the lines following **:**). If you don't do this, your code becomes unreadable (because you have to work through every definition before you can understand any).

Assignment: The stack effect of `swap` can be written like this: `x1 x2 -- x2 x1`. Describe the stack effect of `-`, `drop`, `dup`, `over`, `rot`, `nip`, and `tuck`. Hint: When you are done, you can compare your stack effects to those in this manual (see [\[Word Index\]](#), page [\[undefined\]](#)).

Sometimes programmers put comments at various places in colon definitions that describe the contents of the stack at that place (stack comments); i.e., they are like the first part of a stack-effect comment. E.g.,

```
: cubed ( n -- n^3 )
  dup squared ( n n^2 ) * ;
```

In this case the stack comment is pretty superfluous, because the word is simple enough. If you think it would be a good idea to add such a comment to increase readability, you should also consider factoring the word into several simpler words (see [\[Factoring\]](#), page [\[undefined\]](#)), which typically eliminates the need for the stack comment; however, if you decide not to refactor it, then having such a comment is better than not having it.

The names of the stack items in stack-effect and stack comments in the standard, in this manual, and in many programs specify the type through a type prefix, similar to Fortran and Hungarian notation. The most frequent prefixes are:

<code>n</code>	signed integer
<code>u</code>	unsigned integer
<code>c</code>	character
<code>f</code>	Boolean flags, i.e. <code>false</code> or <code>true</code> .
<code>a-addr, a-</code>	Cell-aligned address
<code>c-addr, c-</code>	Char-aligned address (note that a <code>Char</code> may have two bytes in Windows NT)
<code>xt</code>	Execution token, same size as <code>Cell</code>
<code>w, x</code>	Cell, can contain an integer or an address. It usually takes 32, 64 or 16 bits (depending on your platform and Forth system). A cell is more commonly known as machine word, but the term <i>word</i> already means something different in Forth.
<code>d</code>	signed double-cell integer
<code>ud</code>	unsigned double-cell integer
<code>r</code>	Float (on the FP stack)

You can find a more complete list in [\[Notation\]](#), page [\[undefined\]](#).

Assignment: Write stack-effect comments for all definitions you have written up to now.

3.12 Types

In Forth the names of the operations are not overloaded; so similar operations on different types need different names; e.g., `+` adds integers, and you have to use `f+` to add floating-point numbers. The following prefixes are often used for related operations on different types:

<code>(none)</code>	signed integer
<code>u</code>	unsigned integer
<code>c</code>	character
<code>d</code>	signed double-cell integer
<code>ud, du</code>	unsigned double-cell integer
<code>2</code>	two cells (not-necessarily double-cell numbers)
<code>m, um</code>	mixed single-cell and double-cell operations
<code>f</code>	floating-point (note that in stack comments <code>'f'</code> represents flags, and <code>'r'</code> represents FP numbers; also, you need to include the exponent part in literal FP numbers, see [Floating Point Tutorial] , page [undefined]).

If there are no differences between the signed and the unsigned variant (e.g., for `+`), there is only the prefix-less variant.

Forth does not perform type checking, neither at compile time, nor at run time. If you use the wrong operation, the data are interpreted incorrectly:

```
-1 u.
```

If you have only experience with type-checked languages until now, and have heard how important type-checking is, don't panic! In my experience (and that of other Forthers), type errors in Forth code are usually easy to find (once you get used to it), the increased vigilance of the programmer tends to catch some harder errors in addition to most type errors, and you never have to work around the type system, so in most situations the lack of type-checking seems to be a win (projects to add type checking to Forth have not caught on).

3.13 Factoring

If you try to write longer definitions, you will soon find it hard to keep track of the stack contents. Therefore, good Forth programmers tend to write only short definitions (e.g., three lines). The art of finding meaningful short definitions is known as factoring (as in factoring polynomials).

Well-factored programs offer additional advantages: smaller, more general words, are easier to test and debug and can be reused more and better than larger, specialized words.

So, if you run into difficulties with stack management, when writing code, try to define meaningful factors for the word, and define the word in terms of those. Even if a factor contains only two words, it is often helpful.

Good factoring is not easy, and it takes some practice to get the knack for it; but even experienced Forth programmers often don't find the right solution right away, but only when rewriting the program. So, if you don't come up with a good solution immediately, keep trying, don't despair.

3.14 Designing the stack effect

In other languages you can use an arbitrary order of parameters for a function; and since there is only one result, you don't have to deal with the order of results, either.

In Forth (and other stack-based languages, e.g., PostScript) the parameter and result order of a definition is important and should be designed well. The general guideline is to design the stack effect such that the word is simple to use in most cases, even if that complicates the implementation of the word. Some concrete rules are:

- Words consume all of their parameters (e.g., `.`).
- If there is a convention on the order of parameters (e.g., from mathematics or another programming language), stick with it (e.g., `-`).
- If one parameter usually requires only a short computation (e.g., it is a constant), pass it on the top of the stack. Conversely, parameters that usually require a long sequence of code to compute should be passed as the bottom (i.e., first) parameter. This makes the code easier to read, because the reader does not need to keep track of the bottom item through a long sequence of code (or, alternatively, through stack manipulations). E.g., `!` (store, see `<undefined>` [Memory], page `<undefined>`) expects the address on top of the stack because it is usually simpler to compute than the stored value (often the address is just a variable).
- Similarly, results that are usually consumed quickly should be returned on the top of stack, whereas a result that is often used in long computations should be passed as bottom result. E.g., the file words like `open-file` return the error code on the top of stack, because it is usually consumed quickly by `throw`; moreover, the error code has to be checked before doing anything with the other results.

These rules are just general guidelines, don't lose sight of the overall goal to make the words easy to use. E.g., if the convention rule conflicts with the computation-length rule, you might decide in favour of the convention if the word will be used rarely, and in favour of the computation-length rule if the word will be used frequently (because with frequent use the cost of breaking the computation-length rule would be quite high, and frequent use makes it easier to remember an unconventional order).

3.15 Local Variables

You can define local variables (*locals*) in a colon definition:

```
: swap { a b -- b a }
  b a ;
1 2 swap .s 2drop
```

(If your Forth system does not support this syntax, include `compat/anslocal.fs` first).

In this example `{ a b -- b a }` is the locals definition; it takes two cells from the stack, puts the top of stack in `b` and the next stack element in `a`. `--` starts a comment ending with `}`. After the locals definition, using the name of the local will push its value on the stack. You can omit the comment part (`-- b a`):

```
: swap ( x1 x2 -- x2 x1 )
  { a b } b a ;
```


In Gforth you can have several locals definitions, anywhere in a colon definition; in contrast, in a standard program you can have only one locals definition per colon definition, and that locals definition must be outside any control structure.

With locals you can write slightly longer definitions without running into stack trouble. However, I recommend trying to write colon definitions without locals for exercise purposes to help you gain the essential factoring skills.

Assignment: Rewrite your definitions until now with locals

Reference: [\[Locals\]](#), page [\[undefined\]](#).

3.16 Conditional execution

In Forth you can use control structures only inside colon definitions. An **if**-structure looks like this:

```
: abs ( n1 -- +n2 )
  dup 0 < if
    negate
  endif ;
5 abs .
-5 abs .
```

if takes a flag from the stack. If the flag is non-zero (true), the following code is performed, otherwise execution continues after the **endif** (or **else**). **<** compares the top two stack elements and produces a flag:

```
1 2 < .
2 1 < .
1 1 < .
```

Actually the standard name for **endif** is **then**. This tutorial presents the examples using **endif**, because this is often less confusing for people familiar with other programming languages where **then** has a different meaning. If your system does not have **endif**, define it with

```
: endif postpone then ; immediate
```

You can optionally use an **else**-part:

```
: min ( n1 n2 -- n )
  2dup < if
    drop
  else
    nip
  endif ;
2 3 min .
3 2 min .
```

Assignment: Write **min** without **else**-part (hint: what's the definition of **nip**?).

Reference: [\[Selection\]](#), page [\[undefined\]](#).

3.17 Flags and Comparisons

In a false-flag all bits are clear (0 when interpreted as integer). In a canonical true-flag all bits are set (-1 as a two's-complement signed integer); in many contexts (e.g., `if`) any non-zero value is treated as true flag.

```
false .
true .
true hex u. decimal
```

Comparison words produce canonical flags:

```
1 1 = .
1 0= .
0 1 < .
0 0 < .
-1 1 u< . \ type error, u< interprets -1 as large unsigned number
-1 1 < .
```

Gforth supports all combinations of the prefixes `0 u d d0 du f f0` (or none) and the comparisons `= <> < > <= >=`. Only a part of these combinations are standard (for details see the standard, [\[Numeric comparison\]](#), page [\[undefined\]](#), [\[Floating Point\]](#), page [\[undefined\]](#), or [\[Word Index\]](#), page [\[undefined\]](#)).

You can use `and` or `xor` or `invert` as operations on canonical flags. Actually they are bitwise operations:

```
1 2 and .
1 2 or .
1 3 xor .
1 invert .
```

You can convert a zero/non-zero flag into a canonical flag with `0<>` (and complement it on the way with `0=`; indeed, it is more common to use `0=` instead of `invert` for canonical flags).

```
1 0= .
1 0<> .
```

While you can use `if` without `0<>` to test for zero/non-zero, you sometimes need to use `0<>` when combining zero/non-zero values with `and` or `xor` because of their bitwise nature. The simplest, least error-prone, and probably clearest way is to use `0<>` in all these cases, but in some cases you can use fewer `0<>`s. Here are some stack effects, where *fc* represents a canonical flag, and *fz* represents zero/non-zero (every *fc* also works as *fz*):

```
or ( fz1 fz2 -- fz3 )
and ( fz1 fc -- fz2 )
and ( fc fz1 -- fz2 )
```

So, if you see code like this:

```
( n1 n2 ) 0<> and if
```

This tests whether *n1* and *n2* are non-zero and if yes, performs the code after `if`; it treats *n1* as zero/non-zero and uses `0<>` to convert *n2* into a canonical flag; the `and` then produces an *fz*, which is consumed by the `if`.

You can use the all-bits-set feature of canonical flags and the bitwise operation of the Boolean operations to avoid `ifs`:

```
: foo ( n1 -- n2 )
  0= if
    14
  else
    0
  endif ;
0 foo .
1 foo .

: foo ( n1 -- n2 )
  0= 14 and ;
0 foo .
1 foo .
```

Assignment: Write `min` without `if`.

For reference, see [\[Boolean Flags\]](#), page [\[undefined\]](#), [\[Numeric comparison\]](#), page [\[undefined\]](#), and [\[Bitwise operations\]](#), page [\[undefined\]](#).

3.18 General Loops

The endless loop is the most simple one:

```
: endless ( -- )
  0 begin
    dup . 1+
    again ;
endless
```

Terminate this loop by pressing *Ctrl-C* (in Gforth). `begin` does nothing at run-time, `again` jumps back to `begin`.

A loop with one exit at any place looks like this:

```
: log2 ( +n1 -- n2 )
\ logarithmus dualis of n1>0, rounded down to the next integer
assert( dup 0> )
2/ 0 begin
  over 0> while
    1+ swap 2/ swap
  repeat
  nip ;
7 log2 .
8 log2 .
```

At run-time `while` consumes a flag; if it is 0, execution continues behind the `repeat`; if the flag is non-zero, execution continues behind the `while`. `Repeat` jumps back to `begin`, just like `again`.

In Forth there are a number of combinations/abbreviations, like `1+`. However, `2/` is not one of them; it shifts its argument right by one bit (arithmetic shift right), and viewed

as division that always rounds towards negative infinity (floored division), like Gforth's / (since Gforth 0.7), but unlike / in many other Forth systems.

```
-5 2 / . \ -2 or -3
-5 2/ . \ -3
```

`assert(` is no standard word, but you can get it on systems other than Gforth by including `compat/assert.fs`. You can see what it does by trying

```
0 log2 .
```

Here's a loop with an exit at the end:

```
: log2 ( +n1 -- n2 )
\ logarithmus dualis of n1>0, rounded down to the next integer
assert( dup 0 > )
-1 begin
  1+ swap 2/ swap
  over 0 <=
until
nip ;
```

`Until` consumes a flag; if it is zero, execution continues at the `begin`, otherwise after the `until`.

Assignment: Write a definition for computing the greatest common divisor.

Reference: [\[General Loops\]](#), page [\[General Loops\]](#).

3.19 Counted loops

```
: ^ ( n1 u -- n )
\ n = the uth power of n1
1 swap 0 u+do
  over *
loop
nip ;
3 2 ^ .
4 3 ^ .
```

`U+do` (from `compat/loops.fs`, if your Forth system doesn't have it) takes two numbers of the stack (`u3 u4 --`), and then performs the code between `u+do` and `loop` for `u3-u4` times (or not at all, if `u3-u4<0`).

You can see the stack effect design rules at work in the stack effect of the loop start words: Since the start value of the loop is more frequently constant than the end value, the start value is passed on the top-of-stack.

You can access the counter of a counted loop with `i`:

```
: fac ( u -- u! )
1 swap 1+ 1 u+do
  i *
loop ;
5 fac .
7 fac .
```

There is also `+do`, which expects signed numbers (important for deciding whether to enter the loop).

Assignment: Write a definition for computing the *nth* Fibonacci number.

You can also use increments other than 1:

```
: up2 ( n1 n2 -- )
  +do
    i .
    2 +loop ;
10 0 up2

: down2 ( n1 n2 -- )
  -do
    i .
    2 -loop ;
0 10 down2
```

Reference: [\[Counted Loops\]](#), page [\[undefined\]](#).

3.20 Recursion

Usually the name of a definition is not visible in the definition; but earlier definitions are usually visible:

```
1 0 / . \ "Floating-point unidentified fault" in Gforth on some platforms
: / ( n1 n2 -- n )
  dup 0= if
    -10 throw \ report division by zero
  endif
  / \ old version
;
1 0 /
```

For recursive definitions you can use `recursive` (non-standard) or `recurse`:

```
: fac1 ( n -- n! ) recursive
  dup 0> if
    dup 1- fac1 *
  else
    drop 1
  endif ;
7 fac1 .

: fac2 ( n -- n! )
  dup 0> if
    dup 1- recurse *
  else
    drop 1
  endif ;
8 fac2 .
```

Assignment: Write a recursive definition for computing the nth Fibonacci number.

Reference (including indirect recursion): See [\[Calls and returns\]](#), page [\[undefined\]](#).

3.21 Leaving definitions or loops

EXIT exits the current definition right away. For every counted loop that is left in this way, an UNLOOP has to be performed before the EXIT:

```
: ...
... u+do
... if
... unloop exit
endif
...
loop
... ;
```

LEAVE leaves the innermost counted loop right away:

```
: ...
... u+do
... if
... leave
endif
...
loop
... ;
```

Reference: [\[Calls and returns\]](#), page [\[undefined\]](#), [\[Counted Loops\]](#), page [\[undefined\]](#).

3.22 Return Stack

In addition to the data stack Forth also has a second stack, the return stack; most Forth systems store the return addresses of procedure calls there (thus its name). Programmers can also use this stack:

```
: foo ( n1 n2 -- )
.s
>r .s
r@ .
>r .s
r@ .
r> .
r@ .
r> . ;
1 2 foo
```

`>r` takes an element from the data stack and pushes it onto the return stack; conversely, `r>` moves an element from the return to the data stack; `r@` pushes a copy of the top of the return stack on the data stack.

Forth programmers usually use the return stack for storing data temporarily, if using the data stack alone would be too complex, and factoring and locals are not an option:

```
: 2swap ( x1 x2 x3 x4 -- x3 x4 x1 x2 )
  rot >r rot r> ;
```

The return address of the definition and the loop control parameters of counted loops usually reside on the return stack, so you have to take all items, that you have pushed on the return stack in a colon definition or counted loop, from the return stack before the definition or loop ends. You cannot access items that you pushed on the return stack outside some definition or loop within the definition of loop.

If you miscount the return stack items, this usually ends in a crash:

```
: crash ( n -- )
  >r ;
5 crash
```

You cannot mix using locals and using the return stack (according to the standard; Gforth has no problem). However, they solve the same problems, so this shouldn't be an issue.

Assignment: Can you rewrite any of the definitions you wrote until now in a better way using the return stack?

Reference: [\[Return stack\]](#), page [\[undefined\]](#).

3.23 Memory

You can create a global variable `v` with

```
variable v ( -- addr )
```

`v` pushes the address of a cell in memory on the stack. This cell was reserved by `variable`. You can use `!` (store) to store values from the stack into this cell and `@` (fetch) to load the value from memory onto the stack:

```
v .
5 v ! .s
v @ .
```

You can see a raw dump of memory with `dump`:

```
v 1 cells .s dump
```

`Cells (n1 -- n2)` gives you the number of bytes (or, more generally, address units (aus)) that `n1 cells` occupy. You can also reserve more memory:

```
create v2 20 cells allot
v2 20 cells dump
```

creates a variable-like word `v2` and reserves 20 uninitialized cells; the address pushed by `v2` points to the start of these 20 cells (see [\[CREATE\]](#), page [\[undefined\]](#)). You can use address arithmetic to access these cells:

```
3 v2 5 cells + !
```

```
v2 20 cells dump
```

You can reserve and initialize memory with `,:`

```
create v3
  5 , 4 , 3 , 2 , 1 ,
v3 @ .
v3 cell+ @ .
v3 2 cells + @ .
v3 5 cells dump
```

Assignment: Write a definition `vsum (addr u -- n)` that computes the sum of `u` cells, with the first of these cells at `addr`, the next one at `addr cell+` etc.

The difference between `variable` and `create` is that `variable` allots a cell, and that you cannot allot additional memory to a variable in Standard Forth.

You can also reserve memory without creating a new word:

```
here 10 cells allot .
here .
```

The first `here` pushes the start address of the memory area, the second `here` the address after the dictionary area. You should store the start address somewhere, or you will have a hard time finding the memory area again.

`Allot` manages dictionary memory. The dictionary memory contains the system's data structures for words etc. on Gforth and most other Forth systems. It is managed like a stack: You can free the memory that you have just `allotted` with

```
-10 cells allot
here .
```

Note that you cannot do this if you have created a new word in the meantime (because then your `allotted` memory is no longer on the top of the dictionary “stack”).

Alternatively, you can use `allocate` and `free` which allow freeing memory in any order:

```
10 cells allocate throw .s
20 cells allocate throw .s
swap
free throw
free throw
```

The `throws` deal with errors (e.g., out of memory).

And there is also a garbage collector (<https://www.complang.tuwien.ac.at/forth/garbage-collection.zip>), which eliminates the need to `free` memory explicitly.

Reference: `<undefined>` [Memory], page `<undefined>`.

3.24 Characters and Strings

On the stack characters take up a cell, like numbers. In memory they have their own size (one 8-bit byte on most systems), and therefore require their own words for memory access:

```
create v4
  104 c, 97 c, 108 c, 108 c, 111 c,
v4 4 chars + c@ .
v4 5 chars dump
```


The preferred representation of strings on the stack is **addr u-count**, where **addr** is the address of the first character and **u-count** is the number of characters in the string.

```
v4 5 type
```

You get a string constant with

```
s" hello, world" .s
type
```

Make sure you have a space between **s"** and the string; **s"** is a normal Forth word and must be delimited with white space (try what happens when you remove the space).

However, this interpretive use of **s"** is quite restricted: the string exists only until the next call of **s"** (some Forth systems keep more than one of these strings, but usually they still have a limited lifetime).

```
s" hello," s" world" .s
type
type
```

You can also use **s"** in a definition, and the resulting strings then live forever (well, for as long as the definition):

```
: foo s" hello," s" world" ;
foo .s
type
type
```

Assignment: **Emit (c --)** types **c** as character (not a number). Implement **type (addr u --)**.

Reference: [\[Memory Blocks\]](#), page [\[undefined\]](#).

3.25 Alignment

On many processors cells have to be aligned in memory, if you want to access them with **@** and **!** (and even if the processor does not require alignment, access to aligned cells is faster).

Create aligns **here** (i.e., the place where the next allocation will occur, and that the **created** word points to). Likewise, the memory produced by **allocate** starts at an aligned address. Adding a number of **cells** to an aligned address produces another aligned address.

However, address arithmetic involving **char+** and **chars** can create an address that is not cell-aligned. **Aligned (addr -- a-addr)** produces the next aligned address:

```
v3 char+ aligned .s @ .
v3 char+ .s @ .
```

Similarly, **align** advances **here** to the next aligned address:

```
create v5 97 c,
here .
align here .
1000 ,
```

Note that you should use aligned addresses even if your processor does not require them, if you want your program to be portable.

Reference: [\[Address arithmetic\]](#), page [\[undefined\]](#).

3.26 Floating Point

Floating-point (FP) numbers and arithmetic in Forth works mostly as one might expect, but there are a few things worth noting:

The first point is not specific to Forth, but so important and yet not universally known that I mention it here: FP numbers are not reals. Many properties (e.g., arithmetic laws) that reals have and that one expects of all kinds of numbers do not hold for FP numbers. If you want to use FP computations, you should learn about their problems and how to avoid them; a good starting point is *David Goldberg, What Every Computer Scientist Should Know About Floating-Point Arithmetic* (https://docs.oracle.com/cd/E19957-01/806-3568/ncg_goldberg.html), *ACM Computing Surveys* 23(1):5–48, March 1991.

In Forth source code literal FP numbers need an exponent, e.g., `1e0`; this can also be written shorter as `1e`, longer as `+1.0e+0`, and many variations in between. The reason for this is that, for historical reasons, Forth interprets a decimal point alone (e.g., `1.`) as indicating a double-cell integer. Examples:

```
2e 2e f+ f.
```

Another requirement for literal FP numbers is that the current base is decimal; with a hex base `1e` is interpreted as an integer.

Forth has a separate stack for FP numbers in conformance with Forth-2012. One advantage of this model is that cells are not in the way when accessing FP values, and vice versa. Forth has a set of words for manipulating the FP stack: `fdup fswap fdrop fover frot` and (non-standard) `fnip ftuck fpick`.

FP arithmetic words are prefixed with `F`. There is the usual set `f+ f- f* f/ f** fnegate` as well as a number of words for other functions, e.g., `fsqrt fsin fln fmin`. One word that you might expect is `f=`; but `f=` is non-standard, because FP computation results are usually inaccurate, so exact comparison is usually a mistake, and one should use approximate comparison. Unfortunately, `f~`, the standard word for that purpose, is not well designed, so Gforth provides `f~abs` and `f~rel` as well.

And of course there are words for accessing FP numbers in memory (`f@ f!`), and for address arithmetic (`floats float+ faligned`). There are also variants of these words with an `sf` and `df` prefix for accessing IEEE format single-precision and double-precision numbers in memory; their main purpose is for accessing external FP data (e.g., that has been read from or will be written to a file).

Here is an example of a dot-product word and its use:

```
: v* ( f_addr1 nstride1 f_addr2 nstride2 ucount -- r )
  >r swap 2swap swap 0e r> 0 ?DO
    dup f@ over + 2swap dup f@ f* f+ over + 2swap
  LOOP
  2drop 2drop ;
```

```
create v 1.23e f, 4.56e f, 7.89e f,
```

```
v 1 floats v 1 floats 3 v* f.
```

Assignment: Write a program to solve a quadratic equation. Then read *Henry G. Baker, You Could Learn a Lot from a Quadratic*

(<https://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.111.4448&rep=rep1&type=pdf>), *ACM SIGPLAN Notices*, 33(1):30–39, January 1998, and see if you can improve your program. Finally, find a test case where the original and the improved version produce different results.

Reference: [\[Floating Point\]](#), page [\[Floating point stack\]](#), page [\[Number Conversion\]](#), page [\[Memory Access\]](#), page [\[Address arithmetic\]](#), page [\[Address arithmetic\]](#).

3.27 Files

This section gives a short introduction into how to use files inside Forth. It's broken up into five easy steps:

1. Open an ASCII text file for input
2. Open a file for output
3. Read input file until string matches (or some other condition is met)
4. Write some lines from input (modified or not) to output
5. Close the files.

Reference: [\[General files\]](#), page [\[General files\]](#).

3.27.1 Open file for input

```
s" foo.in" r/o open-file throw Value fd-in
```

3.27.2 Create file for output

```
s" foo.out" w/o create-file throw Value fd-out
```

The available file modes are `r/o` for read-only access, `r/w` for read-write access, and `w/o` for write-only access. You could open both files with `r/w`, too, if you like. All file words return error codes; for most applications, it's best to pass there error codes with `throw` to the outer error handler.

If you want words for opening and assigning, define them as follows:

```
0 Value fd-in
0 Value fd-out
: open-input ( addr u -- ) r/o open-file throw to fd-in ;
: open-output ( addr u -- ) w/o create-file throw to fd-out ;
```

Usage example:

```
s" foo.in" open-input
s" foo.out" open-output
```

3.27.3 Scan file for a particular line

```
256 Constant max-line
Create line-buffer max-line 2 + allot

: scan-file ( addr u -- )
  begin
    line-buffer max-line fd-in read-line throw
```

```

while
  >r 2dup line-buffer r> compare 0=
until
else
  drop
then
  2drop ;

```

`read-line (addr u1 fd -- u2 flag ior)` reads up to `u1` bytes into the buffer at `addr`, and returns the number of bytes read, a flag that is false when the end of file is reached, and an error code.

`compare (addr1 u1 addr2 u2 -- n)` compares two strings and returns zero if both strings are equal. It returns a positive number if the first string is lexically greater, a negative if the second string is lexically greater.

We haven't seen this loop here; it has two exits. Since the `while` exits with the number of bytes read on the stack, we have to clean up that separately; that's after the `else`.

Usage example:

```
s" The text I search is here" scan-file
```

3.27.4 Copy input to output

```

: copy-file ( -- )
begin
  line-buffer max-line fd-in read-line throw
while
  line-buffer swap fd-out write-line throw
repeat
drop ;

```

3.27.5 Close files

```

fd-in close-file throw
fd-out close-file throw

```

Likewise, you can put that into definitions, too:

```

: close-input ( -- ) fd-in close-file throw ;
: close-output ( -- ) fd-out close-file throw ;

```

Assignment: How could you modify `copy-file` so that it copies until a second line is matched? Can you write a program that extracts a section of a text file, given the line that starts and the line that terminates that section?

3.28 Interpretation and Compilation Semantics and Immediacy

When a word is compiled, it behaves differently from being interpreted. E.g., consider `+`:

```

1 2 + .
: foo + ;

```

These two behaviours are known as compilation and interpretation semantics. For normal words (e.g., `+`), the compilation semantics is to append the interpretation semantics to

the currently defined word (`foo` in the example above). I.e., when `foo` is executed later, the interpretation semantics of `+` (i.e., adding two numbers) will be performed.

However, there are words with non-default compilation semantics, e.g., the control-flow words like `if`. You can use `immediate` to change the compilation semantics of the last defined word to be equal to the interpretation semantics:

```
: [F00] ( -- )
  5 . ; immediate

[F00]
: bar ( -- )
  [F00] ;
bar
see bar
```

Two conventions to mark words with non-default compilation semantics are names with brackets (more frequently used) and to write them all in upper case (less frequently used).

For some words, such as `if`, using their interpretation semantics is usually a mistake, so we mark them as `compile-only`, and you get a warning when you interpret them.

```
: flip ( -- )
  6 . ; compile-only \ but not immediate
flip

: flop ( -- )
  flip ;
flop
```

In this example, first the interpretation semantics of `flip` is used (and you get a warning); the second use of `flip` uses the compilation semantics (and you get no warning). You can also see in this example that `compile-only` is a property that is evaluated at text interpretation time, not at run-time.

The text interpreter has two states: in interpret state, it performs the interpretation semantics of words it encounters; in compile state, it performs the compilation semantics of these words.

Among other things, `:` switches into compile state, and `;` switches back to interpret state. They contain the factors `]` (switch to compile state) and `[` (switch to interpret state), that do nothing but switch the state.

```
: xxx ( -- )
  [ 5 . ]
;

xxx
see xxx
```

These brackets are also the source of the naming convention mentioned above.

Reference: [\[Interpretation and Compilation Semantics\]](#), page [\[undefined\]](#).

3.29 Execution Tokens

' word gives you the execution token (XT) of a word. The XT is a cell representing the interpretation semantics of a word. You can execute this semantics with `execute`:

```
' + .s
1 2 rot execute .
```

The XT is similar to a function pointer in C. However, parameter passing through the stack makes it a little more flexible:

```
: map-array ( ... addr u xt -- ... )
\ executes xt ( ... x -- ... ) for every element of the array starting
\ at addr and containing u elements
{ xt }
cells over + swap ?do
  i @ xt execute
1 cells +loop ;
```

```
create a 3 , 4 , 2 , -1 , 4 ,
a 5 ' . map-array .s
0 a 5 ' + map-array .
s" max-n" environment? drop .s
a 5 ' min map-array .
```

You can use `map-array` with the XTs of words that consume one element more than they produce. In theory you can also use it with other XTs, but the stack effect then depends on the size of the array, which is hard to understand.

Since XTs are cell-sized, you can store them in memory and manipulate them on the stack like other cells. You can also compile the XT into a word with `compile,:`

```
: foo1 ( n1 n2 -- n )
  [ ' + compile, ] ;
see foo1
```

This is non-standard, because `compile,` has no compilation semantics in the standard, but it works in good Forth systems. For the broken ones, use

```
: [compile,] compile, ; immediate

: foo1 ( n1 n2 -- n )
  [ ' + ] [compile,] ;
see foo1
```

' is a word with default compilation semantics; it parses the next word when its interpretation semantics are executed, not during compilation:

```
: foo ( -- xt )
  ' ;
see foo
: bar ( ... "word" -- ... )
  ' execute ;
see bar
1 2 bar + .
```

You often want to parse a word during compilation and compile its XT so it will be pushed on the stack at run-time. `[']` does this:

```
: xt-+ ( -- xt )
  ['] + ;
see xt-+
1 2 xt-+ execute .
```

Many programmers tend to see `'` and the word it parses as one unit, and expect it to behave like `[']` when compiled, and are confused by the actual behaviour. If you are, just remember that the Forth system just takes `'` as one unit and has no idea that it is a parsing word (attempts to convenience programmers in this issue have usually resulted in even worse pitfalls, see *State-smartness—Why it is evil and How to Exorcise it* (<https://www.complang.tuwien.ac.at/papers/ertl98.ps.gz>)).

Note that the state of the interpreter does not come into play when creating and executing XTs. I.e., even when you execute `'` in compile state, it still gives you the interpretation semantics. And whatever that state is, `execute` performs the semantics represented by the XT (i.e., for XTs produced with `'` the interpretation semantics).

Reference: `<undefined>` [Tokens for Words], page `<undefined>`.

3.30 Exceptions

`throw (n --)` causes an exception unless `n` is zero.

```
100 throw .s
0 throw .s
```

`catch (... xt -- ... n)` behaves similar to `execute`, but it catches exceptions and pushes the number of the exception on the stack (or 0, if the xt executed without exception). If there was an exception, the stacks have the same depth as when entering `catch`:

```
.s
3 0 ' / catch .s
3 2 ' / catch .s
```

Assignment: Try the same with `execute` instead of `catch`.

`Throw` always jumps to the dynamically next enclosing `catch`, even if it has to leave several call levels to achieve this:

```
: foo 100 throw ;
: foo1 foo ." after foo" ;
: bar ['] foo1 catch ;
bar .
```

It is often important to restore a value upon leaving a definition, even if the definition is left through an exception. You can ensure this like this:

```
: ...
  save-x
  ['] word-changing-x catch ( ... n )
  restore-x
  ( ... n ) throw ;
```

However, this is still not safe against, e.g., the user pressing `Ctrl-C` when execution is between the `catch` and `restore-x`.

Gforth provides an alternative exception handling syntax that is safe against such cases: `try ... restore ... endtry`. If the code between `try` and `endtry` has an exception, the stack depths are restored, the exception number is pushed on the stack, and the execution continues right after `restore`.

The safer equivalent to the restoration code above is

```
: ...
  save-x
  try
    word-changing-x 0
  restore
  restore-x
endtry
throw ;
```

Reference: `<undefined>` [Exception Handling], page `<undefined>`.

3.31 Defining Words

`:`, `create`, and `variable` are definition words: They define other words. `constant` is another definition word:

```
5 constant foo
foo .
```

You can also use the prefixes `2` (double-cell) and `f` (floating point) with `variable` and `constant`.

You can also define your own defining words. E.g.:

```
: variable ( "name" -- )
  create 0 , ;
```

You can also define defining words that create words that do something other than just producing their address:

```
: constant ( n "name" -- )
  create ,
does> ( -- n )
  ( addr ) @ ;

5 constant foo
foo .
```

The definition of `constant` above ends at the `does>`; i.e., `does>` replaces `;`, but it also does something else: It changes the last defined word such that it pushes the address of the body of the word and then performs the code after the `does>` whenever it is called.

In the example above, `constant` uses `,` to store 5 into the body of `foo`. When `foo` executes, it pushes the address of the body onto the stack, then (in the code after the `does>`) fetches the 5 from there.

The stack comment near the `does>` reflects the stack effect of the defined word, not the stack effect of the code after the `does>` (the difference is that the code expects the address of the body that the stack comment does not show).

You can use these definition words to do factoring in cases that involve (other) definition words. E.g., a field offset is always added to an address. Instead of defining

```
2 cells constant offset-field1
```

and using this like

```
( addr ) offset-field1 +
```

you can define a definition word

```
: simple-field ( n "name" -- )
  create ,
does> ( n1 -- n1+n )
  ( addr ) @ + ;
```

Definition and use of field offsets now look like this:

```
2 cells simple-field field1
create mystruct 4 cells allot
mystruct .s field1 .s drop
```

If you want to do something with the word without performing the code after the `does>`, you can access the body of a created word with `>body (xt -- addr)`:

```
: value ( n "name" -- )
  create ,
does> ( -- n1 )
  @ ;
: to ( n "name" -- )
  ' >body ! ;
```

```
5 value foo
foo .
7 to foo
foo .
```

Assignment: Define `defer ("name" --)`, which creates a word that stores an XT (at the start the XT of `abort`), and upon execution `executes` the XT. Define `is (xt "name" --)` that stores `xt` into `name`, a word defined with `defer`. Indirect recursion is one application of `defer`.

Reference: `<undefined>` [User-defined Defining Words], page `<undefined>`.

3.32 Arrays and Records

Forth has no standard words for defining arrays, but you can build them yourself based on address arithmetic. You can also define words for defining arrays and records (see `<undefined>` [Defining Words], page `<undefined>`).

One of the first projects a Forth newcomer sets out upon when learning about defining words is an array defining word (possibly for n-dimensional arrays). Go ahead and do it, I did it, too; you will learn something from it. However, don't be disappointed when you later learn that you have little use for these words (inappropriate use would be even worse). I have not found a set of useful array words yet; the needs are just too diverse, and named, global arrays (the result of naive use of defining words) are often not flexible enough (e.g.,

consider how to pass them as parameters). Another such project is a set of words to help dealing with strings.

On the other hand, there is a useful set of record words, and it has been defined in `compat/struct.fs`; these words are predefined in Gforth. They are explained in depth elsewhere in this manual (see see `<undefined>` [Structures], page `<undefined>`). The `simple-field` example above is simplified variant of fields in this package.

3.33 POSTPONE

You can compile the compilation semantics (instead of compiling the interpretation semantics) of a word with `POSTPONE`:

```
: MY-+ ( Compilation: -- ; Run-time of compiled code: n1 n2 -- n )
  POSTPONE + ; immediate
: foo ( n1 n2 -- n )
  MY-+ ;
1 2 foo .
see foo
```

During the definition of `foo` the text interpreter performs the compilation semantics of `MY-+`, which performs the compilation semantics of `+`, i.e., it compiles `+` into `foo`.

This example also displays separate stack comments for the compilation semantics and for the stack effect of the compiled code. For words with default compilation semantics these stack effects are usually not displayed; the stack effect of the compilation semantics is always `(--)` for these words, the stack effect for the compiled code is the stack effect of the interpretation semantics.

Note that the state of the interpreter does not come into play when performing the compilation semantics in this way. You can also perform it interpretively, e.g.:

```
: foo2 ( n1 n2 -- n )
  [ MY-+ ] ;
1 2 foo .
see foo
```

However, there are some broken Forth systems where this does not always work, and therefore this practice was been declared non-standard in 1999.

Here is another example for using `POSTPONE`:

```
: MY-- ( Compilation: -- ; Run-time of compiled code: n1 n2 -- n )
  POSTPONE negate POSTPONE + ; immediate compile-only
: bar ( n1 n2 -- n )
  MY-- ;
2 1 bar .
see bar
```

You can define `ENDIF` (which you can use instead of `THEN`) in this way:

```
: ENDIF ( Compilation: orig -- )
  POSTPONE then ; immediate
```

Assignment: Write `MY-2DUP` that has compilation semantics equivalent to `2dup`, but compiles `over over`.

3.34 Literal

You cannot POSTPONE numbers:

```
: [F00] POSTPONE 500 ; immediate
```

Instead, you can use LITERAL (compilation: n --; run-time: -- n):

```
: [F00] ( compilation: --; run-time: -- n )
  500 POSTPONE literal ; immediate
```

```
: flip [F00] ;
flip .
see flip
```

LITERAL consumes a number at compile-time (when it's compilation semantics are executed) and pushes it at run-time (when the code it compiled is executed). A frequent use of LITERAL is to compile a number computed at compile time into the current word:

```
: bar ( -- n )
  [ 2 2 + ] literal ;
see bar
```

Assignment: Write]L which allows writing the example above as : bar (-- n) [2 2 +]L ;

3.35 Advanced macros

Reconsider map-array from <undefined> [Execution Tokens], page <undefined>. It frequently performs `execute`, a relatively expensive operation in some Forth implementations. You can use `compile`, and `POSTPONE` to eliminate these `executes` and produce a word that contains the word to be performed directly:

```
: compile-map-array ( compilation: xt -- ; run-time: ... addr u -- ... )
\ at run-time, execute xt ( ... x -- ... ) for each element of the
\ array beginning at addr and containing u elements
{ xt }
POSTPONE cells POSTPONE over POSTPONE + POSTPONE swap POSTPONE ?do
  POSTPONE @ POSTPONE @ xt compile,
  1 cells POSTPONE literal POSTPONE +loop ;

: sum-array ( addr u -- n )
  0 rot rot [ ' + compile-map-array ] ;
see sum-array
a 5 sum-array .
```

You can use the full power of Forth for generating the code; here's an example where the code is generated in a loop:

```
: compile-vmul-step ( compilation: n --; run-time: n1 addr1 -- n2 addr2 )
\ n2=n1+(addr1)*n, addr2=addr1+cell
POSTPONE tuck POSTPONE @
POSTPONE literal POSTPONE * POSTPONE +
POSTPONE swap POSTPONE cell+ ;
```

```

: compile-vmul ( compilation: addr1 u -- ; run-time: addr2 -- n )
\ n=v1*v2 (inner product), where the v_i are represented as addr_i u
0 postpone literal postpone swap
[ ' compile-vmul-step compile-map-array ]
postpone drop ;
see compile-vmul

: a-vmul ( addr -- n )
\ n=a*v, where v is a vector that's as long as a and starts at addr
[ a 5 compile-vmul ] ;
see a-vmul
a a-vmul .

```

This example uses `compile-map-array` to show off, but you could also use `map-array` instead (try it now!).

You can use this technique for efficient multiplication of large matrices. In matrix multiplication, you multiply every row of one matrix with every column of the other matrix. You can generate the code for one row once, and use it for every column. The only downside of this technique is that it is cumbersome to recover the memory consumed by the generated code when you are done (and in more complicated cases it is not possible portably).

3.36 Compilation Tokens

This section is Gforth-specific. You can skip it.

' `word compile`, compiles the interpretation semantics. For words with default compilation semantics this is the same as performing the compilation semantics. To represent the compilation semantics of other words (e.g., words like `if` that have no interpretation semantics), Gforth has the concept of a compilation token (CT, consisting of two cells), and words `comp'` and `[comp']`. You can perform the compilation semantics represented by a CT with `execute`:

```

: foo2 ( n1 n2 -- n )
[ comp' + execute ] ;
see foo

```

You can compile the compilation semantics represented by a CT with `postpone,:`

```

: foo3 ( -- )
[ comp' + postpone, ] ;
see foo3

```

`[comp' word postpone,]` is equivalent to `POSTPONE word`. `comp'` is particularly useful for words that have no interpretation semantics:

```

' if
comp' if .s 2drop

```

Reference: [\[Tokens for Words\]](#), page [\[undefined\]](#).

3.37 Wordlists and Search Order

The dictionary is not just a memory area that allows you to allocate memory with `allot`, it also contains the Forth words, arranged in several wordlists. When searching for a word

in a wordlist, conceptually you start searching at the youngest and proceed towards older words (in reality most systems nowadays use hash-tables); i.e., if you define a word with the same name as an older word, the new word shadows the older word.

Which wordlists are searched in which order is determined by the search order. You can display the search order with `order`. It displays first the search order, starting with the wordlist searched first, then it displays the wordlist that will contain newly defined words.

You can create a new, empty wordlist with `wordlist (-- wid)`:

```
wordlist constant mywords
```

`Set-current (wid --)` sets the wordlist that will contain newly defined words (the *current* wordlist):

```
mywords set-current
order
```

Gforth does not display a name for the wordlist in `mywords` because this wordlist was created anonymously with `wordlist`.

You can get the current wordlist with `get-current (-- wid)`. If you want to put something into a specific wordlist without overall effect on the current wordlist, this typically looks like this:

```
get-current mywords set-current ( wid )
create someword
( wid ) set-current
```

You can write the search order with `set-order (wid1 .. widn n --)` and read it with `get-order (-- wid1 .. widn n)`. The first searched wordlist is topmost.

```
get-order mywords swap 1+ set-order
order
```

Yes, the order of wordlists in the output of `order` is reversed from stack comments and the output of `.s` and thus unintuitive.

Assignment: Define `>order (wid --)` which adds `wid` as first searched wordlist to the search order. Define `previous (--)`, which removes the first searched wordlist from the search order. Experiment with boundary conditions (you will see some crashes or situations that are hard or impossible to leave).

The search order is a powerful foundation for providing features similar to Modula-2 modules and C++ namespaces. However, trying to modularize programs in this way has disadvantages for debugging and reuse/factoring that overcome the advantages in my experience (I don't do huge projects, though). These disadvantages are not so clear in other languages/programming environments, because these languages are not so strong in debugging and reuse.

Reference: [\[Word Lists\]](#), page [\[undefined\]](#).

4 An Introduction to Standard Forth

The difference of this chapter from the Tutorial (see [\[Tutorial\]](#), page [\[undefined\]](#)) is that it is slower-paced in its examples, but uses them to dive deep into explaining Forth internals (not covered by the Tutorial). Apart from that, this chapter covers far less material. It is suitable for reading without using a computer.

The primary purpose of this manual is to document Gforth. However, since Forth is not a widely-known language and there is a lack of up-to-date teaching material, it seems worthwhile to provide some introductory material. For other sources of Forth-related information, see [\[Forth-related information\]](#), page [\[undefined\]](#).

The examples in this section should work on any Standard Forth; the output shown was produced using Gforth. Each example attempts to reproduce the exact output that Gforth produces. If you try out the examples (and you should), what you should type is shown *like this* and Gforth's response is shown *like this*. The single exception is that, where the example shows RET it means that you should press the “carriage return” key. Unfortunately, some output formats for this manual cannot show the difference between *this* and *this* which will make trying out the examples harder (but not impossible).

Forth is an unusual language. It provides an interactive development environment which includes both an interpreter and compiler. Forth programming style encourages you to break a problem down into many small fragments (*factoring*), and then to develop and test each fragment interactively. Forth advocates assert that breaking the edit-compile-test cycle used by conventional programming languages can lead to great productivity improvements.

4.1 Introducing the Text Interpreter

When you invoke the Forth image, you will see a startup banner printed and nothing else (if you have Gforth installed on your system, try invoking it now, by typing *gforthRET*). Forth is now running its command line interpreter, which is called the *Text Interpreter* (also known as the *Outer Interpreter*). (You will learn a lot about the text interpreter as you read through this chapter, for more detail see [\[The Text Interpreter\]](#), page [\[undefined\]](#)).

Although it's not obvious, Forth is actually waiting for your input. Type a number and press the RET key:

```
45RET  ok
```

Rather than give you a prompt to invite you to input something, the text interpreter prints a status message *after* it has processed a line of input. The status message in this case (“ok” followed by carriage-return) indicates that the text interpreter was able to process all of your input successfully. Now type something illegal:

```
qwer341RET
*the terminal*:2: Undefined word
>>>qwer341<<<
Backtrace:
$2A95B42A20 throw
$2A95B57FB8 no.extensions
```

The exact text, other than the “Undefined word” may differ slightly on your system, but the effect is the same; when the text interpreter detects an error, it discards any remaining

text on a line, resets certain internal state and prints an error message. For a detailed description of error messages see [\[Error messages\]](#), page [\[undefined\]](#).

The text interpreter waits for you to press carriage-return, and then processes your input line. Starting at the beginning of the line, it breaks the line into groups of characters separated by spaces. For each group of characters in turn, it makes two attempts to do something:

- It tries to treat it as a command. It does this by searching a *name dictionary*. If the group of characters matches an entry in the name dictionary, the name dictionary provides the text interpreter with information that allows the text interpreter to perform some actions. In Forth jargon, we say that the group of characters names a *word*, that the dictionary search returns an *execution token* (*xt*) corresponding to the *definition* of the word, and that the text interpreter executes the *xt*. Often, the terms *word* and *definition* are used interchangeably.
- If the text interpreter fails to find a match in the name dictionary, it tries to treat the group of characters as a number in the current number base (when you start up Forth, the current number base is base 10). If the group of characters legitimately represents a number, the text interpreter pushes the number onto a stack (we'll learn more about that in the next section).

If the text interpreter is unable to do either of these things with any group of characters, it discards the group of characters and the rest of the line, then prints an error message. If the text interpreter reaches the end of the line without error, it prints the status message “ok” followed by carriage-return.

This is the simplest command we can give to the text interpreter:

```
RET ok
```

The text interpreter did everything we asked it to do (nothing) without an error, so it said that everything is “ok”. Try a slightly longer command:

```
12 dup fred dupRET
*the terminal*:3: Undefined word
12 dup >>>fred<<< dup
Backtrace:
$2A95B42A20 throw
$2A95B57FB8 no.extensions
```

When you press the carriage-return key, the text interpreter starts to work its way along the line:

- When it gets to the space after the 2, it takes the group of characters 12 and looks them up in the name dictionary¹. There is no match for this group of characters in the name dictionary, so it tries to treat them as a number. It is able to do this successfully, so it puts the number, 12, “on the stack” (whatever that means).
- The text interpreter resumes scanning the line and gets the next group of characters, *dup*. It looks it up in the name dictionary and (you'll have to take my word for this) finds it, and executes the word *dup* (whatever that means).

¹ We can't tell if it found them or not, but assume for now that it did not

- Once again, the text interpreter resumes scanning the line and gets the group of characters **fred**. It looks them up in the name dictionary, but can't find them. It tries to treat them as a number, but they don't represent any legal number.

At this point, the text interpreter gives up and prints an error message. The error message shows exactly how far the text interpreter got in processing the line. In particular, it shows that the text interpreter made no attempt to do anything with the final character group, **dup**, even though we have good reason to believe that the text interpreter would have no problem looking that word up and executing it a second time.

4.2 Stacks, postfix notation and parameter passing

In procedural programming languages (like C and Pascal), the building-block of programs is the *function* or *procedure*. These functions or procedures are called with *explicit parameters*. For example, in C we might write:

```
total = total + new_volume(length,height,depth);
```

where `new_volume` is a function-call to another piece of code, and `total`, `length`, `height` and `depth` are all variables. `length`, `height` and `depth` are parameters to the function-call.

In Forth, the equivalent of the function or procedure is the *definition* and parameters are implicitly passed between definitions using a shared stack that is visible to the programmer. Although Forth does support variables, the existence of the stack means that they are used far less often than in most other programming languages. When the text interpreter encounters a number, it will place (*push*) it on the stack. There are several stacks (the actual number is implementation-dependent ...) and the particular stack used for any operation is implied unambiguously by the operation being performed. The stack used for all integer operations is called the *data stack* and, since this is the stack used most commonly, references to “the data stack” are often abbreviated to “the stack”.

The stacks have a last-in, first-out (LIFO) organisation. If you type:

```
1 2 3RET ok
```

Then this instructs the text interpreter to place three numbers on the (data) stack. An analogy for the behaviour of the stack is to take a pack of playing cards and deal out the ace (1), 2 and 3 into a pile on the table. The 3 was the last card onto the pile (“last-in”) and if you take a card off the pile then, unless you're prepared to fiddle a bit, the card that you take off will be the 3 (“first-out”). The number that will be first-out of the stack is called the *top of stack*, which is often abbreviated to *TOS*.

To understand how parameters are passed in Forth, consider the behaviour of the definition `+` (pronounced “plus”). You will not be surprised to learn that this definition performs addition. More precisely, it adds two numbers together and produces a result. Where does it get the two numbers from? It takes the top two numbers off the stack. Where does it place the result? On the stack. You can act out the behaviour of `+` with your playing cards like this:

- Pick up two cards from the stack on the table
- Stare at them intently and ask yourself “what *is* the sum of these two numbers”
- Decide that the answer is 5
- Shuffle the two cards back into the pack and find a 5

- Put a 5 on the remaining ace that's on the table.

If you don't have a pack of cards handy but you do have Forth running, you can use the definition `.s` to show the current state of the stack, without affecting the stack. Type:

```
clearstacks 1 2 3RET ok
.sRET <3> 1 2 3 ok
```

The text interpreter looks up the word `clearstacks` and executes it; it tidies up the stacks (data and floating point stack) and removes any entries that may have been left on them by earlier examples. The text interpreter pushes each of the three numbers in turn onto the stack. Finally, the text interpreter looks up the word `.s` and executes it. The effect of executing `.s` is to print the “<3>” (the total number of items on the stack) followed by a list of all the items on the stack; the item on the far right-hand side is the TOS.

You can now type:

```
+ .sRET <2> 1 5 ok
```

which is correct; there are now 2 items on the stack and the result of the addition is 5.

If you're playing with cards, try doing a second addition: pick up the two cards, work out that their sum is 6, shuffle them into the pack, look for a 6 and place that on the table. You now have just one item on the stack. What happens if you try to do a third addition? Pick up the first card, pick up the second card – ah! There is no second card. This is called a *stack underflow* and constitutes an error. If you try to do the same thing with Forth it often reports an error (probably a Stack Underflow or an Invalid Memory Address error).

The opposite situation to a stack underflow is a *stack overflow*, which simply accepts that there is a finite amount of storage space reserved for the stack. To stretch the playing card analogy, if you had enough packs of cards and you piled the cards up on the table, you would eventually be unable to add another card; you'd hit the ceiling. Gforth allows you to set the maximum size of the stacks. In general, the only time that you will get a stack overflow is because a definition has a bug in it and is generating data on the stack uncontrollably.

There's one final use for the playing card analogy. If you model your stack using a pack of playing cards, the maximum number of items on your stack will be 52 (I assume you didn't use the Joker). The maximum *value* of any item on the stack is 13 (the King). In fact, the only possible numbers are positive integer numbers 1 through 13; you can't have (for example) 0 or 27 or 3.52 or -2. If you change the way you think about some of the cards, you can accommodate different numbers. For example, you could think of the Jack as representing 0, the Queen as representing -1 and the King as representing -2. Your *range* remains unchanged (you can still only represent a total of 13 numbers) but the numbers that you can represent are -2 through 10.

In that analogy, the limit was the amount of information that a single stack entry could hold, and Forth has a similar limit. In Forth, the size of a stack entry is called a *cell*. The actual size of a cell is implementation dependent and affects the maximum value that a stack entry can hold. A Standard Forth provides a cell size of at least 16-bits, and most desktop systems use a cell size of 32-bits.

Forth does not do any type checking for you, so you are free to manipulate and combine stack items in any way you wish. A convenient way of treating stack items is as 2's

complement signed integers, and that is what Standard words like `+` do. Therefore you can type:

```
-5 12 + .sRET <1> 7 ok
```

If you use numbers and definitions like `+` in order to turn Forth into a great big pocket calculator, you will realise that it's rather different from a normal calculator. Rather than typing $2 + 3 =$ you had to type `2 3 +` (ignore the fact that you had to use `.s` to see the result). The terminology used to describe this difference is to say that your calculator uses *Infix Notation* (parameters and operators are mixed) whilst Forth uses *Postfix Notation* (parameters and operators are separate), also called *Reverse Polish Notation*.

Whilst postfix notation might look confusing to begin with, it has several important advantages:

- it is unambiguous
- it is more concise
- it fits naturally with a stack-based system

To examine these claims in more detail, consider these sums:

```
6 + 5 * 4 =
4 * 5 + 6 =
```

If you're just learning maths or your maths is very rusty, you will probably come up with the answer 44 for the first and 26 for the second. If you are a bit of a whizz at maths you will remember the *convention* that multiplication takes precedence over addition, and you'd come up with the answer 26 both times. To explain the answer 26 to someone who got the answer 44, you'd probably rewrite the first sum like this:

```
6 + (5 * 4) =
```

If what you really wanted was to perform the addition before the multiplication, you would have to use parentheses to force it.

If you did the first two sums on a pocket calculator you would probably get the right answers, unless you were very cautious and entered them using these keystroke sequences:

```
6 + 5 = * 4 = 4 * 5 = + 6 =
```

Postfix notation is unambiguous because the order that the operators are applied is always explicit; that also means that parentheses are never required. The operators are *active* (the act of quoting the operator makes the operation occur) which removes the need for “=”.

The sum $6 + 5 * 4$ can be written (in postfix notation) in two equivalent ways:

```
6 5 4 * +      or:
5 4 * 6 +
```

An important thing that you should notice about this notation is that the *order* of the numbers does not change; if you want to subtract 2 from 10 you type `10 2 -`.

The reason that Forth uses postfix notation is very simple to explain: it makes the implementation extremely simple, and it follows naturally from using the stack as a mechanism for passing parameters. Another way of thinking about this is to realise that all Forth definitions are *active*; they execute as they are encountered by the text interpreter. The result of this is that the syntax of Forth is trivially simple.

4.3 Your first Forth definition

Until now, the examples we've seen have been trivial; we've just been using Forth as a bigger-than-pocket calculator. Also, each calculation we've shown has been a "one-off" – to repeat it we'd need to type it in again² In this section we'll see how to add new words to Forth's vocabulary.

The easiest way to create a new word is to use a *colon definition*. We'll define a few and try them out before worrying too much about how they work. Try typing in these examples; be careful to copy the spaces accurately:

```
: add-two 2 + . ;
: greet ." Hello and welcome" ;
: demo 5 add-two ;
```

Now try them out:

```
greetRET Hello and welcome ok
greet greetRET Hello and welcomeHello and welcome ok
4 add-twoRET 6 ok
demoRET 7 ok
9 greet demo add-twoRET Hello and welcome7 11 ok
```

The first new thing that we've introduced here is the pair of words `:` and `;`. These are used to start and terminate a new definition, respectively. The first word after the `:` is the name for the new definition.

As you can see from the examples, a definition is built up of words that have already been defined; Forth makes no distinction between definitions that existed when you started the system up, and those that you define yourself.

The examples also introduce the words `.` (dot), `."` (dot-quote) and `dup` (dewp). Dot takes the value from the top of the stack and displays it. It's like `.s` except that it only displays the top item of the stack and it is destructive; after it has executed, the number is no longer on the stack. There is always one space printed after the number, and no spaces before it. Dot-quote defines a string (a sequence of characters) that will be printed when the word is executed. The string can contain any printable characters except `"`. A `"` has a special function; it is not a Forth word but it acts as a delimiter (the way that delimiters work is described in the next section). Finally, `dup` duplicates the value at the top of the stack. Try typing `5 dup .s` to see what it does.

We already know that the text interpreter searches through the dictionary to locate names. If you've followed the examples earlier, you will already have a definition called `add-two`. Lets try modifying it by typing in a new definition:

```
: add-two dup . ." + 2 = " 2 + . ;RET redefined add-two ok
```

Forth recognised that we were defining a word that already exists, and printed a message to warn us of that fact. Let's try out the new definition:

```
9 add-twoRET 9 + 2 = 11 ok
```

All that we've actually done here, though, is to create a new definition, with a particular name. The fact that there was already a definition with the same name did not make

² That's not quite true. If you press the up-arrow key on your keyboard you should be able to scroll back to any earlier command, edit it and re-enter it.

any difference to the way that the new definition was created (except that Forth printed a warning message). The old definition of `add-two` still exists (try `demo` again to see that this is true). Any new definition will use the new definition of `add-two`, but old definitions continue to use the version that already existed at the time that they were `compiled`.

Before you go on to the next section, try defining and redefining some words of your own.

4.4 How does that work?

Now we're going to take another look at the definition of `add-two` from the previous section. From our knowledge of the way that the text interpreter works, we would have expected this result when we tried to define `add-two`:

```
: add-two 2 + . ;RET
*the terminal*:4: Undefined word
: >>>add-two<<< 2 + . ;
```

The reason that this didn't happen is bound up in the way that `:` works. The word `:` does two special things. The first special thing that it does is to prevent the text interpreter from ever seeing the characters `add-two`. The text interpreter uses a variable called `>IN` (pronounced "to-in") to keep track of where it is in the input line. When it encounters the word `:` it behaves in exactly the same way as it does for any other word; it looks it up in the name dictionary, finds its `xt` and executes it. When `:` executes, it looks at the input buffer, finds the word `add-two` and advances the value of `>IN` to point past it. It then does some other stuff associated with creating the new definition (including creating an entry for `add-two` in the name dictionary). When the execution of `:` completes, control returns to the text interpreter, which is oblivious to the fact that it has been tricked into ignoring part of the input line.

Words like `:` – words that advance the value of `>IN` and so prevent the text interpreter from acting on the whole of the input line – are called *parsing words*.

The second special thing that `:` does is change the value of a variable called `state`, which affects the way that the text interpreter behaves. When Gforth starts up, `state` has the value 0, and the text interpreter is said to be *interpreting*. During a colon definition (started with `:`), `state` is set to -1 and the text interpreter is said to be *compiling*.

In this example, the text interpreter is compiling when it processes the string `"2 + . ;"`. It still breaks the string down into character sequences in the same way. However, instead of pushing the number 2 onto the stack, it lays down (*compiles*) some magic into the definition of `add-two` that will make the number 2 get pushed onto the stack when `add-two` is *executed*. Similarly, the behaviours of `+` and `.` are also compiled into the definition.

Certain kinds of words do not get compiled. These so-called *immediate words* get executed (performed *now*) regardless of whether the text interpreter is interpreting or compiling. The word `;` is an immediate word. Rather than being compiled into the definition, it executes. Its effect is to terminate the current definition, which includes changing the value of `state` back to 0.

When you execute `add-two`, it has a *run-time effect* that is exactly the same as if you had typed `2 + . RET` outside of a definition.

In Forth, every word or number can be described in terms of two properties:

- Its *interpretation semantics* describe how it will behave when the text interpreter encounters it in *interpret* state. The interpretation semantics of a word are represented by its *execution token* (see <undefined> [Execution token], page <undefined>).
- Its *compilation semantics* describe how it will behave when the text interpreter encounters it in *compile* state. The compilation semantics of a word are represented by its *compilation token* (see <undefined> [Compilation token], page <undefined>).

Numbers are always treated in a fixed way:

- When the number is *interpreted*, its behaviour is to push the number onto the stack.
- When the number is *compiled*, a piece of code is appended to the current definition that pushes the number when it runs. (In other words, the compilation semantics of a number are to postpone its interpretation semantics until the run-time of the definition that it is being compiled into.)

Words don't always behave in such a regular way, but most have *default semantics* which means that they behave like this:

- The *interpretation semantics* of the word are to do something useful.
- The *compilation semantics* of the word are to append its *interpretation semantics* to the current definition (so that its run-time behaviour is to do something useful).

The actual behaviour of any particular word can be controlled by using the words **immediate** and **compile-only** when the word is defined. These words set flags in the name dictionary entry of the most recently defined word, and these flags are retrieved by the text interpreter when it finds the word in the name dictionary.

A word that is marked as *immediate* has compilation semantics that are identical to its interpretation semantics. In other words, it behaves like this:

- The *interpretation semantics* of the word are to do something useful.
- The *compilation semantics* of the word are to do something useful (and actually the same thing); i.e., it is executed during compilation.

Marking a word as *compile-only* means that the text interpreter produces a warning when encountering this word in interpretation state; ticking the word (with ' or ['] also produces a warning.

It is never necessary to use **compile-only** (and it is not even part of Standard Forth, though it is provided by many implementations) but it is good etiquette to apply it to a word that will not behave correctly (and might have unexpected side-effects) in interpret state. For example, it is only legal to use the conditional word **IF** within a definition. If you forget this and try to use it elsewhere, the fact that (in Gforth) it is marked as **compile-only** allows the text interpreter to generate a helpful warning.

This example shows the difference between an immediate and a non-immediate word:

```
: show-state state @ . ;
: show-state-now show-state ; immediate
: word1 show-state ;
: word2 show-state-now ;
```

The word **immediate** after the definition of **show-state-now** makes that word an immediate word. These definitions introduce a new word: **@** (pronounced “fetch”). This word

fetches the value of a variable, and leaves it on the stack. Therefore, the behaviour of **show-state** is to print a number that represents the current value of **state**.

When you execute **word1**, it prints the number 0, indicating that the system is interpreting. When the text interpreter compiled the definition of **word1**, it encountered **show-state** whose compilation semantics are to append its interpretation semantics to the current definition. When you execute **word1**, it performs the interpretation semantics of **show-state**. At the time that **word1** (and therefore **show-state**) is executed, the system is interpreting.

When you pressed RET after entering the definition of **word2**, you should have seen the number -1 printed, followed by “ok”. When the text interpreter compiled the definition of **word2**, it encountered **show-state-now**, an immediate word, whose compilation semantics are therefore to perform its interpretation semantics. It is executed straight away (even before the text interpreter has moved on to process another group of characters; the ; in this example). The effect of executing it is to display the value of **state** *at the time that the definition of word2 is being defined*. Printing -1 demonstrates that the system is compiling at this time. If you execute **word2** it does nothing at all.

Before leaving the subject of immediate words, consider the behaviour of **.** in the definition of **greet**, in the previous section. This word is both a parsing word and an immediate word. Notice that there is a space between **.** and the start of the text **Hello and welcome**, but that there is no space between the last letter of **welcome** and the **"** character. The reason for this is that **.** is a Forth word; it must have a space after it so that the text interpreter can identify it. The **"** is not a Forth word; it is a *delimiter*. The examples earlier show that, when the string is displayed, there is neither a space before the **H** nor after the **e**. Since **.** is an immediate word, it executes at the time that **greet** is defined. When it executes, its behaviour is to search forward in the input line looking for the delimiter. When it finds the delimiter, it updates **>IN** to point past the delimiter. It also compiles some magic code into the definition of **greet**; the xt of a run-time routine that prints a text string. It compiles the string **Hello and welcome** into memory so that it is available to be printed later. When the text interpreter gains control, the next word it finds in the input stream is **;** and so it terminates the definition of **greet**.

4.5 Forth is written in Forth

When you start up a Forth compiler, a large number of definitions already exist. In Forth, you develop a new application using bottom-up programming techniques to create new definitions that are defined in terms of existing definitions. As you create each definition you can test and debug it interactively.

If you have tried out the examples in this section, you will probably have typed them in by hand; when you leave Gforth, your definitions will be lost. You can avoid this by using a text editor to enter Forth source code into a file, and then loading code from the file using **include** (see [\[Forth source files\]](#), page [\[undefined\]](#)). A Forth source file is processed by the text interpreter, just as though you had typed it in by hand³.

Gforth also supports the traditional Forth alternative to using text files for program entry (see [\[Blocks\]](#), page [\[undefined\]](#)).

³ Actually, there are some subtle differences – see [\[The Text Interpreter\]](#), page [\[undefined\]](#).

In common with many, if not most, Forth compilers, most of Gforth is actually written in Forth. All of the `.fs` files in the installation directory⁴ are Forth source files, which you can study to see examples of Forth programming.

Gforth maintains a history file that records every line that you type to the text interpreter. This file is preserved between sessions, and is used to provide a command-line recall facility. If you enter long definitions by hand, you can use a text editor to paste them out of the history file into a Forth source file for reuse at a later time (for more information see [\[Command-line editing\]](#), page [\(undefined\)](#)).

4.6 Review - elements of a Forth system

To summarise this chapter:

- Forth programs use *factoring* to break a problem down into small fragments called *words* or *definitions*.
- Forth program development is an interactive process.
- The main command loop that accepts input, and controls both interpretation and compilation, is called the *text interpreter* (also known as the *outer interpreter*).
- Forth has a very simple syntax, consisting of words and numbers separated by spaces or carriage-return characters. Any additional syntax is imposed by *parsing words*.
- Forth uses a stack to pass parameters between words. As a result, it uses postfix notation.
- To use a word that has previously been defined, the text interpreter searches for the word in the *name dictionary*.
- Words have *interpretation semantics* and *compilation semantics*.
- The text interpreter uses the value of `state` to select between the use of the *interpretation semantics* and the *compilation semantics* of a word that it encounters.
- The relationship between the *interpretation semantics* and *compilation semantics* for a word depends upon the way in which the word was defined (for example, whether it is an *immediate* word).
- Forth definitions can be implemented in Forth (called *high-level definitions*) or in some other way (usually a lower-level language and as a result often called *low-level definitions*, *code definitions* or *primitives*).
- Many Forth systems are implemented mainly in Forth.

4.7 Where To Go Next

Amazing as it may seem, if you have read (and understood) this far, you know almost all the fundamentals about the inner workings of a Forth system. You certainly know enough to be able to read and understand the rest of this manual and the Standard Forth document, to learn more about the facilities that Forth in general and Gforth in particular provide. Even scarier, you know almost enough to implement your own Forth system. However, that's not a good idea just yet... better to try writing some programs in Gforth.

⁴ For example, `/usr/local/share/gforth...`

Forth has such a rich vocabulary that it can be hard to know where to start in learning it. This section suggests a few sets of words that are enough to write small but useful programs. Use the word index in this document to learn more about each word, then try it out and try to write small definitions using it. Start by experimenting with these words:

- Arithmetic: `+` `-` `*` `/` `/MOD` `*/` `ABS` `INVERT`
- Comparison: `MIN` `MAX` `=`
- Logic: `AND` `OR` `XOR` `NOT`
- Stack manipulation: `DUP` `DROP` `SWAP` `OVER`
- Loops and decisions: `IF` `ELSE` `THEN` `?DO` `I` `LOOP`
- Input/Output: `.` `."` `EMIT` `CR` `KEY`
- Defining words: `:` `;` `CREATE`
- Memory allocation words: `ALLOT` `,`
- Tools: `SEE` `WORDS` `.S` `MARKER`

When you have mastered those, go on to:

- More defining words: `VARIABLE` `CONSTANT` `VALUE` `TO` `CREATE` `DOES>`
- Memory access: `@` `!`

When you have mastered these, there's nothing for it but to read through the whole of this manual and find out what you've missed.

4.8 Exercises

TODO: provide a set of programming exercises linked into the stuff done already and into other sections of the manual. Provide solutions to all the exercises in a `.fs` file in the distribution.

5 Literals in source code

5.1 Integer and character literals

To push an integer number on the data stack, you write the number in source code, e.g., 123. You can prefix the digits with `-` to indicate a negative number, e.g. `-123`. This works both inside colon definitions and outside. The number is interpreted according to the value in `base` (see [\[Number Conversion\]](#), page [\[undefined\]](#)). The digits are 0 to 9 and `a` (decimal 10) to `z` (decimal 35), but only digits smaller than `base @` are recognized. The conversion is case-insensitive, so `A` and `a` are the same digit.

You can make the base explicit for the number by using a prefix:

- `#` – decimal
- `%` – binary
- `$` – hexadecimal
- `&` – decimal (non-standard)
- `0x` – hexadecimal, if `base < 33` (non-standard).

For combinations including base-prefix and sign, the standard order is to have the base-prefix first (e.g., `#-123`); Gforth supports both orders.

You can put a decimal point `.` at the end of a number (or, non-standardly, anywhere else except before a prefix) to get a double-cell integer (e.g., `#-123.` or `#-.123` (the same number)). If users experienced in another programming language see or write such a number without base prefix (e.g., `-123.`), they may expect that the number represents a floating-point value. To clear up the confusion early, Gforth warns of such usage; to avoid the warnings, the best approach is to always write double numbers with a base prefix (e.g., `#-123.`)

Here are some examples, with the equivalent decimal number shown after in braces:

`$-41` (-65), `%1001101` (205), `%1001.0001` (145, a double-precision number), `#905` (905), `$abc` (2478), `$ABC` (2478).

You can get the numeric value of a (character) code point by surrounding the character with `'` (e.g., `'a'`). The trailing `'` is required by the standard, but you can leave it away in Gforth. Note that this also works for non-ASCII characters. For many uses, it is more useful to have the character as a string rather than as a cell; see below for the string syntax.

5.2 Floating-point number and complex literals

For floating-point numbers in Forth, you recognize them due to their exponent. I.e. `1.` is a double-cell integer, and `1e0` is a floating-point number; the latter can be (and usually is) shortened to `1e`. Both the significand (the part before the `e` or `E`) and the exponent may have signs (including `+`); the significand must contain at least one digit and may contain a decimal point, the exponent can be empty. Floating-point numbers always use decimal base for both significand and exponent, and are only recognized when the base is decimal. Examples are: `1e 1e0 1.e 1.e0 +1e+0` (which all represent the same number) `+12.E-4`.

A Gforth extension (since 1.0) is to write a floating-point number in scaled notation: It can optionally have a sign, then one or more digits, then use one of the mostly SI-defined

scaling symbols (aka metric prefixes) or %, and then optionally more digits. Here's the full list of scaling symbols that Gforth accepts:

- Q e30 quetta
- R e27 ronna
- Y e24 yotta
- Z e21 zetta
- X e18 exa (not E)
- P e15 peta
- T e12 tera
- G e9 giga
- M e6 mega
- k e3 kilo
- h e2 hecto
- d e-1 deci
- % e-2 percent (not c)
- m e-3 milli
- u e-6 micro (not μ)
- n e-9 nano
- p e-12 pico
- f e-15 femto
- a e-18 atto
- z e-21 zepto
- y e-24 yocto
- r e-27 ronto
- q e-30 quecto

Unlike most of the rest of Gforth, scaling symbols are treated case-sensitively. Using the scaled notation is equivalent to using a decimal point instead of the scaling symbol and appending the exponential notation at the end. Examples of scaled notation: `6k5` (6500e) `23%` (0.23e).

In Gforth (since 1.0) you can input a complex number with `real+imaginaryi`, where both `real` and `imaginary` are strings that are recognized as floating-point numbers. E.g., `1e+2ei`. This pushes the values `1e` and `2e` on the floating-point stack, so one might just as well have written `1e 2e`, but `1e+2ei` makes the intent obvious.

5.3 String and Environment variable Literals

In Gforth (since 1.0) you can input a string by surrounding it with `"` (e.g. `"abc"`, `"a b"`). The result is the starting address and byte (=char) count of the string on the data stack.

You have to escape any `"` inside the string with `\` (e.g., `"double-quote->\"<-"`). In addition, this string syntax supports all the ways to write control characters that are supported by `s\` (see [\[String and character literals\]](#), page [\[undefined\]](#)). A disadvantage of this string syntax is that it is non-standard; for standard programs, use `s\` instead.

In Gforth (since 1.0) you can input an environment variable by surrounding its name with `${...}`, e.g., `${HOME}`; the result is a string descriptor on the data stack in the format described above. This is equivalent to `"HOME" getenv`, i.e., the environment variable is resolved at run-time.

5.4 Literals for tokens and addresses

Gforth (since 1.0) also recognizes the following literals:

You can input an execution token (xt) of a word by prefixing the name of the word with the backquote ``` (e.g., ``dup`). An advantage over using `'` or `[]` is you do not need to switch between them when copying and pasting code from inside to outside a colon definition or vice versa. A disadvantage is that this syntax is non-standard.

You can input a name token (nt) of a word by prefixing the name of the word with ```` (e.g., ```dup`). This syntax is also non-standard.

You can input a body address of a word by surrounding it with `<` and `>` (e.g., `<spaces>`). You can also input an address that is at a positive offset from the body address (typically an address in that body), by putting `+` and a number (see syntax above) between the word name and the closing `>` (e.g., `<spaces+$15>`, `<spaces+-3>`). You will get the body address plus the number. This feature exists to allow copying and pasting the output of ... (see [\[Examining data\]](#), page [\[undefined\]](#)).

In addition, by default Gforth recognizes words with `rec-nt` and `rec-scope`, and stores in or adds to value-flavoured words with `rec-to`, but these do not recognize literals, so they are discussed elsewhere (see [\[Default Recognizers\]](#), page [\[undefined\]](#)).

5.5 Disambiguating recognizers

In some cases where two recognizers match the same string, you can specify in Gforth (since 1.0) which recognizer you want to use, with `recognizer?string`, where *recognizer* is the name of the recognizer without the `rec-` prefix, and *string* is the string you want to recognize. E.g., `float?1.` uses `rec-float` to recognize a string that would otherwise be recognized as a double-cell integer number (because `rec-num` is earlier in the recognizer sequence than `rec-float`).

6 Forth Words

6.1 Notation

The Forth words are described in this section in the glossary notation that has become a de-facto standard for Forth texts:

word Stack effect wordset pronunciation

Description

word The name of the word.

Stack effect

The stack effect is written in the notation *before* -- *after*, where *before* and *after* describe the top of stack entries before and after the execution of the word. The rest of the stack is not touched by the word. The top of stack is rightmost, i.e., a stack sequence is written as it is typed in.

Gforth has several stacks, in particular, the data stack, return stack and floating-point stack. However, it uses a unified stack effect notation, where one stack effect description describes all three stack effects, and the name of the item indicates which stack the item is on: floating-point stack items start with *r*. Return stack items are prefixed with *R*:, but are otherwise the same as data stack items. E.g., in the stack effect (*w1 w2 -- R:w1 R:w2*) *w1* is a cell on the data stack, and *R:w1* is a cell on the return stack with the same value. So a unified stack effect

(*r1 n1 R:n2 -- R:n3 n4 r2*)

is equivalent to the separated stack effect notation

(*n1 -- n4*) (*R: n2 -- n3*) (*F: r1 -- r2*)

The name of a stack item describes the type and/or the function of the item. See below for a discussion of the types.

Words generally have different stack effects in different contexts. If only one stack effect is shown, it's the stack effect for the execution/interpretation semantics.¹ The stack effect of default compilation semantics is (--) and is not shown.

The stack-effects of non-default compilation semantics are shown if they are other than (--). Such words usually also have a run-time semantics, and their stack effects are then shown as in this example

; (*compilation colon-sys -- ; run-time nest-sys --*)

Further stack effects, such as those of defined words, of passed xts, are shown in the description part of the glossary entry.

Also note that in code templates or examples there can be comments in parentheses that display the stack picture at this point; there is no -- in these places, because there is no before-after situation.

¹ Gforth 1.0 does not make a difference between interpretation and execution semantics.

pronunciation

How the word is pronounced.

wordset The wordset specifies if a word has been standardized (indicated by a capitalized wordset name), it is an environmental query string (indicated by “environment”), or if it is a Gforth-specific word (lower case).

The Forth standard is divided into several word sets. In theory, a standard system need not support all of them, but in practice, serious systems on non-tiny machines support almost all standardized words (some systems require explicit loading of some word sets, however), so it does not increase portability in practice to be parsimonious in using word sets.

For the Gforth-specific words, we have the following categories:

*gforth**gforth-<version>*

We intend to permanently support this word in Gforth and it has been available since Gforth *<version>* (possibly not as stable word at that time).

You see *gforth* in the source code (e.g., when using *locate*), and *gforth-<version>* in the documentation (e.g., when using *help*). So if you want to know since which Gforth version a word is available, use *help word*.

library The word belongs to a library that is independent of Gforth, but is delivered with Gforth and documented in this manual. Gforth 1.0 includes libraries with the following wordset names: *mini-oof* *mini-oof2* *minos2* *minos2-bidi* *objects* *oof* *regex-cg* *regex-pattern* *regex-replace* *cilk*

gforth-experimental

This word is available in the present version and may turn into a stable word or may be removed in a future release of Gforth. Feedback welcome.

gforth-internal

This word is an internal factor, not a supported word, and it may be removed in a future release of Gforth. If you see a word in the source code (e.g., with *locate*) without a wordset, that word is also an internal factor.

gforth-obsolete

This word will be removed in a future release of Gforth.

Description

A description of the behaviour of the word.

The type of a stack item is specified by the prefix of the name:

f Boolean flags, i.e. *false* or *true*.
c Char

w	
x	Cell, can contain an integer or an address
n	signed integer
u	unsigned integer
d	signed double-cell integer
ud	unsigned double-cell integer
r	Float (on the FP stack)
addr	Address without further information
a-	Cell-aligned address
c-	Char-aligned address, address used to point to a character or start of a string.
f-	Float-aligned address
df-	Address aligned for IEEE double precision float
sf-	Address aligned for IEEE single precision float
xt	Execution token, same size as Cell
nt	Name token, same size as Cell
wid	Word list ID, same size as Cell
ior, wior	I/O result code, cell-sized. In Gforth, you can throw iors.
"	String in the input stream (not on the stack), typically space-delimited.
'	String in the input stream, delimited by the last character before the closing ' . E.g., 'ccc" indicates a string in the input stream that is terminated by " .

6.2 Case insensitivity

Gforth is case-insensitive for ASCII characters and case-sensitive for non-ASCII characters. I.e., you can invoke Standard words using upper, lower or mixed case.

For now, Standard Forth only *requires* implementations to recognise Standard words when they are typed entirely in upper case. You can use whatever case you like for words that you define, but in a Standard program you have to use the words in the same case that you defined them.

Gforth supports case sensitivity through **cs-wordlists** (case-sensitive wordlists, see [\(undefined\)](#) [Word Lists], page [\(undefined\)](#)).

6.3 Comments

Forth supports two styles of comment; the *in-line* comment starting with **(** and ending with **)**, and the comment to the end of the line line starting with ****. Don't forget the space after the starting word.

((compilation 'ccc<close-paren>' - ; run-time -) core,file "paren"

Comment, usually till the next `)`: parse and discard all subsequent characters in the parse area until `)"` is encountered. During interactive input, an end-of-line also acts as a comment terminator. For file input, it does not; if the end-of-file is encountered whilst parsing for the `)"` delimiter, Gforth will generate a warning.

`\ (compilation 'ccc<newline>' - ; run-time -)` core-ext,block-ext “backslash”

Comment until the end of line: parse and discard all remaining characters in the parse area, except while `loading` from a block: while `loading` from a block, parse and discard all remaining characters in the 64-byte line.

`\G (compilation 'ccc<newline>' - ; run-time -)` gforth-0.2 “backslash-gee”

Equivalent to `\`. Used right below the start of a definition to describe the behaviour of a word. In Gforth’s source code these comments are those that are then inserted in the documentation.

6.4 Boolean Flags

A Boolean flag is cell-sized. A cell with all bits clear represents the flag `false` and a flag with all bits set represents the flag `true`. Words that check a flag (for example, `IF`) will treat a cell that has *any* bit set as `true`.

`true (- f)` core-ext “true”

`Constant - f` is a cell with all bits set.

`false (- f)` core-ext “false”

`Constant - f` is a cell with all bits clear.

`on (a-addr -)` gforth-0.2 “on”

Set the (value of the) variable at `a-addr` to `true`.

`off (a-addr -)` gforth-0.2 “off”

Set the (value of the) variable at `a-addr` to `false`.

`select (u1 u2 f - u)` gforth-1.0 “select”

If `f` is false, `u` is `u2`, otherwise `u1`.

6.5 Arithmetic

Forth arithmetic is not checked, i.e., you will not hear about integer overflow on addition or multiplication, you may hear about division by zero if you are lucky. The operator is written after the operands, but the operands are still in the original order. I.e., the infix `2-1` corresponds to `2 1 -`.

6.5.1 Single precision

By default, numbers in Forth are single-precision integers that are one cell (a machine word, e.g., 64 bits on a 64-bit system) in size. They can be signed or unsigned, depending upon how you treat them. For the rules used by the text interpreter for recognising single-precision integers see `<undefined>` [Literals], page `<undefined>`.

`+`, `1+`, `under+`, `-`, `1-`, `*` are defined for signed operands, but they also work for unsigned numbers. For division words see `<undefined>` [Integer division], page `<undefined>`.

`+` (`n1 n2 - n`) core “plus”

1+ (*n1* - *n2*) core “one-plus”
under+ (*n1* *n2* *n3* - *n* *n2*) gforth-0.3 “under-plus”
 add *n3* to *n1* (giving *n*)
- (*n1* *n2* - *n*) core “minus”
1- (*n1* - *n2*) core “one-minus”
***** (*n1* *n2* - *n*) core “star”
negate (*n1* - *n2*) core “negate”
abs (*n* - *u*) core “abs”
min (*n1* *n2* - *n*) core “min”
max (*n1* *n2* - *n*) core “max”
umin (*u1* *u2* - *u*) gforth-0.5 “umin”
umax (*u1* *u2* - *u*) gforth-1.0 “umax”

6.5.2 Double precision

For the rules used by the text interpreter for recognising double-precision integers, see [\[Literals\]](#), page [\[undefined\]](#).

A double precision number is represented by a cell pair, with the most significant cell at the top-of-stack (TOS). It is trivial to convert an unsigned single to a double: simply push a 0 onto the TOS. Numbers are represented by Gforth using 2’s complement arithmetic, so converting a signed single to a (signed) double requires sign-extension across the most significant cell. This can be achieved using **s>d**. You cannot convert a number from single-cell to double-cell without knowing whether it represents an unsigned or a signed number. By contrast, in 2’s complement arithmetic the conversion from double to single just **drops** the most significant cell, and **d>s** just documents the intent.

D+ and **d-** are defined for signed operands, but also work for unsigned numbers.

s>d (*n* - *d*) core “s-to-d”
d>s (*d* - *n*) double “d-to-s”
d+ (*ud1* *ud2* - *ud*) double “d-plus”
d- (*d1* *d2* - *d*) double “d-minus”
dnegate (*d1* - *d2*) double “d-negate”
dabs (*d* - *ud*) double “d-abs”
dmin (*d1* *d2* - *d*) double “d-min”
dmax (*d1* *d2* - *d*) double “d-max”

6.5.3 Mixed precision

m+ (*d1* *n* - *d2*) double “m-plus”
m* (*n1* *n2* - *d*) core “m-star”
um* (*u1* *u2* - *ud*) core “u-m-star”

6.5.4 Integer division

Below you find a considerable number of words for dealing with divisions. A major difference between them is in dealing with signed division: Do the words support signed division? Those with the `u` prefix do not.

Do signed division words round towards negative infinity (floored division, suffix `F`), or towards 0 (symmetric division, suffix `S`). The standard leaves the issue implementation-defined for most standard words (`/ mod /mod */ */mod m*/`). Gforth implements these words as floored (since Gforth 0.7), but there are systems that implement them as symmetric. There is only a difference between floored and symmetric division if the dividend and the divisor have different signs, and the dividend is not a multiple of the divisor. The following table illustrates the results:

dividend	divisor	floored		symmetric	
		remainder	quotient	remainder	quotient
10	7	3	1	3	1
-10	7	4	-2	-3	-1
10	-7	-4	-2	3	-1
-10	-7	-3	1	-3	1

The common case where floored vs. symmetric makes a difference is when dividends `n1` with varying sign are divided by the same positive divisor `n2`; in that case you usually want floored division, because then the remainder is always positive and does not change sign depending on the dividend; also, with floored division, the quotient always increases by 1 when `n1` increases by `n2`, while with symmetric division there is no increase in the quotient for $-n2 < n1 < n2$ (the quotient is 0 in this range).

In any case, if you divide numbers where floored vs. symmetric makes a difference, you should think about which variant is the right one for you, and then use either the appropriately suffixed Gforth words, or the standard words `fm/mod` or `sm/rem`.

In the following, “remainder” (symmetric) has the same sign as the dividend or is 0, while “modulus” (floored) has the same sign as the divisor or is 0.

The following words perform single-by-single-cell division:

`/ (n1 n2 - n)` core “slash”

`n=n1/n2`

`/s (n1 n2 - n)` gforth-1.0 “slash-s”

`/f (n1 n2 - n)` gforth-1.0 “slash-f”

`u/ (u1 u2 - u)` gforth-1.0 “u-slash”

`mod (n1 n2 - n)` core “mod”

`n` is the modulus of `n1/n2`

`mods (n1 n2 - n)` gforth-1.0 “mod-s”

`modf (n1 n2 - n)` gforth-1.0 “modf”

`umod (u1 u2 - u)` gforth-1.0 “umod”

`/mod (n1 n2 - n3 n4)` core “slash-mod”

`n1=n2*n4+n3`; `n3` is the modulus, `n4` the quotient.

`/mods (n1 n2 - n3 n4)` gforth-1.0 “slash-mod-s”

$n1=n2*n4+n3$; $n3$ is the remainder, $n4$ the quotient
`/modf (n1 n2 - n3 n4) gforth-1.0 “slash-mod-f”`

$n1=n2*n4+n3$; $n3$ is the modulus, $n4$ the quotient
`u/mod (u1 u2 - u3 u4) gforth-1.0 “u-slash-mod”`

$u1=u2*u4+u3$; $u3$ is the modulus, $u4$ the quotient

The following words perform double-by-single-cell division with single-cell results; these words are roughly as fast as the words above on some architectures (e.g., AMD64), but much slower on others (e.g., an order of magnitude on various ARM A64 CPUs).

`fm/mod (d1 n1 - n2 n3) core “f-m-slash-mod”`

Floored division: $d1 = n3*n1+n2$, $n1>n2>=0$ or $0>=n2>n1$.

`sm/rem (d1 n1 - n2 n3) core “s-m-slash-rem”`

Symmetric division: $d1 = n3*n1+n2$, $\text{sign}(n2)=\text{sign}(d1)$ or 0.

`um/mod (ud u1 - u2 u3) core “u-m-slash-mod”`

$ud=u3*u1+u2$, $0<=u2<u1$

`du/mod (d u - n u1) gforth-1.0 “du-slash-mod”`

$d=n*u+u1$, $0<=u1<u$; PolyForth style mixed division

`*/ ((n1 n2 n3 - n4) core “star-slash”`

$n4=(n1*n2)/n3$, with the intermediate result being double

`*/s (n1 n2 n3 - n4) gforth-1.0 “star-slash-s”`

$n4=(n1*n2)/n3$, with the intermediate result being double

`*/f (n1 n2 n3 - n4) gforth-1.0 “star-slash-f”`

$n4=(n1*n2)/n3$, with the intermediate result being double

`u*/ (u1 u2 u3 - u4) gforth-1.0 “u-star-slash”`

$u4=(u1*u2)/u3$, with the intermediate result being double.

`*/mod (n1 n2 n3 - n4 n5) core “star-slash-mod”`

$n1*n2=n3*n5+n4$, with the intermediate result $(n1*n2)$ being double; $n4$ is the modulus, $n5$ the quotient.

`*/mods (n1 n2 n3 - n4 n5) gforth-1.0 “star-slash-mod-s”`

$n1*n2=n3*n5+n4$, with the intermediate result $(n1*n2)$ being double; $n4$ is the remainder, $n5$ the quotient

`*/modf (n1 n2 n3 - n4 n5) gforth-1.0 “star-slash-mod-f”`

$n1*n2=n3*n5+n4$, with the intermediate result $(n1*n2)$ being double; $n4$ is the modulus, $n5$ the quotient

`u*/mod (u1 u2 u3 - u4 u5) gforth-1.0 “u-star-slash-mod”`

$u1*u2=u3*u5+u4$, with the intermediate result $(u1*u2)$ being double.

The following words perform division with double-cell results; these words are much slower than the words above.

`ud/mod (ud1 u2 - urem udquot) gforth-0.2 “ud/mod”`

divide unsigned double *ud1* by *u2*, resulting in a unsigned double quotient *uquot* and a single remainder *urem*.

m*/ (*d1 n2 u3 - dquot*) double “m-star-slash”

dquot=(*d1***n2*)/*u3*, with the intermediate result being triple-precision. In Forth-2012 *u3* is only allowed to be a positive signed number.

You can use the environmental query **floored** (see [\(undefined\)](#) [Environmental Queries], page [\(undefined\)](#)) to learn whether **/ mod /mod */ */mod m*/** use floored or symmetric division on the system your program is being loaded on; alternatively, **-1 3 /** also produces -1 on floored and 0 on symmetric systems.

One other aspect of the integer division words is that most of them can overflow, and division by zero is mathematically undefined. What happens if you hit one of these conditions depends on the engine, the hardware, and the operating system: The engine **gforth** tries hard to throw the appropriate error -10 (Division by zero) or -11 (Result out of range), but on some platforms throws -55 (Floating-point unidentified fault). The engine **gforth-fast** may produce an inappropriate throw code (and error message), or may produce no error, just produce a bogus value. I.e., you should not bet on such conditions being thrown, but for quicker debugging **gforth** catches more and produces more accurate errors than **gforth-fast**.

6.5.5 Two-stage integer division

On most hardware, multiplication is significantly faster than division. So if you have to divide many numbers by the same divisor, it is usually faster to determine the reciprocal of the divisor once and multiply the numbers with the reciprocal. If you divide by a constant, Gforth performs this optimization automatically.

However, for cases where the divisor is not known during compilation, Gforth provides words that allow you to implement this optimization without too much fuss.

Let’s start with an example: You want to divide all elements of an array of cells by the same number *n*. A straightforward way to implement this is:

```
: array/ ( addr u n -- )
  -rot cells bounds u+do
    i @ over / i !
  1 cells +loop
drop ;
```

A possibly more efficient version looks like this:

```
: array/ ( addr u n -- )
  {: | reci[ staged/-size ] :}
  reci[ /f-stage1m
  cells bounds u+do
    i @ reci[ /f-stage2m i !
  1 cells +loop ;
```

This example first creates a local buffer **reci[** with size **staged/-size** for storing the reciprocal data. Then **/f-stage1m** computes the reciprocal of *n* and stores it in **reci[**. Finally, inside the loop **/f-stage2m** uses the data in **reci[** to compute the quotient.

There are some limitations: Only positive divisors are supported for **/f-stage1m**; for **u/-stage1m** you can use a divisor of 2 or higher. You get an error if you try to use an

unsupported divisor. You must initialize the reciprocal buffer for the floored second-stage words with `/f-stage1m` and for the unsigned second-stage words with `u/-stage1m`. You must not modify the reciprocal buffer between the first stage and the second stage; basically, don't treat it as a memory buffer, but as something that is only mutable by the first stage; the point of this rule is that future versions of Gforth will not consider aliasing of this buffer.

Measurements show that staged division is not always beneficial:

<code>break</code>	100	<code>elem</code>	
<code>even</code>	<code>speedup</code>	<code>core</code>	
7	2.09	Skylake (Core i5-6600K)	
-	0.94	Rocket Lake (Xeon E-2388G)	
40	1.09	Golden Cove (Core i3-1315U P-core)	
-	0.85	Gracemont (Core i3-1315U E-core)	
6	1.68	Zen2 (Ryzen 9 3900X)	
-	0.56	Zen3 (Ryzen 7 5800X)	

The words are:

`staged/-size (- u) gforth-1.0 "staged-slash-size"`

Size of buffer for `u/-stage1m` or `/f-stage1m`.

`/f-stage1m (n a-reci -) gforth-1.0 "slash-f-stage1m"`

Compute the reciprocal of n and store it in the buffer *a-reci* of size `staged/-size`. Throws an error if $n < 1$.

`/f-stage2m (n1 a-reci - nquotient) gforth-1.0 "slash-f-stage2m"`

Nquotient is the result of dividing $n1$ by the divisor represented by *a-reci*, which was computed by `/f-stage1m`.

`modf-stage2m (n1 a-reci - umodulus) gforth-1.0 "mod-f-stage2m"`

Umodulus is the remainder of dividing $n1$ by the divisor represented by *a-reci*, which was computed by `/f-stage1m`.

`/modf-stage2m (n1 a-reci - umodulus nquotient) gforth-1.0 "slash-mod-f-stage2m"`

Nquotient is the quotient and *umodulus* is the remainder of dividing $n1$ by the divisor represented by *a-reci*, which was computed by `/f-stage1m`.

`u/-stage1m (u a-reci -) gforth-1.0 "u-slash-stage1m"`

Compute the reciprocal of u and store it in the buffer *a-reci* of size `staged/-size`. Throws an error if $u < 2$.

`u/-stage2m (u1 a-reci - uquotient) gforth-1.0 "u-slash-stage2m"`

Uquotient is the result of dividing $u1$ by the divisor represented by *a-reci*, which was computed by `u/-stage1m`.

`umod-stage2m (u1 a-reci - umodulus) gforth-1.0 "u-mod-stage2m"`

Umodulus is the remainder of dividing $u1$ by the divisor represented by *a-reci*, which was computed by `u/-stage1m`.

`u/mod-stage2m (u1 a-reci - umodulus uquotient) gforth-1.0 "u-slash-mod-stage2m"`

Uquotient is the quotient and *umodulus* is the remainder of dividing $u1$ by the divisor represented by *a-reci*, which was computed by `u/-stage1m`.

Gforth currently does not support staged symmetrical division.

You can recover the divisor from (the address of) a reciprocal with **staged/-divisor @**: **staged/-divisor (addr1 - addr2)** gforth-1.0 “staged-slash-divisor”

Addr1 is the address of a reciprocal, *addr2* is the address containing the divisor from which the reciprocal was computed.

This can be useful when looking at the decompiler output of Gforth: a division by a constant is often compiled to a literal containing the address of a reciprocal followed by a second-stage word.

The performance impact of using these words strongly depends on the architecture (does it have hardware division?) and the specific implementation (how fast is hardware division?), but just to give you an idea about the relative performance of these words, here are the cycles per iteration of a microbenchmark (which performs the mentioned word once per iteration) on two AMD64 implementations; the *norm* column shows the normal division word (e.g., *u/*), while the *stg2* column shows the corresponding stage2 word (e.g., *u/-stage2m*):

Skylake			Zen2		
norm	stg2		norm	stg2	
41.3	15.8	<i>u/</i>	35.2	21.4	<i>u/</i>
39.8	19.7	<i>umod</i>	36.9	25.8	<i>umod</i>
44.0	25.3	<i>u/mod</i>	43.0	33.9	<i>u/mod</i>
48.7	16.9	<i>/f</i>	36.2	22.5	<i>/f</i>
47.9	20.5	<i>modf</i>	37.9	27.1	<i>modf</i>
53.0	24.6	<i>/modf</i>	45.8	35.4	<i>/modf</i>
227.2		<i>u/stage1</i>	101.9		<i>u/stage1</i>
159.8		<i>/fstage1</i>	97.7		<i>/fstage1</i>

6.5.6 Bitwise operations

and (w1 w2 - w) core “and”

or (w1 w2 - w) core “or”

xor (w1 w2 - w) core “x-or”

invert (w1 - w2) core “invert”

mux (u1 u2 u3 - u) gforth-1.0 “mux”

Multiplex: For every bit in *u3*: for a 1 bit, select the corresponding bit from *u1*, otherwise the corresponding bit from *u2*. E.g., %0011 %1100 %1010 mux gives %0110

lshift (u1 u - u2) core “l-shift”

Shift *u1* left by *u* bits.

rshift (u1 u - u2) core “r-shift”

Shift *u1* (cell) right by *u* bits, filling the shifted-in bits with zero (logical/unsigned shift).

arshift (n1 u - n2) gforth-1.0 “ar-shift”

Shift *n1* (cell) right by *u* bits, filling the shifted-in bits from the sign bit of *n1* (arithmetic shift).

dlshift (ud1 u - ud2) gforth-1.0 “dlshift”

Shift *ud1* (double-cell) left by *u* bits.

drshift (ud1 u - ud2) gforth-1.0 “drshift”

Shift *ud1* (double-cell) right by *u* bits, filling the shifted-in bits with zero (logical/unsigned shift).

darshift (*d1 u - d2*) gforth-1.0 “darshift”

Shift *d1* (double-cell) right by *u* bits, filling the shifted-in bits from the sign bit of *d1* (arithmetic shift).

2* (*n1 - n2*) core “two-star”

Shift left by 1; also works on unsigned numbers

2/ (*n1 - n2*) core “two-slash”

Arithmetic shift right by 1. For signed numbers this is a floored division by 2 (note that / is symmetric on some systems, but 2/ always floors).

d2* (*d1 - d2*) double “d-two-star”

Shift double-cell left by 1; also works on unsigned numbers

d2/ (*d1 - d2*) double “d-two-slash”

Arithmetic shift right by 1. For signed numbers this is a floored division by 2.

>pow2 (*u1 - u2*) gforth-1.0 “to-pow2”

u2 is the lowest power-of-2 number with $u2 \geq u1$.

log2 (*u - n*) gforth-1.0 “log2”

N is the rounded-down binary logarithm of *u*, i.e., the index of the first set bit; if *u*=0, *n*=-1.

pow2? (*u - f*) gforth-1.0 “pow-two-query”

f is true if and only if *u* is a power of two, i.e., there is exactly one bit set in *u*.

ctz (*x - u*) gforth-1.0 “c-t-z”

count trailing zeros in binary representation of *x*

Unlike most other operations, rotation of narrower units cannot easily be synthesized from rotation of wider units, so using cell-wide and double-wide rotation operations means that the results depend on the cell width. For published algorithms or cell-width-independent results, you usually need to use a fixed-width rotation operation.

wrol (*u1 u - u2*) gforth-1.0 “wrol”

Rotate the least significant 16 bits of *u1* left by *u* bits, set the other bits to 0.

wror (*u1 u - u2*) gforth-1.0 “wror”

Rotate the least significant 16 bits of *u1* right by *u* bits, set the other bits to 0.

lrol (*u1 u - u2*) gforth-1.0 “lrol”

Rotate the least significant 32 bits of *u1* left by *u* bits, set the other bits to 0.

lror (*u1 u - u2*) gforth-1.0 “lror”

Rotate the least significant 32 bits of *u1* right by *u* bits, set the other bits to 0.

rol (*u1 u - u2*) gforth-1.0 “rol”

Rotate all bits of *u1* left by *u* bits.

ror (*u1 u - u2*) gforth-1.0 “ror”

Rotate all bits of *u1* right by *u* bits.

drol (*ud1 u - ud2*) gforth-1.0 “drol”

Rotate all bits of *ud1* (double-cell) left by *u* bits.

dror (*ud1 u ud2*) gforth-1.0 “dror”

Rotate all bits of *ud1* (double-cell) right by *u* bits.

6.5.7 Numeric comparison

All these comparison words produce -1 (all bits set) if the condition is true, otherwise 0. Note that the words that compare for equality (= <> 0= 0<> d= d<> d0= d0<>) work for both signed and unsigned numbers.

< (*n1 n2 f*) core “less-than”

<= (*n1 n2 f*) gforth-0.2 “less-or-equal”

<> (*n1 n2 f*) core-ext “not-equals”

= (*n1 n2 f*) core “equals”

> (*n1 n2 f*) core “greater-than”

>= (*n1 n2 f*) gforth-0.2 “greater-or-equal”

0< (*n f*) core “zero-less-than”

0<= (*n f*) gforth-0.2 “zero-less-or-equal”

0<> (*n f*) core-ext “zero-not-equals”

0= (*n f*) core “zero-equals”

0> (*n f*) core-ext “zero-greater-than”

0>= (*n f*) gforth-0.2 “zero-greater-or-equal”

u< (*u1 u2 f*) core “u-less-than”

u<= (*u1 u2 f*) gforth-0.2 “u-less-or-equal”

u> (*u1 u2 f*) core-ext “u-greater-than”

u>= (*u1 u2 f*) gforth-0.2 “u-greater-or-equal”

within (*u1 u2 u3 f*) core-ext “within”

u2<*u3* and *u1* in [*u2*,*u3*) or: *u2*>=*u3* and *u1* not in [*u3*,*u2*). This works for unsigned and signed numbers (but not a mixture). Another way to think about this word is to consider the numbers as a circle (wrapping around from **max-u** to 0 for unsigned, and from **max-n** to **min-n** for signed numbers); now consider the range from *u2* towards increasing numbers up to and excluding *u3* (giving an empty range if *u2*=*u3*); if *u1* is in this range, **within** returns true.

d< (*d1 d2 f*) double “d-less-than”

d<= (*d1 d2 f*) gforth-0.2 “d-less-or-equal”

d<> (*d1 d2 f*) gforth-0.2 “d-not-equals”

d= (*d1 d2 f*) double “d-equals”

d> (*d1 d2 f*) gforth-0.2 “d-greater-than”

d>= (*d1 d2 f*) gforth-0.2 “d-greater-or-equal”

d0< (*d f*) double “d-zero-less-than”

d0<= (*d f*) gforth-0.2 “d-zero-less-or-equal”

d0<> (*d f*) gforth-0.2 “d-zero-not-equals”

```

d0= ( d - f ) double "d-zero-equals"
d0> ( d - f ) gforth-0.2 "d-zero-greater-than"
d0>= ( d - f ) gforth-0.2 "d-zero-greater-or-equal"
du< ( ud1 ud2 - f ) double-ext "d-u-less-than"
du<= ( ud1 ud2 - f ) gforth-0.2 "d-u-less-or-equal"
du> ( ud1 ud2 - f ) gforth-0.2 "d-u-greater-than"
du>= ( ud1 ud2 - f ) gforth-0.2 "d-u-greater-or-equal"

```

6.5.8 Floating Point

For the rules used by the text interpreter for recognising floating-point numbers see `<undefined>` [Number Conversion], page `<undefined>`.

Gforth has a separate floating point stack, but the documentation uses the unified notation.²

Floating point numbers have a number of unpleasant surprises for the unwary (e.g., floating point addition is not associative) and even a few for the wary. You should not use them unless you know what you are doing or you don't care that the results you get may be totally bogus. If you want to learn about the problems of floating point numbers (and how to avoid them), you might start with *David Goldberg, What Every Computer Scientist Should Know About Floating-Point Arithmetic* (https://docs.oracle.com/cd/E19957-01/806-3568/ncg_goldberg.html), *ACM Computing Surveys* 23(1):5–48, March 1991.

Conversion between integers and floating-point:

```

s>f ( n - r ) floating-ext "s-to-f"
d>f ( d - r ) floating "d-to-f"
f>s ( r - n ) floating-ext "f-to-s"
f>d ( r - d ) floating "f-to-d"

```

Arithmetics:

```

f+ ( r1 r2 - r3 ) floating "f-plus"
f- ( r1 r2 - r3 ) floating "f-minus"
f* ( r1 r2 - r3 ) floating "f-star"
f/ ( r1 r2 - r3 ) floating "f-slash"
fnegate ( r1 - r2 ) floating "f-negate"
fabs ( r1 - r2 ) floating-ext "f-abs"
fcopysign ( r1 r2 - r3 ) gforth-1.0 "fcopysign"

```

`r3` takes its absolute value from `r1` and its sign from `r2`

```

fmax ( r1 r2 - r3 ) floating "f-max"
fmin ( r1 r2 - r3 ) floating "f-min"
floor ( r1 - r2 ) floating "floor"

```

² It's easy to generate the separate notation from that by just separating the floating-point numbers out: e.g. `(n r1 u r2 -- r3)` becomes `(n u --) (F: r1 r2 -- r3)`.

Round towards the next smaller integral value, i.e., round toward negative infinity.

fround (*r1* - *r2*) floating “f-round”

Round to the nearest integral value.

ftrunc (*r1* - *r2*) floating-ext “f-trunc”

round towards 0

f** (*r1* *r2* - *r3*) floating-ext “f-star-star”

$r3 = r1^{r2}$

fsqrt (*r1* - *r2*) floating-ext “f-square-root”

fexp (*r1* - *r2*) floating-ext “f-e-x-p”

$r2 = e^{r1}$

fexpm1 (*r1* - *r2*) floating-ext “f-e-x-p-m-one”

$r2 = e^{r1} - 1$

fln (*r1* - *r2*) floating-ext “f-l-n”

Natural logarithm: $r1 = e^{r2}$

flnp1 (*r1* - *r2*) floating-ext “f-l-n-p-one”

Inverse of **fexpm1**: $r1+1 = e^{r2}$

flog (*r1* - *r2*) floating-ext “f-log”

The decimal logarithm: $r1 = 10^{r2}$

falog (*r1* - *r2*) floating-ext “f-a-log”

$r2 = 10^{r1}$

f2* (*r1* - *r2*) gforth-0.2 “f2*”

Multiply *r1* by 2.0e0

f2/ (*r1* - *r2*) gforth-0.2 “f2/”

Multiply *r1* by 0.5e0

1/f (*r1* - *r2*) gforth-0.2 “1/f”

Divide 1.0e0 by *r1*.

Vector arithmetics:

v* (*f-addr1* *nstride1* *f-addr2* *nstride2* *ucount* - *r*) gforth-0.5 “v-star”

dot-product: $r = v1 * v2$. The first element of *v1* is at *f-addr1*, the next at *f-addr1*+*nstride1* and so on (similar for *v2*). Both vectors have *ucount* elements.

faxpy (*ra* *f-x* *nstridex* *f-y* *nstridey* *ucount* -) gforth-0.5 “faxpy”

$vy = ra * vx + vy$, where *vy* is the vector starting at *f-y* with stride *nstridey* bytes, and *vx* is the vector starting at *f-x* with stride *nstridex*, and both vectors contain *ucount* elements.

Angles in floating point operations are given in radians (a full circle has 2 pi radians).

fsin (*r1* - *r2*) floating-ext “f-sine”

fcos (*r1* - *r2*) floating-ext “f-cos”

fsincos (*r1* - *r2* *r3*) floating-ext “f-sine-cos”

```

    r2=sin(r1), r3=cos(r1)
ftan ( r1 - r2 ) floating-ext "f-tan"
fasin ( r1 - r2 ) floating-ext "f-a-sine"
facos ( r1 - r2 ) floating-ext "f-a-cos"
fatan ( r1 - r2 ) floating-ext "f-a-tan"
fatan2 ( r1 r2 - r3 ) floating-ext "f-a-tan-two"

```

$r1/r2=\tan(r3)$. Forth-2012 does not require, but probably intends this to be the inverse of `fsincos`. In Gforth it is.

```

fsinh ( r1 - r2 ) floating-ext "f-cinch"
fcosh ( r1 - r2 ) floating-ext "f-cosh"
ftanh ( r1 - r2 ) floating-ext "f-tan-h"
fasinh ( r1 - r2 ) floating-ext "f-a-cinch"
facosh ( r1 - r2 ) floating-ext "f-a-cosh"
fatanh ( r1 - r2 ) floating-ext "f-a-tan-h"
pi ( - r ) gforth-0.2 "pi"

```

Fconstant – r is the value pi; the ratio of a circle's area to its diameter.

Special values in IEEE754 can be derived by for example dividing by zero. The most common ones are defined as floating point constants for easy usage.

```

infinity ( - r ) gforth-1.0 "infinity"
floating point infinity
inf ( - r ) gforth-1.0 "inf"

```

Synonym of **infinity** to allow copying and pasting from the output of ..., See <undefined> [Examining data], page <undefined>.

```

-infinity ( - r ) gforth-1.0 "-infinity"
floating point -infinity
-inf ( - r ) gforth-1.0 "-inf"

```

Synonym of **-infinity** to allow copying and pasting from the output of ..., See <undefined> [Examining data], page <undefined>.

```

NaN ( - r ) gforth-1.0 "NaN"
floating point Not a Number

```

6.6 Floating-point comparisons

One particular problem with floating-point arithmetic is that comparison for equality often fails when you would expect it to succeed. For this reason approximate equality is often preferred (but you still have to know what you are doing). Also note that IEEE NaNs may compare differently from what you might expect. The comparison words are:

```

f~rel ( r1 r2 r3 - flag ) gforth-0.5 "f~rel"

```

Approximate equality with relative error: $|r1-r2| < r3 * |r1+r2|$.

```

f~abs ( r1 r2 r3 - flag ) gforth-0.5 "f~abs"

```

Approximate equality with absolute error: $|r1-r2|<r3$.

`f~ (r1 r2 r3 - flag) floating-ext “f-proximate”`

Forth-2012 medley for comparing `r1` and `r2` for equality: `r3>0: f~abs; r3=0: bitwise comparison; r3<0: fnegate f~rel.`

`f= (r1 r2 - f) gforth-0.2 “f-equals”`

`f<> (r1 r2 - f) gforth-0.2 “f-not-equals”`

`f< (r1 r2 - f) floating “f-less-than”`

`f<= (r1 r2 - f) gforth-0.2 “f-less-or-equal”`

`f> (r1 r2 - f) gforth-0.2 “f-greater-than”`

`f>= (r1 r2 - f) gforth-0.2 “f-greater-or-equal”`

`f0< (r - f) floating “f-zero-less-than”`

`f0<= (r - f) gforth-0.2 “f-zero-less-or-equal”`

`f0<> (r - f) gforth-0.2 “f-zero-not-equals”`

`f0= (r - f) floating “f-zero-equals”`

`f0> (r - f) gforth-0.2 “f-zero-greater-than”`

`f0>= (r - f) gforth-0.2 “f-zero-greater-or-equal”`

6.7 Stack Manipulation

Gforth maintains a number of separate stacks:

- A data stack (also known as the *parameter stack*) – for characters, cells, addresses, and double cells.
- A floating point stack – for holding floating point (FP) numbers.
- A return stack – for holding the return addresses of colon definitions and other (non-FP) data.
- A locals stack – for holding local variables.

6.7.1 Data stack

`drop (w -) core “drop”`

`nip (w1 w2 - w2) core-ext “nip”`

`dup (w - w w) core “dupe”`

`over (w1 w2 - w1 w2 w1) core “over”`

`third (w1 w2 w3 - w1 w2 w3 w1) gforth-1.0 “third”`

`fourth (w1 w2 w3 w4 - w1 w2 w3 w4 w1) gforth-1.0 “fourth”`

`swap (w1 w2 - w2 w1) core “swap”`

`rot (w1 w2 w3 - w2 w3 w1) core “rote”`

`-rot (w1 w2 w3 - w3 w1 w2) gforth-0.2 “not-rote”`

`tuck (w1 w2 - w2 w1 w2) core-ext “tuck”`

`pick (S:... u - S:... w) core-ext “pick”`

Actually the stack effect is `x0 ... xu u -- x0 ... xu x0 .`

`roll (x0 x1 .. xn n - x1 .. xn x0)` core-ext “roll”

`?dup (w - S:... w)` core “question-dupe”

Actually the stack effect is: `(0 -- 0 | x\0 -- x x)`. It performs a `dup` if `x` is nonzero.

`2drop (w1 w2 -)` core “two-drop”

`2nip (w1 w2 w3 w4 - w3 w4)` gforth-0.2 “two-nip”

`2dup (w1 w2 - w1 w2 w1 w2)` core “two-dupe”

`2over (w1 w2 w3 w4 - w1 w2 w3 w4 w1 w2)` core “two-over”

`2swap (w1 w2 w3 w4 - w3 w4 w1 w2)` core “two-swap”

`2rot (w1 w2 w3 w4 w5 w6 - w3 w4 w5 w6 w1 w2)` double-ext “two-rote”

`2tuck (w1 w2 w3 w4 - w3 w4 w1 w2 w3 w4)` gforth-0.2 “two-tuck”

6.7.2 Floating point stack

`fdrop (r -)` floating “f-drop”

`fnip (r1 r2 - r2)` gforth-0.2 “f-nip”

`fdup (r - r r)` floating “f-dupe”

`fover (r1 r2 - r1 r2 r1)` floating “f-over”

`fthird (r1 r2 r3 - r1 r2 r3 r1)` gforth-1.0 “fthird”

`ffourth (r1 r2 r3 r4 - r1 r2 r3 r4 r1)` gforth-1.0 “ffourth”

`fswap (r1 r2 - r2 r1)` floating “f-swap”

`frot (r1 r2 r3 - r2 r3 r1)` floating “f-rote”

`f-rot (r1 r2 r3 - r3 r1 r2)` gforth-1.0 “f-not-rote”

`ftuck (r1 r2 - r2 r1 r2)` gforth-0.2 “f-tuck”

`fpick (f:... u - f:... r)` gforth-0.4 “fpick”

Actually the stack effect is `r0 ... ru u -- r0 ... ru r0 .`

6.7.3 Return stack

The return stack primarily exists for storing system data, such as return addresses and loop control parameters, but Forth also allows programmers to make use of it, albeit with restrictions stemming from the other uses. The primary use is for temporary storage of data; locals also provide this capability, and usually in a more convenient way; some purists (or puritans) prefer to avoid locals, though.

In Gforth 1.0 you can use the return stack during text interpretation (and you cannot use locals for that). The only limitation here is that you cannot pass data on the return stack into or out of an included file, block, or `evaluated` string. Example:

```
1 >r
: foo [ r> ] literal ;
foo . \ prints 1
```

This interpretive usage of return-stack words is non-standard, and many other Forth systems do not have support this usage, or limit it to within one line.

In Gforth you can use the return stack for storing data while you also keep and access data in locals. However, the standard puts restrictions on mixing return stack and locals usage, for easy locals implementations, and there are systems that actually rely on these restrictions. So, if you want to produce a standard compliant program and you are using local variables in a definition, forget about return stack manipulations in that word (refer to the standard document for the exact rules).

```
>r ( w - R:w ) core "to-r"
r> ( R:w - w ) core "r-from"
r@ ( R:w - R:w w ) core "r-fetch"
r'@ ( r:w r:w2 - r:w r:w2 w ) gforth-1.0 "r-tick-fetch"
```

The second item on the return stack

```
rpick ( R:wu ... R:w0 u - R:wu ... R:w0 wu ) gforth-1.0 "rpick"
wu is the uth element on the return stack; 0 rpick is equivalent to r@.
rdrop ( R:w - ) gforth-0.2 "rdrop"
2>r ( w1 w2 - R:w1 R:w2 ) core-ext "two-to-r"
2r> ( R:w1 R:w2 - w1 w2 ) core-ext "two-r-from"
2r@ ( R:w1 R:w2 - R:w1 R:w2 w1 w2 ) core-ext "two-r-fetch"
2rdrop ( R:w1 R:w2 - ) gforth-0.2 "two-r-drop"
n>r ( x1 .. xn n - R:xn..R:x1 R:n ) tools-ext "n-to-r"
```

In Standard Forth, the order of items on the return stack is not specified, and the only thing you can do with the items on the return stack is to use **nr>**

```
nr> ( R:xn..R:x1 R:n - x1 .. xn n ) tools-ext "n-r-from"
```

In Standard Forth, the order of items on the return stack is not specified, and the only thing you can do with the items on the return stack is to use **nr>**

On some platforms (particularly, 32-bit platforms) floating-point numbers are not naturally aligned on the return stack and this can lead to (usually, but not always) small performance disadvantages.

```
f>r ( r - ) gforth-experimental "f-to-r"
Actual stack effect: ( r -- R:r )
fr> ( - r ) gforth-experimental "f-r-from"
Actual stack effect: ( R:r -- r )
fr@ ( - r ) gforth-experimental "f-r-fetch"
Actual stack effect: ( R:r -- R:r r )
```

6.7.4 Locals stack

Gforth uses a separate locals stack. It is described, along with the reasons for its existence, in [\[Locals implementation\]](#), page [\[undefined\]](#).

6.7.5 Stack pointer manipulation

In the stack effects of the following words, ignore the occurrences of “...” in the stack-pointer fetching words.

`sp0 (- a-addr) gforth-0.4 “sp0”`

User variable – initial value of the data stack pointer.

`sp@ (S:... - a-addr) gforth-0.2 “sp-fetch”`

`sp! (a-addr - S:...) gforth-0.2 “sp-store”`

`fp0 (- a-addr) gforth-0.4 “fp0”`

User variable – initial value of the floating-point stack pointer.

`fp@ (f:... - f-addr) gforth-0.2 “fp-fetch”`

`fp! (f-addr - f:...) gforth-0.2 “fp-store”`

`rp0 (- a-addr) gforth-0.4 “rp0”`

User variable – initial value of the return stack pointer.

`rp@ (- a-addr) gforth-0.2 “rp-fetch”`

`rp! (a-addr -) gforth-0.2 “rp-store”`

`lp0 (- a-addr) gforth-0.4 “lp0”`

User variable – initial value of the locals stack pointer.

`lp@ (- c-addr) gforth-0.2 “lp-fetch”`

C-addr is the current value of the locals stack pointer.

`lp! (c-addr -) gforth-internal “lp-store”`

6.8 Memory

In addition to the Standard Forth memory allocation words, there is also a garbage collector (<https://www.complang.tuwien.ac.at/forth/garbage-collection.zip>).

6.8.1 Memory model

Standard Forth considers a Forth system as consisting of several address spaces, of which only *data space* is managed and accessible with the memory words in standard programs. Memory not necessarily in data space includes the stacks, the code (called code space) and the headers (called name space). Gforth allows at least read access to all these logical spaces, but does not guarantee that code accessing the stacks, the threaded or native code, or the headers is portable or will work in the next Gforth version; Gforth provides some accessor words for these purposes, however.

Another division of memory is between dictionary and heap memory.³ In heap memory you can free allocations in arbitrary order, but you cannot grow allocations in-place (see `<undefined>` [Heap Allocation], page `<undefined>`). In dictionary memory deallocation is impractical for the most part, but you can grow allocations in place (see `<undefined>` [Dictionary allocation], page `<undefined>`). Gforth (since 1.0) allows having several sections

³ The term *dictionary* is also used to refer to the search data structure embodied in word lists and headers. The search data (word headers) reside in dictionary memory.

of dictionary memory in order to allow more flexibility in this growing (see [\[Sections\]](#), page [\(undefined\)](#)).

One relevant concept in this context is the *contiguous region*: It means a piece of memory that is contiguous, without any system data interleaved with it. In heap memory each allocation forms one contiguous region, and separate allocations are not contiguous with any other allocations. In dictionary memory all allocations in a section are contiguous, unless something happens that ends the contiguous region; a typical reason for ending a contiguous region is defining a word in that section.

Gforth provides one big address space, and address arithmetic can be performed between any addresses. However, in the dictionary headers or code are interleaved with data, so almost the only contiguous regions are those described by Standard Forth as contiguous; but you can be sure that, within a section the dictionary is allocated towards increasing addresses even between contiguous regions. The memory order of allocations in the heap is platform-dependent (and possibly different from one run to the next).

6.8.2 Dictionary allocation

Dictionary allocation is a stack-oriented allocation scheme, i.e., if you want to deallocate X, you also deallocate everything allocated after X.

The allocations using the words below are contiguous and grow the region towards increasing addresses. Other words that allocate dictionary memory of any kind (i.e., defining words including `:noname`) in the same section end the contiguous region and start a new one, but allocating memory in a different section does not end a contiguous region.

In Standard Forth only `created` words are guaranteed to produce an address that is the start of the following contiguous region. In particular, the cell allocated by `variable` is not guaranteed to be contiguous with following `alloted` memory.

You can deallocate memory by using `allot` with a negative argument (with some restrictions, see `allot`). For larger deallocations use `marker`.

`here` (`- addr`) core “here”

Return the address of the next free location in data space.

`unused` (`- u`) core-ext “unused”

Return the amount of free space remaining (in address units) in the region addressed by `here`.

`allot` (`n -`) core “allot”

Reserve n address units of data space without initialization. n is a signed number, passing a negative n releases memory. In Forth-2012 you can only deallocate memory from the current contiguous region in this way. In Gforth you can deallocate anything in this way but named words. The system does not check this restriction.

`->here` (`addr -`) gforth-1.0 “to-here”

Change the value of `here` to `addr`.

`c,` (`c -`) core “c-comma”

Reserve data space for one char and store c in the space.

`f,` (`f -`) gforth-0.2 “f-comma”

Reserve data space for one floating-point number and store f in the space.

`, (w -)` core “comma”

Reserve data space for one cell and store w in the space.

`2, (w1 w2 -)` gforth-0.2 “two-comma”

Reserve data space for two cells and store the double $w1\ w2$ there, $w2$ first (lower address).

`w, (x -)` gforth-1.0 “w-comma”

Reserve 2 bytes of data space and store the least significant 16 bits of x there.

`l, (l -)` gforth-1.0 “l-comma”

Reserve 4 bytes of data space and store the least significant 32 bits of x there.

`x, (x -)` gforth-1.0 “x-comma”

Reserve 8 bytes of data space and store (the least significant 64 bits) of x there. Reserve 8 bytes of data space and store w there.

`xd, (xd -)` gforth-1.0 “x-d-comma”

Reserve 8 bytes of data space and store the least significant 64 bits of x there.

`A, (addr -)` gforth-0.2 “a-comma”

Reserve data space for one cell, and store $addr$ there. For our cross-compiler this provides the type information necessary for a relocatable image; normally, though, this is equivalent to `,.`

`mem, (addr u -)` gforth-0.6 “mem,”

Reserve u bytes of dictionary space and copy u bytes starting at $addr$ there. If you want the memory to be aligned, precede `mem,` with an alignment word.

`save-mem-dict (addr1 u - addr2 u)` gforth-0.7 “save-mem-dict”

Copy the memory block $addr1\ u$ to a newly **alloted** memory block of size u ; the target memory block starts at $addr2$.

Memory accesses have to be aligned (see $\langle\text{undefined}\rangle$ [Address arithmetic], page $\langle\text{undefined}\rangle$). So of course you should allocate memory in an aligned way, too. I.e., before allocating a cell, **here** must be cell-aligned, etc. The words below align **here** if it is not already. Basically it is only already aligned for a type, if the last allocation was a multiple of the size of this type and if **here** was aligned for this type before.

After freshly **createing** a word, **here** is aligned in Standard Forth (**maxaligned** in Gforth).

`align (-)` core “align”

If the data-space pointer is not aligned, reserve enough space to align it.

`falign (-)` floating “f-align”

If the data-space pointer is not float-aligned, reserve enough space to align it.

`sfsalign (-)` floating-ext “s-f-align”

If the data-space pointer is not single-float-aligned, reserve enough space to align it.

`dfalign (-)` floating-ext “d-f-align”

If the data-space pointer is not double-float-aligned, reserve enough space to align it.

`maxalign (-)` gforth-0.2 “maxalign”

Align data-space pointer for all Forth alignment requirements.

6.8.3 Sections

If you want to do something that allocates memory from the dictionary or compiles code in the middle of a contiguous region of another dictionary allocation, or in the middle of a colon definition, that's not possible with a single dictionary pointer, leading to complicated workarounds.

Gforth provides dictionary sections to address this problem. Each section has its own dictionary pointer, and allocating or compiling something in one section does not interrupt the contiguity of allocations in other sections. In this respect Gforth's sections are similar to sections and segments in assembly languages.

One difference is that the most common usage of sections is as a stack of sections, which is useful for building nested definitions or dictionary-allocated data structures: Use `next-section` for the inner definition or data structure, switch back with `previous-section`.

Words like `latest` (see [\(undefined\) \[Name token\]](#), page [\(undefined\)](#)) and `latesttxt` (see [\(undefined\) \[Anonymous Definitions\]](#), page [\(undefined\)](#)) refer to the most recent definition in the current section. Quotations (see [\(undefined\) \[Quotations\]](#), page [\(undefined\)](#)) and the implicit quotation of `does>` (see [\(undefined\) \[User-defined defining words using CREATE\]](#), page [\(undefined\)](#)) are in a different section than the containing definition, so after the quotation ends (and the section is switched back), words like `latest` report the outer definition rather than the quotation.

An example of such a usage of the section stack is:

```
create my2x2matrix
  next-section here 1 , 2 , previous-section ,
  next-section here 3 , 4 , previous-section ,

\ now print my2x2matrix[0,1], i.e., "2":
my2x2matrix 0 cells + @ 1 cells + @ .
```

This works also for allocating section memory while compiling a definition, or defining a definition during a contiguous region, e.g.:

```
create mydispatchtable
  next-section :noname ." foo" ; previous-section ,
  next-section :noname ." bar" ; previous-section ,

\ now dispatch mydispatchtable[1]
mydispatchtable 1 cells + @ execute
```

Note that the interpretation semantics of `[:` (see [\(undefined\) \[Quotations\]](#), page [\(undefined\)](#)) switches to the next section internally, so you can write `mydispatchtable` also as follows:

```
create mydispatchtable
  [: ." foo" ;] ,
  [: ." bar" ;] ,
```

The interpretation semantics of `does>` uses a separate section, so the `does>` does not end the contiguous region, and you can define a word `mydispatch` that includes the dispatch code, as follows:

```
create mydispatch
```

```

does> ( u -- )
      ( u addr ) swap cells + @ execute ;
      [: ." foo" ;] ,
      [: ." bar" ;] ,

      1 mydispatch \ prints "bar"
next-section ( - ) gforth-1.0 "next-section"

```

Switch to the next section in the section stack. If there is no such section yet, create it (with the size being a quarter of the size of the current section).

```
previous-section ( - ) gforth-1.0 "previous-section"
```

Switch to the previous section in the section stack; the now-next section continues to exist with everything that was put there. Throw an exception if there is no previous section.

The bottom section in the section stack has the size given with the `--dictionary-size` command-line parameter (see `<undefined>` [Invoking Gforth], page `<undefined>`).

In addition to the stack of anonymous sections you can also have named sections that you define with:

```
extra-section ( usize "name" - ) gforth-1.0 "extra-section"
```

Define a new word *name* and create a section *s* with at least *usize* unused bytes. *Name* execution (... *xt* -- ...): When calling *name*, the current section is *c*. Switch the current section to be *s*, *execute* *xt*, then switch the current section back to *c*.

As an example, here's a variant of the `my2x2matrix` definition:

```

4 cells extra-section myvec

create my2x2matrix
  ' here myvec 1 ' , myvec 2 ' , myvec ,
  ' here myvec 3 ' , myvec 4 ' , myvec ,

```

Currently a named section does not start a dictionary stack, and using `next-section` inside a named section throws an error.

You can show the existing sections with:

```
.sections ( - ) gforth-1.0 "dot-sections"
```

Show all the sections and their status.

At the time of this writing this outputs:

	start	size	used	name
	\$7F9A5A516000	32768	96	noname
	\$7F9A5A1A1000	131072	208	noname
	\$7F9A5A1C2000	524288	2128	noname
	\$7F9A4BDFD000	2097152	32680	noname
>	\$7F9A4BFFE040	8388608	659272	Forth
	\$7F9A5A51F000	20480	1448	locals-headers

The lines describe the different sections: First the section stack, with sections called `noname` and (the bottom) `Forth`, then the extra-sections. The columns are the start address of the section, the gross size (including section management overhead), how much of the section is already used, and the name. The size and used columns are in decimal base.

In the section **Forth**, not all of the remaining size can be used for **allotting** memory, because room must be left for **pad** (see [\[Memory Blocks\]](#), page [\[undefined\]](#)). The current section is marked with **>**. Also, if you use **word** (see [\[The Input Stream\]](#), page [\[undefined\]](#)), you must leave room in the current section for the parsed string and its length byte.

6.8.4 Heap allocation

Heap allocation supports deallocation of allocated memory in any order. It does not affect dictionary allocation (i.e., heap allocation does not end a contiguous region). In Gforth, these words are implemented using the standard C library calls `malloc()`, `free()` and `realloc()`.

The memory region produced by one invocation of **allocate** or **resize** is internally contiguous. There is no contiguity between such a region and any other region (including others allocated from the heap).

allocate (*u* – *a_addr* *wior*) memory “allocate”

Allocate *u* address units of contiguous data space. This data space is not initialized. If the allocation is successful, *a_addr* is the start address of the allocated region and *wior* is 0. If the allocation fails, *a_addr* is arbitrary and *wior* is a non-zero I/O result code.

free (*a_addr* – *wior*) memory “free”

Return the region of data space starting at *a_addr* to the system. The region must originally have been obtained using **allocate** or **resize**, otherwise the result of **free** is unpredictable. If the operation is successful, *wior* is 0. If the operation fails, *wior* is a non-zero I/O result code.

resize (*a_addr1* *u* – *a_addr2* *wior*) memory “resize”

Change the size of the allocated area at *a_addr1* to *u* address units, possibly moving the contents to a different area. *a_addr2* is the address of the resulting area. If the operation is successful, *wior* is 0. If the operation fails, *wior* is a non-zero I/O result code. If *a_addr1* is 0, Gforth’s (but not the Standard) **resize** allocates *u* address units.

6.8.4.1 Memory blocks and heap allocation

Additional words for dealing with memory blocks are described in [\[Memory Blocks\]](#), page [\[undefined\]](#). An alternative to the following words are among the **\$string** words (see [\[String words\]](#), page [\[undefined\]](#)).

save-mem (*addr1* *u* – *addr2* *u*) gforth-0.2 “save-mem”

Copy the memory block *addr* *u* to *addr2*, which is the start of a newly heap allocated *u*-byte region.

extend-mem (*addr1* *u1* *u* – *addr* *addr2* *u2*) gforth-experimental “extend-mem”

Addr1 *u1* is a memory block in heap memory. Increase the size of this memory block by *u* aus, possibly reallocating it. *C-addr2* *u2* is the resulting memory block (*u2*=*u1*+*u*), *addr* is the start of the *u* additional aus (*addr*=*addr2*+*u1*).

free-mem-var (*addr* –) gforth-experimental “free-mem-var”

Addr is the address of a 2variable containing a memory block descriptor *c-addr* *u* in heap memory; **free-mem-var** frees the memory block and stores 0 0 in the 2variable.

Usage example:

```
2variable myblock
```

```
"foo" save-mem myblock 2!
myblock 2@ "bar" tuck >r >r extend-mem myblock 2! r> swap r> move
myblock 2@ type \ prints "foobar"
myblock free-mem-var
```

6.8.4.2 Growable memory buffers

The following words are useful for growable memory buffers. One can alternatively use `$strings` (see `<undefined>` [`$string words`], page `<undefined>`), and the differences are: When the used memory in the buffer shrinks, `$strings` may resize the buffer, while `adjust-buffer` does not, which may be preferable for a buffer that is reused all the time. However, `$strings` have one cell less memory overhead, and for longer-term storage the shrinking may be worthwhile.

`buffer% (u1 u2 -)` gforth-experimental “buffer-percent”

u1 is the alignment and *u2* is the size of a buffer descriptor.

`init-buffer (addr -)` gforth-experimental “init-buffer”

`adjust-buffer (u addr -)` gforth-experimental “adjust-buffer”

Adjust `buffer%` at `addr` to length *u*. This may grow the allocated area, but never shrinks it.

You can get the current address and length of such a buffer with `2@`.

Typical usage:

```
create mybuf buffer% %allot mybuf init-buffer
s" frobnicate" mybuf adjust-buffer mybuf 2@ move
mybuf 2@ type
s" foo" mybuf adjust-buffer mybuf 2@ move
mybuf 2@ type
```

6.8.5 Memory Access

`@ (a-addr - w)` core “fetch”

w is the cell stored at *a-addr*.

`! (w a-addr -)` core “store”

Store *w* into the cell at *a-addr*.

`+! (n a-addr -)` core “plus-store”

Add *n* to the cell at *a-addr*.

`!@ (w1 a-addr - w2)` gforth-experimental “store-fetch”

Fetch *w2* from *a-addr*, then store *w1* there. There is also `atomic!@` (see `<undefined>` [Hardware operations for multi-tasking], page `<undefined>`).

`+!@ (u1 a-addr - u2)` gforth-experimental “plus-store-fetch”

Fetch *u2* from *a-addr*, then increment this location by *u1*. There is also `atomic+!@` (see `<undefined>` [Hardware operations for multi-tasking], page `<undefined>`).

`c@ (c-addr - c)` core “c-fetch”

c is the char stored at *c-addr*.

`c! (c c-addr -)` core “c-store”

Store c into the char at $c\text{-}addr$.

2@ ($a\text{-}addr - w1\ w2$) core “two-fetch”

$w2$ is the content of the cell stored at $a\text{-}addr$, $w1$ is the content of the next cell.

2! ($w1\ w2\ a\text{-}addr -$) core “two-store”

Store $w2$ into the cell at $c\text{-}addr$ and $w1$ into the next cell.

f@ ($f\text{-}addr - r$) floating “f-fetch”

r is the float at address $f\text{-}addr$.

f! ($r\ f\text{-}addr -$) floating “f-store”

Store r into the float at address $f\text{-}addr$.

sf@ ($sf\text{-}addr - r$) floating-ext “s-f-fetch”

Fetch the single-precision IEEE floating-point value r from the address $sf\text{-}addr$.

sf! ($r\ sf\text{-}addr -$) floating-ext “s-f-store”

Store r as single-precision IEEE floating-point value to the address $sf\text{-}addr$.

df@ ($df\text{-}addr - r$) floating-ext “d-f-fetch”

Fetch the double-precision IEEE floating-point value r from the address $df\text{-}addr$.

df! ($r\ df\text{-}addr -$) floating-ext “d-f-store”

Store r as double-precision IEEE floating-point value to the address $df\text{-}addr$.

6.8.6 Special Memory Accesses

This section is about memory accesses useful for communicating with other software or other computers. This means that the accesses are of a certain bit width (independent of Gforth’s cell width), are possibly not naturally aligned and typically have a certain byte order that may be different from the native byte order of the system that Gforth runs on.

We use the following prefixes:

c	8 bits (character)
w	16 bits
l	32 bits
x	64 bits represented as one cell
xd	64 bits represented as two cells

The **x**-prefix words do not work properly on 32-bit systems, so for code that is intended to be portable to 32-bit systems you should use **xd**-prefix words. Note that **xd**-prefix words work on 64-bit systems: there the upper cell is just 0 (for unsigned values) or a sign extension of the lower cell.

The memory-access words below all work with arbitrarily (un)aligned addresses (unlike **@**, **!**, **f@**, **f!**, which require alignment on some hardware), and use native byte order (like these words),

w@ ($c\text{-}addr - u$) gforth-0.5 “w-fetch”

u is the zero-extended 16-bit value stored at $c\text{-}addr$.

w! ($w\ c\text{-}addr -$) gforth-0.7 “w-store”

Store the bottom 16 bits of w at c_addr .

l@ ($c_addr - u$) gforth-0.7 “l-fetch”

u is the zero-extended 32-bit value stored at c_addr .

l! ($w c_addr -$) gforth-0.7 “l-store”

Store the bottom 32 bits of w at c_addr .

x@ ($c_addr - u$) gforth-1.0 “x-fetch”

u is the zero-extended 64-bit value stored at c_addr .

x! ($w c_addr -$) gforth-1.0 “x-store”

Store the bottom 64 bits of w at c_addr .

xd@ ($c_addr - ud$) gforth-1.0 “x-d-fetch”

ud is the zero-extended 64-bit value stored at c_addr .

xd! ($ud c_addr -$) gforth-1.0 “x-d-store”

Store the bottom 64 bits of ud at c_addr .

For accesses with a specific byte order, you have to perform byte-order adjustment immediately after a fetch (before the sign-extension), or immediately before the store. The results of these byte-order adjustment words are always zero-extended.

wbe ($u1 - u2$) gforth-1.0 “wbe”

Convert 16-bit value in $u1$ from native byte order to big-endian or from big-endian to native byte order (the same operation)

wle ($u1 - u2$) gforth-1.0 “wle”

Convert 16-bit value in $u1$ from native byte order to little-endian or from little-endian to native byte order (the same operation)

lbe ($u1 - u2$) gforth-1.0 “lbe”

Convert 32-bit value in $u1$ from native byte order to big-endian or from big-endian to native byte order (the same operation)

lle ($u1 - u2$) gforth-1.0 “lle”

Convert 32-bit value in $u1$ from native byte order to little-endian or from little-endian to native byte order (the same operation)

xbe ($u1 - u2$) gforth-1.0 “xbe”

Convert 64-bit value in $u1$ from native byte order to big-endian or from big-endian to native byte order (the same operation)

xle ($u1 - u2$) gforth-1.0 “xle”

Convert 64-bit value in $u1$ from native byte order to little-endian or from little-endian to native byte order (the same operation)

xdbe ($ud1 - ud2$) gforth-1.0 “xdbe”

Convert 64-bit value in $ud1$ from native byte order to big-endian or from big-endian to native byte order (the same operation)

xdle ($ud1 - ud2$) gforth-1.0 “xdle”

Convert 64-bit value in $ud1$ from native byte order to little-endian or from little-endian to native byte order (the same operation)

For signed fetches with a specific byte order, you have first have to perform an unsigned fetch and a byte-order correction, and finally use a sign-extension word:

`c>s (x - n) gforth-1.0 “c-to-s”`

Sign-extend the 8-bit value in x to cell n .

`w>s (x - n) gforth-1.0 “w-to-s”`

Sign-extend the 16-bit value in x to cell n .

`l>s (x - n) gforth-1.0 “l-to-s”`

Sign-extend the 32-bit value in x to cell n .

`x>s (x - n) gforth-1.0 “x>s”`

Sign-extend the 64-bit value in x to cell n .

`xd>s (xd - d) gforth-1.0 “xd>s”`

Sign-extend the 64-bit value in xd to double-cell d .

Overall, this leads to sequences like

```
w@ wbe w>s    \ 16-bit unaligned signed big-endian fetch
>r lle r> 1! \ 32-bit unaligned little-endian store
```

6.8.7 Address arithmetic

Address arithmetic is the foundation on which you can build data structures like arrays, records (see [\[Structures\]](#), page [\(undefined\)](#)) and objects (see [\[Object-oriented Forth\]](#), page [\(undefined\)](#)).

Standard Forth does not specify the sizes of the data types. Instead, it offers a number of words (e.g., `cells`) for computing sizes and doing address arithmetic.

Address arithmetic is performed in terms of address units (aus); on most systems the address unit is one byte. There is also word-addressed⁴ hardware in some embedded systems, and on these systems the au is one cell. Finally, Forth-2012 also supports systems where a char needs more than one au. However, the common practice is that `1 chars` produces 1, and this will be standardized in the next release of the standard.

The basic address arithmetic words are `+` and `-`. E.g., if you have the address of a cell, perform `1 cells +`, and you will have the address of the next cell.

Standard Forth also defines words for aligning addresses for specific types. Some hardware requires that accesses to specific data types must only occur at specific addresses; e.g., that (4-byte) cells may only be accessed at addresses divisible by 4. Even if a machine allows unaligned accesses, it can usually perform aligned accesses faster.

For the performance-conscious: alignment operations are usually only necessary during the definition of a data structure, not during the (more frequent) accesses to it.

Standard Forth defines no words for character-aligning addresses, but given that `1 chars=1` is common practice, that’s not a big loss.

Standard Forth guarantees that addresses returned by `CREATED` words are cell-aligned; in addition, Gforth guarantees that these addresses are aligned for all Forth purposes.⁵

⁴ In Forth terminology: cell-addressed.

⁵ Some SIMD extensions of some instruction sets impose more severe alignment constraints that `create` currently does not satisfy.

Note that the Standard Forth word `char` has nothing to do with address arithmetic.

`chars` ($n1 - n2$) core “chars”

$n2$ is the number of address units of $n1$ chars.

`char+` ($c\text{-}addr1 - c\text{-}addr2$) core “char-plus”

1 chars +.

`char-` ($c\text{-}addr1 - c\text{-}addr2$) gforth-0.7 “char-minus”

1 chars -

`cells` ($n1 - n2$) core “cells”

$n2$ is the number of address units of $n1$ cells.

`cell+` ($a\text{-}addr1 - a\text{-}addr2$) core “cell-plus”

1 cells +

`cell-` ($a\text{-}addr1 - a\text{-}addr2$) core “cell-minus”

1 cells -

`cell/` ($n1 - n2$) gforth-1.0 “cell-divide”

$N2$ is the number of cells that fit into $n1$ aus, rounded towards negative infinity.

`cell` ($-u$) gforth-0.2 “cell”

Constant – 1 cells

`aligned` ($c\text{-}addr - a\text{-}addr$) core “aligned”

$a\text{-}addr$ is the smallest aligned address greater than or equal to $c\text{-}addr$.

`floats` ($n1 - n2$) floating “floats”

$n2$ is the number of address units of $n1$ floats.

`float+` ($f\text{-}addr1 - f\text{-}addr2$) floating “float-plus”

1 floats +.

`float` ($-u$) gforth-0.3 “float”

Constant – the number of address units corresponding to a floating-point number.

`float/` ($n1 - n2$) gforth-1.0 “float-divide”

$N2$ is the number of floats that fit into $n1$ aus, rounded towards negative infinity.

`faligned` ($c\text{-}addr - f\text{-}addr$) floating “f-aligned”

$f\text{-}addr$ is the first float-aligned address greater than or equal to $c\text{-}addr$.

`sfloats` ($n1 - n2$) floating-ext “s-floats”

$n2$ is the number of address units of $n1$ single-precision IEEE floating-point numbers.

`sfloat+` ($sf\text{-}addr1 - sf\text{-}addr2$) floating-ext “s-float-plus”

1 sfloats +.

`sfloat/` ($n1 - n2$) gforth-1.0 “s-float-divide”

$N2$ is the number of sfloats that fit into $n1$ aus, rounded towards negative infinity.

`sfaligned` ($c\text{-}addr - sf\text{-}addr$) floating-ext “s-f-aligned”

$sf\text{-}addr$ is the first single-float-aligned address greater than or equal to $c\text{-}addr$.

`dfloats` ($n1 - n2$) floating-ext “d-floats”

$n2$ is the number of address units of $n1$ double-precision IEEE floating-point numbers.

dfloat+ (*df-addr1* – *df-addr2*) floating-ext “d-float-plus”

1 dfloats +.

dfloat/ ($n1 - n2$) gforth-1.0 “d-float-divide”

$N2$ is the number of dfloats that fit into $n1$ aus, rounded towards negative infinity.

dfaligned (*c-addr* – *df-addr*) floating-ext “d-f-aligned”

df-addr is the first double-float-aligned address greater than or equal to *c-addr*.

maxaligned (*addr1* – *addr2*) gforth-0.2 “maxaligned”

addr2 is the first address after *addr1* that satisfies all alignment restrictions.

***aligned** (*addr1* *n* – *addr2*) gforth-1.0 “star-aligned”

addr2 is the aligned version of *addr1* with respect to the alignment n ; n must be a power of 2.

***align** ($n -$) gforth-1.0 “star-align”

Align **here** with respect to the alignment n .

waligned (*addr* – *addr'*) gforth-1.0 “waligned”

Addr' is the next even address \geq *addr*.

walign (–) gforth-1.0 “walign”

Align **here** to even.

laligned (*addr* – *addr'*) gforth-1.0 “laligned”

Addr' is the next address \geq *addr* divisible by 4.

lalign (–) gforth-1.0 “lalign”

Align **here** to be divisible by 4.

xaligned (*addr* – *addr'*) gforth-1.0 “xaligned”

Addr' is the next address \geq *addr* divisible by 8.

xalign (–) gforth-1.0 “xalign”

Align **here** to be divisible by 8.

The environmental query **address-unit-bits** (see [\(undefined\)](#) [Environmental Queries], page [\(undefined\)](#)) and the following words may be useful to those who want to write software portable to non-byte-addressed machines.

/w (– *u*) gforth-0.7 “slash-w”

address units for a 16-bit value

/l (– *u*) gforth-0.7 “slash-l”

address units for a 32-bit value

/x (– *u*) gforth-1.0 “slash-x”

address units for a 64-bit value

6.8.8 Memory Blocks

Memory blocks often represent character strings; For ways of storing character strings in memory see [\[String representations\]](#), page [\[undefined\]](#). For other string-processing words see [\[Displaying characters and strings\]](#), page [\[undefined\]](#).

In case you want to write a program that is portable to systems with `1 chars > 1` (not recommended), you have to note the difference between words that take a number of aus (e.g., `erase`) and words that take a number of chars (e.g., `blank`), and insert `chars` as appropriate.

When copying characters between overlapping memory regions, use `move`. `Cmove` and `cmove>` tend to be slower than a well-implemented `move`.

`move (c-from c-to ucount -) core “move”`

Copy the contents of `ucount` aus at `c-from` to `c-to`. `move` works correctly even if the two areas overlap.

`cmove (c-from c-to u -) string “c-move”`

Copy the contents of `ucount` characters from data space at `c-from` to `c-to`. The copy proceeds `char-by-char` from low address to high address; i.e., for overlapping areas it is safe if `c-to ≤ c-from`.

`cmove> (c-from c-to u -) string “c-move-up”`

Copy the contents of `ucount` characters from data space at `c-from` to `c-to`. The copy proceeds `char-by-char` from high address to low address; i.e., for overlapping areas it is safe if `c-to ≥ c-from`.

`fill (c-addr u c -) core “fill”`

Store `c` in `u` chars starting at `c-addr`.

`erase (addr u -) core-ext “erase”`

Clear all bits in `u` aus starting at `addr`.

`blank (c-addr u -) string “blank”`

Store the space character into `u` chars starting at `c-addr`.

`pad (- c-addr) core-ext “pad”`

`c-addr` is the address of a transient region that can be used as temporary data storage. At least 84 characters of space is available.

6.9 Strings and Characters

6.9.1 Characters

Forth supports chars (aka bytes), used by words such as `c@`; these can be used to represent an ASCII character.

Forth also supports extended characters, which may be represented by a sequence of several bytes (i.e., several chars). A common character encoding is the UTF-8 representation of Unicode.

In general, most code does not have to worry about extended characters: In the string representation it does not matter whether a byte is a part of an extended character, or it is a character by itself, and words that consume chars (like `emit`) also work when the extended

character is transferred as a sequence of chars. Forth still provides words for dealing with extended characters (see [\[Xchars and Unicode\]](#), page [\[undefined\]](#)).

In Unicode terms, chars are *code units*, whereas extended characters are *code points*. Note that an Unicode *abstract character* can consist of a sequence of code points, but Forth (like other programming languages) has no data type for individual abstract characters; of course, they can be represented as strings.

You can use the usual integer words on chars and Xchars on the stack, but Gforth also has some words for dealing with chars on the stack:

toupper (*c1* – *c2*) gforth-0.2 “toupper”

If *c1* is a lower-case ASCII character, *c2* is the equivalent upper-case character, otherwise *c2* is *c1*.

6.9.2 String representations

Forth commonly represents strings as cell pair *c-addr u* on the stack; *u* is the length of the string in bytes (aka chars), and *c-addr* is the address of the first byte of the string. Note that a code point may be represented by a sequence of several chars in the string (and a Unicode “abstract character” may consist of several code points). See [\[String words\]](#), page [\[undefined\]](#).

Another string representation is used with the string library of words containing **\$**. It represents the string on the stack through the address of a cell-sized string handle, which can be located in, e.g., a variable. See [\[\\$string words\]](#), page [\[undefined\]](#).

A legacy string representation are *counted strings*, represented on the stack by *c-addr*. The char addressed by *c-addr* contains a character-count, *n*, of the string and the string occupies the subsequent *n* char addresses in memory. Counted strings are limited to 255 bytes in length. While counted strings may look attractive due to needing only one stack item, due to their limitations we recommend avoiding them, especially as input parameters of words. See [\[Counted string words\]](#), page [\[undefined\]](#).

6.9.3 String and Character literals

The nicest way to write a string literal is to write it as **"STRING"**. For these kinds of string literals as well as for **s** some sequences are not put in the resulting string as is, but are replaced as shown below. The sequences are mostly the same as in C (exceptions noted):

\a	7 #bell (alert)
\b	8 #bs (backspace)
\e	27 #esc (escape, not in C99)
\f	12 #ff (form feed)
\l	10 #lf (line feed, not in C)
\m	13 10 CR LF (not in C)
\n	sequence produced by newline (in C this produces a LF)
\q	34 " (double quote, not in C)
\r	13 #cr (carriage return)

<code>\t</code>	9 <code>#tab</code> (horizontal tab)
<code>\uXXXX</code>	Unicode code point <code>XXXX</code> (in hex); auto-merges surrogate pairs (not in Forth-2012 nor C)
<code>\UXXXXXXXX</code>	Unicode code point <code>XXXXXXXX</code> (in hex, not in Forth-2012 nor C)
<code>\v</code>	11 VT (vertical tab)
<code>\xXX</code>	raw byte (not code point) <code>XX</code> (in hex)
<code>\z</code>	0 NUL (not in C)
<code>\\</code>	<code>\</code>
<code>\"</code>	<code>"</code> (the <code>\</code> does not terminate the string; not in Forth-2012)
<code>\XXX</code>	raw byte; <code>XXX</code> is 1-3 octal digits (not in Forth-2012).

A `\` before any other character is reserved.

Note that `\xXX` produces raw bytes, while `\uXXXX` and `\UXXXXXXXX` produce code points for the current encoding. E.g., if we use UTF-8 encoding and want to encode ä (code point U+00E4), you can write the letter ä itself, or write `\xc3\xa4` (the UTF-8 bytes for this code point), `\u00e4`, or `\U000000e4`.

The `"STRING"` syntax is non-standard, so for portability you may want to use one of the following words:

`s\"` (*Interpretation* 'ccc' – *c-addr u*) core-ext,file-ext “s-backslash-quote”

Interpretation: Parse the string *ccc* delimited by a `"` (but not `\`), and convert escaped characters as described above. Store the resulting string in newly allocated heap memory, and push its descriptor *c-addr u*.

Compilation (`'ccc' --`): Parse the string *ccc* delimited by a `"` (but not `\`), and convert escaped characters as described above. Append the run-time semantics below to the current definition.

Run-time (`-- c-addr u`): Push a descriptor for the resulting string.

`S"` (*Interpretation* 'ccc' – *c-addr u*) core,file “s-quote”

Interpretation: Parse the string *ccc* delimited by a `"` (double quote). Store the resulting string in newly allocated heap memory, and push its descriptor *c-addr u*.

Compilation (`'ccc' --`): Parse the string *ccc* delimited by a `"` (double quote). Append the run-time semantics below to the current definition.

Run-time (`-- c-addr u`): Push a descriptor for the parsed string.

All these ways of interpreting strings consume heap memory; normally you can just live with the string consuming memory until the end of the Gforth session, but if that is a problem for some reason, you can **free** the string when you no longer need it. Forth-2012 only guarantees two buffers of 80 characters each, so in standard programs you should assume that the string lives only until the next-but-one `s"`.

On the other hand, the compilation semantics of string literals of any form allocates the string in the dictionary, and you cannot **free** it, and it lives as long as the word it is compiled into (also in Forth-2012).

Likewise, You can get the code *xc* of a character *C* with '*C*'. This way has been standardized since Forth-2012. An older way to get it is to use one of the following words:

```
char ( '<spaces>ccc' - c ) core,xchar-ext "char"
```

Skip leading spaces. Parse the string *ccc* and return *c*, the display code representing the first character of *ccc*.

```
[char] ( compilation '<spaces>ccc' - ; run-time - c ) core,xchar-ext "bracket-char"
```

Compilation: skip leading spaces. Parse the string *ccc*. Run-time: return *c*, the display code representing the first character of *ccc*. Interpretation semantics for this word are undefined.

You usually use **char** outside and **[char]** inside colon definitions, or you just use '*C*'.

Note that, e.g.,

```
"C" type
```

is (slightly) more efficient than

```
'C' xemit
```

because the latter converts the code point into a sequence of bytes and individually **emits** them. Similarly, dealing with general characters is usually more efficient when representing them as strings rather than code points.

There are the following words for producing commonly-used characters and strings that cannot be produced with **S"** or '*C*':

```
newline ( - c-addr u ) gforth-0.5 "newline"
```

String containing the newline sequence of the host OS

```
bl ( - c-char ) core "b-l"
```

c-char is the character value for a space.

```
#tab ( - c ) gforth-0.2 "number-tab"
```

```
#lf ( - c ) gforth-0.2 "number-l-f"
```

```
#cr ( - c ) gforth-0.2 "number-c-r"
```

```
#ff ( - c ) gforth-0.2 "number-f-f"
```

```
#bs ( - c ) gforth-0.2 "number-b-s"
```

```
#del ( - c ) gforth-0.2 "number-del"
```

```
#bell ( - c ) gforth-0.2 "number-bell"
```

```
#esc ( - c ) gforth-0.5 "number-esc"
```

```
#eof ( - c ) gforth-0.7 "number-e-o-f"
```

actually EOT (ASCII code 4 aka **^D**)

6.9.4 String words

Words that are used for memory blocks are also useful for strings, so for words that move, copy, and fill strings, see [\[Memory Blocks\]](#), page [\[undefined\]](#). For words that display characters and strings, see [\[Displaying characters and strings\]](#), page [\[undefined\]](#).

The following words work on previously existing strings:

```
compare ( c-addr1 u1 c-addr2 u2 - n ) string "compare"
```

Compare two strings lexicographically, based on the values of the bytes in the strings (i.e., case-sensitive and without locale-specific collation order). If they are equal, *n* is 0; if the string in *c-addr1 u1* is smaller, *n* is -1; if it is larger, *n* is 1.

str= (*c-addr1 u1 c-addr2 u2 - f*) gforth-0.6 “str-equals”

Byte-wise equality

str< (*c-addr1 u1 c-addr2 u2 - f*) gforth-0.6 “str-less-than”

Byte-wise lexicographic comparison.

string-prefix? (*c-addr1 u1 c-addr2 u2 - f*) gforth-0.6 “string-prefix-question”

Is *c-addr2 u2* a prefix of *c-addr1 u1*?

string-suffix? (*c-addr1 u1 c-addr2 u2 - f*) gforth-1.0 “string-suffix-question”

Is *c-addr2 u2* a suffix of *c-addr1 u1*?

search (*c-addr1 u1 c-addr2 u2 - c-addr3 u3 flag*) string “search”

Search the string specified by *c-addr1, u1* for the string specified by *c-addr2, u2*. If *flag* is true: match was found at *c-addr3* with *u3* characters remaining. If *flag* is false: no match was found; *c-addr3, u3* are equal to *c-addr1, u1*.

scan (*c-addr1 u1 c - c-addr2 u2*) gforth-0.2 “scan”

Skip all characters not equal to *c*. The result starts with *c* or is empty. **Scan** is limited to single-byte (ASCII) characters. Use **search** to search for multi-byte characters.

scan-back (*c-addr u1 c - c-addr u2*) gforth-0.7 “scan-back”

The last occurrence of *c* in *c-addr u1* is at *c-addr+u2-1*; if it does not occur, *u2=0*.

skip (*c-addr1 u1 c - c-addr2 u2*) gforth-0.2 “skip”

Skip all characters equal to *c*. The result starts with the first non-*c* character, or it is empty. **Scan** is limited to single-byte (ASCII) characters.

\$split (*c-addr u char - c-addr u1 c-addr2 u2*) gforth-0.7 “string-split”

Divides a string *c-addr u* into two, with *char* as separator. *U1* is the length of the string up to, but excluding the first occurrence of the separator, *c-addr2 u2* is the part of the input string behind the separator. If the separator does not occur in the string, *u1=u*, *u2=0* and *c-addr2=c-addr+u*.

nosplit? (*addr1 u1 addr2 u2 - addr1 u1 addr2 u2 flag*) gforth-experimental “nosplit?”

Used on the result of **\$split**, *flag* is true if and only if the separator does not occur in the input string of **\$split**.

-trailing (*c-addr u1 - c-addr u2*) string “dash-trailing”

Adjust the string specified by *c-addr, u1* to remove all trailing spaces. *u2* is the length of the modified string.

/string (*c-addr1 u1 n - c-addr2 u2*) string “slash-string”

Adjust the string specified by *c-addr1, u1* to remove *n* characters from the start of the string.

safe/string (*c-addr1 u1 n - c-addr2 u2*) gforth-1.0 “safe-slash-string”

Adjust the string specified by *c-addr1, u1* to remove *n* characters from the start of the string. Unlike **/string**, **safe/string** removes at least 0 and at most *u1* characters.

insert (*c-addr1 u1 c-addr2 u2 -*) gforth-0.7 “insert”

Move the contents of the buffer *c-addr2 u2* towards higher addresses by *u1* chars, and copy the string *c-addr1 u1* into the first *u1* chars of the buffer.

delete (*c-addr u u1* -) gforth-0.7 “delete”

In the memory block *c-addr u*, delete the first *u1* chars by copying the contents of the block starting at *c-addr+u1* there; fill the *u1* characters at the end of the block with blanks.

cstring>sstring (*c-addr* - *c-addr u*) gforth-0.2 “cstring-to-sstring”

C-addr is the start address of a zero-terminated string, *u* is its length.

The following words compare case-insensitively for ASCII characters, but case-sensitively for non-ASCII characters (like in lookup in wordlists).

capscompare (*c-addr1 u1 c-addr2 u2* - *n*) gforth-0.7 “capscompare”

Compare two strings lexicographically, based on the values of the bytes in the strings, but comparing ASCII characters case-insensitively, and non-ASCII characters case-sensitively and without locale-specific collation order. If they are equal, *n* is 0; if the first string is smaller, *n* is -1; if the first string is larger, *n* is 1.

capsstring-prefix? (*c-addr1 u1 c-addr2 u2* - *f*) gforth-1.0 “capsstring-prefix?”

Like **string-prefix?**, but case-insensitive for ASCII characters: Is *c-addr2 u2* a prefix of *c-addr1 u1*?

capssearch (*c-addr1 u1 c-addr2 u2* - *c-addr3 u3 flag*) gforth-1.0 “capssearch”

Like **search**, but case-insensitive for ASCII characters: Search for *c-addr2 u2* in *c-addr1 u1*; *flag* is true if found.

The following words create or extend strings on the heap:

s+ (*c-addr1 u1 c-addr2 u2* - *c-addr u*) gforth-0.7 “s-plus”

c-addr u is a newly allocated string that contains the concatenation of *c-addr1 u1* (first) and *c-addr2 u2* (second).

append (*c-addr1 u1 c-addr2 u2* - *c-addr u*) gforth-0.7 “append”

C-addr u is the concatenation of *c-addr1 u1* (first) and *c-addr2 u2* (second). *c-addr1 u1* is an allocated string, and **append** resizes it (possibly moving it to a new address) to accommodate *u* characters.

>string-execute (... *xt* - ... *c-addr u*) gforth-1.0 “>string-execute”

Execute *xt* while the standard output (**type**, **emit**, and everything that uses them) is redirected to a string. The resulting string is *c-addr u*, which is in heap memory; it is the responsibility of the caller of **>string-execute** to **free** this string.

\$tmp (*xt* - *addr u*) gforth-1.0 “string-t-m-p”

Like **>string-execute**, but the result is deallocated when **\$tmp** is invoked the next time, and you must not **free** it yourself.

One could define **s+** using **>string-execute**, as follows:

```
: s+ ( c-addr1 u1 c-addr2 u2 -- c-addr u )
  [: 2swap type type ;] >string-execute ;
```

For concatenating just two strings **>string-execute** is inefficient, but for concatenating many strings **>string-execute** can be more efficient.

6.9.5 String words

The following string library stores strings in ordinary cell-size variables (string handles). These handles contain a pointer to a cell-counted string allocated from the heap. The string library originates from bigFORTH.

Because there is only one permanent reference to the contents (the one in the handle), the string can be relocated or deleted without worrying about dangling references; this requires that the programmer uses references produced by, e.g., `$@` only for temporary purposes, i.e., these references are not passed out, e.g., as return values or stored in global memory, and words that may change the handle are not called while these references exist.

This library is complemented by the cell-pair representation: You use the `$string` words for variable strings which are cumbersome with the `c-addr u` representation. You use the cell-pair representation for processing (e.g., inspecting) strings while they do not change.

`$! (addr1 u $addr -) gforth-0.7 "string-store"`

stores a newly allocated string buffer at an address, frees the previous buffer if necessary.

`$@ ($addr - addr2 u) gforth-0.7 "string-fetch"`

returns the stored string.

`$@len ($addr - u) gforth-0.7 "string-fetch-len"`

returns the length of the stored string.

`$!len (u $addr -) gforth-0.7 "string-store-len"`

changes the length of the stored string. Therefore we must change the memory area and adjust address and count cell as well.

`$+!len (u $addr - addr) gforth-1.0 "string-plus-store-len"`

make room for `u` bytes at the end of the memory area referenced by `$addr`; `addr` is the address of the first of these bytes.

`$del ($addr off u -) gforth-0.7 "string-del"`

Deletes `u` bytes at offset `off` bytes in the string `$addr`.

`$ins (addr1 u $addr off -) gforth-0.7 "string-ins"`

Inserts string `addr1 u` at offset `off` bytes in the string `$addr`.

`$+! (addr1 u $addr -) gforth-0.7 "string-plus-store"`

appends a string to another.

`c$+! (char $addr -) gforth-1.0 "c-string-plus-store"`

append a character to a string.

`$free ($addr -) gforth-1.0 "string-free"`

free the string pointed to by `addr`, and set `addr` to 0

`$init ($addr -) gforth-1.0 "string-init"`

store an empty string there, regardless of what was in before

`$iter (.. $addr char xt - ..) gforth-0.7 "string-iter"`

Splits the string in `$addr` using `char` as separator. For each part, its descriptor `c-addr u` is pushed and `xt (... c-addr u -- ...)` is executed.

`$over (addr u $addr off -) gforth-1.0 "string-over"`

Overwrite *u* bytes at offset *off* bytes in the string *\$addr* with the string at *addr u*.

\$exec (*xt \$addr -*) gforth-1.0 “string-exec”

execute *xt* while the standard output (TYPE, EMIT, and everything that uses them) is appended to the string in *\$addr*.

\$. (*\$addr -*) gforth-1.0 “string-dot”

print a string, shortcut

\$slurp (*fid \$addr -*) gforth-1.0 “string-slurp”

Read the file *fid* until the end (without closing it) and put the read data into the string at *\$addr*.

\$slurp-file (*c-addr u \$addr -*) gforth-1.0 “string-slurp-file”

Put all the data in the file named *c-addr u* into the string at *\$addr*.

\$+slurp (*fid \$addr -*) gforth-1.0 “string-plus-slurp”

Read the file *fid* until the end (without closing it) and append the read data to the string at *\$addr*.

\$+slurp-file (*c-addr u \$addr -*) gforth-1.0 “string-plus+slurp-file”

Append all the data in the file named *c-addr u* to the string at *\$addr*.

\$[] (*u \$[]addr - addr'*) gforth-1.0 “string-array”

Addr' is the address of the *uth* element of the string array *\$[]addr*. The array is resized if needed.

\$[]! (*c-addr u n \$[]addr -*) gforth-1.0 “string-array-store”

Store string *c-addr y* into the string array *\$[]addr* at index *n*. The array is resized if needed.

\$[]+! (*c-addr u n \$[]addr -*) gforth-1.0 “string-array-plus-store”

Append the string *c-addr u* to the string at index *n*. The array is resized if needed. Don't confuse this with **\$+[]!**.

\$+[]! (*c-addr u \$[]addr -*) gforth-1.0 “string-append-array”

Store the string *c-addr u* as the new last element of string array *\$[]addr*. The array is resized if needed.

\$[]@ (*n \$[]addr - addr u*) gforth-1.0 “string-array-fetch”

fetch a string from array index *n* — return the zero string if empty, and don't accidentally grow the array.

\$[]# (*\$[]addr - len*) gforth-1.0 “string-array-num”

return the number of elements in an array

\$[]map (*\$[]addr xt -*) gforth-1.0 “string-array-map”

execute *xt* for all elements of the string array *\$[]addr*. *xt* is (*addr u -*), getting one string at a time

\$[]slurp (*fid \$[]addr -*) gforth-1.0 “string-array-slurp”

slurp a file *fid* line by line into a string array *\$[]addr*

\$[]slurp-file (*addr u \$[]addr -*) gforth-1.0 “string-array-slurp-file”

slurp a named file *addr* *u* line by line into a string array *\$/addr*

```
$[] . ( $/addr - ) gforth-1.0 "string-array-dot"
```

print all array entries

```
$[]free ( $/addr - ) gforth-1.0 "string-array-free"
```

\$/addr contains the address of a cell-counted string that contains the addresses of a number of cell-counted strings; *\$[]free* frees these strings, frees the array, and sets *addr* to 0

```
$Variable ( "name" - ) gforth-1.0 "string-variable"
```

Defines a string variable whose content is preserved across savesystem

```
$[]Variable ( "name" - ) gforth-1.0 "string-array-variable"
```

Defines a string array variable whose content is preserved across savesystem

6.9.6 Counted string words

Counted strings store the length as byte at the address pointed to, followed by the bytes of the string. Their possible length is severely limited, and you cannot create a substring in-place without destroying the input string. Therefore we recommend against using counted strings. Nevertheless, if you have to deal with counted strings, here are some words for that:

```
count ( c-addr1 - c-addr2 u ) core "count"
```

c-addr2 is the first character and *u* the length of the counted string at *c-addr1*.

The following word has no useful interpretation semantics (unlike *s*) and no interpretive counterpart (unlike *[char]*), so you should use it only inside colon definitions (if at all):

```
C" ( compilation "ccc<quote>" - ; run-time - c-addr ) core-ext "c-quote"
```

Compilation: parse a string *ccc* delimited by a " (double quote). At run-time, return *c-addr* which specifies the counted string *ccc*. Interpretation semantics are undefined.

```
place ( c-addr1 u c-addr2 - ) gforth-experimental "place"
```

Create a counted string of length *u* at *c-addr2* and copy the string *c-addr1* *u* into that location. Up to 256 bytes starting at *c-addr2* will be written, so make sure that the buffer at *c-addr2* has that much space (or check that *u+1* does not exceed the buffer size before calling *place*)

```
string, ( c-addr u - ) gforth-0.2 "string-comma"
```

Reserve *u+1* bytes of dictionary space and store the string *c-addr* *u* there as counted string.

6.10 Control Structures

Control structures in Forth cannot be used interpretively, only in a colon definition⁶. We do not like this limitation, but have not seen a satisfying way around it yet, although many schemes have been proposed.

⁶ To be precise, in Standard Forth the control-flow words have no interpretation semantics, and in Gforth the interpretation semantics of the control-flow words are not useful for interpretive control flow (see *<undefined>* [Interpretation and Compilation Semantics], page *<undefined>*).

6.10.1 Selection

```

flag IF
  code
THEN

```

If *flag* is non-zero (as far as IF etc. are concerned, a non-zero cell represents truth), *code* is executed.

You may wonder why **then** ends an **if** construct, which is at odds with the usage of **then** in some other programming languages, and with the idiom “if ... then ...” in English. According to *Webster’s New Encyclopedic Dictionary*, *then* (*adv.*) has the following meanings:

... 2b: following next after in order ... 3d: as a necessary consequence (if you were there, then you saw them).

Forth’s **then** has the meaning 2b, whereas **THEN** in Pascal and many other programming languages has the meaning 3d. If you do not like this usage of **then**, Gforth (but not Standard Forth) also has **endif**, which can be used in its place. Adding **ENDIF** to a system that only supplies **THEN** is simple:

```

: ENDIF   POSTPONE then ; immediate
flag IF
  code1
ELSE
  code2
THEN

```

If *flag* is true, *code1* is executed, otherwise *code2* is executed.

Gforth also provides the words **?DUP-IF** and **?DUP-0=-IF**, so you can avoid using **?dup**. Using these alternatives is also more efficient than using **?dup**. Definitions in Standard Forth for **ENDIF**, **?DUP-IF** and **?DUP-0=-IF** are provided in `compat/control.fs`.

```

x
CASE
  x1 OF code1 ENDOF
  x2 OF code2 ENDOF
  ...
  ( x ) default-code ( x )
ENDCASE ( )

```

Executes the first *codei*, where the *xi* is equal to *x*. If no *xi* matches, the optional *default-code* is executed. The optional default case can be added by simply writing the code after the last **ENDOF**. It may use *x*, which is on top of the stack, but must not consume it. The value *x* is consumed by this construction (either by an **OF** that matches, or by the **ENDCASE**, if no **OF** matches). Example:

```

: num-name ( n -- c-addr u )
case
  0 of s" zero " endof
  1 of s" one " endof
  2 of s" two " endof
  \ default case:

```

```

    s" other number"
    rot \ get n on top so ENDCASE can drop it
  endcase ;

```

Programming style note: To keep the code understandable, you should ensure that you change the stack in the same way (wrt. number and types of stack items consumed and pushed) on all paths through a selection structure.

6.10.2 General Loops

```

BEGIN
  code1
  flag WHILE
  code2
REPEAT

```

code1 is executed and *flag* is computed. If it is true, *code2* is executed and the loop is restarted; If *flag* is false, execution continues after the **REPEAT**.

```

BEGIN
  code
  flag
UNTIL

```

code is executed. The loop is restarted if **flag** is false.

Programming style note: To keep the code understandable, a complete iteration of the loop should not change the number and types of the items on the stacks.

```

BEGIN
  code
AGAIN

```

This is an endless loop. You can leave it by leaving the enclosing colon definition with **exit** or **throw**, or with **while** (see <undefined> [General loops with multiple exits], page <undefined>).

6.10.3 Counted Loops

The basic counted loop is:

```

limit start ?DO
  body
LOOP

```

This performs one iteration for every integer, starting from *start* and up to, but excluding *limit*. The counter, or *index*, can be accessed with **i**. For example, the loop:

```

10 0 ?DO
  i .
LOOP

```

prints 0 1 2 3 4 5 6 7 8 9

The index of the innermost loop can be accessed with **i**, the index of the next loop with **j**, and the index of the third loop with **k**.

You can access the limit of the innermost loop with `i'` and `i'-i` with `delta-i`. E.g., running

```
: foo 7 5 ?do cr i . i' . delta-i . loop ;
prints
5 7 2
6 7 1
```

The loop control data are kept on the return stack, so there are some restrictions on mixing return stack accesses and counted loop words. In particular, if you put values on the return stack outside the loop, you cannot read them inside the loop⁷. If you put values on the return stack within a loop, you have to remove them before the end of the loop and before accessing the index of the loop.

There are several variations on the counted loop:

- `LEAVE` leaves the innermost counted loop immediately; execution continues after the associated `LOOP` or `NEXT`. For example:

```
10 0 ?DO i DUP . 3 = IF LEAVE THEN LOOP
prints 0 1 2 3
```

- `UNLOOP` prepares for an abnormal loop exit, e.g., via `EXIT`. `UNLOOP` removes the loop control parameters from the return stack so `EXIT` can get to its return address. For example:

```
: demo 10 0 ?DO i DUP . 3 = IF UNLOOP EXIT THEN LOOP ." Done" ;
prints 0 1 2 3
```

- If *start* is greater than *limit*, a `?DO` loop is entered (and `LOOP` iterates until they become equal by wrap-around arithmetic). This behaviour is usually not what you want. Therefore, Gforth offers `+DO` and `U+DO` (as replacements for `?DO`), which do not enter the loop if *start* is greater than *limit*; `+DO` is for signed loop parameters, `U+DO` for unsigned loop parameters.
- `?DO` can be replaced by `DO`. `DO` always enters the loop, independent of the loop parameters. Do not use `DO`, even if you know that the loop is entered in any case. Such knowledge tends to become invalid during maintenance of a program, and then the `DO` will make trouble.
- `LOOP` can be replaced with `n+LOOP`; this updates the index by *n* instead of by 1. The loop is terminated when the border between *limit-1* and *limit* is crossed. E.g.:

```
4 0 +DO i . 2 +LOOP
prints 0 2
4 1 +DO i . 2 +LOOP
prints 1 3
```

- The behaviour of `n+LOOP` is peculiar when *n* is negative:

```
-1 0 ?DO i . -1 +LOOP
prints 0 -1
0 0 ?DO i . -1 +LOOP
```

⁷ Not in a way that is portable.

prints nothing.

We recommend not combining ?DO with +LOOP. Gforth offers several alternatives:

If you want -1 +LOOP's behaviour of including an iteration where I=limit, start the loop with -[DO or U-[DO (where the [is inspired by the mathematical notation for inclusive ranges, e.g., [1,n]):

```
-1 0 -[DO i . -1 +LOOP
```

prints 0 -1.

```
0 0 -[DO i . -1 +LOOP
```

prints 0.

```
0 -1 -[DO i . -1 +LOOP
```

prints nothing.

If you want to exclude the limit, you instead use 1 -LOOP (or generally u -LOOP) and start the loop with ?DO, -DO or U-DO. -LOOP terminates the loop when the border between *limit+1* and *limit* is crossed. E.g.:

```
-2 0 -DO i . 1 -LOOP
```

prints 0 -1

```
-1 0 -DO i . 1 -LOOP
```

prints 0

```
0 0 -DO i . 1 -LOOP
```

prints nothing.

Unfortunately, +DO, U+DO, -DO, U-DO and -LOOP are not defined in Standard Forth. However, an implementation for these words that uses only standard words is provided in `compat/loops.fs`.

- A common task is to iterate over the elements of an array, forwards or backwards. Iterating over the addresses of the elements has two benefits: It avoids the need to keep the start address of the array around, reducing the data stack load; and it avoids the need to perform address computations in every iteration. The disadvantage is that, starting with the usual array representations *addr uelems* or *addr ubytes*, some processing is required to produce a start and limit address. Gforth has **bounds** for getting there from the *addr ubytes* representation, so you can write a forward loop through a cell array *v* as:

```
create v 1 , 3 , 7 ,
: foo v 3 cells bounds U+DO i @ . cell +LOOP ;
foo
```

which prints 1 3 7. Preprocessing the inputs for walking backwards is more involved, so Gforth provide a loop construct of the form MEM-DO...LOOP that does it for you: It takes an array in *addr ubytes* representation and the element size, and iterates over the addresses of the elements in backwards order:

```
create v 1 , 3 , 7 ,
: foo1 v 3 cell array>mem MEM-DO i @ . LOOP ;
foo1
```

This prints 7 3 1. `ARRAY>MEM` converts the *addr uelems uelemsize* representation into the *addr ubytes uelemsize* representation expected by `MEM-DO`. This loop is finished with `LOOP` which decrements by *uelemsize* when it finishes a `MEM-DO`.

Gforth also adds `MEM+DO` for completeness. It takes the same parameters as `MEM-DO`, but walks forwards through the array:

```
create v 1 , 3 , 7 ,
: foo2 v 3 cell array>mem MEM+DO i @ . LOOP ;
foo2
```

prints 1 3 7.

- Another counted loop is:

```
  n
FOR
  body
NEXT
```

This is the preferred loop of native code compiler writers who are too lazy to optimize `?DO` loops properly. This loop structure is not defined in Standard Forth. In Gforth, this loop iterates *n+1* times; *i* produces values starting with *n* and ending with 0. Other Forth systems may behave differently, even if they support `FOR` loops. To avoid problems, don't use `FOR` loops.

The counted-loop words are:

`?DO (compilation – do-sys ; run-time w1 w2 – | loop-sys)` core-ext “question-do”

See <undefined> [Counted Loops], page <undefined>.

`+DO (compilation – do-sys ; run-time n1 n2 – | loop-sys)` gforth-0.2 “plus-do”

See <undefined> [Counted Loops], page <undefined>.

`U+DO (compilation – do-sys ; run-time u1 u2 – | loop-sys)` gforth-0.2 “u-plus-do”

See <undefined> [Counted Loops], page <undefined>.

`bounds (u1 u2 – u3 u1)` gforth-0.2 “bounds”

Given a memory block represented by starting address *addr* and length *u* in aus, produce the end address *addr+u* and the start address in the right order for `u+do` or `?do`.

`-[do (compilation – do-sys ; run-time n1 n2 – | loop-sys)` gforth-experimental “minus-bracket-do”

Start of a counted loop with negative stride; Skips the loop if *n2*<*n1*; such a counted loop ends with `+loop` where the increment is negative; it runs as long as *I*≥*n1*.

`u-[do (compilation – do-sys ; run-time u1 u2 – | loop-sys)` gforth-experimental “u-minus-bracket-do”

Start of a counted loop with negative stride; Skips the loop if *u2*<*u1*; such a counted loop ends with `+loop` where the increment is negative; it runs as long as *I*≥*u1*.

`-DO (compilation – do-sys ; run-time n1 n2 – | loop-sys)` gforth-0.2 “minus-do”

See <undefined> [Counted Loops], page <undefined>.

`U-DO (compilation – do-sys ; run-time u1 u2 – | loop-sys)` gforth-0.2 “u-minus-do”

See <undefined> [Counted Loops], page <undefined>.

`array>mem (uelements uelemsize – ubytes uelemsize)` gforth-experimental “array>mem”

*ubytes=uelements*uelemsize*

mem+do (*compilation – w xt do-sys; run-time addr ubytes+nstride –*) gforth-experimental “mem-plus-do”

Starts a counted loop that starts with *I* as *addr* and then steps upwards through memory with *nstride* wide steps as long as *I*<*addr+ubytes*. Must be finished with **loop**.

mem-do (*compilation – w xt do-sys; run-time addr ubytes+nstride –*) gforth-experimental “mem-minus-do”

Starts a counted loop that starts with *I* as *addr+ubytes-ustride* and then steps backwards through memory with *-nstride* wide steps as long as *I*>=*addr*. Must be finished with **loop**.

DO (*compilation – do-sys ; run-time w1 w2 – loop-sys*) core “DO”

See <undefined> [Counted Loops], page <undefined>.

FOR (*compilation – do-sys ; run-time u – loop-sys*) gforth-0.2 “FOR”

See <undefined> [Counted Loops], page <undefined>.

LOOP (*compilation do-sys – ; run-time loop-sys1 – | loop-sys2*) core “LOOP”

See <undefined> [Counted Loops], page <undefined>.

+LOOP (*compilation do-sys – ; run-time loop-sys1 n – | loop-sys2*) core “plus-loop”

See <undefined> [Counted Loops], page <undefined>.

-LOOP (*compilation do-sys – ; run-time loop-sys1 u – | loop-sys2*) gforth-0.2 “minus-loop”

See <undefined> [Counted Loops], page <undefined>.

NEXT (*compilation do-sys – ; run-time loop-sys1 – | loop-sys2*) gforth-0.2 “NEXT”

See <undefined> [Counted Loops], page <undefined>.

i (*R:n – R:n n*) core “i”

n is the index of the innermost counted loop.

j (*R:n R:w1 R:w2 – n R:n R:w1 R:w2*) core “j”

n is the index of the next-to-innermost counted loop.

k (*R:n R:w1 R:w2 R:w3 R:w4 – n R:n R:w1 R:w2 R:w3 R:w4*) gforth-0.3 “k”

n is the index of the third-innermost counted loop.

i' (*R:w R:w2 – R:w R:w2 w*) gforth-0.2 “i-tick”

The limit of the innermost counted loop

delta-i (*r:ulimit r:u – r:ulimit r:u u2*) gforth-1.0 “delta-i”

u2=*I'*-*I* (difference between limit and index).

LEAVE (*compilation – ; run-time loop-sys –*) core “LEAVE”

See <undefined> [Counted Loops], page <undefined>.

?LEAVE (*compilation – ; run-time f | f loop-sys –*) gforth-0.2 “question-leave”

See <undefined> [Counted Loops], page <undefined>.

unloop (*R:w1 R:w2 –*) core “unloop”

DONE (*compilation do-sys – ; run-time –*) gforth-0.2 “DONE”

resolves all LEAVEs up to the do-sys

The standard does not allow using **CS-PICK** and **CS-ROLL** on *do-sys*. Gforth allows it, except for the do-sys produced by **MEM+DO** and **MEM-DO**, but it's your job to ensure that for

every `?DO` etc. there is exactly one `UNLOOP` on any path through the definition (`LOOP` etc. compile an `UNLOOP` on the fall-through path). Also, you have to ensure that all `LEAVEs` are resolved (by using one of the loop-ending words or `DONE`).

6.10.4 General loops with multiple exits

For counted loops, you can use `leave` in several places. For `begin` loops, you have the following options:

Use `exit` (possibly several times) in the loop to leave not just the loop, but the whole colon definition. E.g.,:

```
: foo
  begin
    condition1 while
      condition2 if
        exit-code2 exit then
      condition3 if
        exit-code3 exit then
    ...
  repeat
  exit-code1 ;
```

The disadvantage of this approach is that, if you want to have some common code afterwards, you either have to wrap `foo` in another definition that contains the common code, or you have to call the common code several times, from each exit-code.

Another approach is to use several `whiles` in a `begin` loop. You have to append a `then` behind the loop for every additional `while`. E.g.,;

```
begin
  condition1 while
    condition2 while
      condition3 while
        again then then then
```

Here I used `again` at the end of the loop so that I would have a `then` for each `while`; `repeat` would result in one less `then`, but otherwise the same behaviour. For an explanation of why this works, See [\[Arbitrary control structures\]](#), page [\[Arbitrary control structures\]](#).

We can have common code afterwards, but, as presented above, we cannot have different exit-codes for the different exits. You can have these different exit-codes, as follows:

```
begin
  condition1 while
    condition2 while
      condition3 while
        again then exit-code3
      else exit-code2 then
    else exit-code1 then
```

This is relatively hard to comprehend, because the exit-codes are relatively far from the exit conditions (it does not help that we are not used to such control structures, either). The following extended `case` does not have this problem.

6.10.5 General control structures with case

Gforth provides an extended **case** that solves the problems of the multi-exit loops discussed above, and offers additional options. You can find a portable implementation of this extended **case** in `compat/caseext.fs`.

There are three additional words in the extension. The first is **?of** which allows general tests (rather than just testing for equality) in a **case**; e.g.,

```
: sgn ( n -- -1|0|1 )
  ( n ) case
    dup 0 < ?of drop -1 endof
    dup 0 > ?of drop 1 endof
    \ otherwise leave the 0 on the stack
  0 endcase ;
```

Note that **endcase** drops a value, which works fine much of the time with **of**, but usually not with **?of**, so we leave a 0 on the stack for **endcase** to drop. The **n** that is passed into **sgn** is also 0 if neither **?of** triggers, and that is then passed out.

The second additional word is **next-case**, which allows turning **case** into a loop. Our triple-exit loop becomes:

```
case
  condition1 ?of exit-code1 endof
  condition2 ?of exit-code2 endof
  condition3 ?of exit-code3 endof
  ...
next-case
common code afterwards
```

As you can see, this solves both problems of the variants discussed above (see [\(undefined\)](#) [General loops with multiple exits], page [\(undefined\)](#)). Note that **next-case** does not drop a value, unlike **endcase**.⁸

The last additional word is **contof**, which is used instead of **endof** and starts the next iteration instead of leaving the loop. This can be used in ways similar to Dijkstra's guarded command *do*, e.g.:

```
: gcd ( n1 n2 -- n )
  case
    2dup > ?of tuck - contof
    2dup < ?of over - contof
  endcase ;
```

Here the two **?ofs** have different ways of continuing the loop; when neither **?of** triggers, the two numbers are equal and are the gcd. **Endcase** drops one of them, leaving the other as **n**.

You can also combine these words. Here's an example that uses each of the **case** words once, except **endcase**:

```
: collatz ( u -- )
```

⁸ The name **next-case** has a -, unlike the other **case** words, because VFX Forth has a **next-case** that works like Gforth's **next-case**, but also contains a **nextcase** that drops a value; in VFX you need to pair **next-case** with **begincase**, however.

```

\ print the 3n+1 sequence starting at u until we reach 1
case
  dup .
  1 of endof
  dup 1 and ?of 3 * 1+ contof
  2/
next-case ;

```

This example keeps the current value of the sequence on the stack. If it is 1, the `of` triggers, drops the value, and leaves the `case` structure. For odd numbers, the `?of` triggers, computes $3n+1$, and starts the next iteration with `contof`. Otherwise, if the number is even, it is divided by 2, and the loop is restarted with `next-case`.

The `case` words are:

`case` (*compilation* - *case-sys* ; *run-time* -) core-ext “case”

Start a `case` structure.

`endcase` (*compilation* *case-sys* - ; *run-time* *x* -) core-ext “end-case”

Finish the `case` structure; drop *x*, and continue behind the `endcase`. Dropping *x* is useful in the original `case` construct (with only `ofs`), but you may have to supply an *x* in other cases (especially when using `?of`).

`next-case` (*compilation* *case-sys* - ; *run-time* -) gforth-1.0 “next-case”

Restart the `case` loop by jumping to the matching `case`. Note that `next-case` does not drop a cell, unlike `endcase`.

`of` (*compilation* - *of-sys* ; *run-time* *x1 x2* - | *x1*) core-ext “of”

If $x1=x2$, continue (dropping both); otherwise, leave *x1* on the stack and jump behind `endof` or `contof`.

`?of` (*compilation* - *of-sys* ; *run-time* *f* -) gforth-1.0 “question-of”

If *f* is true, continue; otherwise, jump behind `endof` or `contof`.

`endof` (*compilation* *case-sys1 of-sys* - *case-sys2* ; *run-time* -) core-ext “end-of”

Exit the enclosing `case` structure by jumping behind `endcase`/`next-case`.

`contof` (*compilation* *case-sys1 of-sys* - *case-sys2* ; *run-time* -) gforth-1.0 “cont-of”

Restart the `case` loop by jumping to the enclosing `case`.

Internally, *of-sys* is an `orig`; and *case-sys* is a cell and some stack-depth information, 0 or more `origs`, and a `dest`.

6.10.6 Arbitrary control structures

Standard Forth permits and supports using control structures in a non-nested way. Information about incomplete control structures is stored on the control-flow stack. This stack may be implemented on the Forth data stack, and this is what we have done in Gforth.

An *orig* entry represents an unresolved forward branch, a *dest* entry represents a backward branch target. A few words are the basis for building any control structure possible (except control structures that need storage, like calls, coroutines, and backtracking).

`IF` (*compilation* - *orig* ; *run-time* *f* -) core “IF”

At run-time, if $f=0$, execution continues after the **THEN** (or **ELSE**) that consumes the *orig*, otherwise right after the **IF** (see [⟨undefined⟩ \[Selection\]](#), page [⟨undefined⟩](#)).

AHEAD (*compilation orig ; run-time -*) tools-ext “AHEAD”

At run-time, execution continues after the **THEN** that consumes the *orig*.

THEN (*compilation orig - ; run-time -*) core “THEN”

The **IF**, **AHEAD**, **ELSE** or **WHILE** that pushed *orig* jumps right after the **THEN** (see [⟨undefined⟩ \[Selection\]](#), page [⟨undefined⟩](#)).

BEGIN (*compilation - dest ; run-time -*) core “BEGIN”

The **UNTIL**, **AGAIN** or **REPEAT** that consumes the *dest* jumps right behind the **BEGIN** (see [⟨undefined⟩ \[General Loops\]](#), page [⟨undefined⟩](#)).

UNTIL (*compilation dest - ; run-time f -*) core “UNTIL”

At run-time, if $f=0$, execution continues after the **BEGIN** that produced *dest*, otherwise right after the **UNTIL** (see [⟨undefined⟩ \[General Loops\]](#), page [⟨undefined⟩](#)).

AGAIN (*compilation dest - ; run-time -*) core-ext “AGAIN”

At run-time, execution continues after the **BEGIN** that produced the *dest* (see [⟨undefined⟩ \[General Loops\]](#), page [⟨undefined⟩](#)).

CS-PICK (*dest0/orig0 dest1/orig1 ... destu/origu u - ... dest0/orig0*) tools-ext “c-s-pick”

CS-ROLL (*destu/origu .. dest0/orig0 u - .. dest0/orig0 destu/origu*) tools-ext “c-s-roll”

CS-DROP (*dest/orig -*) gforth-1.0 “CS-DROP”

The Standard words **cs-pick** and **cs-roll** allow you to manipulate the control-flow stack in a portable way. Without them, you would need to know how many stack items are occupied by a control-flow entry (Many systems use one cell. In Gforth they currently take four cells, but this may change in the future).

When using **cs-pick** and **cs-drop** on an *orig*, you need to use one **cs-drop** for every **cs-pick** (and vice versa) of a given *orig*, because the *orig* must be resolved by **then** exactly once.

Some standard control structure words are built from these words:

ELSE (*compilation orig1 - orig2 ; run-time -*) core “ELSE”

At run-time, execution continues after the **THEN** that consumes the *orig*; the **IF**, **AHEAD**, **ELSE** or **WHILE** that pushed *orig1* jumps right after the **ELSE**. (see [⟨undefined⟩ \[Selection\]](#), page [⟨undefined⟩](#)).

WHILE (*compilation dest - orig dest ; run-time f -*) core “WHILE”

At run-time, if $f=0$, execution continues after the **REPEAT** (or **THEN** or **ELSE**) that consumes the *orig*, otherwise right after the **WHILE** (see [⟨undefined⟩ \[General Loops\]](#), page [⟨undefined⟩](#)).

REPEAT (*compilation orig dest - ; run-time -*) core “REPEAT”

At run-time, execution continues after the **BEGIN** that produced the *dest*; the **WHILE**, **IF**, **AHEAD** or **ELSE** that pushed *orig* jumps right after the **REPEAT**. (see [⟨undefined⟩ \[General Loops\]](#), page [⟨undefined⟩](#)).

Gforth adds some more control-structure words:

ENDIF (*compilation orig - ; run-time -*) gforth-0.2 “ENDIF”

Same as **THEN**.

?dup-IF (*compilation – orig ; run-time n – n|*) gforth-0.2 “question-dupe-if”

This is the preferred alternative to the idiom “**?DUP IF**”, since it can be better handled by tools like stack checkers. Besides, it’s faster.

?DUP-0=-IF (*compilation – orig ; run-time n – n|*) gforth-0.2 “question-dupe-zero-equals-if”

6.10.7 Calls and returns

A definition can be called simply by writing the name of the definition to be called. Normally a definition is invisible during its own definition. If you want to write a directly recursive definition, you can use **recursive** to make the current definition visible, or **recurse** to call the current definition directly.

recursive (*compilation – ; run-time –*) gforth-0.2 “recursive”

Make the current definition visible, enabling it to call itself recursively.

recurse (*... – ...*) core “recurse”

Alias to the current definition.

For examples of using these words, See [\[Recursion Tutorial\]](#), page [\[undefined\]](#).

Programming style note: I prefer using **recursive** to **recurse**, because calling the definition by name is more descriptive (if the name is well-chosen) than the somewhat cryptic **recurse**. E.g., in a quicksort implementation, it is much better to read (and think) “now sort the partitions” than to read “now do a recursive call”.

For mutual recursion, Gforth offers the defining word **forward**. You can use it to create a forward reference which is resolved automatically, and does not incur additional costs like the indirection of **Defer**. However, these forward definitions only work for colon definitions. Here’s a usage example:

```
forward foo

: bar ( ... -- ... )
... foo ... ;

: foo ( ... -- ... ) \ resolves the forward definition
... bar ... ;
```

The words used for forward definitions are:

forward (*"name" –*) gforth-1.0 “forward”

Defines a forward reference to a colon definition. Defining a colon definition with the same name in the same wordlist resolves the forward references. Use **.unresolved** to check whether any forwards are unresolved.

.unresolved (*–*) gforth-1.0 “.unresolved”

print all unresolved forward references

In Standard Forth, you use **Deferred** words for mutual recursion, like this:

```
Defer foo

: bar ( ... -- ... )
```

```

... foo ... ;

:noname ( ... -- ... )
... bar ... ;
IS foo

```

Deferred words are discussed in more detail in [\[Deferred Words\]](#), page [\[undefined\]](#).

The current definition returns control to the calling definition when the end of the definition is reached or **EXIT** is encountered.

EXIT (*compilation* – ; *run-time nest-sys* –) core “EXIT”

Return to the calling definition; usually used as a way of forcing an early return from a definition. Before **EXITing** you must clean up the return stack and **UNLOOP** any outstanding **?DO...LOOPs**.

?EXIT (–) gforth-0.2 “question-exit”

Return to the calling definition if *f* is true.

6.10.8 Exception Handling

If a word detects an error condition that it cannot handle, it can **throw** an exception. In the simplest case, this will terminate your program, and report an appropriate error.

throw (*y1 .. ym nerror* – *y1 .. ym / z1 .. zn nerror*) exception “throw”

If *nerror* is 0, drop it and continue. Otherwise, transfer control to the next dynamically enclosing exception handler, reset the stacks accordingly, and push *nerror*.

fast-throw (... *nerror* – ... *nerror*) gforth-experimental “fast-throw”

Lightweight **throw** variant: only for non-zero *nerrors*, and does not store a backtrace or deal with missing **catch**.

Throw consumes a cell-sized error number on the stack. There are some predefined error numbers in Standard Forth (see **errors.fs**). In Gforth (and most other systems) you can use the iors produced by various words as error numbers (e.g., a typical use of **allocate** is **allocate throw**). Gforth also provides the word **exception** to define your own error numbers (with decent error reporting); a Standard Forth version of this word (but without the error messages) is available in **compat/except.fs**. And finally, you can use your own error numbers (anything outside the range -4095..0), but won’t get nice error messages, only numbers. For example, try:

```

-10 throw          \ Standard defined
-267 throw         \ system defined
s" my error" exception throw \ user defined
7 throw           \ arbitrary number

```

exception (*addr u* – *n*) gforth-0.2 “exception”

n is a previously unused **throw** value in the range (-4095...-256). Consecutive calls to **exception** return consecutive decreasing numbers. Gforth uses the string *addr u* as an error message.

There are also cases where you have a word (typically modeled after POSIX’ **strerror**) for converting an error number into a string. You can use the following word to get these strings into Gforth’s error handling:

exceptions (*xt n1 - n2*) gforth-1.0 “exceptions”

Xt (**+n -- c-addr u**) converts an error number in the range $0 \leq n < n1$ into an error message. **Exceptions** reserves *n1* error codes in the range $n2 - n1 < n3 \leq n2$. When (at some later point in time) the Gforth error code *n3* in that range is thrown, it pushes *n2-n3* and then executes *xt* to produce the error message.

As an example, if the **errno** errors (and the conversion using **strerror**) was not already directly supported by Gforth, you could tie **strerror** in as follows:

```
' strerror 1536 exceptions constant errno-base
: errno-ior ( -- n )
\ n is the Gforth ior corresponding to the value in errno, so
\ we have to convert between the ranges here.
\ ERRNO is not a Gforth word, so you would have to use the
\ C interface to access it.
errno errno-base over - swap 0<> and ;
```

When you call a C function that can set **errno** (with the C interface, see (undefined) [C Interface], page (undefined)), you can use one of the following words for converting that error into a **throw**:

?errno-throw (*f -*) gforth-1.0 “question-errno-throw”

If *f* <> 0, throws an error code based on the value of **errno**.

?ior (*x -*) gforth-1.0 “question-i-o-r”

If *f* = -1, throws an error code based on the value of **errno**.

Which of these you should use depends on how the C function indicates that an error has happened. When the system then catches a throw performed by one of these words, it produces the proper error message (such as “Permission denied”).

Note that the **errno** numbers are not directly used as throw codes (because the Forth standard specifies that positive throw codes must not be system-defined), but maps them into a different number range.

A common idiom to **THROW** a specific *err#* if a flag is true is this:

```
( flag ) 0<> err# and throw
```

Your program can provide exception handlers to catch exceptions. An exception handler can be used to correct the problem, or to clean up some data structures and just throw the exception to the next exception handler. Note that **throw** jumps to the dynamically innermost exception handler. The system’s exception handler is outermost, and just prints an error and restarts command-line interpretation (or, in batch mode (i.e., while processing the shell command line), leaves Gforth).

The Standard Forth way to catch exceptions is **catch**:

catch (*x1 .. xn xt - y1 .. ym 0 / z1 .. zn error*) exception “catch”

Executes *xt*. If execution returns normally, **catch** pushes 0 on the stack. If execution returns through **throw**, all the stacks are reset to the depth on entry to **catch**, and the TOS (the *xt* position) is replaced with the throw code.

catch-nobt (*x1 .. xn xt - y1 .. ym 0 / z1 .. zn error*) gforth-experimental “catch-nobt”

perform a catch that does not record backtraces on errors

nothrow (*-*) gforth-0.7 “nothrow”

Use this (or the standard sequence `['] false catch 2drop`) after a `catch` or `endtry` that does not rethrow; this ensures that the next `throw` will record a backtrace.

The most common use of exception handlers is to clean up the state when an error happens. E.g.,

```
base @ >r hex \ actually the HEX should be inside foo to protect
              \ against exceptions between HEX and CATCH
['] foo catch ( nerror|0 )
r> base !
( nerror|0 ) throw \ pass it on
```

A use of `catch` for handling the error `myerror` might look like this:

```
['] foo catch
CASE
  myerror OF ... ( do something about it ) nothrow END OF
  dup throw \ default: pass other errors on, do nothing on non-errors
ENDCASE
```

Having to wrap the code into a separate word is often cumbersome, therefore Gforth provides an alternative syntax:

```
TRY
  code1
  IFERROR
    code2
  THEN
    code3
ENDTRY
```

This performs *code1*. If *code1* completes normally, execution continues with *code3*. If there is an exception in *code1* or before `endtry`, the stacks are reset to the depth during `try`, the throw value is pushed on the data stack, and execution continues at *code2*, and finally falls through to *code3*.

`try (compilation - orig ; run-time - R:sys1) gforth-0.5 "try"`

Start an exception-catching region.

`endtry (compilation - ; run-time R:sys1 -) gforth-0.5 "endtry"`

End an exception-catching region.

`iferror (compilation orig1 - orig2 ; run-time -) gforth-0.7 "iferror"`

Starts the exception handling code (executed if there is an exception between `try` and `endtry`). This part has to be finished with `then`.

If you don't need *code2*, you can write `restore` instead of `iferror then`:

```
TRY
  code1
  RESTORE
  code3
ENDTRY
```

The cleanup example from above in this syntax:

```
base @ { oldbase }
```



```

TRY
  hex foo \ now the hex is placed correctly
  0       \ value for throw
RESTORE
  oldbase base !
ENDTRY
throw

```

An additional advantage of this variant is that an exception between **restore** and **endtry** (e.g., from the user pressing **Ctrl-C**) restarts the execution of the code after **restore**, so the base will be restored under all circumstances.

However, you have to ensure that this code does not cause an exception itself, otherwise the **iferror/restore** code will loop. Moreover, you should also make sure that the stack contents needed by the **iferror/restore** code exist everywhere between **try** and **endtry**; in our example this is achieved by putting the data in a local before the **try** (you cannot use the return stack because the exception frame (*sys1*) is in the way there).

This kind of usage corresponds to Lisp's **unwind-protect**.

If you do not want this exception-restarting behaviour, you achieve this as follows:

```

TRY
  code1
ENDTRY-IFERROR
  code2
THEN

```

If there is an exception in *code1*, then *code2* is executed, otherwise execution continues behind the **then** (or in a possible **else** branch). This corresponds to the construct

```

TRY
  code1
RECOVER
  code2
ENDTRY

```

in Gforth before version 0.7. So you can directly replace **recover**-using code; however, we recommend that you check if it would not be better to use one of the other **try** variants while you are at it.

To ease the transition, Gforth provides two compatibility files: **endtry-iferror.fs** provides the **try ... endtry-iferror ... then** syntax (but not **iferror** or **restore**) for old systems; **recover-endtry.fs** provides the **try ... recover ... endtry** syntax on new systems, so you can use that file as a stopgap to run old programs. Both files work on any Gforth (they just do nothing if the system already has the syntax it implements), so you can unconditionally **require** one of these files, even if you use a mix old and new Gforths. **restore (compilation orig1 - ; run-time -) gforth-0.7 "restore"**

Starts restoring code, that is executed if there is an exception, and if there is no exception. **endtry-iferror (compilation orig1 - orig2 ; run-time R:sys1 -) gforth-0.7 "endtry-iferror"**

End an exception-catching region while starting exception-handling code outside that region (executed if there is an exception between **try** and **endtry-iferror**). This part has to be finished with **then** (or **else...then**).

Here's the error handling example:

```

TRY
  foo
ENDTRY-IFERROR
CASE
  myerror OF ... ( do something about it ) nothrow ENDOF
  throw \ pass other errors on
ENDCASE
THEN

```

Programming style note: As usual, you should ensure that the stack depth is statically known at the end: either after the **throw** for passing on errors, or after the **ENDTRY** (or, if you use **catch**, after the end of the selection construct for handling the error).

There are two alternatives to **throw**: **Abort**" is conditional and you can provide an error message. **Abort** just produces an "Aborted" error.

The problem with these words is that exception handlers cannot differentiate between different **abort**"s; they just look like **-2 throw** to them (the error message cannot be accessed by standard programs). Similarly, **abort** looks like **-1 throw** to exception handlers.

ABORT" (*compilation 'ccc' - ; run-time ... f -*) core,exception-ext "abort-quote"

If any bit of *f* is non-zero, perform the function of **-2 throw**, displaying the string *ccc* if there is no exception frame on the exception stack.

abort (*?? - ??*) core,exception-ext "abort"

-1 throw.

For problems that are not that awful that you need to abort execution, you can just display a warning. The variable **warnings** allows to tune how many warnings you see.

WARNING" (*compilation 'ccc' - ; run-time f -*) gforth-1.0 "warning-quote"

if *f* is non-zero, display the string *ccc* as warning message.

warnings (*- addr*) gforth-0.2 "warnings"

Set warnings level to

- 0 turns warnings off
- 1 turns normal warnings on
- 2 turns beginner warnings on
- 3 turns pedantic warnings on
- 4 turns warnings into errors (including beginner warnings)

6.11 Defining Words

Defining words are used to extend Forth by creating new entries in the dictionary.

6.11.1 CREATE

The simplest defining word is `CREATE`, used like this:

```
CREATE new-word1
```

`CREATE` is a parsing word, i.e., it takes an argument from the input stream (`new-word1` in our example). It generates a dictionary entry for `new-word1`. When `new-word1` is executed, all that it does is leave an address on the stack. The address represents the value of the dictionary pointer (`HERE`) at the time that `new-word1` was defined. Therefore, `CREATE` is a way of associating a name with the address of a region of memory.

`Create ("name" -)` core “Create”

Note that Standard Forth guarantees only for `create` that its body is contiguous with the following dictionary allocations (e.g., `allot`, see [\(undefined\)](#) [Dictionary allocation], page [\(undefined\)](#)). Also, in Standard Forth only `created` words can be modified with `does>` (see [\(undefined\)](#) [User-defined Defining Words], page [\(undefined\)](#)). And in Standard Forth `>body` can only be applied to `created` words.

By extending this example to reserve some memory in data space, we end up with something like a *variable*. Here are two different ways to do it:

```
CREATE new-word2 1 cells allot \ reserve 1 cell without initializing it
CREATE new-word3 4 ,           \ reserve 1 cell and initialise it (to 4)■
```

The variable can be examined and modified using `@` (“fetch”) and `!` (“store”) like this:

```
new-word2 @ .      \ get address, fetch from it and display
1234 new-word2 !    \ new value, get address, store to it
```

A similar mechanism can be used to create arrays. For example, an 80-character text buffer:

```
CREATE text-buf 80 allot \ uninitialized

text-buf 0 + c@ \ the 1st character (offset 0)
text-buf 3 + c@ \ the 4th character (offset 3)
```

You can build arbitrarily complex data structures by allocating appropriate areas of memory. For further discussions of this, and to learn about some Gforth tools that make it easier, See [\(undefined\)](#) [Structures], page [\(undefined\)](#).

6.11.2 Variables

The previous section showed how a sequence of commands could be used to generate a variable. As a final refinement, the whole code sequence can be wrapped up in a defining word, making it easier to create new variables:

```
: myvariableX ( "name" -- a-addr ) CREATE 1 cells allot ;
: myvariable0 ( "name" -- a-addr ) CREATE 0 , ;

myvariableX foo \ variable foo starts off with an unknown value
myvariable0 joe \ whilst joe is initialised to 0

45 3 * foo !    \ set foo to 135
1234 joe !      \ set joe to 1234
3 joe +!        \ increment joe by 3.. to 1237
```

Not surprisingly, there is no need to define `myvariableX`, since Forth already has a definition `Variable`. Standard Forth does not guarantee that a `Variable` is initialised when it is created (i.e., it may behave like `myvariableX`). In contrast, Gforth's `Variable` initialises the variable to 0 (i.e., it behaves exactly like `myvariable0`). Forth also provides `2Variable` and `fvariable` for double and floating-point variables, respectively – they are initialised to `#0.` and `0e` in Gforth. If you use a `Variable` to store a boolean, you can use `on` and `off` to toggle its state (see `<undefined>` [Boolean Flags], page `<undefined>`).

`Variable ("name" –)` core “Variable”

Define *name* and reserve a cell at *addr*.

name execution: `(-- addr)`.

`AVariable ("name" –)` gforth-0.2 “AVariable”

Works like `variable`, but (when used in cross-compiled code) tells the cross-compiler that the cell stored in the variable is an address.

`2Variable ("name" –)` double “two-variable”

Define *name* and reserve two cells starting at *addr*.

name execution: `(-- addr)`.

`fvariable ("name" –)` floating “f-variable”

Define *name* and reserve a float at *f-addr*.

name execution: `(-- f-addr)`.

Finally, for buffers of arbitrary length there is

`buffer: (u "name" –)` core-ext “buffer-colon”

Define *name* and reserve *u* bytes starting at *addr*. Gforth initializes the reserved bytes to 0, but the standard does not guarantee this.

name execution: `(-- addr)`.

6.11.3 Constants

`Constant` allows you to declare a fixed value and refer to it by name. For example:

```
12 Constant INCHES-PER-FOOT \ is integer appropriate
2.54e fconstant CM-PER-INCH
```

A `Variable` can be both read and written, so its run-time behaviour is to supply an address through which its current value can be manipulated. In contrast, the value of a `Constant` cannot be changed once it has been declared⁹ so it's not necessary to supply the address – it is more efficient to return the value of the constant directly. That's exactly what happens; the run-time effect of a constant is to put its value on the top of the stack (You can find one way of implementing `Constant` in `<undefined>` [User-defined Defining Words], page `<undefined>`).

Forth also provides `2Constant` and `fconstant` for defining double and floating-point constants, respectively.

`Constant (w "name" –)` core “Constant”

Define *name*.

name execution: `(– w)`

`AConstant (addr "name" –)` gforth-0.2 “AConstant”

⁹ Well, often it can be – but not in a Standard, portable way. It's safer to use a `Value` (read on).

Like **constant**, but defines a constant for an address (this only makes a difference in the cross-compiler).

2Constant (*w1 w2 "name" -*) double “two-constant”

Define *name*.

name execution: (*- w1 w2*)

fconstant (*r "name" -*) floating “f-constant”

Define *name*.

name execution: (*- r*)

6.11.4 Values

A **Value** behaves like a **Constant**, but it can be changed. **TO** and **+TO** are parsing words that change a value. Alternatively, you can change a value *v* by writing **->v** (equivalent to **TO v**) or **+>v** (equivalent to **+TO v**).

Here are some examples:

```
12 value apples \ Define APPLES with an initial value of 12
34 to apples    \ Change the value of APPLES. TO is a parsing word
34 ->apples     \ Change the value of APPLES. Non-standard usage
1  +to apples   \ Increment APPLES. Non-standard usage.
1  +>apples     \ Increment APPLES. Non-standard usage.
apples          \ puts 36 on the top of the stack.
```

Value (*w "name" -*) core-ext “Value”

Define *name* with the initial value *w*

name execution: (*- w2*) push the current value of *name*.

to name run-time: (*w3 -*) change the value of *name* to *w3*.

+to name run-time: (*n|u -*) increment the value of *name* by *n|u*

AValue (*w "name" -*) gforth-0.6 “AValue”

Like **value**, but defines a value for an address (this only makes a difference in the cross-compiler).

2Value (*w1 w2 "name" -*) double-ext “two-value”

Define *name* with the initial value *w*

name execution: (*- w3 w4*) push the current value of *name*.

to name run-time: (*w5 w6 -*) change the value of *name* to *w5 w6*.

+to name run-time: (*d|ud -*) increment the value of *name* by *d|ud*

fvalue (*r "name" -*) floating-ext “f-value”

Define *name* with the initial value *r*

name execution: (*- r2*) push the current value of *name*.

to name run-time: (*r3 -*) change the value of *name* to *r3*.

+to name run-time: (*r4 -*) increment the value of *name* by *r4*

TO (*value "name" -*) core-ext “TO”

Changes the value of *name* to be equal to *value*. The type of *value* depends on the type of *name* (see the defining word for *name* for the exact stack effect). An alternative syntax is to write **->name**.

+TO (*value "name" -*) gforth-1.0 “+TO”

Adds *value* to the value of *name*. The type of *value* depends on the type of *name* (see the defining word for *name* for the exact stack effect). An alternative syntax is to write `+>name`.

Words that produce their value on execution and that can be changed with `to` or `+to` are called value-flavoured (in contrast to the variable-flavoured words that produce their address on execution). They are defined by some of the words listed above, but also by some locals definition words (see [\[Locals definition words\]](#), page [\[undefined\]](#)) and some field definition words (see [\[Value-Flavoured and Defer-Flavoured Fields\]](#), page [\[undefined\]](#)).

Sometimes you want to take the address of a value-flavoured word. Because this has some potential performance disadvantages, Gforth asks you to be explicit about it, and define the word as addressable. Once you have done that, you can get the address with `addr`. The following example is equivalent to the one above:

```
12 addressable: value apples
34 addr apples ! \ Change the value of APPLES. ADDR is a parsing word
1 +to apples    \ Increment APPLES
addr apples @    \ puts 35 on the top of the stack.
```

`addressable: (-) gforth-experimental “addressable:”`

Addressable: should be used in front of a defining word for a value-flavoured word (e.g., *value*). It allows to use `addr` on the word defined by that defining word.

`addr ("name" - addr) gforth-1.0 “addr”`

Addr is the address where the value of *name* is stored. *Name* has to be defined with any value-flavoured defining word (e.g. *value*) preceded by **addressable:**.

For now using `addr` on a non-**addressable:** value results in a warning. In the future, when we change the code generation in a way that results in potentially faster code for non-**addressable:** values, but where the use of `addr` on such values could produce unexpected results, such usage will result in an error.

6.11.5 Colon Definitions

```
: name ( ... -- ... )
  word1 word2 word3 ;
```

Creates a word called **name** that, upon execution, executes `word1 word2 word3`. **name** is a *(colon) definition*.

The explanation above is somewhat superficial. For simple examples of colon definitions see [\[Your first definition\]](#), page [\[undefined\]](#). For an in-depth discussion of some of the issues involved, See [\[Interpretation and Compilation Semantics\]](#), page [\[undefined\]](#).

```
: ( "name" - colon-sys ) core “colon”
; ( compilation colon-sys - ; run-time nest-sys - ) core “semicolon”
```

6.11.6 Inline Definitions

We plan to perform automatic inlining eventually, but for now you can perform inlining with

`inline: ("name" - inline:-sys) gforth-experimental “inline-colon”`

Start inline colon definition. The code between `inline:` and `;inline` has to compile (not perform) the code to be inlined, but the resulting definition *name* is a colon definition that performs the inlined code. Note that the compiling code must have the stack effect (--), otherwise you will get an error when Gforth tries to create the colon definition for *name*.

```
;inline ( inline:-sys - ) gforth-experimental "semi-inline"
```

end inline definition started with `inline:`

As an example, you can define an inlined word and use it with

```
inline: my2dup ( a b -- a b a b )
  ]] over over [[ ;inline
```

```
#1. my2dup d. d.
: foo my2dup ;
#1. foo d. d.
see foo
```

Inline words are related to macros (see [\[Macros\]](#), page [\[undefined\]](#)); the difference is that a macro has immediate compilation semantics while an `inline:-`defined word has default compilation semantics; this means that you normally use a macro only inside a colon definition, while you can use an `inline:` word also interpretively. But that also means that you can do some things with macros that you cannot do as an `inline:` word. E.g.,

```
\ Doesn't work:
\ inline: endif ]] then [[ ;inline
\ Instead, write a macro:
: endif ]] then [[ ; immediate
```

Conversely, for words that would be fine as non-immediate colon definitions, define them as non-immediate colon definitions or (if utmost performance is required) as `inline:` words; don't define them as macros, because then you cannot properly use them interpretively:

```
: another2dup ]] over over [[ ; immediate
\ Doesn't work:
\ #1. another2dup d. d.
```

You may wonder why you have to write compiling code between `inline:` and `;inline`. That's because the implementation of an inline word like `my2dup` above works similar to:

```
: compile-my2dup ( xt -- )
  drop ]] over over [[ ;

: my2dup [ 0 compile-my2dup ] ;
' compile-my2dup set-optimizer
```

The `DROP` and `0` are there because `compile-my2dup` is the implementation of `compile`, for `my2dup`, and `compile`, expects an `xt` (see [\[User-defined compile-comma\]](#), page [\[undefined\]](#)).

6.11.7 Anonymous Definitions

Sometimes you want to define an *anonymous word*; a word without a name. You can do this with:

```
:noname ( - xt colon-sys ) core-ext "colon-no-name"
```

This leaves the execution token for the word on the stack after the closing `;`. Here's an example in which a deferred word is initialised with an `xt` from an anonymous colon definition:

```
Defer deferred
:noname ( ... -- ... )
... ;
IS deferred
```

Gforth provides an alternative way of doing this, using two separate words:

```
noname ( - ) gforth-0.2 "noname"
```

The next defined word will be anonymous. The defining word will leave the input stream alone. The `xt` of the defined word will be given by `latestxt`, its `nt` by `latestnt` (see [\(undefined\)](#) [Name token], page [\(undefined\)](#)).

```
latestxt ( - xt ) gforth-0.6 "latestxt"
```

xt is the execution token of the most recent word defined in the current section.

The previous example can be rewritten using `noname` and `latestxt`:

```
Defer deferred
noname : ( ... -- ... )
... ;
latestxt IS deferred
```

`noname` works with any defining word, not just `:`.

`latestxt` also works when the last word was not defined as `noname`. It also has the useful property that it is valid as soon as the header for a definition has been built. Thus:

```
latestxt . : foo [ latestxt . ] ; ' foo .
```

prints 3 numbers; the last two are the same.

6.11.8 Quotations

A quotation is an anonymous colon definition inside another colon definition. Quotations are useful when dealing with words that consume an execution token, like `catch` or `outfile-execute`. E.g. consider the following example of using `outfile-execute` (see [\(undefined\)](#) [Redirection], page [\(undefined\)](#)):

```
: some-warning ( n -- )
  cr ." warning# " . ;

: print-some-warning ( n -- )
  ['] some-warning stderr outfile-execute ;
```

Here we defined `some-warning` as a helper word whose `xt` we could pass to `outfile-execute`. Instead, we can use a quotation to define such a word anonymously inside `print-some-warning`:

```
: print-some-warning ( n -- )
  [: cr ." warning# " . ;] stderr outfile-execute ;
```

The quotation is bounded by `[:` and `;`. It produces an execution token at run-time.

```
[: ( compile-time: - quotation-sys flag colon-sys ) gforth-1.0 "bracket-colon"
```


Starts a quotation in the next section.

```
;] ( compile-time: quotation-sys - ; run-time: - xt ) gforth-1.0 "semi-bracket"
```

Ends a quotation (represented by *xt*) and switch to the previous section. `latestxt` and `latestnt` refer to the last word in the current section, i.e., not to the quotation.

6.11.9 Supplying the name of a defined word

By default, a defining word takes the name for the defined word from the input stream. Sometimes you want to supply the name from a string. You can do this with:

```
nextname ( c-addr u - ) gforth-0.2 "nextname"
```

The next defined word will have the name *c-addr u*; the defining word will leave the input stream alone.

For example:

```
s" foo" nextname create
```

is equivalent to:

```
create foo
```

`nextname` works with any defining word.

6.11.10 User-defined Defining Words

You can define new defining words in terms of any existing defining word, but `:` and `create...does>/set-does>` are particularly flexible, whereas the children of, e.g., `constant` are all just constants.

6.11.10.1 User-defined defining words with colon definitions

Colon definitions are very flexible, so you can write a defining word that defines a new colon definition at its run-time. Here is an example:

```
: myconstant { : w -- : }
  : w postpone literal postpone ; ;
```

When defining `5 myconstant five`, `myconstant` first stashes *w* in a local (for reasons explained later), then calls `:`, which starts the definition of `five`. Then it uses `postpone literal` (see (undefined) [Compiling words], page (undefined)) to compile *w* (i.e., 5) into this colon definition, and then `postpone ;` to end it. You can look at the result with `see five`:

```
: five #5 ;
```

Can't we just leave *w* on the data stack for consumption by `postpone literal`? No: `:` pushes a colon-sys on the data stack, so we have to first move *w* elsewhere so we can later access it. In this example, we used a local variable, but moving *w* on the return stack and back would also have been an option.

A more convenient, but Gforth-specific way to write `myconstant` is:

```
: myconstant { : w -- : }
  : ]] w ; [[ ;
```

The features used in this code are explained elsewhere (see (undefined) [Macros], page (undefined)).

A disadvantage of this approach is that it consumes more memory than the approach of the next section: E.g, here are the memory costs of defining `five` with the various implementations:

```

builtin  : does> set-does> opt
    48   64   48    48    48  bytes header+threaded code
    0    23    0     0     0  bytes native code
    16   16   32    16    16  compiled threaded code
    4    23   34     7     4  compiled native code

```

Builtin refers to using `constant`, `:` to using `myconstant` (defined above), *does>* to using `myconstant2`, *set-does>* to using `myconstant3` (both from see `<undefined>` [User-defined defining words using CREATE], page `<undefined>`), and *opt* to using `myconstant4` (see `<undefined>` [User-defined compile-comma], page `<undefined>`).

The lines where the label starts with “bytes” report the space consumption of defining the word `five` itself; the native code is for `gforth-fast` on AMD64 (native code for the `gforth` engine is larger).

The lines where the label starts with “compiled” report the space consumption (also in bytes) for the invocation of `five` in the word `: foo five * ;`. The native code can be bigger or smaller in other contexts.

6.11.10.2 User-defined defining words using create

If you want the words defined with your defining words to behave differently from words defined with standard defining words, you can write your defining word like this:

```

: def-word ( "name" -- )
    CREATE code1
DOES> ( ... -- ... )
    code2 ;

```

```
def-word name
```

This fragment defines a *defining word* `def-word` and then executes it. When `def-word` executes, it `CREATEs` a new word *name*, and executes the code *code1*. The code *code2* is not executed at this time. The word *name* is sometimes called a *child* of `def-word`.

When you execute *name*, the address of the body of *name* is pushed on the data stack and *code2* is executed. The address of the body of *name* is the address `HERE` returns immediately after the `CREATE`, i.e., the address a `created` word returns by default).

You can understand the behaviour of `def-word` and *name* by considering the following definitions:

```

: def-word1 ( "name" -- )
    CREATE code1 ;

: action1 ( ... -- ... )
    code2 ;

```

```
def-word1 name1
```

Using `name1 action1` is equivalent to using *name*.

You can use **def-word** to define a set of child words that behave similarly; they all have a common run-time behaviour determined by *code2*. Typically, the *code1* sequence builds a data area in the body of the child word. The structure of the data is common to all children of **def-word**, but the data values are specific – and private – to each child word.

As an example, here's how you can define **myconstant2** with **does>**:

```
: myconstant2 ( w "name" -- )
  create ,
does> ( -- w )
  @ ;
```

Here **create** defines a word *name*, then **,** stores *w* in *name*'s data area, then the **does>** changes *name*'s behaviour and returns to the caller of **myconstant2**: When *name* is invoked, the new behaviour first pushes the address of the data area (as before), but then also performs the code after the **does>**. In the present case, this code fetches the value of the constant from the data area.

The stack effect besides the **does** reflects the stack effect of *name* execution, not the stack effect of the code after the **does>** (this is not common practice yet but we still recommend it).

Does> splits the definition into two subdefinitions and has a number of disadvantages. Alternatively, Gforth allows you to provide the second part as an execution token by using **set-does>**. So the general scheme is:

```
: def-word ( "name" -- ; name execution: ... -- ... )
  create code1
  xt-code2 set-does>
  code3 ;
```

The difference from the definition using **does>** is that on *name* execution, after pushing the data address, *xt-code2* is **executed**, rather than calling the code after the **does>**. This also allows putting *code3* in *def-word*; this is particularly relevant when you want to also use **set-optimizer** (see <undefined> [User-defined compile-comma], page <undefined>) on the defined word, because **does>/set-does>** calls **set-optimizer** itself, so using **set-optimizer** before **does>/set-does>** has no effect.

Here *xt-code2* could be the xt of an existing word, or it could be provided through a quotation (see <undefined> [Quotations], page <undefined>).

Another advantage of **set-does>** is that the result is a little more efficient if the execution token passed to it is that of a primitive. This advantages comes to fruition in:

```
: myconstant3 ( w "name" -- ; name execution: -- w )
  create ,
  ['] @ set-does> ;
```

During *name* execution, after pushing the body address of *name*, **@** is executed.

The efficiency advantage shows up in the comparisons of compiled code size (see <undefined> [User-defined defining words with colon definitions], page <undefined>); the execution time also benefits.

6.11.10.3 Applications of CREATE..DOES>

You may wonder how to use this feature. Here are some usage patterns:

When you see a sequence of code occurring several times, and you can identify a meaning, you will factor it out as a colon definition. When you see similar colon definitions, you can factor them using `CREATE..DOES>`. E.g., an assembler usually defines several words that look very similar:

```
: ori, ( reg-target reg-source n -- )
    0 asm-reg-reg-imm ;
: andi, ( reg-target reg-source n -- )
    1 asm-reg-reg-imm ;
```

This could be factored with:

```
: reg-reg-imm ( op-code -- )
    CREATE ,
DOES> ( reg-target reg-source n -- )
    @ asm-reg-reg-imm ;

0 reg-reg-imm ori,
1 reg-reg-imm andi,
```

Another view of `CREATE..DOES>` is to consider it as a crude way to supply a part of the parameters for a word (known as *currying* in the functional language community). E.g., `+` needs two parameters. Creating versions of `+` with one parameter fixed can be done like this:

```
: curry+ ( n1 "name" -- )
    CREATE ,
DOES> ( n2 -- n1+n2 )
    @ + ;

3 curry+ 3+
-2 curry+ 2-
```

6.11.10.4 The gory details of `CREATE..DOES>`

`DOES> (compilation colon-sys1 – colon-sys2)` core “does”

Changes the current word such that it pushes its body address and then calls the code behind the `does>`. Also changes the `compile`, implementation accordingly. Call `set-optimizer` afterwards if you want a more efficient implementation.

You can put the `does>`-part in a different definition than the `create` part. This allows us to, e.g., select among different `DOES>`-parts:

```
: does1
DOES> ( ... -- ... )
    code1 ;

: does2
DOES> ( ... -- ... )
    code2 ;

: def-word ( ... -- ... )
    create ...
```

```

IF
  does1
ELSE
  does2
THEN ;

```

In this example, the selection of whether to use `does1` or `does2` is made at definition-time, i.e., at the time when the child word is **CREATED**.

Note that the property of `does>` to end the definition makes it necessary to introduce extra definitions `does1` and `does2`. You can avoid that with `set-does>`:

```

: def-word ( ... -- ... )
  create ...
  IF
    [: code1 ;] set-does>
  ELSE
    [: code2 ;] set-does>
  THEN ;

```

`set-does>` (*xt* –) gforth-1.0 “set-does>”

Changes the current word such that it pushes its body address and then executes *xt*. Also changes the `compile`, implementation accordingly. Call `set-optimizer` afterwards if you want a more efficient implementation.

In a standard program you can apply a `DOES>`-part only if the last word was defined with **CREATE**. In Gforth, the `DOES>`-part will override the behaviour of the last word defined in any case. In a standard program, you can use `DOES>` only in a colon definition. In Gforth, you can also use it in interpretation state, in a kind of one-shot mode; for example:

```

CREATE name ( ... -- ... )
  initialization
DOES>
  code ;

```

is equivalent to the standard:

```

:noname
DOES>
  code ;
CREATE name EXECUTE ( ... -- ... )
  initialization

```

Gforth also supports quotations in interpreted code, and quotations save and restore the current definition, so you can also write the example above also as:

```

CREATE name ( ... -- ... )
  initialization
  [: code ;] set-does>

```

`>body` (*xt* – *a-addr*) core “to-body”

a-addr is the address of the body (aka parameter field or data field) of the word represented by *xt*

You can access the data area of a **created** word with `>body`, including words where the behaviour has been changed with `does>/set-does>`. So if you know that `five` has

been defined with, e.g., `myconstant3` (see [\(undefined\)](#) [User-defined defining words using CREATE], page [\(undefined\)](#)), you can change its value with

```
7 ' five >body !
```

and performing `five` will then push 7. By contrast, for words defined with `myconstant` (defined using `:`, see [\(undefined\)](#) [User-defined defining words with colon definitions], page [\(undefined\)](#)) you cannot change the value in this way.

However, if a word uses `set-optimizer` (see [\(undefined\)](#) [User-defined compile-comma], page [\(undefined\)](#)) for a more efficient implementation of the compiled code for a word, in many cases the compiled code does not read data from the body of this word, and in that case changing the data by using `>body` will not have the desired effect. So looking at the source code of a defining word and seeing `create` is not enough to conclude that you can change the data and it will affect all existing uses. An example of that is `myconstant4` (see [\(undefined\)](#) [User-defined compile-comma], page [\(undefined\)](#)).

So it's a good idea to document whether the intention behind a defining word using `create` is that it's data should be changeable through `>body`.

6.11.10.5 Advanced `does>` usage example

The MIPS disassembler (`arch/mips/disasm.fs`) contains many words for disassembling instructions, that follow a very repetitive scheme:

```
:noname disasm-operands s" inst-name" type ;
entry-num cells table + !
```

Of course, this inspires the idea to factor out the commonalities to allow a definition like

```
disasm-operands entry-num table define-inst inst-name
```

The parameters `disasm-operands` and `table` are usually correlated. Moreover, before I wrote the disassembler, there already existed code that defines instructions like this:

```
entry-num inst-format inst-name
```

This code comes from the assembler and resides in `arch/mips/insts.fs`.

So I had to define the `inst-format` words that performed the scheme above when executed. At first I chose to use run-time code-generation:

```
: inst-format ( entry-num "name" -- ; compiled code: addr w -- )
:noname Postpone disasm-operands
name Postpone sliteral Postpone type Postpone ;
swap cells table + ! ;
```

Note that this supplies the other two parameters of the scheme above.

An alternative would have been to write this using `create/does>`:

```
: inst-format ( entry-num "name" -- )
here name string, ( entry-num c-addr ) \ parse and save "name"
noname create , ( entry-num )
latestxt swap cells table + !
does> ( addr w -- )
\ disassemble instruction w at addr
@ >r
disasm-operands
```

```
r> count type ;
```

Somehow the first solution is simpler, mainly because it's simpler to shift a string from definition-time to use-time with `sliteral` than with `string`, and friends.

I wrote a lot of words following this scheme and soon thought about factoring out the commonalities among them. Note that this uses a two-level defining word, i.e., a word that defines ordinary defining words.

This time a solution involving `postpone` and friends seemed more difficult (try it as an exercise), so I decided to use a `create/does>` word; since I was already at it, I also used `create/does>` for the lower level (try using `postpone` etc. as an exercise), resulting in the following definition:

```
: define-format ( disasm-xt table-xt -- )
  \ define an instruction format that uses disasm-xt for
  \ disassembling and enters the defined instructions into table
  \ table-xt
  create 2,
does> ( u "inst" -- )
  \ defines an anonymous word for disassembling instruction inst,
  \ and enters it as u-th entry into table-xt
  2@ swap here name string, ( u table-xt disasm-xt c-addr ) \ remember string
  noname create 2,      \ define anonymous word
  execute latestxt swap ! \ enter xt of defined word into table-xt
does> ( addr w -- )
  \ disassemble instruction w at addr
  2@ >r ( addr w disasm-xt R: c-addr )
  execute ( R: c-addr ) \ disassemble operands
  r> count type ; \ print name
```

Note that the tables here (in contrast to above) do the `cells +` by themselves (that's why you have to pass an `xt`). This word is used in the following way:

```
' disasm-operands ' table define-format inst-format
```

As shown above, the defined instruction format is then used like this:

```
entry-num inst-format inst-name
```

In terms of currying, this kind of two-level defining word provides the parameters in three stages: first *disasm-operands* and *table*, then *entry-num* and *inst-name*, finally *addr w*, i.e., the instruction to be disassembled.

Of course this did not quite fit all the instruction format names used in `insts.fs`, so I had to define a few wrappers that conditioned the parameters into the right form.

If you have trouble following this section, don't worry. First, this is involved and takes time (and probably some playing around) to understand; second, this is the first two-level `create/does>` word I have written in seventeen years of Forth; and if I did not have `insts.fs` to start with, I may well have elected to use just a one-level defining word (with some repeating of parameters when using the defining word). So it is not necessary to understand this, but it may improve your understanding of Forth.

6.11.10.6 Words with user-defined to etc.

When you define a word *x*, you can set its execution semantics with **set-does>** (see (undefined) [User-defined defining words using CREATE], page (undefined)) or **set-execute** (see (undefined) [Header methods], page (undefined)). But you can also change the semantics of

```
to x          \ aka ->x
+to x         \ aka +>x
action-of x \ aka `x defer@
is x          \ aka `x defer!
addr x
```

This is all achieved through a common mechanism described in this section. As an example, let's define **dvalue** (it behaves in Gforth exactly like **2value**, see (undefined) [Values], page (undefined)). The code is as follows, explained below:

```
: d+! ( d addr -- )
  dup >r 2@ d+ r> 2! ;

\          to +to action-of is  addr
to-table: d!-table 2! d+!      n/a      n/a [noop]

' >body d!-table to-class: dvalue-to

: dvalue ( d "name" -- )
  create 2,
  ['] 2@ set-does>
  ['] dvalue-to set-to ;

#5. dvalue x
#2. +to x
x d. \ prints 7
```

First, we define the support word **d+!**.

Next, we define **d!-table**, a table of the various **to**-like actions.

For actions that are not supported, we put **n/a** in the table, and when you try to use, e.g., **is x**, exception -21 (unsupported operation) is thrown.

For the **to** and **+to** actions, we have to provide words with the stack effect (**d addr --**), where *addr* is the address where the data of the value-flavoured word is stored. For **addr** (only supported for **addressable:** words), we have to provide a word with the stack effect (**addr1 -- addr2**); in the usual case, both addresses are the same, and we can just provide **[noop]**. For the general case, see the description of **to-table:** below.

Next, the defining word **to-class:** combines the **d!-table** with the address-computation word **>body**, resulting in the definition of **dvalue-to**.¹⁰ The address-computation word has the stack effect (**... xt -- addr**). When invoking **+to x**,

¹⁰ The same **to-table** is often combined with different address computation words (e.g., for global values, user values, value-flavoured fields and locals), that's why the definition of the **to-table** is separated from the definition of the **to-class**.

the *xt* of *x* is pushed and then the address-computation word (*>body*) is called; the result is the address that is then passed on to *d+!* (from *d!-table*).

For *dvalue* that's all, but in other cases, e.g., value-flavoured fields (see *<undefined>* [Value-Flavoured and Defer-Flavoured Fields], page *<undefined>*), additional stack items can be consumed by the address-computation word, and those have to be provided by the user as stack-top values when invoking, e.g., *to field*.

Next, we have the definition of *dvalue*, which is a straightforward *create...set-does>* word that also tells *name* with *set-to* how it should behave for *to* etc.

Finally, we use *dvalue* to define *x* and use it. The line using *+to* exercises the *set-to* mechanism:

```
#2. +to x
performs
#2. ' x >body d+!
```

The *>body* is the address-computation word given in the definition of *dvalue-to*, and the *d+!* is the *+to* entry in *d!-table*.

These are the words mentioned above:

```
to-table: ( "name" "to-word" "+to-word" "addr-word" "action-of-word" "is-word" - ) gforth-
experimental "to-table-colon"
```

Create a table *name* with entries for *TO*, *+TO*, *ACTION-OF*, *IS*, and *ADDR*. The words for these entries are called with *xt* on the stack, where *xt* belongs to the word behind *to* (or *+to* etc.). Use *n/a* to mark unsupported operations. Default entries operations can be left away at the end of the line; the default for the *addr* entry is *[noop]* while the default for the other entries is *n/a*.

The stack effects of the actions are:

- For the *to* and *+to* action: (*value* *addr* --), where *value* has the appropriate type (e.g., a double-cell in our *dvalue* example).
- For the *action-of* action: (*addr* -- *xt*)
- For the *is* action: (*xt* *addr* --)
- For the *addr* action: (*addr1* -- *addr2*)

The *addr* input parameter in all these cases is the address of the memory where the value of the *xt* is stored.

The default mechanism means that *d!-table* could instead have been defined as follows:

```
\
to-table: d!-table 2! d+!
n/a ( - ) gforth-experimental "not-available"
```

This word can be ticked, but throws an "Operation not supported" exception on interpretation and compilation. Use this for methods etc. that aren't supported.

```
[noop] ( - ) gforth-experimental "bracket-noop"
```

Does nothing, both when executed and when compiled.

```
to-class: ( xt table "name" - ) gforth-experimental "to-class-colon"
```

Create a to-class implementation *name*, where *xt* (... *xt* -- *addr*) computes the address to access the data, and *table* (created with *to-table*;) contains the words for accessing it.

```
>uvalue ( xt - addr ) gforth-internal "to-uvalue"
```

Xt is the *xt* of a word *x* defined with *uvalue*; *addr* is the address of the data of *x* in the current task. This word is useful for building, e.g., *uvalue*. Do not use it to circumvent that you cannot get the address of a *uvalue* with *addr*; in the future Gforth may perform optimizations that assume that *uvalues* can only be accessed through their name.

```
set-to ( to-xt - ) gforth-1.0 "set-to"
```

Changes the implementations of the to-class methods of the most recently defined word to come from the to-class that has the *xt* *to-xt*.

6.11.10.7 User-defined compile,

You can also change the implementation of *compile*, for a word, with

```
set-optimizer ( xt - ) gforth-1.0 "set-optimizer"
```

Changes the current word such that *compile*,ing it executes *xt* (with the same stack contents as passed to *compile*,). Note that *compile*, must be consistent with *execute*, so you must use *set-optimizer* only to install a more efficient implementation of the same behaviour.

```
opt: ( compilation - colon-sys2 ; run-time - nest-sys ) gforth-1.0 "opt:"
```

Starts a nameless colon definition; when it is complete, this colon definition will become the *compile*, implementation of the latest word (before the *opt*:).

Note that the resulting *compile*, must still be equivalent to *postpone literal* *postpone execute*, so *set-optimizer* is useful for efficiency, not for changing the behaviour. There is nothing that prevents you from shooting yourself in the foot, however. You can check whether your uses of *set-optimizer* are correct by comparing the results when you use it with the results you get when you disable your uses by first defining

```
: set-optimizer drop ;
```

As an example of the use of *set-optimizer*, we can enhance *myconstant3* as follows.

```
: myconstant4 ( n "name" -- ; name: -- n )
  create ,
  ['] @ set-does>
  [: >body @ postpone literal ;] set-optimizer
;
```

The only change is the addition of the *set-optimizer* line. When you define a constant and compile it:

```
5 myconstant4 five
: foo five ;
```

the compiled *five* in *foo* is now compiled to the literal 5 instead of a generic invocation of *five*. The quotation has the same stack effect as *compile*,: (*xt* --). The passed *xt* belongs to the *compile*,d word, i.e., *five* in the example. In the example the *xt* is first converted to the body address, then the value 5 at that place is fetched, and that value is compiled with the *postpone literal* (see <undefined> [Literals], page <undefined>)).

This use of `set-optimizer` assumes that the user does not change the value of a constant with, e.g., `6 ' five >body !`. While `five` has been defined with `create`, that is an implementation detail of `CONSTANT`, and if you don't document it, the user must not rely on it. And if you use `set-optimizer` in a way that assumes that the body does not change (like is done here), you must not document that `create` is used; and conversely, if you document it, you have to write the `compile`, implementation such that it can deal with changing bodies.

Note that the call to `set-optimizer` has to be performed after the call to `set-does>` (or `does>`, because `set-does>` overwrites the `compile`, implementation itself.

We can also apply `set-optimizer` to individual words rather than inside a defining word like `constant`. In this case, the xt of the word passed to optimizer is usually unnecessary and is dropped. As an simple example, let's define a word that is inlined when being compiled:

```
: compile-my2dup ( xt -- )
  drop ]] over over [[ ;

: my2dup over over ;
' compile-my2dup set-optimizer

: foo my2dup ;
see my2dup
```

An alternative way to define `my2dup` is:

```
: my2dup over over ;
opt: drop ]] over over [[ ;
```

`Opt:` starts an anonymous definition that is then (internally) attached to `my2dup` with `set-optimize`.

Finally an even more convenient way to write this is to use `inline:` (see [\(undefined\)](#) [Inline Definitions], page [\(undefined\)](#)), but it is limited to inlining.

The engine `gforth-itc` uses `,` for `compile`, in nearly all cases and `set-optimizer` usually has no effect there.

6.11.10.8 Creating from a prototype

In the above we show how to define a word by first using `create`, and then modifying it with `immediate`, `set-does>`, `set-to`, `set-optimizer` etc.

An alternative way is to create a prototype using these words, and then create a new word from that prototype. This kind of copying does not cover the body, so that has to be allocated and initialized explicitly. Taking `dvalue` above, we could instead define it as:

```
create dvalue-prototype ( -- d )
`2@ set-does>
`dvalue-to set-to

: dvalue ( d "name" -- ; name: -- d )
  ``dvalue-prototype create-from 2, reveal ;
```

An advantage of this approach is that creating words with **dvalue** is now faster.¹¹ But this advantage is only relevant if the number of words created with this defining word is huge.

```
create-from ( nt "name" - ) gforth-1.0 "create-from"
```

Create a word *name* that behaves like *nt*, but with an empty body. *nt* must be the nt of a named word. The resulting header is not yet **revealed**; use **reveal** to reveal it or **latest** to get its xt. Creating a word with **create-from** without using any **set-** words is faster than if you create a word using **set-** words, **immediate**, or **does>**. You can use **noname** with **create-from**.

```
reveal ( - ) gforth-0.2 "reveal"
```

Put the current word in the wordlist current at the time of the header definition.

```
reveal! ( xt wid - ) core-ext "reveal-store"
```

Add *xt* to a wordlist. Mapped to **DEFER!**.

The performance advantage does not extend to using **noname** with the defining word. Therefore we also have

```
noname-from ( xt - ) gforth-1.0 "noname-from"
```

Create a nameless word that behaves like *xt*, but with an empty body. *xt* must be the nt of a nameless word.

Here's a usage example:

```
`dvalue-prototype noname create-from
latestnt constant noname-dvalue-prototype

: noname-dvalue ( d -- xt ; xt execution: -- d )
  noname-dvalue-prototype noname-from 2,
  latestxt ;
```

6.11.10.9 Making a word current

Many words mentioned above, such as **immediate** or **set-optimizer** change the "current" or "most recently defined" word. Sometimes you want to change an earlier word. You can do this with

```
make-latest ( nt - ) gforth-1.0 "make-latest"
```

Make *nt* the latest definition, which can be manipulated by **immediate** and **set-*** operations. If you have used (especially compiled) the word referred to by *nt* already, do not change the behaviour of the word (only its implementation), otherwise you may get a surprising mix of behaviours that is not consistent between Gforth engines and versions.

6.11.10.10 Const-does>

A frequent use of **create...does>** is for transferring some values from definition-time to run-time. Other ways of achieving this are closures (see <undefined> [Closures], page <undefined>), and with colon definitions (see <undefined> [User-defined defining words with colon definitions], page <undefined>), but another way of achieving this is to use

```
const-does> ( run-time: w*uw r*ur uw ur "name" - ) gforth-obsolete "const-does"
```

¹¹ The non-prototype method first duplicates the header methods of **create**, modify them, and eventually deduplicate them. The **create-from** approach eliminates this overhead.

Defines *name* and returns.

name execution: pushes *w*uw r*ur*, then performs the code following the `const-does>`.

A typical use of this word is:

```
: curry+ ( n1 "name" -- )
1 0 CONST-DOES> ( n2 -- n1+n2 )
+ ;
```

```
3 curry+ 3+
```

Here the 1 0 means that 1 cell and 0 floats are transferred from definition to run-time.

The advantages of using `const-does>` compared to `create}{...@word{does>` are:

- You don't have to deal with storing and retrieving the values, i.e., your program becomes more writable and readable.
- When using `does>`, you have to introduce a `@` that cannot be optimized away automatically (because the system does not know whether you allow to access the data with `>body...!`). You can address this problem with `set-optimizer` (see [\(undefined\)](#) [User-defined compile-comma], page [\(undefined\)](#)), but `const-does>` avoids it; however, the current implementation is still not particularly efficient.

A Standard Forth implementation of `const-does>` is available in `compat/const-does.fs`.

6.11.11 Deferred Words

The defining word `Defer` allows you to define a word by name without defining its behaviour; the definition of its behaviour is deferred. Here are two situation where this can be useful:

- Where you want to allow the behaviour of a word to be altered later, and for all precompiled references to the word to change when its behaviour is changed.
- For mutual recursion: See [\(undefined\)](#) [Calls and returns], page [\(undefined\)](#).

In the following example, `foo` always invokes the version of `greet` that prints “Good morning” whilst `bar` always invokes the version that prints “Hello”. There is no way of getting `foo` to use the later version without re-ordering the source code and recompiling it.

```
: greet ." Good morning" ;
: foo ... greet ... ;
: greet ." Hello" ;
: bar ... greet ... ;
```

This problem can be solved by defining `greet` as a `Deferred` word. The behaviour of a `Deferred` word can be defined and redefined at any time by using `IS` to associate the xt of a previously-defined word with it. The previous example becomes:

```
Defer greet ( -- )
: foo ... greet ... ;
: bar ... greet ... ;
: greet1 ( -- ) ." Good morning" ;
: greet2 ( -- ) ." Hello" ;
' greet2 IS greet \ make greet behave like greet2
```

Programming style note: You should write a stack comment for every deferred word, and put only XT's into deferred words that conform to this stack effect. Otherwise it's too difficult to use the deferred word.

One thing to note is that IS has special compilation semantics, such that it parses the name at compile time (like T0):

```
: set-greet ( xt -- )
  IS greet ;
```

```
' greet1 set-greet
```

```
Defer ( "name" - ) core-ext "Defer"
```

Define a deferred word *name*; you have to set it to an xt before executing it.

name execution: execute the most recent xt that *name* has been set to.

IS *name* run-time: (*xt* -) Set *name* to execute *xt*.

```
IS ( xt "name" - ) core-ext "IS"
```

changes the deferred word *name* to execute *xt*

You can extract the xt of a deferred word with *action-of*:

```
action-of greet ( xt ) >name id.
```

```
action-of ( interpretation "name" - xt; compilation "name" - ; run-time - xt ) core-
ext "action-of"
```

Xt is the XT that is currently assigned to *name*.

One usage for deferred words is the definition of a an action (e.g., initialization) in several pieces, each piece in a different source file dealing with the matters of that source file. This can be done with

```
defer myspeech ( -- )
:noname cr ." <central message>" ; is myspeech
```

```
\ and in every source file where you want to add a piece, something like
:noname ( -- )
  cr ." <introduction>"
  [ action-of myspeech compile, ]
  cr ." <conclusion>"
; is myspeech
```

The [*action-of myspeech compile,*] calls the previous content of *myspeech*. Gforth offers the words *:is* and *defers* to express the last definition more conveniently:

```
:is myspeech ( -- )
  cr ." <introduction>"
  defers myspeech
  cr ." <conclusion>" ;
:is ( "name" - ) gforth-experimental "is"
```

define a *noname* that is assigned to the deferred word *name* at ;.

```
defers ( compilation "name" - ; run-time ... - ... ) gforth-0.2 "defers"
```

Compiles the present contents of the deferred word *name* into the current definition. I.e., this produces static binding as if *name* was not deferred.

Another usage is to change a deferred word temporarily, and later change it back. Gforth provides words for supporting this usage. The use of **preserve** is shown in this example:

```
: smalltalk ( -- )
  greet ." Isn't the weather nice?" ;

\ here GREET performs GREET2
: when-in-rome ( xt -- )
  [: ." Buon Giorno!" ;] is greet
  execute
  preserve greet \ Equivalent to: ['] greet2 is greet
;

' greet1 is greet
greet \ "Good Morning"
' smalltalk when-in-rome \ "Buon Giorno! Isn't the weather nice?"
greet \ "Hello"

preserve ( compilation "name" - ; run-time - ) gforth-1.0 "preserve"
```

Name has to be a defer-flavoured word that does not consume additional stack items for addressing (i.e., not a defer-flavoured field). **Preserve** *name* changes *name* at run-time to execute the same XT that it had at compile time. I.e., **Preserve** *name* is equivalent to [*action-of name*] literal is *name*.

Preserve is only appropriate when you want to restore the deferred word to a fixed xt. If you want to change a deferred temporarily and then restore its old run-time value, use **wrap-xt**:

```
: when-in-rome2 ( xt -- )
  [: ." Buon Giorno!" ;] ['] greet rot wrap-xt ;

' greet1 is greet
greet \ "Good Morning"
' smalltalk when-in-rome2 \ "Buon Giorno! Isn't the weather nice?"
greet \ "Good Morning"

wrap-xt ( ... xt1 xt2 xt3 - ... ) gforth-1.0 "wrap-xt"
```

Set deferred word *xt2* to *xt1* and execute *xt3*. Restore afterwards.

For implementing words like **wrap-xt** to which you pass the xt of a deferred word, you cannot use **is** and **action-of**, which consume a name from the input stream. Instead, you use the words **defer!** and **defer@**.

defer! (*xt xt-deferred* -) core-ext "defer-store"

xt-deferred belongs to a word defined with **defer**, it is changed to execute *xt* on execution.

If *xt-deferred* belongs to another defer-flavoured word (e.g., a defer-flavoured field), the location associated with ... *xt-deferred* is changed to execute *xt*.

If *xt-deferred* is the xt of a word that is not defer-flavoured, throw -21 (Unsupported operation).

defer@ (... *xt-deferred* - *xt*) core-ext "defer-fetch"

If *xt-deferred* belongs to a word defined with **defer**, *xt* represents the word currently associated with the deferred word *xt-deferred*.

If *xt-deferred* belongs to another defer-flavoured word (e.g., a defer-flavoured field), *xt* is the word associated with the location indicated by ... *xt-deferred* (e.g., for a defer-flavoured field ... is the structure address).

If *xt-deferred* is the xt of a word that is not defer-flavoured, throw -21 (Unsupported operation).

A deferred word can only inherit execution semantics from the xt (because that is all that an xt can represent – for more discussion of this see [\[Tokens for Words\]](#), page [\[undefined\]](#)); by default it will have default interpretation and compilation semantics deriving from this execution semantics. However, you can change the interpretation and compilation semantics of the deferred word in the usual ways:

```
: bar .... ; immediate
Defer fred immediate
Defer jim

' bar IS jim \ jim has default semantics
' bar IS fred \ fred is immediate
```

6.11.12 Synonyms

The defining word **synonym** allows you to define a word by name that has the same behaviour as some other word. Here are two situation where this can be useful:

- When you want access to a word's definition from a different word list (for an example of this, see the definitions in the **Root** word list in the Gforth source).
- When you want to create a synonym; a definition that can be known by either of two names (for example, **THEN** and **ENDIF** can be defined as synonyms).

Synonym (*name* "oldname" –) tools-ext "Synonym"

Define *name* to behave the same way as *oldname*: Same interpretation semantics, same compilation semantics, same **to**, **+to**, **is**, **action-of** and **addr** semantics.

Gforth also offers the Gforth-specific **alias**, that allows to define another word with the same execution token, but otherwise default semantics (no copying of compilation or other semantics). You can then change, e.g., the compilation semantics with, e.g., **immediate**.

Alias (*xt* "name" –) gforth-0.2 "Alias"

Define *name* as a word that performs *xt*. Unlike for deferred words, aliases don't have an indirection overhead when compiled.

Example:

```
: foo ." foo" ; immediate

' foo Alias bar1 \ bar1 is not an immediate word
' foo Alias bar2 immediate \ bar2 is an immediate word
synonym bar3 foo \ bar3 is an immediate word
: test-bar1 bar1 ; \ no output
test-bar1 \ "foo"
: test-bar2 bar2 ; \ "foo"
```



```

test-bar2          \ no output
: test-bar3 bar3 ; \ "foo"
test-bar3          \ no output

```

Both synonyms and aliases have a different `nt` than the original, but ticking it (or using `name>interpret`) produces the same `xt` as the original (see `<undefined>` [Tokens for Words], page `<undefined>`).

6.12 Structures

A structure (aka record) is a collection of fields that are stored together. The fields can have different types and are accessed by name. There are typically several instances of a structure, otherwise programmers tend to prefer using a variable or `somesuch` for each field.

In Forth you can use raw address arithmetic to access fields of structures, but using field names and defining field access words with the defining words described in this section makes the code more readable.

6.12.1 Standard Structures

The Forth 2012 standard defines a number of words for defining fields and structures.

A typical example of defining a structure with several fields is:

```

0 \ offset of first field, 0 in the usual case
  field: intlist-next ( intlist -- addr1 )
  field: intlist-val  ( intlist -- addr2 )
constant intlist ( -- u )

```

An equivalent alternative way of defining this structure is:

```

begin-structure intlist ( -- u )
  field: intlist-next ( intlist -- addr1 )
  field: intlist-val  ( intlist -- addr2 )
end-structure

```

`Intlist` returns the size of the structure. The convention for the field names here is to prepend the structure name, so that you don't run into conflicts when several structures have `next` and `val` fields; in Forth, by default field names are in the same wordlist (i.e., the same name space) as the other words (including other field names), and trying to use the search order (see `<undefined>` [Word Lists], page `<undefined>`) for avoiding conflicts is rather cumbersome (unless you use the scope recognizer see `<undefined>` [Dealing with existing Recognizers], page `<undefined>`).

You can then use that to allocate an instance of that structure and then use the field words to access the fields of that instance:

```

intlist allocate throw constant my-intlist1
0 my-intlist1 intlist-next !
5 my-intlist1 intlist-val  !

intlist allocate throw constant my-intlist2
my-intlist1 my-intlist2 intlist-next !
7          my-intlist2 intlist-val  !

```

```

: intlist-sum ( intlist -- n )
\ "intlist" is a pointer to the first element of a linked list
\ "n" is the sum of the intlist-val fields in the linked list
  0 BEGIN ( intlist1 n1 )
    over
  WHILE ( list1 n1 )
    over intlist-val @ +
    swap intlist-next @ swap
  REPEAT
  nip ;

```

```
my-intlist2 intlist-sum . \ prints "12"
```

In addition to **field:** for cell-aligned and cell-sized fields, you can define fields sized and aligned for various types with:

```
begin-structure ( "name" - struct-sys 0 ) facility-ext "begin-structure"
```

```
end-structure ( struct-sys +n - ) facility-ext "end-structure"
```

end a structure started with **begin-structure**

```
cfield: ( u1 "name" - u2 ) facility-ext "c-field-colon"
```

Define a char-sized field

```
field: ( u1 "name" - u2 ) facility-ext "field-colon"
```

Define an aligned cell-sized field

```
2field: ( u1 "name" - u2 ) gforth-0.7 "two-field-colon"
```

Define an aligned double-cell-sized field

```
ffield: ( u1 "name" - u2 ) floating-ext "f-field-colon"
```

Define a faligned float-sized field

```
sffield: ( u1 "name" - u2 ) floating-ext "s-f-field-colon"
```

Define a sfaigned sfloat-sized field

```
dffield: ( u1 "name" - u2 ) floating-ext "d-f-field-colon"
```

Define a dfaigned dfloat-sized field

```
wfield: ( u1 "name" - u2 ) gforth-1.0 "w-field-colon"
```

Define a naturally aligned field for a 16-bit value.

```
lfield: ( u1 "name" - u2 ) gforth-1.0 "l-field-colon"
```

Define a naturally aligned field for a 32-bit value.

```
xfield: ( u1 "name" - u2 ) gforth-1.0 "x-field-colon"
```

Define a naturally aligned field for a 64-bit-value.

If you need something beyond these field types, you can use **+field** to define fields of arbitrary size. You have to ensure the correct alignment yourself in this case. E.g., if you want to put one struct inside another struct, you would do it with

```

0
cfield:                nested-foo
aligned intlist +field nested-bar

```

constant nested

In this example the field **nested-bar** contains an **intlist** structure, so the size of **intlist** is passed to **+field**. An **intlist** must be cell-aligned (it contains cell fields), and this is achieved by aligning the current field offset with **aligned** before the field definition. Our recommendation is to always precede the usage of **+field** with an appropriate alignment word (except if character-alignment is good enough for the field); this ensures that the field will stay correctly aligned even if other fields are later inserted before the **+field**-defined field.

+field (*noffset1 nsize "name" - noffset2*) facility-ext “plus-field”

Defining word; defines *name* (*addr1 -- addr2*), where *addr2* is *addr1+noffset1*. *noffset2* is *noffset1+nsize*.

The first field is at the base address of a structure and the word for this field (e.g., **list-next**) actually does not change the address on the stack. You may be tempted to leave it away in the interest of run-time and space efficiency. This is not necessary, because Gforth and other Forth systems optimize this case: If you compile a first-field word, no code is generated. So, in the interest of readability and maintainability you should include the word for the field when accessing the field.

6.12.2 Value-Flavoured and Defer-Flavoured Fields

In addition to the variable-flavoured fields that produce an address (see [\(undefined\)](#) [Standard Structures], page [\(undefined\)](#)), Gforth also provides value-flavoured fields. Like all fields, value-flavoured fields consume the start address of the struct, but they produce their value and you can apply **to**, **+to** and (if the field is **addressable**;, see [\(undefined\)](#) [Values], page [\(undefined\)](#)) **addr** on them. E.g., we can do something like the **intlist** definition (see [\(undefined\)](#) [Standard Structures], page [\(undefined\)](#)):

```
0
      value: intlist>next ( intlista -- intlista1 )
      addressable: value: intlist>val ( intlista -- n )
      constant intlista ( -- u )
```

This means that there are the following ways of accessing **intlist>val**:

```
intlist>val ( intlista -- n )
->intlist>val ( n intlista -- ) \ aka to intlist>val
+>intlist>val ( n intlista -- ) \ aka +to intlist>val
addr intlist>val ( intlista -- addr )
```

And here's the earlier example (see [\(undefined\)](#) [Standard Structures], page [\(undefined\)](#)) rewritten to use **intlista**:

```
intlista allocate throw constant my-intlista1
0 my-intlista1 to intlist>next
5 my-intlista1 to intlist>val

intlista allocate throw constant my-intlista2
my-intlista1 my-intlista2 to intlist>next
7      my-intlista2 to intlist>val

: intlista-sum ( intlista -- n )
```

```

\ "intlista" is a pointer to the first element of a linked list
\ "n" is the sum of the intlist>val fields in the linked list
0 BEGIN ( intlista1 n1 )
  over
  WHILE ( list1 n1 )
    over intlist>val +
    swap intlist>next swap
  REPEAT
  nip ;

```

```
my-intlista2 intlista-sum . \ prints "12"
```

Depending on the type of the field, the value can be something different than a single cell.

value: (*u1* "*name*" - *u2*) gforth-experimental "value:"

Name is a value-flavoured field; in-memory-size: cell; on-stack: cell

cvalue: (*u1* "*name*" - *u2*) gforth-experimental "cvalue:"

Name is a value-flavoured field; in-memory-size: char; on-stack: unsigned cell

wvalue: (*u1* "*name*" - *u2*) gforth-experimental "wvalue:"

Name is a value-flavoured field; in-memory-size: 16 bits; on-stack: unsigned cell

lvalue: (*u1* "*name*" - *u2*) gforth-experimental "lvalue:"

Name is a value-flavoured field; in-memory-size: 32 bits; on-stack: unsigned cell

scvalue: (*u1* "*name*" - *u2*) gforth-experimental "scvalue:"

Name is a value-flavoured field; in-memory-size: char; on-stack: signed cell

swvalue: (*u1* "*name*" - *u2*) gforth-experimental "swvalue:"

Name is a value-flavoured field; in-memory-size: 16 bits; on-stack: signed cell

slvalue: (*u1* "*name*" - *u2*) gforth-experimental "slvalue:"

Name is a value-flavoured field; in-memory-size: 32 bits; on-stack: signed cell

2value: (*u1* "*name*" - *u2*) gforth-experimental "2value:"

Name is a value-flavoured field; in-memory-size: 2 cells; on-stack: 2 cells; **+to** performs double-cell addition (**d+**).

fvalue: (*u1* "*name*" - *u2*) gforth-experimental "fvalue:"

Name is a value-flavoured field; in-memory-size: float; on-stack: float

sfvalue: (*u1* "*name*" - *u2*) gforth-experimental "sfvalue:"

Name is a value-flavoured field; in-memory-size: 32-bit float; on-stack: float

dfvalue: (*u1* "*name*" - *u2*) gforth-experimental "dfvalue:"

Name is a value-flavoured field; in-memory-size: 64-bit float; on-stack: float

zvalue: (*u1* "*name*" - *u2*) gforth-experimental "zvalue:"

Name is a value-flavoured field; in-memory-size: 2 floats; on-stack: 2 floats; **+to** performs componentwise addition.

\$value: (*u1* "*name*" - *u2*) gforth-experimental "\$value:"

Name is a value-flavoured field; in-memory-size: cell; on-stack: c-addr u (see <undefined> [String words], page <undefined>); (c-addr u) +to *name* appends c-addr u to the string in the field.

Gforth also has field words for dealing with dynamically-sized arrays. A field for such an array contains just a cell that points to the actual data, and this cell has to be set to 0 before accessing the array the first time. When accessing the field (without operator, or with *to* or *+to*), there has to be the index and the structure address on the stack, with the structure address on top. Any further items consumed by *to* or *+to* are below the index on the stack. The array expands to the size given by the maximum access; any unset elements are 0; for *\$value[]* accessing them produces a 0-length (i.e., empty) string.

Here is a usage example:

```
0
  value[]: bla>x[]
  $value[]: bla>$y[]
constant bla

bla allocate throw constant mybla
mybla bla erase \ set all fields to 0

5 2 mybla to bla>x[] \ access at index 2
7 0 mybla to bla>x[] \ access at index 0
2 mybla bla>x[] . \ prints "5"
3 mybla bla>x[] . \ prints "0"
"foo" 2 mybla to bla>$y[] \ access at index 2
"bla" 1 mybla to bla>$y[] \ access at index 1
"bar" 2 mybla +to bla>$y[] \ access at index 2
0 mybla bla>$y[] . . \ prints "0 0"
1 mybla bla>$y[] type \ prints "bla"
2 mybla bla>$y[] type \ prints "foobar"
value[]: ( u1 "name" - u2 ) gforth-experimental "value[]:"
```

Name is a value-flavoured array field; in-memory-size: cell; on-stack: cell

```
$value[]: ( u1 "name" - u2 ) gforth-experimental "$value[]:"
```

Name is a value-flavoured array field; in-memory-size: cell; on-stack: c-addr u (see <undefined> [String words], page <undefined>); (c-addr u) +to *name* appends c-addr u to the string in the array element.

Finally, you can define defer-flavoured fields. Here is a usage example:

```
0
  addressable: defer: foo'bar
constant foo

foo allocate throw constant my-foo
:noname ." test" ; my-foo is foo'bar
my-foo foo'bar \ prints "test"
my-foo addr foo'bar @ execute \ prints "test"
my-foo action-of foo'bar execute \ prints "test"
```

```

my-foo `foo'bar defer@ execute \ prints "test"
:noname ." test1" ; my-foo `foo'bar defer!
my-foo foo'bar \ prints "test1"
defer: ( u1 "name" - u2 ) gforth-experimental "defer:"

```

Name is a defer-flavoured field

For documentation of `is`, `action-of`, `defer@`, `defer!`, see See `<undefined>` [Deferred Words], page `<undefined>`. Note however, that when used on defer-flavoured fields, all these words consume the start address of the structure, unlike for words defined with `defer`.

6.12.3 Structure Extension

You can create a new structure starting with an existing structure and its fields. E.g., if we also want to define `floatlist`, we can factor out the `...-next` field into a general structure `list` without payload, and then define `intlist` and `floatlist` as extensions of `list`:¹²

```

0
  field: list-next ( list -- addr )
constant list ( -- u )

list
  field: intlist-val ( intlist -- addr )
constant intlist ( -- u )

list
  ffield: floatlist-val ( floatlist -- addr )
constant floatlist ( -- u )

```

Note that in this variant there is no `intlist-next` nor a `floatlist-next`, just a `list-next`; so when you use, e.g., a `floatlist`, the organization through extension of `list` is exposed. This may make it harder to refactor things, so you may prefer to also introduce synonyms `intlist-next` and `floatlist-next`.

If you prefer to use `begin-structure...end-structure`, you can do the equivalent definition as follows:

```

begin-structure list ( -- u )
  field: list-next ( list -- addr )
end-structure

list extend-structure intlist
  field: intlist-val ( intlist -- addr )
end-structure

list extend-structure floatlist
  ffield: floatlist-val ( floatlist -- addr )
end-structure

extend-structure ( n "name" - struct-sys n ) gforth-1.0 "extend-structure"

```

Start a new structure *name* as extension of an existing structure with size *n*.

¹² This feature is also known as *extended records* in Oberon.

6.12.4 Gforth structs

Gforth has had structs before the standard had them; they are a little different, and you can still use them. One benefit of the Gforth structs is that they propagate knowledge of alignment requirements, so if you build the `nested` structure (see [\[Standard Structures\]](#), page [\[Standard Structures\]](#)), you do not need to look inside `intlist` to find out the proper alignment, and you also do not need to mention alignment at all. Instead, this example would look like:

```
struct
  cell% field intlist-next
  cell% field intlist-val
end-struct intlist%

struct
  char%    field nested-foo
  intlist% field nested-bar
end-struct nested%
```

The fields are variable-flavoured, i.e., they work in the same way as those defined with `field:`, `+field` etc.

A disadvantage of the Gforth structs is that, with the standard going for something else, you need to learn additional material to write and understand code that uses them. Another disadvantage of the Gforth structs is that they do not support value-flavoured or defer-flavoured fields. On the balance, in our opinion the disadvantages now outweigh the advantages, so we recommend using the standard structure words (see [\[Standard Structures\]](#), page [\[Standard Structures\]](#)). Nevertheless, here is the documentation for Gforth's structs.

The `list` and `intlist` examples look like this with Gforth structs:

```
struct
  cell% field list-next
end-struct list%

list%
  cell% field intlist-val
end-struct intlist%
```

`Intlist%` contains information about size and alignment, and you use `%size` to get the size, e.g., for allocation:

```
intlist% %size allocate throw constant my-intlist1
```

A shorthand for that is

```
intlist% %alloc constant my-intlist1
```

The fields behave the same way, so the rest of the example works as with standard structures.

In addition to specifying single cells with `cell%`, you can also specify an array of, e.g., 10 cells like this:

```
cell% 10 * field bla-blub
\ equivalent to the standard:
```

```
\ aligned 10 cells +field bla-blub
```

You can use `cell% 10 *` not just with `field`, but also in other places where an alignment and size is expected, e.g., with `%alloc`.

```
%align ( align size - ) gforth-0.4 “percent-align”
```

Align the data space pointer to the alignment *align*.

```
%alignment ( align size - align ) gforth-0.4 “percent-alignment”
```

The alignment of the structure.

```
%alloc ( align size - addr ) gforth-0.4 “percent-alloc”
```

Allocate *size* address units with alignment *align*, giving a data block at *addr*; **throw** an **ior** code if not successful.

```
%allocate ( align size - addr ior ) gforth-0.4 “percent-allocate”
```

Allocate *size* address units with alignment *align*, similar to `allocate`.

```
%allot ( align size - addr ) gforth-0.4 “percent-allot”
```

Allot *size* address units of data space with alignment *align*; the resulting block of data is found at *addr*.

```
cell% ( - align size ) gforth-0.4 “cell-percent”
```

```
char% ( - align size ) gforth-0.4 “char-percent”
```

```
dfloat% ( - align size ) gforth-0.4 “d-float-percent”
```

```
double% ( - align size ) gforth-0.4 “double-percent”
```

```
end-struct ( align size "name" - ) gforth-0.2 “end-struct”
```

Define a structure/type descriptor *name* with alignment *align* and size *size1* (*size* rounded up to be a multiple of *align*).

name execution: *– align size1*

```
field ( align1 offset1 align size "name" - align2 offset2 ) gforth-0.2 “field”
```

Create a field *name* with offset *offset1*, and the type given by *align size*. *offset2* is the offset of the next field, and *align2* is the alignment of all fields.

name execution: *addr1 – addr2*.

addr2=addr1+offset1

```
float% ( - align size ) gforth-0.4 “float-percent”
```

```
sfloat% ( - align size ) gforth-0.4 “s-float-percent”
```

```
%size ( align size - size ) gforth-0.4 “percent-size”
```

The size of the structure.

```
struct ( - align size ) gforth-0.2 “struct”
```

An empty structure, used to start a structure definition.

6.13 User-defined Stacks

Gforth supports user-defined stacks. They are used for implementing features such as recognizer sequences, but you can also define stacks for your own purposes. And these stacks actually support inserting and deleting at both ends, so they are actually double-ended queues (deques). In addition, they support inserting and deleting in the middle.

In Gforth the stacks grow as necessary, but the interface is designed to also support resource-constrained systems that allocate fixed-size stacks, where exceeding the stack size results in an error. So you should provide the size parameter accordingly.

A stack is represented on the data stack by a cell.

stack (*n* – *stack*) gforth-experimental “stack”

Create an unnamed stack with at least *n* cells space.

stack: (*n* “*name*” –) gforth-experimental “stack-colon”

Create a named stack with at least *n* cells space.

stack> (*stack* – *x*) gforth-experimental “stack-from”

Pop item *x* from top of *stack*.

>stack (*x* *stack* –) gforth-experimental “to-stack”

Push *x* to top of *stack*.

>back (*x* *stack* –) gforth-experimental “to-back”

Insert *x* at the bottom of *stack*.

back> (*stack* – *x*) gforth-experimental “back-from”

Remove item *x* from bottom of *stack*.

+after (*x1* *x2* *stack* –) gforth-experimental “plus-after”

Insert *x1* below every occurrence *x2* in *stack*.

-stack (*x* *stack* –) gforth-experimental “minus-stack”

Delete every occurrence of *x* from anywhere in *stack*.

set-stack (*x1* .. *xn* *n* *stack* –) gforth-experimental “set-stack”

Overwrite the contents of *stack* with *n* elements from the data stack, with *xn* becoming the top of *stack*.

get-stack (*stack* – *x1* .. *xn* *n*) gforth-experimental “get-stack”

Push the contents of *stack* on the data stack, with the top element in *stack* being pushed as *xn*.

6.14 Interpretation and Compilation Semantics

The *interpretation semantics* of a (named) word are what the text interpreter does when it encounters the word in interpret state. It also appears in some other contexts, e.g., the execution token returned by ' *word* identifies the interpretation semantics of *word* (in other words, ' *word* **execute** is equivalent to interpret-state text interpretation of *word*).

The *compilation semantics* of a (named) word are what the text interpreter does when it encounters the word in compile state. It also appears in other contexts, e.g, **POSTPONE** *word* compiles¹³ the compilation semantics of *word*.

¹³ In standard terminology, “appends to the current definition”.

Most words have default compilation semantics: compile the execution semantics (stack effect (--)). But a number of words have other compilation semantics, documented for the individual word (including its stack effect).

The standard also talks about *execution semantics*. In the standard it never differs from the interpretation semantics if both are defined, but one or both of them may not be defined. Gforth makes no difference between interpretation and execution semantics, so these terms are used interchangeably.

In Gforth (since 1.0) all words have defined interpretation/execution semantics. For many words that have no defined interpretation nor execution semantics in the standard (e.g., `if`), the interpretation/execution semantics in Gforth are to perform the compilation semantics.

In the standard, execution semantics are used to define interpretation and compilation semantics by default: By default, the interpretation semantics of a word are to **execute** its execution semantics, and the compilation semantics of a word are to **compile**, its execution semantics.¹⁴

Unnamed words (see `<undefined>` [Anonymous Definitions], page `<undefined>`) cannot be encountered by the text interpreter, ticked, or **postponed**. Such a word is represented by its `xt` (see `<undefined>` [Tokens for Words], page `<undefined>`), and the behaviour when this `xt` is **executed** is called its execution semantics.

You can change the semantics of the most-recently defined word:

```
immediate ( - ) core “immediate”
```

Make the compilation semantics of a word be to **execute** the execution semantics.

```
compile-only ( - ) gforth-0.2 “compile-only”
```

Mark the last definition as compile-only; as a result, the text interpreter and `'` will warn when they encounter such a word.

```
restrict ( - ) gforth-0.2 “restrict”
```

A synonym for **compile-only**

By convention, words with non-default compilation semantics (e.g., immediate words) often have names surrounded with brackets (e.g., `[']`, see `<undefined>` [Execution token], page `<undefined>`).

Note that ticking (`'`) a compile-only word gives a warning (“`<word>` is compile-only”).

6.14.1 Combined Words

Gforth allows you to define *combined words* – words that have an arbitrary combination of interpretation and compilation semantics (some people call them NDCS words, and mean words with non-default and non-immediate compilation semantics).

```
interpret/compile: ( interp-xt comp-xt "name" - ) gforth-0.2 “interpret/compile:”
```

This feature was introduced for implementing **T0** and **S**. I recommend that you do not define such words, as cute as they may be: they make it hard to get at both parts of the word in some contexts. E.g., assume you want to get an execution token for the compilation

¹⁴ In standard terminology: The default interpretation semantics are its execution semantics; the default compilation semantics are to append its execution semantics to the execution semantics of the current definition.

part. Instead, define two words, one that embodies the interpretation part, and one that embodies the compilation part. Once you have done that, you can define a combined word with `interpret/compile:` for the convenience of your users.

A typical usage example is:

```
: s"-int ( -- c-addr u )
  ''' parse save-mem ;
: s"-comp ( -- ; run-time: -- c-addr u )
  ''' parse postpone sliteral ;
' s"-int ' s"-comp interpret/compile: s"
```

Some people are not happy with the looks of the definition above, so Gforth also provides additional ways to write this kind of definition:

```
set-compsem ( xt - ) gforth-experimental "set-compsem"
```

change compilation semantics of the last defined word

```
compsem: ( - ) gforth-experimental "compsem:"
```

Changes the compilation semantics of the current definition to perform the definition starting at the `compsem:`.

```
intsem: ( - ) gforth-experimental "intsem:"
```

The current definition's compilation semantics are changed to perform its execution semantics (the word becomes immediate). Then its interpretation semantics are changed to perform the definition starting at the `intsem:`. Note that if you then call `immediate`, the compilation semantics are changed to perform the word's new interpretation semantics.

Note that there are and should be only few combined words, ideally none, and their definitions don't need to be pretty (on the contrary, their ugliness may provide a warning that "here be dragons"). So our recommendation is to use `interpret/compile:`.

It is a bad idea to try to use combined words for optimization of words with default compilation semantics: Gforth has a better mechanism for that (`set-optimizer` and `opt:`, see [\[User-defined compile-comma\]](#), page [\[undefined\]](#)), `[compile]` treats combined words as having non-default compilation semantics, and the intended optimization does not happen when the combined word is ticked and `compile,d`.

Some people try to use *state-smart* words to emulate combined words (words are state-smart if they check `STATE` during execution). E.g., they would try to code `s"` like this:

```
: foobar
  STATE @ IF ( compilation state )
    comp-s"
  ELSE
    int-s"
  THEN ; immediate
```

Although this works if `s"` is only processed by the text interpreter, it does not work in other contexts (like `'` or `POSTPONE`). E.g., `' foobar` will produce an execution token for a state-smart word, not for the interpretation semantics of the original `foobar`; when you execute this execution token (directly with `EXECUTE` or indirectly through `COMPILE,`) in compile state, the result will not be what you expected (i.e., it will not call `int-s"`).

State-smart words are a bad idea. Simply don't write them¹⁵! Gforth provides better alternatives: `interpret/compile:` and `set->comp` for implementing combined words, and `set-optimizer` for implementing optimizations of words with default compilation semantics.

6.15 Tokens for Words

This section describes the creation and use of tokens that represent words.

6.15.1 Execution token

An *execution token* (*xt*) represents some behaviour of a word. You can use `execute` to invoke the behaviour represented by the *xt* and `compile`, (see [\(undefined\) \[Macros\]](#), page [\(undefined\)](#)) to compile it into the current definition. Other uses include deferred words (see [\(undefined\) \[Deferred Words\]](#), page [\(undefined\)](#)).

In particular, there is *the* execution token of a word that represents its interpretation semantics aka execution semantics.¹⁶

For a named word *x*, you can use ``x` to get its execution token:

```
5 ` . ( n xt )
execute ( )      \ execute the xt (i.e., ".")
: foo ` . execute ;
5 foo
```

However, the ``` prefix is a Gforth extension, so you may prefer to use the Standard Forth words:

```
' ( "name" - xt ) core "tick"
```

xt represents *name*'s interpretation semantics. Perform `-14 throw` if the word has no interpretation semantics.

```
['] ( compilation. "name" - ; run-time. - xt ) core "bracket-tick"
```

xt represents *name*'s interpretation semantics. Perform `-14 throw` if the word has no interpretation semantics.

These are parsing words (whereas ``x` is treated as a literal by a recognizer), and you may find the behaviour in interpreted and compiled code unintuitive:

```
5 ' . ( n xt )
execute ( )      \ execute the xt of .
\ does not work as intended:
\ : foo ' . ;
\ 5 foo execute
\ instead:
: foo ['] . ;
5 foo execute    \ execute the xt of .
```

¹⁵ For a more detailed discussion of this topic, see M. Anton Ertl, *State-smartness—Why it is Evil and How to Exorcise it* (<https://www.complang.tuwien.ac.at/papers/ertl98.ps.gz>), EuroForth '98.

¹⁶ The Forth standard has words with undefined interpretation semantics (e.g., `r@`) and words without defined execution semantics (e.g., `s"`) and words with neither (e.g., `if`), but in cases where both interpretation and execution semantics are defined, they are the same; so we treat them as being the same.

```

\ Usage of ' in colon definition:
: bar ' execute ;
5 bar .          \ execute the xt of .

```

' parses at run-time, so if you put it in a colon definition, as in `bar`, it does not consume the next word in the colon definition, but the next word at run-time (i.e., the `.` in the invocation of `bar`). If you want to put a literal xt in a colon definition without writing ``x`, write `['] x`.

Gforth's ``x`, `'` and `[']` warn when you use them on compile-only words, because such usage may be non-portable between different Forth systems.

You can avoid that warning as well as the portability problems by defining an immediate variant of the word, e.g.:

```

: if postpone if ; immediate
: test [ ' if execute ] ." test" then ;

```

The resulting execution token performs the compilation semantics of `if` when **executed**.

Another way to get an xt is `:noname` or `latestxt` (see [⟨undefined⟩](#) [Anonymous Definitions], page [⟨undefined⟩](#)). For anonymous words this gives an xt for the only behaviour the word has (the execution semantics), but you can also use it after defining a named word to get its xt.

```

:noname ." hello" ;
execute

```

An xt occupies one cell and can be manipulated like any other cell.

In Standard Forth the xt is just an abstract data type (i.e., defined by the operations that produce or consume it). The concrete implementation (since Gforth 1.0) is the body address (for old hands: PFA) of the word; in Gforth 0.7 and earlier, the xt was implemented as code field address (CFA, 2 cells before the PFA).

execute (*xt* –) core “execute”

Perform the semantics represented by the execution token, *xt*.

execute-exit (*compilation* – ; *run-time xt nest-sys* –) gforth-1.0 “execute-exit”

Execute **xt** and return from the current definition, in a tail-call-optimized way: The return address **nest-sys** and the locals are deallocated before executing **xt**.

perform (*a-addr* –) gforth-0.2 “perform”

@ **execute**.

Noop is sometimes used to have a placeholder execution token:

noop (–) gforth-0.2 “noop”

6.15.2 Name token

Gforth represents named words by the *name token*, (*nt*). The name token is a cell-sized abstract data type that occurs as argument or result of the words below.

Since Gforth 1.0, for most words the concrete implementation of their nt is the same address as its xt (this is the primary nt for the xt). However, synonyms, aliases, and words defined with **interpret/compile:** get their xt from another word, but still have an nt of their own (that is different from the xt). Therefore, you cannot use xts and nts

interchangeably, even if you are prepared to write code specific to Gforth 1.0. You do not get these alternate nts for the xt with **>name**.

You get the nt of a word *x* with ``x` (since Gforth 1.0) or with

find-name (*c-addr u* – *nt* | 0) gforth-0.2 “find-name”

Find the name *c-addr u* in the current search order. Return its *nt*, if found, otherwise 0.

find-name-in (*c-addr u wid* – *nt* | 0) gforth-1.0 “find-name-in”

search the word list identified by *wid* for the definition named by the string at *c-addr u*. Return its *nt*, if found, otherwise 0.

latest (– *nt*) gforth-0.6 “latest”

nt is the name token of the last word defined in the current section; it is 0 if the last word has no name.

latestnt (– *nt*) gforth-1.0 “latestnt”

nt is the name token of the most recent word defined in the current section.

>name (*xt* – *nt* | 0) gforth-0.2 “to-name”

The primary name token *nt* of the word represented by *xt*. Returns 0 if *xt* is not an xt (using a heuristic check that has a small chance of misidentifying a non-xt as xt), or if the primary nt is of an unnamed word. As of Gforth 1.0, every xt has a primary nt, but other named words may have the same interpretation semantics xt.

xt>name (*xt* – *nt*) gforth-1.0 “xt-to-name”

Produces the primary nt for an xt. If *xt* is not an xt, *nt* is not guaranteed to be an nt.

You can get all the nts in a wordlist with

traverse-wordlist (... *xt wid* – ...) tools-ext “traverse-wordlist”

perform *xt* (... *nt* – *f* ...) once for every word *nt* in the wordlist *wid*, until *f* is false or the wordlist is exhausted. *xt* is free to use the stack underneath.

You can use the nt to access the interpretation and compilation semantics of a word, its name, and the next word in the wordlist:

name>interpret (*nt* – *xt*) tools-ext “name-to-interpret”

xt represents the interpretation semantics of the word *nt*.

name>compile (*nt* – *w xt*) tools-ext “name-to-compile”

w xt is the compilation token for the word *nt*.

name>string (*nt* – *addr u*) tools-ext “name-to-string”

addr count is the name of the word represented by *nt*.

id. (*nt* –) gforth-0.6 “i-d-dot”

Print the name of the word represented by *nt*.

.id (*nt* –) gforth-0.6 “dot-i-d”

F83 name for **id.**

obsolete? (*nt* – *flag*) gforth-1.0 “obsolete?”

true if *nt* is obsolete, i.e., will be removed in a future version of Gforth.

name>link (*nt1* – *nt2* / 0) gforth-1.0 “name-to-link”

For a word *nt1*, returns the previous word *nt2* in the same wordlist, or 0 if there is no previous word.

A nameless word usually has no interpretation nor compilation semantics, no name, and it's not in a wordlist. But in Gforth (since 1.0) all words are equal, so even nameless words have an nt (but they are in no wordlist). You can get that nt with `latestnt`, and the words above that consume nts do something reasonable for these nts.

As a usage example, the following code lists all the words in `forth-wordlist` with non-default compilation semantics:

```
: ndcs-words ( wid -- )
  [: dup name>compile ['] compile, <> if over id. then 2drop true ;]
  swap traverse-wordlist ;

forth-wordlist ndcs-words
```

This code assumes that a word has default compilation semantics if the *xt* part of its compilation token is the *xt* of `compile`,.

The closest thing to the *nt* in older Forth systems is the name field address (NFA), but there are significant differences: in older Forth systems each word had a unique NFA, LFA, CFA and PFA (in this order, or LFA, NFA, CFA, PFA) and there were words for getting from one to the next. In contrast, in Gforth several nts can get the same *xt* from `name>interpret` *xt*; there is a link field in the structure identified by the name token, but searching usually uses a hash table external to these structures; the name in Gforth has a cell-wide count-and-flags field, and the *nt* is not implemented as the address of that count field.

6.15.3 Compilation token

The compilation semantics of a named word is represented by a *compilation token* consisting of two cells: *w xt*. The top cell *xt* is an execution token. The compilation semantics represented by the compilation token can be performed with `execute`, which consumes the whole compilation token, with an additional stack effect determined by the represented compilation semantics.

At present, the *w* part of a compilation token is an execution token, and the *xt* part represents either `execute` or `compile`,¹⁷. However, don't rely on that knowledge, unless necessary; future versions of Gforth may introduce unusual compilation tokens (e.g., a compilation token that represents the compilation semantics of a literal).

You get the compilation token of, e.g., `if` in a standard way with `name>compile`, e.g., ``if name>compile`, but there are also parsing words to get the compilation token of a word:

```
[COMP'] ( compilation "name" - ; run-time - w xt ) gforth-0.2 "bracket-comp-tick"
```

Compilation token *w xt* represents *name*'s compilation semantics.

```
COMP' ( "name" - w xt ) gforth-0.2 "comp-tick"
```

Compilation token *w xt* represents *name*'s compilation semantics.

¹⁷ Depending upon the compilation semantics of the word. If the word has default compilation semantics, the *xt* will represent `compile`,. Otherwise (e.g., for immediate words), the *xt* will represent `execute`.

You can perform the compilation semantics represented by the compilation token with `execute`. You can compile the compilation semantics with `postpone,`. I.e., ``x name>compile postpone,` is equivalent to `postpone x`.

`postpone, (w xt -)` gforth-0.2 “postpone-comma”

Compile the compilation semantics represented by the compilation token `w xt`.

6.16 Compiling words

In contrast to most other languages, Forth has no strict boundary between compilation and run-time. E.g., you can run arbitrary code between defining words (or for computing data used by defining words like `constant`). Moreover, `Immediate` (see [\[Interpretation and Compilation Semantics\]](#), page [\[undefined\]](#), and `[...]` (see below) allow running arbitrary code while compiling a colon definition (exception: you must not allot dictionary space).

6.16.1 Literals

The simplest and most frequent example is to compute a literal during compilation. E.g., the following definition prints an array of strings, one string per line:

```
: .strings ( addr u -- ) \ gforth
  2* cells bounds U+D0
cr i 2@ type
  2 cells +LOOP ;
```

With a simple-minded compiler like Gforth’s, this computes `2 cells` on every loop iteration. You can compute this value once and for all at compile time and compile it into the definition like this:

```
: .strings ( addr u -- ) \ gforth
  2* cells bounds U+D0
cr i 2@ type
  [ 2 cells ] literal +LOOP ;
```

`[` switches the text interpreter to interpret state (you will get an `ok` prompt if you type this example interactively and insert a newline between `[` and `]`), so it performs the interpretation semantics of `2 cells`; this computes a number. `]` switches the text interpreter back into compile state. It then performs `Literal`’s compilation semantics, which are to compile this number into the current word. You can decompile the word with `see .strings` to see the effect on the compiled code.

You can also optimize the `2* cells` into `[2 cells] literal *` in this way.

`[(-)` core “left-bracket”

Enter interpretation state. Immediate word.

`] (-)` core “right-bracket”

Enter compilation state.

`Literal (compilation n - ; run-time - n)` core “Literal”

Compilation semantics: compile the run-time semantics.

Run-time Semantics: push `n`.

Interpretation semantics: undefined.

`ALiteral (compilation addr - ; run-time - addr)` gforth-0.2 “ALiteral”

Works like `literal`, but (when used in cross-compiled code) tells the cross-compiler that the literal is an address.

```
]L ( compilation: n - ; run-time: - n ) gforth-0.5 "[L"
```

equivalent to `] literal`

There are also words for compiling other data types than single cells as literals:

```
2Literal ( compilation w1 w2 - ; run-time - w1 w2 ) double "two-literal"
```

Compile appropriate code such that, at run-time, `w1 w2` are placed on the stack. Interpretation semantics are undefined.

```
FLiteral ( compilation r - ; run-time - r ) floating "f-literal"
```

Compile appropriate code such that, at run-time, `r` is placed on the (floating-point) stack. Interpretation semantics are undefined.

```
SLiteral ( Compilation c-addr1 u ; run-time - c-addr2 u ) string "SLiteral"
```

Compilation: compile the string specified by `c-addr1`, `u` into the current definition. Run-time: return `c-addr2 u` describing the address and length of the string.

You might be tempted to pass data from outside a colon definition to the inside on the data stack. This does not work, because `:` pushes a colon-sys, making stuff below inaccessible. E.g., this does not work:

```
5 : foo literal ; \ error: "unstructured"
```

Instead, you have to pass the value in some other way, e.g., through a variable:

```
variable temp
5 temp !
: foo [ temp @ ] literal ;
```

6.16.2 Macros

`Literal` and friends compile data values into the current definition. You can also write words that compile other words into the current definition. E.g.,

```
: compile-+ ( -- ) \ compiled code: ( n1 n2 -- n )
  POSTPONE + ;

: foo ( n1 n2 -- n )
  [ compile-+ ] ;
1 2 foo .
```

This is equivalent to `: foo + ;` (see `foo` to check this). What happens in this example? `Postpone` compiles the compilation semantics of `+` into `compile-+`; later the text interpreter executes `compile-+` and thus the compilation semantics of `+`, which compile (the execution semantics of) `+` into `foo`.¹⁸

```
postpone ( "name" - ) core "postpone"
```

Compiles the compilation semantics of `name`.

Compiling words like `compile-+` are usually immediate (or similar) so you do not have to switch to interpret state to execute them; modifying the last example accordingly produces:

```
: [compile-+] ( compilation: --; interpretation: -- )
```

¹⁸ A recent RFI answer requires that compiling words should only be executed in compile state, so this example is not guaranteed to work on all standard systems, but on any decent system it will work.

```

\ compiled code: ( n1 n2 -- n )
POSTPONE + ; immediate

: foo ( n1 n2 -- n )
  [compile+] ;
1 2 foo .

```

You will occasionally find the need to POSTPONE several words; putting POSTPONE before each such word is cumbersome, so Gforth provides a more convenient syntax: `]] ... [[`. This allows us to write `[compile+]` as:

```

: [compile+] ( compilation: --; interpretation: -- )
  ]] + [[ ; immediate
]] ( - ) gforth-0.6 "right-bracket-bracket"

```

Switch into postpone state: All words and recognizers are processed as if they were preceded by `postpone`. Postpone state ends when `[[` is recognized.

The unusual direction of the brackets indicates their function: `]]` switches from compilation to postponing (i.e., compilation of compilation), just like `]` switches from immediate execution (interpretation) to compilation. Conversely, `[[` switches from postponing to compilation, analogous to `[` which switches from compilation to immediate execution.

The real advantage of `]] ... [[` becomes apparent when there are many words to POSTPONE. E.g., the word `compile-map-array` (see [\(undefined\)](#) [Advanced macros Tutorial], page [\(undefined\)](#)) can be written much shorter as follows:

```

: compile-map-array ( compilation: xt -- ; run-time: ... addr u -- ... )
\ at run-time, execute xt ( ... x -- ... ) for each element of the
\ array beginning at addr and containing u elements
{: xt: xt :}
]] cells over + swap ?do
  i @ xt 1 cells +loop [[ ;

: sum-array ( addr u -- n )
  0 [ ' + compile-map-array ] ;

```

If you then say `see sum-array`, it shows the following code:

```

: sum-array
  #0 over + swap ?do
    i + #8 +LOOP
;

```

In addition to `]]...[[`, this example shows off some other features:

- It uses a defer-flavoured (defined with `xt: local xt`; mentioning such a local inside `]]...[[` results in `compile`,ing the `xt` in the local
- Not used in the example, but related to the previous point: For a value-flavoured local, using it inside `]]...[[` compiles the value of the local, i.e., `]] 1 [[` is equivalent to `1]] literal [[`.
- It uses the literal `1` inside `]]...[[`. This results in `postpone`ing the `1`, i.e. compiling it when `compile-map-array` is run.

- When `compile-map-array` is run, `1 cells` is compiled and optimized into `#8` by Gforth's constant folding.

Note that parsing words such as `s\"` don't parse at postpone time and therefore not inside `]]...[[`. Instead of `s\"mystring\n\"` you can use the string recognizer and write `"mystring\n"`, which works inside `]]...[[`. Likewise for the parsing word `[']` and the recognizer notation starting with ```.

But if you prefer to use `s\"` (or have a parsing word that has no recognizer replacement), you can do it by switching back to compilation:

```
]] ... [[ s\" mystring\n\" ]] 2literal ... [[
```

Definitions of `]]` and friends in Standard Forth are provided in `compat/macros.fs`.

Immediate compiling words are similar to macros in other languages (in particular, Lisp). The important differences to macros in, e.g., C are:

- You use the same language for defining and processing macros, not a separate preprocessing language and processor.
- Consequently, the full power of Forth is available in macro definitions. E.g., you can perform arbitrarily complex computations, or generate different code conditionally or in a loop (e.g., see [\[Advanced macros Tutorial\]](#), page [\[undefined\]](#)). This power is very useful when writing a parser generators or other code-generating software.
- Macros defined using `postpone` etc. deal with the language at a higher level than strings; name binding happens at macro definition time, so you can avoid the pitfalls of name collisions that can happen in C macros. Of course, Forth is a liberal language and also allows to shoot yourself in the foot with text-interpreted macros like

```
: [compile+] s" +" evaluate ; immediate
```

Apart from binding the name at macro use time, using `evaluate` also makes your definition `state-smart` (see [\[state-smartness\]](#), page [\[undefined\]](#)).

You may want the macro to compile a number into a word. The word to do it is `literal`, but you have to `postpone` it, so its compilation semantics take effect when the macro is executed, not when it is compiled:

```
: [compile-5] ( -- ) \ compiled code: ( -- n )
  5 POSTPONE literal ; immediate

: foo [compile-5] ;
foo .
```

You may want to pass parameters to a macro, that the macro should compile into the current definition. If the parameter is a number, then you can use `postpone literal` (similar for other values).

If you want to pass a word that is to be compiled, the usual way is to pass an execution token and `compile`, it:

```
: twice1 ( xt -- ) \ compiled code: ... -- ...
  dup compile, compile, ;

: 2+ ( n1 -- n2 )
```

```
[ ' 1+ twice1 ] ;
compile, ( xt - ) core-ext "compile-comma"
```

Append the semantics represented by *xt* to the current definition. When the resulting code fragment is run, it behaves the same as if *xt* is **executed**.

```
2compile, ( xt1 xt2 - ) gforth-experimental "two-compile-comma"
```

equivalent to *xt1 compile, xt2 compile,,* but also applies peephole optimization.

An alternative available in Gforth, that allows you to pass the compilation semantics as parameters is to use the compilation token (see [\(undefined\)](#) [Compilation token], page [\(undefined\)](#)). The same example in this technique:

```
: twice ( ... ct -- ... ) \ compiled code: ... -- ...
  2dup 2>r execute 2r> execute ;

: 2+ ( n1 -- n2 )
  [ comp' 1+ twice ] ;
```

In the example above *2>r* and *2r>* ensure that **twice** works even if the executed compilation semantics has an effect on the data stack.

You can also define complete definitions with these words; this provides an alternative to using **does>** (see [\(undefined\)](#) [User-defined Defining Words], page [\(undefined\)](#)). E.g., instead of

```
: curry+ ( n1 "name" -- )
  CREATE ,
DOES> ( n2 -- n1+n2 )
  @ + ;
```

you could define

```
: curry+ ( n1 "name" -- )
  \ name execution: ( n2 -- n1+n2 )
  >r : r> POSTPONE literal POSTPONE + POSTPONE ; ;
```

```
-3 curry+ 3-
see 3-
```

The sequence *>r : r>* is necessary, because **:** puts a colon-sys on the data stack that makes everything below it inaccessible.

This way of writing defining words is sometimes more, sometimes less convenient than using **does>** (see [\(undefined\)](#) [Advanced **does>** usage example], page [\(undefined\)](#)). One advantage of this method is that it can be optimized better, because the compiler knows that the value compiled with **literal** is fixed, whereas the data associated with a **created** word can be changed.

```
[compile] ( compilation "name" - ; run-time ? - ? ) core-ext "bracket-compile"
```

Legacy word. Use **postpone** instead. Works like **postpone** if *name* has non-default compilation semantics. If *name* has default compilation semantics (i.e., is a normal word), compiling **[compile] name** is equivalent to compiling *name* (i.e. **[compile]** is redundant in this case).

```
in-colon-def? ( - flag ) gforth-experimental "in-colon-def?"
```

allows to check if there currently is an active colon definition where you can append code to.

6.17 The Text Interpreter

The text interpreter¹⁹ is an endless loop that processes input from the current input device. It is also called the outer interpreter, in contrast to the inner interpreter (see `<undefined>` [Engine], page `<undefined>`) which executes the compiled Forth code on interpretive implementations.

The text interpreter operates in one of two states: *interpret state* and *compile state*. The current state is defined by the aptly-named variable `state`.

This section starts by describing how the text interpreter behaves when it is in *interpret state*, processing input from the user input device – the keyboard. This is the mode that a Forth system is in after it starts up.

The text interpreter works from an area of memory called the *input buffer*²⁰, which stores your keyboard input when you press the RET key. Starting at the beginning of the input buffer, it skips leading spaces (called *delimiters*) then parses a string (a sequence of non-space characters) until it reaches either a space character or the end of the buffer. Having parsed a string, it makes two attempts to process it:

- It looks for the string in a *dictionary* of definitions. If the string is found, the string names a *definition* (also known as a *word*) and the dictionary search returns information that allows the text interpreter to perform the word's *interpretation semantics*. In most cases, this simply means that the word will be executed.
- If the string is not found in the dictionary, the text interpreter attempts to treat it as a number, using the rules described in `<undefined>` [Number Conversion], page `<undefined>`. If the string represents a legal number in the current radix, the number is pushed onto a parameter stack (the data stack for integers, the floating-point stack for floating-point numbers).

If both attempts fail, the text interpreter discards the remainder of the input buffer, issues an error message and waits for more input. If one of the attempts succeeds, the text interpreter repeats the parsing process until the whole of the input buffer has been processed, at which point it prints the status message “ok” and waits for more input.

The text interpreter keeps track of its position in the input buffer by updating a variable called `>IN` (pronounced “to-in”). The value of `>IN` starts out as 0, indicating an offset of 0 from the start of the input buffer. The region from offset `>IN @` to the end of the input buffer is called the *parse area*²¹. This example shows how `>IN` changes as the text interpreter parses the input buffer:

```
: remaining source >in @ /string
  cr ." ->" type ." <-" ; immediate
```

¹⁹ This is an expanded version of the material in `<undefined>` [Introducing the Text Interpreter], page `<undefined>`.

²⁰ When the text interpreter is processing input from the keyboard, this area of memory is called the *terminal input buffer* (TIB) and is addressed by the (obsolescent) words `TIB` and `#TIB`.

²¹ In other words, the text interpreter processes the contents of the input buffer by parsing strings from the parse area until the parse area is empty.

```
1 2 3 remaining + remaining .

: foo 1 2 3 remaining swap remaining ;
```

The result is:

```
->+ remaining .<-
->.<-5 ok

->SWAP remaining ;-<
->;<- ok
```

The value of `>IN` can also be modified by a word in the input buffer that is executed by the text interpreter. This means that a word can “trick” the text interpreter into either skipping a section of the input buffer²² or into parsing a section twice. For example:

```
: lat ." <<foo>>" ;
: flat ." <<bar>>" >IN DUP @ 3 - SWAP ! ;
```

When `flat` is executed, this output is produced²³:

```
<<bar>><<foo>>
```

This technique can be used to work around some of the interoperability problems of parsing words. Of course, it’s better to avoid parsing words where possible.

Two important notes about the behaviour of the text interpreter:

- It processes each input string to completion before parsing additional characters from the input buffer.
- It treats the input buffer as a read-only region (and so must your code).

When the text interpreter is in compile state, its behaviour changes in these ways:

- If a parsed string is found in the dictionary, the text interpreter will perform the word’s *compilation semantics*. In most cases, this simply means that the execution semantics of the word will be appended to the current definition.
- When a number is encountered, it is compiled into the current definition (as a literal) rather than being pushed onto a parameter stack.
- If an error occurs, `state` is modified to put the text interpreter back into interpret state.
- Each time a line is entered from the keyboard, Gforth prints “`compiled`” rather than “`ok`”.

When the text interpreter is using an input device other than the keyboard, its behaviour changes in these ways:

- When the parse area is empty, the text interpreter attempts to refill the input buffer from the input source. When the input source is exhausted, the input source is set back to the previous input source.
- It doesn’t print out “`ok`” or “`compiled`” messages each time the parse area is emptied.

²² This is how parsing words work.

²³ Exercise for the reader: what would happen if the 3 were replaced with 4?

- If an error occurs, the input source is set back to the user input device.

You can read about this in more detail in [\[Input Sources\]](#), page [\[undefined\]](#).

>in (*- addr*) core “to-in”

uvar variable – *a-addr* is the address of a cell containing the char offset from the start of the input buffer to the start of the parse area.

source (*- addr u*) core “source”

Return address *addr* and length *u* of the current input buffer

tib (*- addr*) core-ext-obsolete “t-i-b”

#tib (*- addr*) core-ext-obsolete “number-t-i-b”

uvar variable – *a-addr* is the address of a cell containing the number of characters in the terminal input buffer. OBSOLETE: **source** supercedes the function of this word.

interpret (... - ...) gforth-0.2 “interpret”

6.17.1 Input Sources

By default, the text interpreter processes input from the user input device (the keyboard) when Forth starts up. The text interpreter can process input from any of these sources:

- The user input device – the keyboard.
- A file, using the words described in [\[Forth source files\]](#), page [\[undefined\]](#).
- A block, using the words described in [\[Blocks\]](#), page [\[undefined\]](#).
- A text string, using **evaluate**.

A program can identify the current input device from the values of **source-id** and **blk**.
source-id (*- 0 | -1 | fileid*) core-ext,file “source-i-d”

Return 0 (the input source is the user input device), -1 (the input source is a string being processed by **evaluate**) or a *fileid* (the input source is the file specified by *fileid*).

blk (*- addr*) block “b-l-k”

uvar variable – This cell contains the current block number (or 0 if the current input source is not a block).

save-input (*- x1 .. xn n*) core-ext “save-input”

The *n* entries *xn - x1* describe the current state of the input source specification, in some platform-dependent way that can be used by **restore-input**.

restore-input (*x1 .. xn n - flag*) core-ext “restore-input”

Attempt to restore the input source specification to the state described by the *n* entries *xn - x1*. *flag* is true if the restore fails. In Gforth with the new input code, it fails only with a flag that can be used to throw again; it is also possible to save and restore between different active input streams. Note that closing the input streams must happen in the reverse order as they have been opened, but in between everything is allowed.

evaluate (... *addr u - ...*) core,block “evaluate”

Save the current input source specification. Store -1 in **source-id** and 0 in **blk**. Set **>IN** to 0 and make the string *c-addr u* the input source and input buffer. Interpret. When the parse area is empty, restore the input source specification.

query (*-*) core-ext-obsolete “query”

Make the user input device the input source. Receive input into the Terminal Input Buffer. Set `>IN` to zero. OBSOLESCENT: superceeded by `accept`.

6.17.2 Number Conversion

You get an overview of how the text interpreter converts its numeric input in [\(undefined\)](#) [Literals in source code], page [\(undefined\)](#). This section describes some related words.

By default, the number base used for integer number conversion is given by the contents of the variable `base`. Note that a lot of confusion can result from unexpected values of `base`. If you change `base` anywhere, make sure to save the old value and restore it afterwards; better yet, use `base-execute`, which does this for you. In general I recommend keeping `base` decimal, and using the prefixes described in [\(undefined\)](#) [Literals in source code], page [\(undefined\)](#), for the popular non-decimal bases.

`base-execute` (*i*x xt u - j*x*) gforth-0.7 “base-execute”

execute *xt* with the content of `BASE` being *u*, and restoring the original `BASE` afterwards.

`base` (*- a-addr*) core “base”

User variable *- a-addr* is the address of a cell that stores the number base used by default for number conversion during input and output. Don’t store to `base`, use `base-execute` instead.

`hex` (*-*) core-ext “hex”

Set `base` to \$10 (hexadecimal). In many cases `base-execute` is a better alternative.

`decimal` (*-*) core “decimal”

Set `base` to #10 (decimal). In many cases `base-execute` is a better alternative.

`dpl` (*- a-addr*) gforth-0.2 “Decimal-PLace”

User variable *- a-addr* is the address of a cell that stores the position of the decimal point in the most recent numeric conversion. Initialised to -1. After the conversion of a number containing no decimal point, `dpl` is -1. After the conversion of 2. it holds 0. After the conversion of 234123.9 it contains 1, and so forth.

Number conversion has a number of traps for the unwary:

- You cannot determine the current number base using the code sequence `base @ .` – the number base is always 10 in the current number base. Instead, use something like `base @ dec .`
- There is a word `bin` but it does *not* set the number base! (see [\(undefined\)](#) [General files], page [\(undefined\)](#)).
- Standard Forth requires the `.` of a double-precision number to be the final character in the string. Gforth allows the `.` to be anywhere.
- The number conversion process does not check for overflow.

You can read numbers into your programs with the words described in [\(undefined\)](#) [Line input and conversion], page [\(undefined\)](#).

6.17.3 Interpret/Compile states

A standard program is not permitted to change `state` explicitly. However, it can change `state` implicitly, using the words `[` and `]`. When `[` is executed it switches `state` to interpret state, and therefore the text interpreter starts interpreting. When `]` is executed it switches

state to compile state and therefore the text interpreter starts compiling. The most common usage for these words is for switching into interpret state and back from within a colon definition; this technique can be used to compile a literal (for an example, see [\[Literals\]](#), page [\(undefined\)](#)) or for conditional compilation (for an example, see [\[Interpreter Directives\]](#), page [\(undefined\)](#)).

6.17.4 Interpreter Directives

These words are usually used in interpret state; typically to control which parts of a source file are processed by the text interpreter. There are only a few Standard Forth Standard words, but Gforth supplements these with a rich set of immediate control structure words to compensate for the fact that the non-immediate versions can only be used in compile state (see [\[Control Structures\]](#), page [\(undefined\)](#)). Typical usage:

```
[undefined] \G [if]
  : \G ... ; immediate
[endif]
```

So if the system does not define `\G`, compile some replacement code (with possibly reduced functionality).

[IF] (*flag* –) tools-ext “bracket-if”

If flag is **TRUE** do nothing (and therefore execute subsequent words as normal). If flag is **FALSE**, parse and discard words from the parse area (refilling it if necessary using **REFILL**) including nested instances of **[IF].. [ELSE].. [THEN]** and **[IF].. [THEN]** until the balancing **[ELSE]** or **[THEN]** has been parsed and discarded. Immediate word.

[ELSE] (–) tools-ext “bracket-else”

Parse and discard words from the parse area (refilling it if necessary using **REFILL**) including nested instances of **[IF].. [ELSE].. [THEN]** and **[IF].. [THEN]** until the balancing **[THEN]** has been parsed and discarded. **[ELSE]** only gets executed if the balancing **[IF]** was **TRUE**; if it was **FALSE**, **[IF]** would have parsed and discarded the **[ELSE]**, leaving the subsequent words to be executed as normal. Immediate word.

[THEN] (–) tools-ext “bracket-then”

Do nothing; used as a marker for other words to parse and discard up to. Immediate word.

[ENDIF] (–) gforth-0.2 “bracket-end-if”

Do nothing; synonym for **[THEN]**

[defined] ("*<spaces>name*" – *flag*) tools-ext “bracket-defined”

returns true if name is found in current search order

[undefined] ("*<spaces>name*" – *flag*) tools-ext “bracket-undefined”

returns false if name is found in current search order

[IFDEF] ("*<spaces>name*" –) gforth-0.2 “bracket-if-def”

If name is found in the current search-order, behave like **[IF]** with a **TRUE** flag, otherwise behave like **[IF]** with a **FALSE** flag. Immediate word.

[IFUNDEF] ("*<spaces>name*" –) gforth-0.2 “bracket-if-un-def”

If name is not found in the current search-order, behave like [IF] with a TRUE flag, otherwise behave like [IF] with a FALSE flag. Immediate word.

[?DO] (*n-limit n-index* -) gforth-0.2 “bracket-question-do”

[DO] (*n-limit n-index* -) gforth-0.2 “bracket-do”

[LOOP] (-) gforth-0.2 “bracket-loop”

[+LOOP] (*n* -) gforth-0.2 “bracket-question-plus-loop”

[FOR] (*n* -) gforth-0.2 “bracket-for”

[NEXT] (*n* -) gforth-0.2 “bracket-next”

[I] (*run-time* - *n*) gforth-0.2 “bracket-i”

At run-time, [I] pushes the loop index of the text-interpretation-time [do] iteration. If you want to process the index at interpretation time, interpret [I] interpretevely, or use INT-[I].

INT-[I] (- *n*) gforth-1.0 “int-bracket-i”

Push the loop index of the [do] iteration at text interpretation time.

[BEGIN] (-) gforth-0.2 “bracket-begin”

[UNTIL] (*flag* -) gforth-0.2 “bracket-until”

[AGAIN] (-) gforth-0.2 “bracket-again”

[WHILE] (*flag* -) gforth-0.2 “bracket-while”

[REPEAT] (-) gforth-0.2 “bracket-repeat”

You can use #line to change Gforth’s idea about the current source line number and source file. This is useful in cases where the Forth file is generated from some other source code file, and you want to get, e.g. error messages etc. that refer to the original source code; then the Forth-code generator needs to insert #line lines in the Forth code wherever appropriate.

#line ("*u*" "["*file*"]" -) gforth-1.0 “#line”

Set the line number to *u* and (if present) the file name to *file*. Consumes the rest of the line.

6.17.5 Recognizers

When the text interpreter processes source code, it divides the code into blank-delimited strings, and then calls recognizers to identify them as words, numbers, etc., until one recognizer identifies (recognizes) the string; if the string is not recognized, the text interpreter reports an error (**undefined word**).

The usual way to deal with recognizers is to just write code that one of them identifies (see <undefined> [Default Recognizers], page <undefined>); however, you can also manipulate them (see <undefined> [Dealing with existing Recognizers], page <undefined>) or even define new ones (see <undefined> [Defining Recognizers], page <undefined>).

6.17.5.1 Default Recognizers

The Standard Forth text interpreter recognizes words in the search order (**rec-nt**), integer numbers (**rec-num**), and floating point numbers (**rec-float**). By default Gforth also recognizes syntaxes for

- strings, e.g., "mystring", with **rec-string**

- complex numbers, e.g., `0e+1ei`, with **rec-complex**
- storing a value or changing a deferred word, e.g., `->myvalue`, with **rec-to**
- the xt representing the interpretation semantics of a word, e.g., ``dup`, with **rec-tick**
- the nt of a word, e.g., ``mysynonym`, with **rec-dtick**
- an address in the body of a word, e.g., `<myarray+8>`, with **rec-body**
- an access to an environment variable of the operating system, e.g., `${HOME}`, with **rec-env**
- a word in a vocabulary, e.g., `myvoc1:myvoc2:myword`, with **rec-scope**
- using a specific recognizer to recognize something, e.g., `float?1.`, with **rec-meta**

You can use **locate** (see [\(undefined\)](#) [Locating source code definitions], page [\(undefined\)](#)) to determine which recognizer recognizes a piece of source code. E.g.:

```
defer mydefer
locate ->mydefer
```

will show that **rec-to** recognizes `->mydefer`. However, if the recognizer recognizes a dictionary word (e.g., the scope recognizer), **locate** will show that word.

You can see which recognizers are used and the order of recognizers with **.recognizers** (-) gforth-experimental “dot-recognizers”

Print the current recognizer order, with the first-searched recognizer leftmost (unlike `.order`). The inverted `~` is displayed instead of **rec-**, which is the common prefix of all recognizers.

Recognizers are typically designed to avoid matching the same strings as other recognizers. E.g., **rec-env** (the environment variable recognizer) requires braces to avoid a conflict with the number recognizer for input strings like `$ADD`. There are a few exceptions to this policy, however:

- Word names can be anything, so they can conflict with any other recognizer (and the search order is searched before other recognizers).

However, they tend not to start with 0 (and if they do, they contain special characters), so if your base is **hex**, it is a good practice to let your numbers start with 0.

In the code bases we have looked at, starting words with `'` (quote aka tick) is much more common than starting them with ``` (backquote aka backtick), so the recognizers for the xt and the nt use ``` to reduce the number of conflicts.

- Both the integer recognizer **rec-num** and the floating-point recognizer **rec-float** recognize, e.g., `1.`. Because **rec-num** is (by default) first, `1.` is recognized as a double-cell integer. If you change the recognizer order to use **rec-float** first, `1.` is recognized as a floating-point number, but loading code written in Standard Forth may behave in a non-standard way.

In any case, it's a good practice to avoid that conflict in your own code as follows: Always write double-cell integers with a number prefix, e.g., `#1.`; and always write floating-point numbers with an **e**, e.g., `1e`.

- We have seen a few word names that start with `->`. You can avoid a conflict by using `to myvalue` or `to?->myvalue` (the latter works with **postpone**).

6.17.5.2 Dealing with existing Recognizers

A recognizer is a word to which you pass a string. If the recognizer recognizes the string, it typically returns some data and the xt of a word for processing the data; this word is called the translator. If the recognizer does not recognize the string, it returns 0.

All recognizers have the stack effect (*c-addr u – i*x xt | 0*).

Recognizers take a string and on success return some data and a translator for interpreting that data. Gforth implements that translator as xt (executing it will perform the appropriate action to handle the token in the current state), but other Forth systems may implement it as actual table, with three xts inside. The first xt is the interpretation/run-time xt, it performs the interpretation semantics on the data (usually, this means it just leaves the data on the stack). The second xt performs the compilation semantics, it gets the data and the run-time semantics xt. The third xt performs the postpone semantics, it also gets the data and the run-time semantics xt. You can use **postponing** to postpone the run-time xt.

Recognizers are organized as stack, so you can arrange the sequence of recognizers in the same way as the vocabulary stack. Recognizer stacks are themselves recognizers, i.e. they are executable, take a string and return a translator.

rec-nt (*addr u – nt translate-nt | 0*) gforth-experimental “rec-nt”

recognize a name token

rec-num (*addr u – n/d table | 0*) gforth-experimental “rec-num”

converts a number to a single/double integer

rec-float (*addr u – r translate-float | 0*) gforth-experimental “rec-float”

recognize floating point numbers

rec-complex (*addr u – z translate-complex | 0*) gforth-1.0 “rec-complex”

Complex numbers are always in the format *a+bi*, where *a* and *b* are floating point numbers including their signs

rec-string (*addr u – addr u' scan-translate-string | 0*) gforth-experimental “rec-string”

Convert strings enclosed in double quotes into string literals, escapes are treated as in *S*”.

rec-to (*addr u – xt n translate-to | 0*) gforth-experimental “rec-to”

words prefixed with *->* are treated as if preceeded by *T0*, with *+>* as *+T0*, with *'>* as *ADDR*, with *@>* as *ACTION-OF*, and with *=>* as *IS*.

rec-tick (*addr u – xt translate-num | 0*) gforth-experimental “rec-tick”

words prefixed with *`* return their xt. Example: *`dup* gives the xt of *dup*

rec-dtick (*addr u – nt translate-num | 0*) gforth-experimental “rec-dtick”

words prefixed with *``* return their nt. Example: *``S*” gives the nt of *S*”

rec-body (*addr u – xt translate-num | 0*) gforth-experimental “rec-body”

words bracketed with *'<' '>'* return their body. Example: *<dup>* gives the body of *dup*

rec-env (*addr u – addr u translate-env | 0*) gforth-1.0 “rec-env”

words enclosed by *#{* and *}* are passed to *getenv* to get the OS-environment variable as string. Example: *#{HOME}* gives the home directory.

rec-scope (*addr u – nt rectype-nt | 0*) gforth-experimental “rec-scope”

Recognizes strings of the form (simplified) **wordlist:word**, where wordlist is found in the search order. The result is the same as for **rec-nt** for *word* (the ordinary word recognizer) if the search order consists only of *wordlist*. The general form can have several wordlists preceding *word*, separated by **:**; the first (leftmost) wordlist is found in the search order, the second in the first, etc. *word* is looked up in the last (rightmost) wordlist.

rec-meta (*addr u* – *xt translate-to* | 0) gforth-1.0 “rec-meta”

words prefixed with *recognizer?* are processed by **rec-recognizer** to disambiguate recognizers. Example: **hex num?cafe num?add** will be parsed as number only Example: **float?123.** will be parsed as float

get-recognizers (– *xt1 .. xtn n*) gforth-obsolete “get-recognizers”

push the content on the recognizer stack

set-recognizers (*xt1 .. xtn n* –) gforth-obsolete “set-recognizers”

set the recognizer stack from content on the stack

recognize (*addr u rec-addr* – ... *rectype*) gforth-experimental “recognize”

apply a recognizer stack to a string, delivering a token

recognizer-sequence: (*xt1 .. xtn n* “*name*” –) gforth-experimental “recognizer-sequence:”

concatenate a stack of recognizers to one recognizer with the name “*name*”. *xtn* is tried first, *xt1* last, just like on the recognizer stack

forth-recognize (*c-addr u* – ... *translate-xt*) recognizer “forth-recognize”

The system recognizer

forth-recognizer (– *xt*) gforth-obsolete “forth-recognizer”

backward compatible to Matthias Trute recognizer API. This construct turns a deferred word into a value-like word.

set-forth-recognize (*xt* –) gforth-obsolete “set-forth-recognize”

Change the system recognizer

?found (*token* | 0 – *token* | *never*) gforth-experimental “?found”

performs an undefined word **throw** if the *token* is 0.

translate: (*int-xt comp-xt post-xt* “*name*” –) gforth-experimental “translate:”

create a new recognizer table. Items are in order of *STATE* value, which are 0 or negative. Up to 7 slots are available for extensions.

translate-nt (*i*x nt* – *j*x*) gforth-experimental “translate-nt”

translate a name token

translate-num (*x* – | *x*) gforth-experimental “translate-num”

translate a number

translate-dnum (*dx* – | *dx*) gforth-experimental “translate-dnum”

translate a double number

translate-float (*r* – | *r*) gforth-experimental “translate-float”

A translator for a float number.

try-recognize (*addr u xt* – *results* | *false*) gforth-experimental “try-recognize”

For nested recognizers: try to recognize *addr u*, and execute *xt* to check if the result is desired. If *xt* returns false, clean up all side effects of the recognizer, and return false. Otherwise return the results of the call to *xt*, of which the topmost is non-zero.

interpreting (*translator* –) gforth-experimental “interpreting”

perform interpreter action of translator

compiling (*translator* –) gforth-experimental “compiling”

perform compile action of translator

postponing (*translator* –) gforth-experimental “postponing”

perform postpone action of translator

translate-method: ("*name*" –) gforth-experimental “translate-method:”

create a new translate method, extending the translator table. You can assign an *xt* to an existing retype by using *xt retype to translator*.

set-state (*xt* –) gforth-experimental “set-state”

change the current state of the system so that executing a translator matches the translate-method passed as *xt*

get-state (– *xt*) gforth-experimental “get-state”

return the currently used translate-method *xt*

6.17.5.3 Defining Recognizers

6.17.6 Text Interpreter Hooks

before-line (–) gforth-1.0 “before-line”

Deferred word called before the text interpreter parses the next line

before-word (–) gforth-0.7 “before-word”

Deferred word called before the text interpreter parses the next word

line-end-hook (–) gforth-0.7 “line-end-hook”

called at every end-of-line when text-interpreting from a file

6.18 The Input Stream

The text interpreter reads from the input stream, which can come from several sources (see [\[Input Sources\]](#), page [\[undefined\]](#)). Some words, in particular defining words, but also words like `'`, read parameters from the input stream instead of from the stack.

Such words are called parsing words, because they parse the input stream. Parsing words are hard to use in other words, because it is hard to pass program-generated parameters through the input stream. They also usually have an unintuitive combination of interpretation and compilation semantics when implemented naively, leading to various approaches that try to produce a more intuitive behaviour (see [\[Combined words\]](#), page [\[undefined\]](#)).

It should be obvious by now that parsing words are a bad idea. If you want to implement a parsing word for convenience, also provide a factor of the word that does not parse, but

takes the parameters on the stack. To implement the parsing word on top of it, you can use the following words:

parse (*xchar* "*ccc<xchar>*" – *c-addr u*) core-ext,xchar-ext “parse”

Parse *ccc*, delimited by *xchar*, in the parse area. *c-addr u* specifies the parsed string within the parse area. If the parse area was empty, *u* is 0.

string-parse (*c-addr1 u1* "*ccc<string>*" – *c-addr2 u2*) gforth-1.0 “string-parse”

Parse *ccc*, delimited by the string *c-addr1 u1*, in the parse area. *c-addr2 u2* specifies the parsed string within the parse area. If the parse area was empty, *u2* is 0.

parse-name ("*name*" – *c-addr u*) core-ext “parse-name”

Get the next word from the input buffer

parse-word (– *c-addr u*) gforth-obsolete “parse-word”

old name for **parse-name**; this word has a conflicting behaviour in some other systems.

name (– *c-addr u*) gforth-obsolete “name”

old name for **parse-name**

word (*char* "<*chars>ccc<char>*– *c-addr*) core “word”

We recommend to use **parse-name** instead of **word**. Skip leading delimiters. Parse *ccc*, delimited by *char*, in the parse area. *c-addr* is the address of a transient region containing the parsed string in counted-string format. If the parse area was empty or contained no characters other than delimiters, the resulting string has zero length. A program may replace characters within the counted string. OBSOLESCENT: the counted string has a trailing space that is not included in its length.

refill (– *flag*) core-ext,block-ext,file-ext “refill”

Attempt to fill the input buffer from the input source. When the input source is the user input device, attempt to receive input into the terminal input device. If successful, make the result the input buffer, set >IN to 0 and return true; otherwise return false. When the input source is a block, add 1 to the value of BLK to make the next block the input source and current input buffer, and set >IN to 0; return true if the new value of BLK is a valid block number, false otherwise. When the input source is a text file, attempt to read the next line from the file. If successful, make the result the current input buffer, set >IN to 0 and return true; otherwise, return false. A successful result includes receipt of a line containing 0 characters.

If you have to deal with a parsing word that does not have a non-parsing factor, you can use **execute-parsing** to pass a string to it:

execute-parsing (... *addr u xt* – ...) gforth-0.6 “execute-parsing”

Make *addr u* the current input source, execute *xt* (... -- ...), then restore the previous input source.

Example:

```
5 s" foo" ' constant execute-parsing
\ equivalent to
5 constant foo
```

A definition of this word in Standard Forth is provided in `compat/execute-parsing.fs`.

If you want to run a parsing word on a file, the following word should help:

execute-parsing-file (*i*x fileid xt - j*x*) gforth-0.6 “execute-parsing-file”

Make *fileid* the current input source, execute *xt* (*i*x -- j*x*), then restore the previous input source.

6.19 Word Lists

A wordlist is a list of named words; you can add new words and look up words by name (and you can remove words in a restricted way with markers). Every named (and **revealed**) word is in one wordlist.

The text interpreter searches the wordlists present in the search order (a stack of wordlists), from the top to the bottom. Within each wordlist, the search starts conceptually at the newest word; i.e., if two words in a wordlist have the same name, the newer word is found.

New words are added to the *compilation wordlist* (aka current wordlist).

A word list is identified by a cell-sized word list identifier (*wid*) in much the same way as a file is identified by a file handle. The numerical value of the *wid* has no (portable) meaning, and might change from session to session.

The Standard Forth “Search order” word set is intended to provide a set of low-level tools that allow various different schemes to be implemented. Gforth also provides **vocabulary**, a traditional Forth word. **compat/vocabulary.fs** provides an implementation in Standard Forth.

forth-wordlist (- *wid*) search “forth-wordlist”

Constant - *wid* identifies the word list that includes all of the standard words provided by Gforth. When Gforth is invoked, this word list is the compilation word list and is at the top of the search order.

definitions (-) search “definitions”

Set the compilation word list to be the same as the word list that is currently at the top of the search order.

get-current (- *wid*) search “get-current”

wid is the identifier of the current compilation word list.

set-current (*wid* -) search “set-current”

Set the compilation word list to the word list identified by *wid*.

in-wordlist (*wordlist "defining-word" -*) gforth-experimental “in-wordlist”

execute *defining-word* with *wordlist* as one-shot current directory. Example: **gui-wordlist in-wordlist : init-gl ... ;** will define **init-gl** in the **gui-wordlist** wordlist.

in ("voc" "defining-word" -) gforth-experimental “in”

execute *defining-word* with *voc* as one-shot current directory. Example: **in gui : init-gl ... ;** will define **init-gl** in the **gui** vocabulary.

get-order (- *widn .. wid1 n*) search “get-order”

Copy the search order to the data stack. The current search order has *n* entries, of which *wid1* represents the wordlist that is searched first (the word list at the top of the search order) and *widn* represents the wordlist that is searched last.

set-order (*widn .. wid1 n -*) search “set-order”

If $n=0$, empty the search order. If $n=-1$, set the search order to the implementation-defined minimum search order (for Gforth, this is the word list **Root**). Otherwise, replace the existing search order with the n *wid* entries such that *wid1* represents the word list that will be searched first and *widn* represents the word list that will be searched last.

wordlist (- *wid*) search “wordlist”

Create a new, empty word list represented by *wid*.

table (- *wid*) gforth-0.2 “table”

Create a lookup table (case-sensitive, no warnings).

cs-wordlist (- *wid*) gforth-1.0 “cs-wordlist”

Create a case-sensitive wordlist.

cs-vocabulary (“*name*” -) gforth-1.0 “cs-vocabulary”

Create a case-sensitive vocabulary

>order (*wid* -) gforth-0.5 “to-order”

Push *wid* on the search order.

previous (-) search-ext “previous”

Drop the wordlist at the top of the search order.

also (-) search-ext “also”

Like **DUP** for the search order. Usually used before a vocabulary (e.g., **also Forth**); the combined effect is to push the wordlist represented by the vocabulary on the search order.

Forth (-) search-ext “Forth”

Replace the *wid* at the top of the search order with the *wid* associated with the word list **forth-wordlist**.

Only (-) search-ext “Only”

Set the search order to the implementation-defined minimum search order (for Gforth, this is the word list **Root**).

order (-) search-ext “order”

Print the search order and the compilation word list. The word lists are printed in the order in which they are searched (which is reversed with respect to the conventional way of displaying stacks). The compilation word list is displayed last.

.voc (*wid* -) gforth-0.2 “dot-voc”

print the name of the wordlist represented by *wid*. Can only print names defined with **vocabulary** or **wordlist constant**, otherwise prints ‘address’.

find (*c-addr* - *xt* +-1 | *c-addr* 0) core,search “find”

We recommend to use **find-name** instead of **find**. Search all word lists in the current search order for the definition named by the counted string at *c-addr*. If the definition is not found, return 0. If the definition is found return 1 (if the definition has non-default compilation semantics) or -1 (if the definition has default compilation semantics). The *xt* returned in interpret state represents the interpretation semantics. The *xt* returned in compile state represented either the compilation semantics (for non-default compilation semantics) or the run-time semantics that the compilation semantics would **compile**, (for default compilation semantics). The Forth-2012 standard does not specify clearly what the

returned *xt* represents (and also talks about immediacy instead of non-default compilation semantics), so this word is questionable in portable programs. If non-portability is ok, **find-name** and friends are better (see [\[Name token\]](#), page [\[undefined\]](#)).

search-wordlist (*c-addr count wid* – 0 | *xt* +-1) search “search-wordlist”

Search the word list identified by *wid* for the definition named by the string at *c-addr count*. If the definition is not found, return 0. If the definition is found return 1 (if the definition is immediate) or -1 (if the definition is not immediate) together with the *xt*. In Gforth, the *xt* returned represents the interpretation semantics. Forth-2012 does not specify clearly what *xt* represents.

words (–) tools “words”

Display a list of all of the definitions in the word list at the top of the search order.

vlist (–) gforth-0.2 “vlist”

Old (pre-Forth-83) name for **WORDS**.

wordlist-words (*wid* –) gforth-0.6 “wordlist-words”

Display the contents of the wordlist *wid*.

mwords ([*pattern*] –) gforth-1.0 “mwords”

list all words matching the optional parameter *pattern*; if none, all words match. Words are listed old to new. Pattern match like **search** (default), you can switch to globbing with ' **mword-filename-match** is **mword-match**.

Root (–) gforth-0.2 “Root”

Add the root wordlist to the search order stack. This vocabulary makes up the minimum search order and contains only a search-order words.

Vocabulary ("*name*" –) gforth-0.2 “Vocabulary”

Create a definition "*name*" and associate a new word list with it. The run-time effect of "*name*" is to replace the *wid* at the top of the search order with the *wid* associated with the new word list.

seal (–) gforth-0.2 “seal”

Remove all word lists from the search order stack other than the word list that is currently on the top of the search order stack.

vocs (–) gforth-0.2 “vocs”

List vocabularies and wordlists defined in the system.

current (– *addr*) gforth-0.2 “current”

Variable – holds the *wid* of the compilation word list.

context (– *addr*) gforth-0.2 “context”

context @ is the *wid* of the word list at the top of the search order.

map-vocs (... *xt* – ...) gforth-1.0 “map-vocs”

Perform *xt* (... *wid* – ...) for all wordlists (including tables and cs-wordlists) in the system.

6.19.1 Vocabularies

Here is an example of creating and using a new wordlist using Standard Forth words:

```
wordlist constant my-new-words-wordlist
: my-new-words get-order nip my-new-words-wordlist swap set-order ;

\ add it to the search order
also my-new-words

\ alternatively, add it to the search order and make it
\ the compilation word list
also my-new-words definitions
\ type "order" to see the problem
```

The problem with this example is that `order` has no way to associate the name `my-new-words` with the wid of the word list (in Gforth, `order` and `vocs` will display `???` for a wid that has no associated name). There is no Standard way of associating a name with a wid.

In Gforth, this example can be re-coded using `vocabulary`, which associates a name with a wid:

```
vocabulary my-new-words

\ add it to the search order
also my-new-words

\ alternatively, add it to the search order and make it
\ the compilation word list
my-new-words definitions
\ type "order" to see that the problem is solved
```

6.19.2 Why use word lists?

Here are some reasons why people use wordlists:

- To prevent a set of words from being used outside the context in which they are valid. Two classic examples of this are an integrated editor (all of the edit commands are defined in a separate word list; the search order is set to the editor word list when the editor is invoked; the old search order is restored when the editor is terminated) and an integrated assembler (the op-codes for the machine are defined in a separate word list which is used when a `CODE` word is defined).
- To organize the words of an application or library into a user-visible set (in `forth-wordlist` or some other common wordlist) and a set of helper words used just for the implementation (hidden in a separate wordlist). This keeps `words'` output smaller, separates implementation and interface, and reduces the chance of name conflicts within the common wordlist.
- To prevent a name-space clash between multiple definitions with the same name. For example, when building a cross-compiler you might have a word `IF` that generates conditional code for your target system. By placing this definition in a different word list you can control whether the host system's `IF` or the target system's `IF` get used

in any particular context by controlling the order of the word lists on the search order stack.

The downsides of using wordlists are:

- Debugging becomes more cumbersome.
- Name conflicts worked around with wordlists are still there, and you have to arrange the search order carefully to get the desired results; if you forget to do that, you get hard-to-find errors (as in any case where you read the code differently from the compiler; **see** can help seeing which of several possible words the name resolves to in such cases). **See** displays just the name of the words, not what wordlist they belong to, so it might be misleading. Using unique names is a better approach to avoid name conflicts.
- You have to explicitly undo any changes to the search order. In many cases it would be more convenient if this happened implicitly. Gforth currently does not provide such a feature, but it may do so in the future.

6.19.3 Word list example

The following example is from the garbage collector (<https://www.complang.tuwien.ac.at/forth/garbage-collection.zip>) and uses wordlists to separate public words from helper words:

```
get-current ( wid )
vocabulary garbage-collector also garbage-collector definitions
... \ define helper words
( wid ) set-current \ restore original (i.e., public) compilation wordlist
... \ define the public (i.e., API) words
    \ they can refer to the helper words
previous \ restore original search order (helper words become invisible)
```

6.20 Environmental Queries

Forth-94 introduced the idea of “environmental queries” as a way for a program running on a system to determine certain characteristics of the system. The Standard specifies a number of strings that might be recognised by a system, and a way of querying them:

environment? (*c-addr u* – *false* / ... *true*) core “environment-query”

c-addr, *u* specify a counted string. If the string is not recognised, return a **false** flag. Otherwise return a **true** flag and some (string-specific) information about the queried string.

Note that, whilst the documentation for (e.g.) **ADDRESS-UNIT-BITS** shows it returning one cell on the stack, querying it using **environment?** will return an additional item; the **true** flag that shows that the string was recognised; so for querying **ADDRESS-UNIT-BITS** the stack effect of **environment?** is (*c-addr u* -- *n true*).

Several environmental queries deal with the system’s limits:

ADDRESS-UNIT-BITS (– *n*) environment “ADDRESS-UNIT-BITS”

Size of one address unit, in bits.

MAX-CHAR (– *u*) environment “MAX-CHAR”

Maximum value of any character in the character set

/COUNTED-STRING (– *n*) environment “slash-counted-string”

Maximum size of a counted string, in characters.

/HOLD (*- n*) environment “slash-hold”

Size of the pictured numeric string output buffer, in characters.

/PAD (*- n*) environment “slash-pad”

Size of the scratch area pointed to by **PAD**, in characters.

CORE (*- f*) environment “CORE”

True if the complete core word set is present. Always true for Gforth.

CORE-EXT (*- f*) environment “CORE-EXT”

True if the complete core extension word set is present. Always true for Gforth.

FLOORED (*- f*) environment “FLOORED”

True if / etc. perform floored division

MAX-N (*- n*) environment “MAX-N”

Largest usable signed integer.

MAX-U (*- u*) environment “MAX-U”

Largest usable unsigned integer.

MAX-D (*- d*) environment “MAX-D”

Largest usable signed double.

MAX-UD (*- ud*) environment “MAX-UD”

Largest usable unsigned double.

return-stack-cells (*- n*) environment “return-stack-cells”

Maximum size of the return stack, in cells.

stack-cells (*- n*) environment “stack-cells”

Maximum size of the data stack, in cells.

floating-stack (*- n*) environment “floating-stack”

n is non-zero, showing that Gforth maintains a separate floating-point stack of depth *n*.

#locals (*- n*) environment “number-locals”

The maximum number of locals in a definition

wordlists (*- n*) environment “wordlists”

the maximum number of wordlists usable in the search order

max-float (*- r*) environment “max-float”

The largest usable floating-point number (implemented as largest finite number in Gforth)

XCHAR-ENCODING (*- addr u*) environment “XCHAR-ENCODING”

Returns a printable ASCII string that represents the encoding, and use the preferred MIME name (if any) or the name in <http://www.iana.org/assignments/character-sets> like “ISO-LATIN-1” or “UTF-8”, with the exception of “ASCII”, where we prefer the alias “ASCII”.

MAX-XCHAR (*- xchar*) environment “MAX-XCHAR”

Maximal value for xchar. This depends on the encoding.

`XCHAR-MAXMEM (- u)` environment “XCHAR-MAXMEM”

Maximal memory consumed by an xchar in address units

Several environmental queries are there for determining the presence of the Forth-94 version of a wordset; they all have the stack effect (-- f) if the string is present (so the `environment?` stack effect for these queries is (c-addr u -- false / f true).

`block block-ext double double-ext exception exception-ext facility
facility-ext file file-ext floating floating-ext locals locals-ext memory-
alloc memory-alloc-ext tools tools-ext search-order search-order-ext string
string-ext`

These wordset queries were rarely used and implemented, so Forth-2012 did not introduce a way to query for the Forth-2012 variants of the wordsets. Instead, the idea is that you use `[defined]` (see `<undefined>` [Interpreter Directives], page `<undefined>`) instead.

Forth-200x (a group that works on the next standard; the documents that they produce are also called Forth-200x) defines extension queries for the extension proposals once they finish changing (CfV stage), so programs using these proposals can check whether a system has them, and maybe load the reference implementation (if one exists). If `environment?` finds such a query, then the corresponding proposal on www.forth200x.org is implemented on the system (but the absence tells you nothing, as usual with `environment?`). These queries have the stack effect (--), which means that for them `environment?` has the stack effect (c-addr u -- false / true), which is more convenient than that of wordset queries. A number of these proposals have been incorporated into Forth-2012. The extension queries are also not particularly popular among Forth system implementors, so going for `[defined]` may be the better approach. Anyway, Gforth implements the following extension queries:

`X:2value X:buffer X:deferred X:defined X:ekeys X:escaped-strings
X:extension-query X:fp-stack X:ftrunc X:fvalue X:locals X:n-to-r X:number-
prefixes X:parse-name X:required X:s-escape-quote X:s-to-f X:structures
X:synonym X:text-substitution X:throw-iors X:traverse-wordlist X:xchar`

In addition, Gforth implements the following Gforth-specific queries:

`gforth (- c-addr u)` gforth-environment “gforth”

Counted string representing a version string for this version of Gforth (for versions > 0.3.0). The version strings of the various versions are guaranteed to be ordered lexicographically.

`os-class (- c-addr u)` gforth-environment “os-class”

Counted string representing a description of the host operating system.

`os-type (- c-addr u)` gforth-environment “os-type”

Counted string equal to “\$host_os”

The Standard requires that the header space used for environmental queries be distinct from the header space used for definitions.

Typically, a Forth system supports environmental queries by creating a set of definitions in a wordlist that is *only* used for environmental queries; that is what Gforth does. There is no Standard way of adding definitions to the set of recognised environmental queries, but

in Gforth and other systems that use the wordlist mechanism, the wordlist used to honour environmental queries can be manipulated just like any other word list.

`environment-wordlist (- wid)` gforth-0.2 “environment-wordlist”

wid identifies the word list that is searched by environmental queries (present in Swift-Forth and VFX).

`environment (-)` gforth-0.6 “environment”

A vocabulary for `environment-wordlist` (present in Win32Forth and VFX).

Here are some examples of using environmental queries:

```
s" address-unit-bits" environment? 0=
[IF]
    cr .( environmental attribute address-units-bits unknown... ) cr
[ELSE]
    drop \ ensure balanced stack effect
[THEN]

\ this might occur in the prelude of a standard program that uses THROW
s" exception" environment? [IF]
    0= [IF]
        : throw abort" exception thrown" ;
    [THEN]
[ELSE] \ we don't know, so make sure
    : throw abort" exception thrown" ;
[THEN]

s" gforth" environment? [IF] .( Gforth version ) TYPE
[ELSE] .( Not Gforth..) [THEN]

\ a program using v*
s" gforth" environment? [IF]
    s" 0.5.0" compare 0< [IF] \ v* is a primitive since 0.5.0
        : v* ( f_addr1 nstride1 f_addr2 nstride2 ucount -- r )
            >r swap 2swap swap 0e r> 0 ?DO
                dup f@ over + 2swap dup f@ f* f+ over + 2swap
            LOOP
            2drop 2drop ;
        [THEN]
[ELSE] \
    : v* ( f_addr1 nstride1 f_addr2 nstride2 ucount -- r )
        ...
    [THEN]
```

Here is an example of adding a definition to the environment word list:

```
get-current environment-wordlist set-current
true constant block
true constant block-ext
set-current
```

You can see what definitions are in the environment word list like this:

```
environment-wordlist wordlist-words
```

6.21 Files

Gforth provides facilities for accessing files that are stored in the host operating system's file-system. Files that are processed by Gforth can be divided into two categories:

- Files that are processed by the Text Interpreter (*Forth source files*).
- Files that are processed by some other program (*general files*).

6.21.1 Forth source files

The simplest way to interpret the contents of a file is to use one of these two formats:

```
include mysource.fs
s" mysource.fs" included
```

You usually want to include a file only if it is not included already (by, say, another source file). In that case, you can use one of these three formats:

```
require mysource.fs
needs mysource.fs
s" mysource.fs" required
```

It is good practice to write your source files such that interpreting them does not change the stack. Source files designed in this way can be used with **required** and friends without complications. For example:

```
1024 require foo.fs drop
```

Here you want to pass the argument 1024 (e.g., a buffer size) to **foo.fs**. Interpreting **foo.fs** has the stack effect ($n - n$), which allows its use with **require**. Of course with such parameters to required files, you have to ensure that the first **require** fits for all uses (i.e., **require** it early in the master load file).

```
include-file (  $i*x$   $wfileid - j*x$  ) file "include-file"
```

Interpret (process using the text interpreter) the contents of the file *wfileid*.

```
included (  $i*x$   $c-addr u - j*x$  ) file "included"
```

include-file the file whose name is given by the string *c-addr u*.

```
included? (  $c-addr u - f$  ) gforth-0.2 "included?"
```

True only if the file *c-addr u* is in the list of earlier included files. If the file has been loaded, it may have been specified as, say, **foo.fs** and found somewhere on the Forth search path. To return **true** from **included?**, you must specify the exact path to the file, even if that is **./foo.fs**

```
include ( ... "file" - ... ) file-ext "include"
```

include-file the file *file*.

```
required (  $i*x$   $addr u - i*x$  ) file-ext "required"
```

include-file the file with the name given by *addr u*, if it is not **included** (or **required**) already. Currently this works by comparing the name of the file (with path) against the names of earlier included files.

```
require ( ... "file" - ... ) file-ext "require"
```


`include-file` *file* only if it is not included already.

`needs` (... "*name*" - ...) gforth-0.2 "needs"

An alias for `require`; exists on other systems (e.g., Win32Forth).

`\\ (-)` gforth-1.0 "\\\""

skip remaining source file

`.included` (-) gforth-0.5 ".included"

List the names of the files that have been `included`.

`sourcefilename` (- *c-addr u*) gforth-0.2 "sourcefilename"

The name of the source file which is currently the input source. The result is valid only while the file is being loaded. If the current input source is no (stream) file, the result is undefined. In Gforth, the result is valid during the whole session (but not across `savesystem` etc.).

`sourceline#` (- *u*) gforth-0.2 "sourceline-number"

The line number of the line that is currently being interpreted from a (stream) file. The first line has the number 1. If the current input source is not a (stream) file, the result is undefined.

A definition in Standard Forth for `required` is provided in `compat/required.fs`.

6.21.2 General files

Files are opened/created by name and type. The following file access methods (FAMs) are recognised:

`r/o` (- *fam*) file "r-o"

`r/w` (- *fam*) file "r-w"

`w/o` (- *fam*) file "w-o"

`bin` (*fam1* - *fam2*) file "bin"

`+fmode` (*fam1 rwxrwxrwx* - *fam2*) gforth-1.0 "plus-f-mode"

add file access mode to *fam* - for create-file only

When a file is opened/created, it returns a file identifier, *wfileid* that is used for all other file commands. All file commands also return a status value, *wior*, that is 0 for a successful operation and an implementation-defined non-zero value in the case of an error.

`open-file` (*c-addr u wfam* - *wfileid wior*) file "open-file"

`create-file` (*c-addr u wfam* - *wfileid wior*) file "create-file"

`close-file` (*wfileid* - *wior*) file "close-file"

`delete-file` (*c-addr u* - *wior*) file "delete-file"

`rename-file` (*c-addr1 u1 c-addr2 u2* - *wior*) file-ext "rename-file"

Rename file *c-addr1 u1* to new name *c-addr2 u2*

`read-file` (*c-addr u1 wfileid* - *u2 wior*) file "read-file"

Read *u1* characters from file *wfileid* into the buffer at *c-addr*. A non-zero *wior* indicates an error. *U2* indicates the length of the read data. End-of-file is not an error and is indicated by *u2* < *u1* and *wior*=0.

`read-line` (*c-addr u1 wfileid* - *u2 flag wior*) file "read-line"

Reads a line from *wfileid* into the buffer at *c-addr u1*. Gforth supports all three common line terminators: LF, CR and CRLF. A non-zero *wior* indicates an error. A false *flag* indicates that **read-line** has been invoked at the end of the file. *u2* indicates the line length (without terminator): *u2\$<\$u1* indicates that the line is *u2* chars long; *u2=u1* indicates that the line is at least *u1* chars long, the *u1* chars of the buffer have been filled with chars from the line, and the next slice of the line will be read with the next **read-line**. If the line is *u1* chars long, the first **read-line** returns *u2=u1* and the next read-line returns *u2=0*.

key-file (*fd - key*) gforth-0.4 “key-file”

Read one character *n* from *wfileid*. This word disables buffering for *wfileid*. If you want to read characters from a terminal in non-canonical (raw) mode, you have to put the terminal in non-canonical mode yourself (using the C interface); the exception is **stdin**: Gforth automatically puts it into non-canonical mode.

key?-file (*wfileid - f*) gforth-0.4 “key-q-file”

f is true if at least one character can be read from *wfileid* without blocking. If you also want to use **read-file** or **read-line** on the file, you have to call **key?-file** or **key-file** first (these two words disable buffering).

file-eof? (*wfileid - flag*) gforth-0.6 “file-eof-query”

Flag is true if the end-of-file indicator for *wfileid* is set.

write-file (*c-addr u1 wfileid - wior*) file “write-file”

write-line (*c-addr u wfileid - ior*) file “write-line”

emit-file (*c wfileid - wior*) gforth-0.2 “emit-file”

flush-file (*wfileid - wior*) file-ext “flush-file”

file-status (*c-addr u - wfam wior*) file-ext “file-status”

file-position (*wfileid - ud wior*) file “file-position”

reposition-file (*ud wfileid - wior*) file “reposition-file”

file-size (*wfileid - ud wior*) file “file-size”

resize-file (*ud wfileid - wior*) file “resize-file”

slurp-file (*c-addr1 u1 - c-addr2 u2*) gforth-0.6 “slurp-file”

c-addr1 u1 is the filename, *c-addr2 u2* is the file’s contents

slurp-fid (*fid - addr u*) gforth-0.6 “slurp-fid”

addr u is the content of the file *fid*

stdin (- *wfileid*) gforth-0.4 “stdin”

The standard input file of the Gforth process.

stdout (- *wfileid*) gforth-0.2 “stdout”

The standard output file of the Gforth process.

stderr (- *wfileid*) gforth-0.2 “stderr”

The standard error output file of the Gforth process.

6.21.3 Redirection

You can redirect the output of **type** and **emit** and all the words that use them (all output words that don't have an explicit target file) to an arbitrary file with the **outfile-execute**, used like this:

```
: some-warning ( n -- )
  cr ." warning# " . ;

: print-some-warning ( n -- )
  ['] some-warning stderr outfile-execute ;
```

After **some-warning** is executed, the original output direction is restored; this construct is safe against exceptions. Similarly, there is **infile-execute** for redirecting the input of **key** and its users (any input word that does not take a file explicitly).

outfile-execute (... *xt file-id* - ...) gforth-0.7 “outfile-execute”

execute *xt* with the output of **type** etc. redirected to *file-id*.

outfile-id (- *file-id*) gforth-0.2 “outfile-id”

File-id is used by **emit**, **type**, and any output word that does not take a file-id as input. By default **outfile-id** produces the process's **stdout**, unless changed with **outfile-execute**.

infile-execute (... *xt file-id* - ...) gforth-0.7 “infile-execute”

execute *xt* with the input of **key** etc. redirected to *file-id*.

infile-id (- *file-id*) gforth-0.4 “infile-id”

File-id is used by **key**, **?key**, and anything that refers to the "user input device". By default **infile-id** produces the process's **stdin**, unless changed with **infile-execute**.

If you do not want to redirect the input or output to a file, you can also make use of the fact that **key**, **emit** and **type** are deferred words (see (undefined) [Deferred Words], page (undefined)). However, in that case you have to worry about the restoration and the protection against exceptions yourself; also, note that for redirecting the output in this way, you have to redirect both **emit** and **type**.

6.21.4 Directories

You can split a file name into a directory and base component:

basename (*c-addr1 u1* - *c-addr2 u2*) gforth-0.7 “basename”

Given a file name *c-addr1 u1*, *c-addr2 u2* is the part of it with any leading directory components removed.

dirname (*c-addr1 u1* - *c-addr1 u2*) gforth-0.7 “dirname”

C-addr1 u2 is the directory name of the file name *c-addr1 u1*, including the final /. If *c-addr1 u1* does not contain a /, *u2*=0.

You can open and read directories similar to files. Reading gives you one directory entry at a time; you can match that to a filename (with wildcards).

open-dir (*c-addr u* - *wdirid wior*) gforth-0.5 “open-dir”

Open the directory specified by *c-addr*, *u* and return *dir-id* for further access to it.

read-dir (*c-addr u1 wdirid* - *u2 flag wior*) gforth-0.5 “read-dir”

Attempt to read the next entry from the directory specified by *dir-id* to the buffer of length *u1* at address *c-addr*. If the attempt fails because there is no more entries, *ior*=0, *flag*=0, *u2*=0, and the buffer is unmodified. If the attempt to read the next entry fails because of any other reason, return *ior*<>0. If the attempt succeeds, store file name to the buffer at *c-addr* and return *ior*=0, *flag*=true and *u2* equal to the size of the file name. If the length of the file name is greater than *u1*, store first *u1* characters from file name into the buffer and indicate "name too long" with *ior*, *flag*=true, and *u2*=*u1*.

close-dir (*wdirid* – *wior*) gforth-0.5 “close-dir”

Close the directory specified by *dir-id*.

filename-match (*c-addr1* *u1* *c-addr2* *u2* – *flag*) gforth-0.5 “match-file”

match the file name *c-addr1* *u1* with the pattern *c-addr2* *u2*. Patterns match char by char except for the special characters '*' and '?', which are wildcards for several (*) or one (?) character.

get-dir (*c-addr1* *u1* – *c-addr2* *u2*) gforth-0.7 “get-dir”

Store the current directory in the buffer specified by *c-addr1*, *u1*. If the buffer size is not sufficient, return 0 0

set-dir (*c-addr* *u* – *wior*) gforth-0.7 “set-dir”

Change the current directory to *c-addr*, *u*. Return an error if this is not possible

=mkdir (*c-addr* *u* *wmode* – *wior*) gforth-0.7 “equals-mkdir”

Create directory *c-addr* *u* with mode *wmode*.

mkdir-parents (*c-addr* *u* *mode* – *ior*) gforth-0.7 “mkdir-parents”

create the directory *c-addr* *u* and all its parents with mode *mode* (modified by umask)

6.21.5 Search Paths

If you specify an absolute filename (i.e., a filename starting with / or ~, or with : in the second position (as in 'C:...')) for **included** and friends, that file is included just as you would expect.

If the filename starts with ./, this refers to the directory that the present file was **included** from. This allows files to include other files relative to their own position (irrespective of the current working directory or the absolute position). This feature is essential for libraries consisting of several files, where a file may include other files from the library. It corresponds to **#include "..."** in C. If the current input source is not a file, . refers to the directory of the innermost file being included, or, if there is no file being included, to the current working directory.

For relative filenames (not starting with ./), Gforth uses a search path similar to Forth's search order (see <undefined> [Word Lists], page <undefined>). It tries to find the given filename in the directories present in the path, and includes the first one it finds. There are separate search paths for Forth source files and general files. If the search path contains the directory ., this refers to the directory of the current file, or the working directory, as if the file had been specified with ./.

Use ~+ to refer to the current working directory (as in the **bash**).

absolute-file? (*addr* *u* – *flag*) gforth-1.0 “absolute-file?”

A filename is absolute if it starts with a / or a ~ (~ expansion), or if it is in the form ./*, extended regexp: `^[/~]|./`, or if it has a colon as second character ("C:..."). Paths simply containing a / are not absolute!

6.21.5.1 Source Search Paths

The search path is initialized when you start Gforth (see `<undefined>` [Invoking Gforth], page `<undefined>`). You can display it and change it using `fpath` in combination with the general path handling words.

```
fpath ( - path-addr ) gforth-0.4 "fpath"
```

```
.fpath ( - ) gforth-0.4 ".fpath"
```

Display the contents of the Forth search path.

```
file>fpath ( addr1 u1 - addr2 u2 ) gforth-1.0 "file>fpath"
```

Searches for a file with the name `c-addr1 u1` in the `fpath`. If successful, `c-addr u2` is the absolute file name or the file name relative to the current working directory. Throws an exception if the file cannot be opened.

Here is an example of using `fpath` and `require`:

```
fpath path= /usr/lib/forth/|./
require timer.fs
```

6.21.5.2 General Search Paths

Your application may need to search files in several directories, like `included` does. To facilitate this, Gforth allows you to define and use your own search paths, by providing generic equivalents of the Forth search path words:

```
open-path-file ( addr1 u1 path-addr - wfileid addr2 u2 0 | ior ) gforth-0.2 "open-path-file"
```

Look in path `path-addr` for the file specified by `addr1 u1`. If found, the resulting path and an (read-only) open file descriptor are returned. If the file is not found, `ior` is what came back from the last attempt at opening the file (in the current implementation).

```
file>path ( c-addr1 u1 path-addr - c-addr2 u2 ) gforth-1.0 "file>path"
```

Searches for a file with the name `c-addr1 u1` in path stored in `path-addr`. If successful, `c-addr u2` is the absolute file name or the file name relative to the current working directory. Throws an exception if the file cannot be opened.

```
clear-path ( path-addr - ) gforth-0.5 "clear-path"
```

Set the path `path-addr` to empty.

```
also-path ( c-addr len path-addr - ) gforth-0.4 "also-path"
```

add the directory `c-addr len` to `path-addr`.

```
.path ( path-addr - ) gforth-0.4 ".path"
```

Display the contents of the search path `path-addr`.

```
path+ ( path-addr "dir" - ) gforth-0.4 "path+"
```

Add the directory `dir` to the search path `path-addr`.

```
path= ( path-addr "dir1|dir2|dir3" - ) gforth-0.4 "path-equals"
```

Make a complete new search path; the path separator is `|`.

Here's an example of creating a custom search path:

```
variable mypath \ no special allocation required, just a variable
mypath path= /lib|usr/lib \ assign initial directories
mypath path+ /usr/local/lib \ append directory
mypath .path \ output: "/lib /usr/lib /usr/local/lib"
```

Search file and show resulting path:

```
s" libm.so" mypath open-path-file throw type close-file \ output: "/lib/libm.so"■
```

6.22 Blocks

When you run Gforth on a modern desk-top computer, it runs under the control of an operating system which provides certain services. One of these services is *file services*, which allows Forth source code and data to be stored in files and read into Gforth (see [\[Files\]](#), page [\(undefined\)](#)).

Traditionally, Forth has been an important programming language on systems where it has interfaced directly to the underlying hardware with no intervening operating system. Forth provides a mechanism, called *blocks*, for accessing mass storage on such systems.

A block is a 1024-byte data area, which can be used to hold data or Forth source code. No structure is imposed on the contents of the block. A block is identified by its number; blocks are numbered contiguously from 1 to an implementation-defined maximum.

A typical system that used blocks but no operating system might use a single floppy-disk drive for mass storage, with the disks formatted to provide 256-byte sectors. Blocks would be implemented by assigning the first four sectors of the disk to block 1, the second four sectors to block 2 and so on, up to the limit of the capacity of the disk. The disk would not contain any file system information, just the set of blocks.

On systems that do provide file services, blocks are typically implemented by storing a sequence of blocks within a single *blocks file*. The size of the blocks file will be an exact multiple of 1024 bytes, corresponding to the number of blocks it contains. This is the mechanism that Gforth uses.

Only one blocks file can be open at a time. If you use block words without having specified a blocks file, Gforth defaults to the blocks file `blocks.fb`. Gforth uses the Forth search path when attempting to locate a blocks file (see [\[Source Search Paths\]](#), page [\(undefined\)](#)).

When you read and write blocks under program control, Gforth uses a number of *block buffers* as intermediate storage. These buffers are not used when you use `load` to interpret the contents of a block.

The behaviour of the block buffers is analagous to that of a cache. Each block buffer has three states:

- Unassigned
- Assigned-clean
- Assigned-dirty

Initially, all block buffers are *unassigned*. In order to access a block, the block (specified by its block number) must be assigned to a block buffer.

The assignment of a block to a block buffer is performed by **block** or **buffer**. Use **block** when you wish to modify the existing contents of a block. Use **buffer** when you don't care about the existing contents of the block²⁴.

Once a block has been assigned to a block buffer using **block** or **buffer**, that block buffer becomes the *current block buffer*. Data may only be manipulated (read or written) within the current block buffer.

When the contents of the current block buffer has been modified it is necessary, *before calling block or buffer again*, to either abandon the changes (by doing nothing) or mark the block as changed (assigned-dirty), using **update**. Using **update** does not change the blocks file; it simply changes a block buffer's state to *assigned-dirty*. The block will be written implicitly when it's buffer is needed for another block, or explicitly by **flush** or **save-buffers**.

Flush writes all *assigned-dirty* blocks back to the blocks file on disk. Leaving Gforth with **bye** also performs a **flush**.

In Gforth, **block** and **buffer** use a *direct-mapped* algorithm to assign a block buffer to a block. That means that any particular block can only be assigned to one specific block buffer, called (for the particular operation) the *victim buffer*. If the victim buffer is *unassigned* or *assigned-clean* it is allocated to the new block immediately. If it is *assigned-dirty* its current contents are written back to the blocks file on disk before it is allocated to the new block.

Although no structure is imposed on the contents of a block, it is traditional to display the contents as 16 lines each of 64 characters. A block provides a single, continuous stream of input (for example, it acts as a single parse area) – there are no end-of-line characters within a block, and no end-of-file character at the end of a block. There are two consequences of this:

- The last character of one line wraps straight into the first character of the following line
- The word `\` – comment to end of line – requires special treatment; in the context of a block it causes all characters until the end of the current 64-character “line” to be ignored.

In Gforth, when you use **block** with a non-existent block number, the current blocks file will be extended to the appropriate size and the block buffer will be initialised with spaces.

Gforth includes a simple block editor (type **use blocked.fb 0 list** for details) but doesn't encourage the use of blocks; the mechanism is only provided for backward compatibility.

Common techniques that are used when working with blocks include:

- A screen editor that allows you to edit blocks without leaving the Forth environment.
- Shadow screens; where every code block has an associated block containing comments (for example: code in odd block numbers, comments in even block numbers). Typically, the block editor provides a convenient mechanism to toggle between code and comments.

²⁴ The Standard Forth definition of **buffer** is intended not to cause disk I/O; if the data associated with the particular block is already stored in a block buffer due to an earlier **block** command, **buffer** will return that block buffer and the existing contents of the block will be available. Otherwise, **buffer** will simply assign a new, empty block buffer for the block.

- Load blocks; a single block (typically block 1) contains a number of **thru** commands which load the whole of the application.

See Frank Sergeant's Pygmy Forth to see just how well blocks can be integrated into a Forth programming environment.

open-blocks (*c-addr u* -) gforth-0.2 "open-blocks"

Use the file, whose name is given by *c-addr u*, as the blocks file.

use ("*file*" -) gforth-0.2 "use"

Use *file* as the blocks file.

block-offset (- *addr*) gforth-0.5 "block-offset"

User variable containing the number of the first block (default since 0.5.0: 0). Block files created with Gforth versions before 0.5.0 have the offset 1. If you use these files you can: **1 offset !**; or add 1 to every block number used; or prepend 1024 characters to the file.

get-block-fid (- *wfileid*) gforth-0.2 "get-block-fid"

Return the file-id of the current blocks file. If no blocks file has been opened, use **blocks.fb** as the default blocks file.

block-position (*u* -) block "block-position"

Position the block file to the start of block *u*.

list (*u* -) block-ext "list"

Display block *u*. In Gforth, the block is displayed as 16 numbered lines, each of 64 characters.

scr (- *a-addr*) block-ext "s-c-r"

User variable containing the block number of the block most recently processed by **list**.

block (*u* - *a-addr*) block "block"

If a block buffer is assigned for block *u*, return its start address, *a-addr*. Otherwise, assign a block buffer for block *u* (if the assigned block buffer has been **updated**, transfer the contents to mass storage), read the block into the block buffer and return its start address, *a-addr*.

buffer (*u* - *a-addr*) block "buffer"

If a block buffer is assigned for block *u*, return its start address, *a-addr*. Otherwise, assign a block buffer for block *u* (if the assigned block buffer has been **updated**, transfer the contents to mass storage) and return its start address, *a-addr*. The subtle difference between **buffer** and **block** mean that you should only use **buffer** if you don't care about the previous contents of block *u*. In Gforth, this simply calls **block**.

empty-buffers (-) block-ext "empty-buffers"

Mark all block buffers as unassigned; if any had been marked as assigned-dirty (by **update**), the changes to those blocks will be lost.

empty-buffer (*buffer* -) gforth-0.2 "empty-buffer"

update (-) block "update"

Mark the state of the current block buffer as assigned-dirty.

updated? (*n* - *f*) gforth-0.2 "updated?"

Return true if **updated** has been used to mark block *n* as assigned-dirty.

save-buffers (-) block “save-buffers”

Transfer the contents of each **updated** block buffer to mass storage, then mark all block buffers as assigned-clean.

save-buffer (*buffer* -) gforth-0.2 “save-buffer”

flush (-) block “flush”

Perform the functions of **save-buffers** then **empty-buffers**.

load (*i*x u - j*x*) block “load”

Text-interpret block *u*. Block 0 cannot be loaded.

thru (*i*x n1 n2 - j*x*) block-ext “thru”

load the blocks *n1* through *n2* in sequence.

+load (*i*x n - j*x*) gforth-0.2 “+load”

Used within a block to load the block specified as the current block + *n*.

+thru (*i*x n1 n2 - j*x*) gforth-0.2 “+thru”

Used within a block to load the range of blocks specified as the current block + *n1* thru the current block + *n2*.

--> (-) gforth-0.2 “chain”

If this symbol is encountered whilst loading block *n*, discard the remainder of the block and load block *n+1*. Used for chaining multiple blocks together as a single loadable unit. Not recommended, because it destroys the independence of loading. Use **thru** (which is standard) or **+thru** instead.

block-included (*a-addr u -*) gforth-0.2 “block-included”

Use within a block that is to be processed by **load**. Save the current blocks file specification, open the blocks file specified by *a-addr u* and **load** block 1 from that file (which may in turn chain or load other blocks). Finally, close the blocks file and restore the original blocks file.

6.23 Other I/O

6.23.1 Simple numeric output

The simplest output functions are those that display numbers from the data stack. Numbers are displayed in the base (aka radix) stored in **base** (see <undefined> [Number Conversion], page <undefined>).

. (*n* -) core “dot”

Display (the signed single number) *n* in free-format, followed by a space.

dec. (*n* -) gforth-0.2 “dec.”

Display *n* as a signed decimal number, followed by a space.

h. (*u* -) gforth-1.0 “h.”

Display *u* as an unsigned hex number, prefixed with a “\$” and followed by a space.

hex. (*u* -) gforth-0.2 “hex.”

Display u as an unsigned hex number, prefixed with a $\$$ and followed by a space. Another name for this word is `h.`, which is present in several other systems, but not in Gforth before 1.0.

`u.` (u -) core “u-dot”

Display (the unsigned single number) u in free-format, followed by a space.

`.r` ($n1$ $n2$ -) core-ext “dot-r”

Display $n1$ right-aligned in a field $n2$ characters wide. If more than $n2$ characters are needed to display the number, all digits are displayed. If appropriate, $n2$ must include a character for a leading “-”.

`u.r` (u n -) core-ext “u-dot-r”

Display u right-aligned in a field n characters wide. If more than n characters are needed to display the number, all digits are displayed.

`dec.r` (u n -) gforth-0.5 “dec.r”

Display u as a unsigned decimal number in a field n characters wide.

`d.` (d -) double “d-dot”

Display (the signed double number) d in free-format. followed by a space.

`ud.` (ud -) gforth-0.2 “u-d-dot”

Display (the signed double number) ud in free-format, followed by a space.

`d.r` (d n -) double “d-dot-r”

Display d right-aligned in a field n characters wide. If more than n characters are needed to display the number, all digits are displayed. If appropriate, n must include a character for a leading “-”.

`ud.r` (ud n -) gforth-0.2 “u-d-dot-r”

Display ud right-aligned in a field n characters wide. If more than n characters are needed to display the number, all digits are displayed.

6.23.2 Formatted numeric output

Forth traditionally uses a technique called *pictured numeric output* for formatted printing of integers. In this technique, digits are extracted from the number (using the current output radix defined by `base`, see [\[Number Conversion\]](#), page [\(undefined\)](#)), converted to ASCII codes and prepended to a string that is built in a scratch-pad area of memory (see [\[Implementation-defined options\]](#), page [\(undefined\)](#)). Arbitrary characters can be prepended to the string during the extraction process. The completed string is specified by an address and length and can be manipulated (`TYPEd`, copied, modified) under program control.

All of the integer output words described in the previous section (see [\[Simple numeric output\]](#), page [\(undefined\)](#)) are implemented in Gforth using pictured numeric output.

Three important things to remember about pictured numeric output:

- It always operates on double-precision numbers; to display a single-precision number, convert it first (for ways of doing this see [\[Double precision\]](#), page [\(undefined\)](#)).

- It always treats the double-precision number as though it were unsigned. The examples below show ways of printing signed numbers.
- The string is built up from right to left; least significant digit first.

Standard Forth supports a single output buffer (aka hold area) that you empty and initialize with `<#` and for which you get the result string with `#>`.

Gforth additionally supports nested usage of this buffer, allowing, e.g., to nest output from the debugging tracer `~~` inside code dealing with the hold area: `<<#` starts a new nest, `#>` produces the result string, and `#>>` unnests: the hold area for the nest is reclaimed, and `#>` now produces the string for the next-outer nest. All of Gforth's higher-level numeric output words use `<<# ... #> ... #>>` and can be nested inside other users of the hold area.

`<# (-)` core “less-number-sign”

Initialise/clear the pictured numeric output string.

`<<# (-)` gforth-0.5 “less-less-number-sign”

Start a hold area that ends with `#>>`. Can be nested in each other and in `<#`. Note: if you do not match up the `<<#`s with `#>>`s, you will eventually run out of hold area; you can reset the hold area to empty with `<#`.

`# (ud1 - ud2)` core “number-sign”

Used between `<<#` and `#>`. Prepend the least-significant digit (according to `base`) of `ud1` to the pictured numeric output string. `ud2` is `ud1/base`, i.e., the number representing the remaining digits.

`#s (ud - 0 0)` core “number-sign-s”

Used between `<<#` and `#>`. Prepend all digits of `ud` to the pictured numeric output string. `#s` will convert at least one digit. Therefore, if `ud` is 0, `#s` will prepend a “0” to the pictured numeric output string.

`hold (char -)` core “hold”

Used between `<<#` and `#>`. Prepend the character `char` to the pictured numeric output string.

`holds (addr u -)` core-ext “holds”

Used between `<<#` and `#>`. Prepend the string `addr u` to the pictured numeric output string.

`sign (n -)` core “sign”

Used between `<<#` and `#>`. If `n` (a *single* number) is negative, prepend “-” to the pictured numeric output string.

`#> (xd - addr u)` core “number-sign-greater”

Complete the pictured numeric output string by discarding `xd` and returning `addr u`; the address and length of the formatted string. A Standard program may modify characters within the string. Does not release the hold area; use `#>>` to release a hold area started with `<<#`, or `<#` to release all hold areas.

`#>> (-)` gforth-0.5 “number-sign-greater-greater”

Release the hold area started with `<<#`.

Here are some examples of using pictured numeric output:

```
: my-u. ( u -- )
```

```

\ Simplest use of pns.. behaves like Standard u.
0          \ convert to unsigned double
<<#       \ start conversion
#s        \ convert all digits
#>        \ complete conversion
TYPE SPACE \ display, with trailing space
#>> ;    \ release hold area

: cents-only ( u -- )
0          \ convert to unsigned double
<<#       \ start conversion
# #       \ convert two least-significant digits
#>        \ complete conversion, discard other digits
TYPE SPACE \ display, with trailing space
#>> ;    \ release hold area

: dollars-and-cents ( u -- )
0          \ convert to unsigned double
<<#       \ start conversion
# #       \ convert two least-significant digits
'.' hold  \ insert decimal point
#s        \ convert remaining digits
'$' hold  \ append currency symbol
#>        \ complete conversion
TYPE SPACE \ display, with trailing space
#>> ;    \ release hold area

: my-. ( n -- )
\ handling negatives.. behaves like Standard .
s>d       \ convert to signed double
swap over dabs \ leave sign byte followed by unsigned double
<<#       \ start conversion
#s        \ convert all digits
rot sign    \ get at sign byte, append "-" if needed
#>        \ complete conversion
TYPE SPACE \ display, with trailing space
#>> ;    \ release hold area

: account. ( n -- )
\ accountants don't like minus signs, they use parentheses
\ for negative numbers
s>d       \ convert to signed double
swap over dabs \ leave sign byte followed by unsigned double
<<#       \ start conversion
2 pick    \ get copy of sign byte
0< IF ')' hold THEN \ right-most character of output
#s        \ convert all digits

```

```

rot          \ get at sign byte
0< IF '(' hold THEN
#>          \ complete conversion
TYPE SPACE  \ display, with trailing space
#>> ;      \ release hold area

```

Here are some examples of using these words:

```

1 my-u. 1
hex -1 my-u. decimal FFFFFFFF
1 cents-only 01
1234 cents-only 34
2 dollars-and-cents $0.02
1234 dollars-and-cents $12.34
123 my-. 123
-123 my. -123
123 account. 123
-456 account. (456)

```

6.23.3 Floating-point output

Floating-point output is always displayed using base 10.

f. (*r* –) floating-ext “f-dot”

Display (the floating-point number) *r* without exponent, followed by a space.

fe. (*r* –) floating-ext “f-e-dot”

Display *r* using engineering notation (with exponent dividable by 3), followed by a space.

fs. (*r* –) floating-ext “f-s-dot”

Display *r* using scientific notation (with exponent), followed by a space.

fp. (*r* –) floating-ext “f-e-dot”

Display *r* using SI prefix notation (with exponent dividable by 3, converted into SI prefixes if available), followed by a space.

Examples of printing the number 1234.5678E23 in the different floating-point output formats are shown below.

```

f. 1234567800000000000000000000.
fe. 123.4567800000000E24
fs. 1.234567800000000E26
fp. 123.456780000000Y

```

The length of the output is influenced by:

precision (*u* –) floating-ext “precision”

u is the number of significant digits currently used by **F.** **FE.** and **FS.**

set-precision (*u* –) floating-ext “set-precision”

Set the number of significant digits currently used by **F.** **FE.** and **FS.** to *u*.

You can control the output in more detail with:

f.rdp (*rf+nr+nd+np* –) gforth-0.6 “f.rdp”

Print float *rf* formatted. The total width of the output is *nr*. For fixed-point notation, the number of digits after the decimal point is *+nd* and the minimum number of significant digits is *np*. **Set-precision** has no effect on **f.rdp**. Fixed-point notation is used if the number of significant digits would be at least *np* and if the number of digits before the decimal point would fit. If fixed-point notation is not used, exponential notation is used, and if that does not fit, asterisks are printed. We recommend using *nr* ≥ 7 to avoid the risk of numbers not fitting at all. We recommend *nr* ≥ *np* + 5 to avoid cases where **f.rdp** switches to exponential notation because fixed-point notation would have too few significant digits, yet exponential notation offers fewer significant digits. We recommend *nr* ≥ *nd* + 2, if you want to have fixed-point notation for some numbers; the smaller the value of *np*, the more cases are shown in fixed-point notation (cases where few or no significant digits remain in fixed-point notation). We recommend *np* > *nr*, if you want to have exponential notation for all numbers.

To give you a better intuition of how they influence the output, here are some examples of parameter combinations; in each line the same number is printed, in each column the same parameter combination is used for printing:

12	13	0	7	3	4	7	3	0	7	3	1	7	5	1	7	7	1	7	0	2	4	2	1
	-1.	234568E-6	-1.	2E-6	-0.	000	-1.	2E-6	-1.	2E-6	-1.	2E-6	-1.	2E-6	-1.	2E-6	-1.	2E-6	-1.	2E-6	****		
	-1.	234568E-5	-1.	2E-5	-0.	000	-1.	2E-5	-.	00001	-1.	2E-5	-1.	2E-5	-1.	2E-5	-1.	2E-5	-1.	2E-5	****		
	-1.	234568E-4	-1.	2E-4	-0.	000	-1.	2E-4	-.	00012	-1.	2E-4	-1.	2E-4	-1.	2E-4	-1.	2E-4	-1.	2E-4	****		
	-1.	234568E-3	-1.	2E-3	-0.	001	-0.	001	-.	00123	-1.	2E-3	-1.	2E-3	-1.	2E-3	-1.	2E-3	-1.	2E-3	****		
	-1.	234568E-2	-1.	2E-2	-0.	012	-0.	012	-.	01235	-1.	2E-2	-1.	2E-2	-1.	2E-2	-1.	2E-2	-1.	2E-2	-.01		
	-1.	234568E-1	-1.	2E-1	-0.	123	-0.	123	-.	12346	-1.	2E-1	-1.	2E-1	-1.	2E-1	-1.	2E-1	-1.	2E-1	-.12		
	-1.	2345679E0	-1.	235	-1.	235	-1.	235	-1.	23E0	-1.	23E0	-1.	23E0	-1.	23E0	-1.	23E0	-1.	23E0	-1E0		
	-1.	2345679E1	-12.	346	-12.	346	-12.	346	-1.	23E1	-1.	23E1	-1.	23E1	-1.	23E1	-1.	23E1	-1.	23E1	-12. -1E1		
	-1.	2345679E2	-1.	23E2	-1.	23E2	-1.	23E2	-1.	23E2	-1.	23E2	-1.	23E2	-1.	23E2	-1.	23E2	-1.	23E2	-123. -1E2		
	-1.	2345679E3	-1.	23E3	-1.	23E3	-1.	23E3	-1.	23E3	-1.	23E3	-1.	23E3	-1.	23E3	-1.	23E3	-1.	23E3	-1235. -1E3		
	-1.	2345679E4	-1.	23E4	-1.	23E4	-1.	23E4	-1.	23E4	-1.	23E4	-1.	23E4	-1.	23E4	-1.	23E4	-1.	23E4	-12346. -1E4		
	-1.	2345679E5	-1.	23E5	-1.	23E5	-1.	23E5	-1.	23E5	-1.	23E5	-1.	23E5	-1.	23E5	-1.	23E5	-1.	23E5	-1.23E5	-1E5	

You can generate a string instead of displaying the number with:

```
f>str-rdp ( rf +nr +nd +np - c-addr nr ) gforth-0.6 "f>str-rdp"
```

Convert *rf* into a string at *c-addr nr*. The conversion rules and the meanings of *nr* *+nd* *np* are the same as for **f.rdp**. The result is in the pictured numeric output buffer and will be destroyed by anything destroying that buffer.

```
f>buf-rdp ( rf c-addr +nr +nd +np - ) gforth-0.6 "f>buf-rdp"
```

Convert *rf* into a string at *c-addr nr*. The conversion rules and the meanings of *nr* *nd* *np* are the same as for **f.rdp**.

There is also a primitive used for implementing higher-level FP-to-string words:

```
represent ( r c-addr u - n f1 f2 ) floating "represent"
```

Convert the decimal significand (aka mantissa) of *r* into a string in buffer *c-addr u*; *n* is the exponent, *f1* is true if *r* is negative, and *f2* is true if *r* is valid (a finite number in Gforth).

6.23.4 Miscellaneous output

```
cr ( - ) core "c-r"
```

Output a newline (of the favourite kind of the host OS). Note that due to the way the Forth command line interpreter inserts newlines, the preferred way to use `cr` is at the start of a piece of text; e.g., `cr ." hello, world"`.

`space` (*u*) core “space”

Display one space.

`spaces` (*u*) core “spaces”

Display *u* spaces.

`out` (*addr*) gforth-1.0 “out”

`Addr` contains a number that tries to give the position of the cursor within the current line on the user output device: It resets to 0 on `cr`, increases by the number of characters by `type` and `emit`, and decreases on `backspaces`. Unfortunately, it does not take into account tabs, multi-byte characters, or the existence of Unicode characters with width 0 and 2, so it only works for simple cases.

`.\` (*compilation* ‘*ccc*’ – ; *run-time* –) gforth-0.6 “dot-backslash-quote”

Like `."`, but translates C-like `\`-escape-sequences (see `S\`).

`."` (*compilation* ‘*ccc*’ – ; *run-time* –) core “dot-quote”

Compilation: Parse a string *ccc* delimited by a `"` (double quote). At run-time, display the string. Interpretation semantics for this word are undefined in standard Forth. Gforth’s interpretation semantics are to display the string.

`.(` (*compilation&interpretation* ‘*ccc*<*close-paren*>’ –) core-ext “dot-paren”

Compilation and interpretation semantics: Parse a string *ccc* delimited by a `)` (right parenthesis). Display the string. This is often used to display progress information during compilation; see examples below.

If you don’t want to worry about whether to use `.(hello)` or `." hello"`, you can write `"hello" type`, which gives you what you usually want (but is less portable to other Forth systems).

As an example, consider the following text, stored in a file `test.fs`:

```
.( text-1)
: my-word
  ." text-2" cr
  .( text-3)
  "text-4" type
;

." text-5"
"text-6" type
```

When you load this code into Gforth, the following output is generated:

```
include test.fs RET text-1text-3text-5text-6 ok
```

- Messages `text-1` and `text-3` are displayed because `.(` is an immediate word; it behaves in the same way whether it is used inside or outside a colon definition.
- Message `text-5` is displayed because of Gforth’s added interpretation semantics for `."`.
- Message `text-6` is displayed because `"text-6" type` is interpreted.

- Message `text-2` is *not* displayed, because the text interpreter performs the compilation semantics for `."` within the definition of `my-word`.
- Message `text-4` is *not* displayed, because `"text-4"` type is compiled into `my-word`.

6.23.5 Displaying characters and strings

`type (c-addr u -)` core “type”

If $u > 0$, display u characters from a string starting with the character stored at $c\text{-}addr$.

`xemit (xc -)` xchar “x-emit”

Prints an xchar on the terminal.

`emit (c -)` core “emit”

Send the byte c to the current output; for ASCII characters, `emit` is equivalent to `xemit`.

`typewhite (addr n -)` gforth-0.2 “typewhite”

Like `type`, but white space is printed instead of the characters.

6.23.6 Terminal output

If you are outputting to a terminal, you may want to control the positioning of the cursor:

`at-xy (x y -)` facility “at-x-y”

Put the cursor at position $x\ y$. The top left-hand corner of the display is at 0 0.

`at-deltaxy (dx dy -)` gforth-0.7 “at-deltaxy”

With the current position at $x\ y$, put the cursor at $x+dx\ y+dy$.

In order to know where to position the cursor, it is often helpful to know the size of the screen:

`form (- nlines ncols)` gforth-0.2 “form”

And sometimes you want to use:

`page (-)` facility “page”

Clear the screen

Note that on non-terminals you should use 12 `emit`, not `page`, to get a form feed.

6.23.6.1 Color output

The following words are used to create (semantic) colorful output; further output is produced in the color and style given by the word; the actual color and style depends on the theme (see below).

`default-color (-)` gforth-1.0 “default-color”

use system-default color

`error-color (-)` gforth-1.0 “error-color”

error color: red

`error-hl-inv (-)` gforth-1.0 “error-hl-inv”

color mod for error highlight inverse

`error-hl-ul (-)` gforth-1.0 “error-hl-ul”

color mod for error highlight underline

`warning-color (-)` gforth-1.0 “warning-color”

color for warnings: blue/yellow on black terminals
info-color (-) gforth-1.0 “info-color”
 color for info: green/cyan on black terminals
success-color (-) gforth-1.0 “success-color”
 color for success: green
input-color (-) gforth-1.0 “input-color”
 color for user-input: black/white (both bold)
status-color (-) gforth-1.0 “status-color”
 color mod for status bar
compile-color (-) gforth-1.0 “compile-color”
 color mod for status bar in compile mode

6.23.6.2 Color themes

Depending on whether you prefer bright or dark background the foreground colors-theme can be changed by:

light-mode (-) gforth-1.0 “light-mode”
 color theme for white background
dark-mode (-) gforth-1.0 “dark-mode”
 color theme for black background
uncolored-mode (-) gforth-1.0 “uncolored-mode”

This mode does not set colors, but uses the default ones.

magenta-input (-) gforth-1.0 “magenta-input”
 make input color easily recognizable (useful in presentations)
default-input (-) gforth-1.0 “default-input”
 make input color easily recognizable (useful in presentations)

Gforth tries to select the best mode automatically. You can set the environment variable **GFORTH_INIT** to **light**, **dark**, **uncolored**, or **auto** (same effect if not setting it at all), to tell Gforth your preference, as well as **magenta** or **default** for the input color preference. Concatenate options with space as separator.

6.23.7 Single-key input

If you want to get a single printable character, you can use **key**; to check whether a character is available for **key**, you can use **key?**.

key (- *char*) core “key”
 Receive (but do not display) one character, *char*.
key-ior (- *char* | *ior*) gforth-1.0 “key-ior”

Receive (but do not display) one character, *char*, in case of an error or interrupt, return the negative *ior* instead.

key? (- *flag*) facility “key-question”

Determine whether a character is available. If a character is available, *flag* is true; the next call to **key** will yield the character. Once **key?** returns true, subsequent calls to **key?** before calling **key** or **ekey** will also return true.

xkey? (*- flag*) xchar “x-key-query”

If you want to process a mix of printable and non-printable characters, you can do that with **ekey** and friends. **Ekey** produces a keyboard event that you have to convert into a character with **ekey>char** or into a key identifier with **ekey>fkey**.

Typical code for using **EKEY** looks like this:

```
ekey ekey>xchar if ( xc )
  ... \ do something with the character
else ekey>fkey if ( key-id )
  case
    k-up                                of ... endof
    k-f1                                of ... endof
    k-left k-shift-mask or k-ctrl-mask or of ... endof
    ...
  endcase
else ( keyboard-event )
  drop \ just ignore an unknown keyboard event type
then then
```

ekey (*- u*) facility-ext “e-key”

Receive a keyboard event *u* (encoding implementation-defined).

ekey>xchar (*u - u false | xc true*) xchar-ext “e-key-to-x-char”

Convert keyboard event *u* into xchar *xc* if possible.

ekey>char (*u - u false | c true*) facility-ext “e-key-to-char”

Convert keyboard event *u* into character *c* if possible. Note that non-ASCII characters produce **false** from both **ekey>char** and **ekey>fkey**. Instead of **ekey>char**, use **ekey>xchar** if available.

ekey>fkey (*u1 - u2 f*) facility-ext “e-key-to-f-key”

If *u1* is a keyboard event in the special key set, convert keyboard event *u1* into key id *u2* and return true; otherwise return *u1* and false.

ekey? (*- flag*) facility-ext “e-key-question”

True if a keyboard event is available.

The key identifiers for cursor keys are:

k-left (*- u*) facility-ext “k-left”

k-right (*- u*) facility-ext “k-right”

k-up (*- u*) facility-ext “k-up”

k-down (*- u*) facility-ext “k-down”

k-home (*- u*) facility-ext “k-home”

aka Pos1

k-end (*- u*) facility-ext “k-end”

k-prior (*- u*) facility-ext “k-prior”

aka PgUp

k-next (- *u*) facility-ext “k-next”

aka PgDn

k-insert (- *u*) facility-ext “k-insert”

k-delete (- *u*) facility-ext “k-delete”

the DEL key on my xterm, not backspace

The key identifiers for function keys (aka keypad keys) are:

k-f1 (- *u*) facility-ext “k-f-1”

k-f2 (- *u*) facility-ext “k-f-2”

k-f3 (- *u*) facility-ext “k-f-3”

k-f4 (- *u*) facility-ext “k-f-4”

k-f5 (- *u*) facility-ext “k-f-5”

k-f6 (- *u*) facility-ext “k-f-6”

k-f7 (- *u*) facility-ext “k-f-7”

k-f8 (- *u*) facility-ext “k-f-8”

k-f9 (- *u*) facility-ext “k-f-9”

k-f10 (- *u*) facility-ext “k-f-10”

k-f11 (- *u*) facility-ext “k-f-11”

k-f12 (- *u*) facility-ext “k-f-12”

Note that **k-f11** and **k-f12** are not as widely available.

You can combine these key identifiers with masks for various shift keys:

k-shift-mask (- *u*) facility-ext “k-shift-mask”

k-ctrl-mask (- *u*) facility-ext “k-ctrl-mask”

k-alt-mask (- *u*) facility-ext “k-alt-mask”

There are a number of keys that have ASCII values, and therefore are unlikely to be reported as special keys, but the combination of these keys with shift keys may be reported as a special key:

k-enter (- *u*) gforth-1.0 “k-enter”

k-backspace (- *u*) gforth-1.0 “k-backspace”

k-tab (- *u*) gforth-1.0 “k-tab”

Moreover, there the following key codes for keys and other events:

k-winch (- *u*) gforth-1.0 “k-winch”

A key code that may be generated when the user changes the window size.

k-pause (- *u*) gforth-1.0 “k-pause”

k-mute (- *u*) gforth-1.0 “k-mute”

k-volup (- *u*) gforth-1.0 “k-volup”

k-voldown (- *u*) gforth-1.0 “k-voldown”

k-sel (- *u*) gforth-1.0 “k-sel”

k-eof (- *u*) gforth-1.0 “k-eof”

Note that, even if a Forth system has **ekey>fkey** and the key identifier words, the keys are not necessarily available or it may not necessarily be able to report all the keys and all the possible combinations with shift masks. Therefore, write your programs in such a way that they are still useful even if the keys and key combinations cannot be pressed or are not recognized.

Examples: Older keyboards often do not have an F11 and F12 key. If you run Gforth in an xterm, the xterm catches a number of combinations (e.g., **Shift-Up**), and never passes it to Gforth. Finally, Gforth currently does not recognize and report combinations with multiple shift keys (so the **shift-ctrl-left** case in the example above would never be entered).

Gforth recognizes various keys available on ANSI terminals (in MS-DOS you need the ANSI.SYS driver to get that behaviour); it works by recognizing the escape sequences that ANSI terminals send when such a key is pressed. If you have a terminal that sends other escape sequences, you will not get useful results on Gforth. Other Forth systems may work in a different way.

Gforth also provides a few words for outputting names of function keys:

fkey. (*u* –) gforth-1.0 “fkey-dot”

Print a string representation for the function key *u*. *U* must be a function key (possibly with modifier masks), otherwise there may be an exception.

simple-fkey-string (*u1* – *c-addr u*) gforth-1.0 “simple-fkey-string”

c-addr u is the string name of the function key *u1*. Only works for simple function keys without modifier masks. Any *u1* that does not correspond to a simple function key currently produces an exception.

6.23.8 Line input and conversion

For ways of storing character strings in memory see [\[String representations\]](#), page [\[undefined\]](#).

Words for inputting one line from the keyboard:

accept (*c-addr* *+n1* – *+n2*) core “accept”

Get a string of up to *n1* characters from the user input device and store it at *c-addr*. *n2* is the length of the received string. The user indicates the end by pressing **RET**. Gforth supports all the editing functions available on the Forth command line (including history and word completion) in **accept**.

edit-line (*c-addr* *n1* *n2* – *n3*) gforth-0.6 “edit-line”

edit the string with length *n2* in the buffer *c-addr* *n1*, like **accept**.

Conversion words:

s>number? (*addr u* – *d f*) gforth-0.5 “s>number?”

converts string *addr u* into *d*, flag indicates success

s>unumber? (*c-addr u* – *ud flag*) gforth-0.5 “s>unumber?”

converts string *c-addr u* into *ud*, flag indicates success

>number (*ud1* *c-addr1* *u1* – *ud2* *c-addr2* *u2*) core “to-number”

Attempt to convert the character string *c-addr1* *u1* to an unsigned number in the current number base. The double *ud1* accumulates the result of the conversion to form *ud2*.

Conversion continues, left-to-right, until the whole string is converted or a character that is not convertible in the current number base is encountered (including + or -). For each convertible character, *ud1* is first multiplied by the value in **BASE** and then incremented by the value represented by the character. *c-addr2* is the location of the first unconverted character (past the end of the string if the whole string was converted). *u2* is the number of unconverted characters in the string. Overflow is not detected.

>float (*c-addr u - f:... flag*) floating “to-float”

Actual stack effect: (*c-addr u - r t | f*). Attempt to convert the character string *c-addr u* to internal floating-point representation. If the string represents a valid floating-point number, *r* is placed on the floating-point stack and *flag* is true. Otherwise, *flag* is false. A string of blanks is a special case and represents the floating-point number 0.

>float1 (*c-addr u c - f:... flag*) gforth-1.0 “to-float1”

Actual stack effect: (*c-addr u c - r t | f*). Attempt to convert the character string *c-addr u* to internal floating-point representation, with *c* being the decimal separator. If the string represents a valid floating-point number, *r* is placed on the floating-point stack and *flag* is true. Otherwise, *flag* is false. A string of blanks is a special case and represents the floating-point number 0.

Obsolescent input and conversion words:

convert (*ud1 c-addr1 - ud2 c-addr2*) core-ext-obsolescent “convert”

Obsolescent: superseded by **>number**.

expect (*c-addr +n -*) core-ext-obsolescent “expect”

Receive a string of at most *+n* characters, and store it in memory starting at *c-addr*. The string is displayed. Input terminates when the <return> key is pressed or *+n* characters have been received. The normal Gforth line editing capabilities are available. The length of the string is stored in **span**; it does not include the <return> character. OBSOLESCENT: superseded by **accept**.

span (*- c-addr*) core-ext-obsolescent “span”

Variable – *c-addr* is the address of a cell that stores the length of the last string received by **expect**. OBSOLESCENT.

6.23.9 Pipes

In addition to using Gforth in pipes created by other processes (see <undefined> [Gforth in pipes], page <undefined>), you can create your own pipe with **open-pipe**, and read from or write to it.

open-pipe (*c-addr u wfam - wfileid wior*) gforth-0.2 “open-pipe”

close-pipe (*wfileid - wretval wior*) gforth-0.2 “close-pipe”

If you write to a pipe, Gforth can throw a **broken-pipe-error**; if you don’t catch this exception, Gforth will catch it and exit, usually silently (see <undefined> [Gforth in pipes], page <undefined>). Since you probably do not want this, you should wrap a **catch** or **try** block around the code from **open-pipe** to **close-pipe**, so you can deal with the problem yourself, and then return to regular processing.

broken-pipe-error (*- n*) gforth-0.6 “broken-pipe-error”

the error number for a broken pipe

6.23.10 Xchars and Unicode

ASCII is only appropriate for the English language. Most western languages however fit somewhat into the Forth frame, since a byte is sufficient to encode the few special characters in each (though not always the same encoding can be used; latin-1 is most widely used, though). For other languages, different char-sets have to be used, several of them variable-width. To deal with this problem, characters are often represented as Unicode codepoints on the stack, and as UTF-8 byte strings in memory. An Unicode codepoint often represents one application-level character, but Unicode also supports decomposed characters that consist of several code points, e.g., a base letter and a combining diacritical mark.

An Unicode codepoint can consume more than one byte in memory, so we adjust our terminology: A char is a raw byte in memory or a value in the range 0-255 on the stack. An xchar (for extended char) stands for one codepoint; it is represented by one or more bytes in memory and may have larger values on the stack. ASCII characters are the same as chars and as xchars: values in the range 0-127, and a single byte with that value in memory.

When using UTF-8 encoding, all other codepoints take more than one byte/char. In most cases, you can just treat such characters as strings in memory and don't need to use the following words, but if you want to deal with individual codepoints, the following words are useful. We currently have no words for dealing with decomposed characters.

The xchar words add a few data types:

- *xc* is an extended char (xchar) on the stack. It occupies one cell, and is a subset of unsigned cell. On 16 bit systems, only the BMP subset of the Unicode character set (i.e., codepoints <65536) can be represented on the stack. If you represent your application characters as strings at all times, you can avoid this limitation.
- *xc-addr* is the address of an xchar in memory. Alignment requirements are the same as *c-addr*. The memory representation of an xchar differs from the stack representation, and depends on the encoding used. An xchar may use a variable number of chars in memory.
- *xc-addr u* is a buffer of xchars in memory, starting at *xc-addr*, *u* chars (i.e., bytes, not xchars) long.

xc-size (*xc* - *u*) xchar “x-c-size”

Computes the memory size of the xchar *xc* in chars.

x-size (*xc-addr u1* - *u2*) xchar “x-size”

Computes the memory size of the first xchar stored at *xc-addr* in chars.

xc@ (*xc-addr* - *xc*) xchar-ext “xc-fetch”

Fetchs the xchar *xc* at *xc-addr1*.

xc@+ (*xc-addr1* - *xc-addr2 xc*) xchar “x-c-fetch-plus”

Fetchs the xchar *xc* at *xc-addr1*. *xc-addr2* points to the first memory location after *xc*.

xc@+? (*xc-addr1 u1* - *xc-addr2 u2 xc*) gforth-experimental “x-c-fetch-plus-query”

Fetchs the first xchar *xc* of the string *xc-addr1 u1*. *xc-addr2 u2* is the remaining string after *xc*.

xc!+? (*xc xc-addr1 u1* - *xc-addr2 u2 f*) xchar “x-c-store-plus-query”

Stores the xchar *xc* into the buffer starting at address *xc-addr1*, *u1* chars large. *xc-addr2* points to the first memory location after *xc*, *u2* is the remaining size of the buffer.

If the xchar *xc* did fit into the buffer, *f* is true, otherwise *f* is false, and *xc-addr2* *u2* equal *xc-addr1* *u1*. *XC!+?* is safe for buffer overflows, and therefore preferred over *XC!+*.

xc!+ (*xc xc-addr1 - xc-addr2*) xchar “x-c-store”

Stores the xchar *xc* at *xc-addr1*. *xc-addr2* is the next unused address in the buffer. Note that this writes up to 4 bytes, so you need at least 3 bytes of padding after the end of the buffer to avoid overwriting useful data if you only check the address against the end of the buffer.

xchar+ (*xc-addr1 - xc-addr2*) xchar “x-char-plus”

Adds the size of the xchar stored at *xc-addr1* to this address, giving *xc-addr2*.

xchar- (*xc-addr1 - xc-addr2*) xchar-ext “x-char-minus”

Goes backward from *xc-addr1* until it finds an xchar so that the size of this xchar added to *xc-addr2* gives *xc-addr1*.

+x/string (*xc-addr1 u1 - xc-addr2 u2*) xchar-ext “plus-x-slash-string”

Step forward by one xchar in the buffer defined by address *xc-addr1*, size *u1* chars. *xc-addr2* is the address and *u2* the size in chars of the remaining buffer after stepping over the first xchar in the buffer.

x\string- (*xc-addr u1 - xc-addr u2*) xchar-ext “x-backslash-string-minus”

Step backward by one xchar in the buffer defined by address *xc-addr* and size *u1* in chars, starting at the end of the buffer. *xc-addr* is the address and *u2* the size in chars of the remaining buffer after stepping backward over the last xchar in the buffer.

-trailing-garbage (*xc-addr u1 - xc-addr u2*) xchar-ext “minus-trailing-garbage”

Examine the last XCHAR in the buffer *xc-addr u1*—if the encoding is correct and it represents a full char, *u2* equals *u1*, otherwise, *u2* represents the string without the last (garbled) xchar.

x-width (*xc-addr u - n*) xchar-ext “x-width”

n is the number of monospace ASCII chars that take the same space to display as the the xchar string starting at *xc-addr*, using *u* chars; assuming a monospaced display font, i.e. char width is always an integer multiple of the width of an ASCII char.

xkey (- *xc*) xchar “x-key”

Reads an xchar from the terminal. This will discard all input events up to the completion of the xchar.

xc-width (*xc - n*) xchar-ext “x-c-width”

xc has a width of *n* times the width of a normal fixed-width glyph.

xhold (*xc -*) xchar-ext “x-hold”

Used between *<<#* and *#>*. Prepend *xc* to the pictured numeric output string. Alternatively, use *holds*.

xc, (*xchar -*) xchar “x-c-comma”

6.23.11 Internationalization and Localization

Programs for end users require to address those in their native language. There is a decades old proposal for such a facility that has been split from other proposals for international character sets like Xchars (see [\[Xchars and Unicode\]](#), page [\[undefined\]](#)) and Substitute (see [\[Substitute\]](#), page [\[undefined\]](#)). Messages displayed on the screen need to be translated from the native language of the developers to the local languages of the user.

Strings subject to translation are declared with `L" string"`. This returns a locale string identifier (LSID). LSIDs are opaque types, taking a cell on the stack. LSIDs can be translated into a locale; locales are languages and country-specific variants of that language.

`L" ("lsid<">" - lsid)` gforth-experimental “l-quote”

Parse a string and define a new lsid, if the string is uniquely new. Identical strings result in identical lsids, which allows to refer to the same lsid from multiple locations using the same string.

`LU" ("lsid<">" - lsid)` gforth-experimental “l-unique-quote”

Parse a string and always define a new lsid, even if the string is not unique.

`native@ (lsid - addr u)` gforth-experimental “native-fetch”

fetch native string from an *lsid*

`locale@ (lsid - addr u)` gforth-experimental “locale-fetch”

fetch the localized string in the current language and country

`locale! (addr u lsid -)` gforth-experimental “locale-store”

Store localized string *addr u* for the current locale and country in *lsid*.

`Language ("name" -)` gforth-experimental “Language”

define a locale. Executing that locale makes it the current locale.

`Country (<lang> "name" -)` gforth-experimental “Country”

define a variant (typical: country) for the current locale. Executing that locale makes it the current locale. You can create variants of variants (a country may have variants within, e.g. think of how many words for rolls/buns there are in many languages).

`locale-file (fid -)` gforth-experimental “locale-file”

read lines from *fid* into the current locale.

`included-locale (addr u -)` gforth-experimental “included-locale”

read lines from the file *addr u* into the current locale.

`include-locale ("name" -)` gforth-experimental “include-locale”

read lines from the file "*name*" into the current locale.

`locale-csv ("name" -)` gforth-experimental “locale-csv”

import comma-separated value table into locales. first line contains locale names, “program” and “default” are special entries; generic languages must precede translations for specific countries. Entries under “program” (must be leftmost) are used to search for the lsid; if empty, the line number-1 is the lsid index.

`.locale-csv (-)` gforth-experimental “dot-locale-csv”

write the locale database in CSV format to the terminal output.

`locale-csv-out ("name" -) gforth-experimental "locale-csv"`

Create file "*name*" and write the locale database out to the file "*name*" in CSV format.

6.23.12 Substitute

This is a simple text macro replacement facility. Texts in the form "**text %macro% text**" are processed, and the macro variables enclosed in '%' are replaced with their associated strings. Two consecutive % are replaced by one %. Macros are defined in a specific wordlist, and return a string upon execution; the standard defines only one way to declare macros, **replaces**, which creates a macro that just returns a string.

`macros-wordlist (- wid) gforth-experimental "macros-wordlist"`

wordlist for string replacement macros

`replaces (addr1 len1 addr2 len2 -) string-ext "replaces"`

create a macro with name *addr2 len2* and content *addr1 len1*. If the macro already exists, just change the content.

`replacer: ("name" -) gforth-experimental "replacer:"`

Start a colon definition *name* in **macros-wordlist**, i.e. this colon definition is a macro. It must have the stack effect (- *addr u*).

`.substitute (addr1 len1 - n / ior) gforth-experimental "dot-substitute"`

substitute all macros in text *addr1 len1* and print the result. *n* is the number of substitutions or, if negative, a throwable *ior*.

`$substitute (addr1 len1 - addr2 len2 n/ior) gforth-experimental "string-substitute"`

substitute all macros in text *addr1 len1*. *n* is the number of substitutions, if negative, it's a throwable *ior*, *addr2 len2* the result.

`substitute (addr1 len1 addr2 len2 - addr2 len3 n/ior) string-ext "substitute"`

substitute all macros in text *addr1 len1*, and copy the result to *addr2 len2*. *n* is the number of substitutions or, if negative, a throwable *ior*, *addr2 len3* the result.

`unescape (addr1 u1 dest - dest u2) string-ext "unescape"`

double all delimiters in *addr1 u1*, so that substitute will result in the original text. Note that the buffer *dest* does not have a size, as in worst case, it will need just twice as many characters as *u1*. *dest u2* is the resulting string.

`$unescape (addr1 u1 - addr2 u2) gforth-experimental "string-unescape"`

same as **unescape**, but creates a temporary destination string with **\$tmp**.

6.23.13 CSV Reader

Comma-separated values (CSV) are a popular text format to interchange data. Gforth provides words for reading CSV files (with all features, including newlines in quoted strings).

`read-csv (addr u xt -) gforth-experimental "read-csv"`

Read CVS file *addr u* and execute *xt* for every field found. *Xt* has the stack effect (*addr u field line --*), i.e. the field string (in de-quoted form), the current field number (starting with 0), and the current line (starting with 1).

`csv-separator (- c) gforth-experimental "csv-separator"`

CSV field separator (default is ‘,’, hence the name "comma-separated"); this is a value and can be changed with `to csv-separator`.

`csv-quote (- c)` gforth-experimental “csv-quote”

CSV quote character (default is ‘”’); this is a value and can be changed with `to csv-quote`.

`.quoted-csv (c-addr u -)` gforth-experimental “dot-quoted-csv”

print a field in CSV format, i.e., with enough quotes that `read-csv` will produce *c-addr u* when encountering the output of `.quoted-csv`.

6.24 OS command line arguments

The usual way to pass arguments to Gforth programs on the command line is via the `-e` option, e.g.

```
gforth -e "123 456" foo.fs -e bye
```

However, you may want to interpret the command-line arguments directly. In that case, you can access the (image-specific) command-line arguments through `next-arg`:

`next-arg (- addr u)` gforth-0.7 “next-arg”

get the next argument from the OS command line, consuming it; if there is no argument left, return 0 0.

Here’s an example program `echo.fs` for `next-arg`:

```
: echo ( -- )
  begin
  next-arg 2dup 0 0 d<> while
    type space
  repeat
  2drop ;
```

```
echo cr bye
```

This can be invoked with

```
gforth echo.fs hello world
```

and it will print

```
hello world
```

The next lower level of dealing with the OS command line are the following words:

`arg (u - addr count)` gforth-0.2 “arg”

Return the string for the *uth* command-line argument; returns 0 0 if the access is beyond the last argument. 0 `arg` is the program name with which you started Gforth. The next unprocessed argument is always 1 `arg`, the one after that is 2 `arg` etc. All arguments already processed by the system are deleted. After you have processed an argument, you can delete it with `shift-args`.

`shift-args (-)` gforth-0.7 “shift-args”

1 `arg` is deleted, shifting all following OS command line parameters to the left by 1, and reducing `argc @`. This word can change `argv @`.

Finally, at the lowest level Gforth provides the following words:

argc (- *addr*) gforth-0.2 “argc”

Variable – the number of command-line arguments (including the command name). Changed by **next-arg** and **shift-args**.

argv (- *addr*) gforth-0.2 “argv”

Variable – a pointer to a vector of pointers to the command-line arguments (including the command-name). Each argument is represented as a C-style zero-terminated string. Changed by **next-arg** and **shift-args**.

6.25 Locals

Local variables can make Forth programming more enjoyable and Forth programs easier to read.

Gforth implements an extended version of the standard Forth locals.

6.25.1 Gforth locals

Locals can be defined with

```
{: local1 local2 ... -- comment :}
or
{: local1 local2 ... :}
or
{: local1 local2 ... | ulocal0 ulocal1 -- comment :}
```

E.g.,

```
: max {: n1 n2 -- n3 :}
  n1 n2 > if
    n1
  else
    n2
  endif ;
```

The similarity of locals definitions with stack comments is intended. A locals definition often replaces the stack comment of a word. The order of the locals corresponds to the order in a stack comment and everything after the **--** is really a comment.

The name of the local may be preceded by a type specifier, e.g., **F:** for a floating point value:

```
: CX* {: F: Ar F: Ai F: Br F: Bi -- Cr Ci :}
\ complex multiplication
Ar Br f* Ai Bi f* f-
Ar Bi f* Ai Br f* f+ ;
```

Gforth currently supports cells (**W:**, **W^**), doubles (**D:**, **D^**), floats (**F:**, **F^**), characters (**C:**, **C^**), and xts (**xt:**) in several flavours:

value-flavoured

(see [\[Values\]](#), page [\[undefined\]](#)) A value-flavoured local (defined with **W:**, **D:** etc.) produces its value and can be changed with **T0** and **+T0**. Also,

if you put **addressable:** in front of the locals definition, you can get its address with **ADDR** (see [\[How long do locals live?\]](#), page [\[undefined\]](#)).

variable-flavoured

(see [\[Variables\]](#), page [\[undefined\]](#)) A variable-flavoured local (defined with **W[^]** etc.) produces its address (see [\[How long do locals live?\]](#), page [\[undefined\]](#)). E.g., the standard word **emit** can be defined in terms of **type** like this:

```
: emit { : C^ char* -- :}
      char* 1 type ;
```

defer-flavoured

(see [\[Deferred Words\]](#), page [\[undefined\]](#)) A defer-flavoured local (defined with **XT:**) **executes** the xt; you can use **action-of** (see [\[Deferred Words\]](#), page [\[undefined\]](#)) to get the xt out of a defer-flavoured local. If the local is defined with **addressable: xt:**, you can use **addr** to get the address where the xt is stored (see [\[How long do locals live?\]](#), page [\[undefined\]](#)). E.g., the standard word **execute** can be defined with a defer-flavoured local like this:

```
: execute { : xt: x -- :}
      x ;
```

A local without type specifier is a **W:** local. You can also leave away the **w:** if you use **addressable:**.

All flavours of locals are initialized with values from the data or (for FP locals) FP stack, with the exception being locals defined behind **|**: Gforth initializes them to 0; some Forth systems leave them uninitialized.

Gforth supports the square bracket notation for local buffers and data structures. These locals are similar to variable-flavored locals, the size is specified as a constant expression. A declaration looks **name[size]**. The Forth expression **size** is evaluated during declaration, it must have the stack effect (**-- +n**), giving the size in bytes. The square bracket **[** is part of the defined name.

Local data structures are initialized by copying *size* bytes from an address passed on the stack; uninitialized local data structures (after **|** in the declaration) are not erased, they just contain whatever data there was on the locals stack before.

Example:

```
begin-structure test-struct
  field: a1
  field: a2
end-structure

: test-local { : foo[ test-struct ] :}
  foo[ a1 ! foo[ a2 !
  foo[ test-struct dump ;
```

Gforth allows defining locals everywhere in a colon definition. This poses the following questions:

6.25.1.1 Locals definitions words

This section documents the words used for defining locals. Note that the run-times for the words (like `W:`) that define a local are performed from the rightmost defined local to the leftmost defined local, such that the rightmost local gets the top of stack.

`{: (- haddr u wid 0)` local-ext “open-brace-colon”

Start locals definitions.

`-- (haddr u wid 0 ... -)` local-ext “dash-dash”

During a locals definitions with `{:` everything from `--` to `}` is ignored. This is typically used when you want to make a locals definition serve double duty as a stack effect description.

`| (-)` local-ext “bar”

Locals defined behind `|` are not initialized from the stack; so the run-time stack effect of the locals definitions after `|` is `(--)`.

`:} (haddr u wid 0 xt1 ... xtn -)` gforth-1.0 “colon-close-brace”

Ends locals definitions.

`{ (- haddr u wid 0)` gforth-0.2 “open-brace”

Start locals definitions. The Forth-2012 standard name for this word is `{:`.

`} (haddr u wid 0 xt1 ... xtn -)` gforth-0.2 “close-brace”

Ends locals definitions. The Forth-2012 standard name for this word is `:}`.

`W: (compilation "name" - a-addr xt; run-time x -)` gforth-0.2 “w-colon”

Define value-flavoured cell local *name* (-- **x1**)

`W^ (compilation "name" - a-addr xt; run-time x -)` gforth-0.2 “w-caret”

Define variable-flavoured cell local *name* (-- **a-addr**)

`D: (compilation "name" - a-addr xt; run-time x1 x2 -)` gforth-0.2 “d-colon”

Define value-flavoured double local *name* (-- **x3 x4**)

`D^ (compilation "name" - a-addr xt; run-time x1 x2 -)` gforth-0.2 “d-caret”

Define variable-flavoured double local *name* (-- **a-addr**)

`C: (compilation "name" - a-addr xt; run-time c -)` gforth-0.2 “c-colon”

Define value-flavoured char local *name* (-- **c1**)

`C^ (compilation "name" - a-addr xt; run-time c -)` gforth-0.2 “c-caret”

Define variable-flavoured char local *name* (-- **c-addr**)

`F: (compilation "name" - a-addr xt; run-time r -)` gforth-0.2 “f-colon”

Define value-flavoured float local *name* (-- **r1**)

`F^ (compilation "name" - a-addr xt; run-time r -)` gforth-0.2 “f-caret”

Define variable-flavoured float local *name* (-- **f-addr**)

`z: (compilation "name" - a-addr xt; run-time z -)` gforth-1.0 “w-colon”

Define value-flavoured complex local *name* (-- **z1**)

`XT: (compilation "name" - a-addr xt; run-time xt1 -)` gforth-1.0 “x-t-colon”

Define defer-flavoured cell local *name* (... -- ...)

Note that `|`, `--` and `:}` are not normally in the search order (they are in the vocabulary `locals-types`), and on some Forth systems they may not even be words (and the standard documents them under `{:`, not as separate word). `}` is also in `locals-types`.

6.25.1.2 Where are locals visible by name?

Basically, the answer is that locals are visible where you would expect it in block-structured languages, and sometimes a little longer. If you want to restrict the scope of a local, enclose its definition in `SCOPE...ENDSCOPE`.

`scope` (*compilation* – *scope* ; *run-time* –) gforth-0.2 “scope”

`endscope` (*compilation* *scope* – ; *run-time* –) gforth-0.2 “endscope”

These words behave like control structure words, so you can use them with `CS-PICK` and `CS-ROLL` to restrict the scope in arbitrary ways.

If you want a more exact answer to the visibility question, here’s the basic principle: A local is visible in all places that can only be reached through the definition of the local²⁵. In other words, it is not visible in places that can be reached without going through the definition of the local. E.g., locals defined in `IF...THEN` are visible until the `THEN`, locals defined in `BEGIN...UNTIL` are visible after the `UNTIL` (until, e.g., a subsequent `ENDSCOPE`).

The reasoning behind this solution is: We want to have the locals visible as long as it is meaningful. The user can always make the visibility shorter by using explicit scoping. In a place that can only be reached through the definition of a local, the meaning of a local name is clear. In other places it is not: How is the local initialized at the control flow path that does not contain the definition? Which local is meant, if the same name is defined twice in two independent control flow paths?

This should be enough detail for nearly all users, so you can skip the rest of this section. If you really must know all the gory details and options, read on.

In order to implement this rule, the compiler has to know which places are unreachable. It knows this automatically after `AHEAD`, `AGAIN`, `EXIT` and `LEAVE`; in other cases (e.g., after most `THROWS`), you can use the word `UNREACHABLE` to tell the compiler that the control flow never reaches that place. If `UNREACHABLE` is not used where it could, the only consequence is that the visibility of some locals is more limited than the rule above says. If `UNREACHABLE` is used where it should not (i.e., if you lie to the compiler), you can produce code whose behaviour is best determined by looking at the implementation (which may change).

`UNREACHABLE` (–) gforth-0.2 “UNREACHABLE”

Another problem with this rule is that at `BEGIN`, the compiler does not know which locals will be visible on the incoming back-edge. All problems discussed in the following are due to this ignorance of the compiler (we discuss the problems using `BEGIN` loops as examples; the discussion also applies to `?DO` and other loops). Perhaps the most insidious example is:

```
AHEAD
BEGIN
  x
  [ 1 CS-ROLL ] THEN
    { : x : }
  ...
```

²⁵ In compiler construction terminology, all places dominated by the definition of the local.

UNTIL

This should be legal according to the visibility rule. The use of `x` can only be reached through the definition; but that appears textually below the use.

From this example it is clear that the visibility rules cannot be fully implemented without major headaches. Our implementation treats common cases as advertised and the exceptions are treated in a safe way: The compiler makes a reasonable guess about the locals visible after a **BEGIN**; if it is too pessimistic, the user will get a spurious error about the local not being defined; if the compiler is too optimistic, it will notice this later and issue a warning. In the case above the compiler would complain about `x` being undefined at its use. You can see from the obscure examples in this section that it takes quite unusual control structures to get the compiler into trouble, and even then it will often do fine.

If the **BEGIN** is reachable from above, the most optimistic guess is that all locals visible before the **BEGIN** will also be visible after the **BEGIN**. This guess is valid for all loops that are entered only through the **BEGIN**, in particular, for normal **BEGIN...WHILE...REPEAT** and **BEGIN...UNTIL** loops and it is implemented in our compiler. When the branch to the **BEGIN** is finally generated by **AGAIN** or **UNTIL**, the compiler checks the guess and warns the user if it was too optimistic:

```
IF
  {: x :}
BEGIN
  \ x ?
  [ 1 cs-roll ] THEN
  ...
UNTIL
```

Here, `x` lives only until the **BEGIN**, but the compiler optimistically assumes that it lives until the **THEN**. It notices this difference when it compiles the **UNTIL** and issues a warning. The user can avoid the warning, and make sure that `x` is not used in the wrong area by using explicit scoping:

```
IF
  SCOPE
  {: x :}
  ENDScope
BEGIN
  [ 1 cs-roll ] THEN
  ...
UNTIL
```

Since the guess is optimistic, there will be no spurious error messages about undefined locals.

If the **BEGIN** is not reachable from above (e.g., after **AHEAD** or **EXIT**), the compiler cannot even make an optimistic guess, as the locals visible after the **BEGIN** may be defined later.

It pessimistically assumes that all locals are visible that were visible at the latest place outside any control structure (i.e., where nothing is on the control-flow stack). This means that in:

```
: foo
  IF {: z :} THEN
```

```

{: x :}
AHEAD
  BEGIN
    ( * )
    [ 1 CS-ROLL ] THEN
    {: y :}
    ...
  UNTIL ;

```

At the place marked with (*), *x* is visible, but *y* is not (although, according to the reachability rule it should); *z* is not and should not be visible there.

However, you can use **ASSUME-LIVE** to make the compiler assume that the same locals are visible at the **BEGIN** as at the point where the top control-flow stack item was created.

ASSUME-LIVE (*orig* – *orig*) gforth-0.2 “ASSUME-LIVE”

E.g.,

```

IF
  {: x :}
  AHEAD
    ASSUME-LIVE
    BEGIN
      x
      [ 1 CS-ROLL ] THEN
      ...
    UNTIL
  THEN

```

Here *x* would not be visible at the use of *x*, because its definition is inside a control structure, but by using **ASSUME-LIVE** the programmer tells the compiler that the locals visible at the **AHEAD** should be visible at the **BEGIN**.

Other cases where the locals are defined before the **BEGIN** can be handled by inserting an appropriate **CS-ROLL** before the **ASSUME-LIVE** (and changing the control-flow stack manipulation behind the **ASSUME-LIVE**).

Cases where locals are defined in a **BEGIN** loop and should be visible in that loop before the definition can only be handled by rearranging the loop. E.g., the “most insidious” example above can be arranged into:

```

BEGIN
  {: x :}
  ... 0=
  WHILE
    x
  REPEAT

```

The ideas in this section have also been published in M. Anton Ertl, *Automatic Scoping of Local Variables* (<https://www.complang.tuwien.ac.at/papers/ertl1941.ps.gz>), EuroForth '94.

6.25.1.3 How long do locals live?

The right answer for the lifetime question would be: A local lives at least as long as it can be accessed. For a regular value-flavoured local this means: until the end of its visibility. However, an addressable value-flavoured or variable-flavoured local could be accessed through its address far beyond its visibility scope. Ultimately, this would mean that such locals would have to be garbage collected. Since this entails un-Forth-like implementation complexities, we adopted the same cowardly solution as some other languages (e.g., C): The local lives only as long as it is visible; afterwards its address is invalid (and programs that access it afterwards are erroneous).

6.25.1.4 Locals programming style

The freedom to define locals anywhere has the potential to change programming styles dramatically. In particular, the need to use the return stack for intermediate storage vanishes. Moreover, all stack manipulations (except PICKs and ROLLs with run-time determined arguments) can be eliminated: If the stack items are in the wrong order, just write a locals definition for all of them; then write the items in the order you want.

This seems a little far-fetched and eliminating stack manipulations is unlikely to become a conscious programming objective. Still, the number of stack manipulations will be reduced dramatically if local variables are used liberally (e.g., compare `max` (see `<undefined>` [Gforth locals], page `<undefined>`) with a traditional implementation of `max`).

This shows one potential benefit of locals: making Forth programs more readable. Of course, this benefit will only be realized if the programmers continue to honour the principle of factoring instead of using the added latitude to make the words longer.

Using `T0` can and should be avoided. Without `T0`, every value-flavoured local has only a single assignment and many advantages of functional languages apply to Forth. I.e., programs are easier to analyse, to optimize and to read: It is clear from the definition what the local stands for, it does not turn into something different later.

E.g., a definition using `T0` might look like this:

```
: strcmp { addr1 u1 addr2 u2 -- n :}
  u1 u2 min 0
  ?do
    addr1 c@ addr2 c@ -
    ?dup-if
    unloop exit
  then
    addr1 char+ T0 addr1
    addr2 char+ T0 addr2
  loop
  u1 u2 - ;
```

Here, `T0` is used to update `addr1` and `addr2` at every loop iteration. `strcmp` is a typical example of the readability problems of using `T0`. When you start reading `strcmp`, you think that `addr1` refers to the start of the string. Only near the end of the loop you realize that it is something else.

This can be avoided by defining two locals at the start of the loop that are initialized with the right value for the current iteration.

```

: strcmp { : addr1 u1 addr2 u2 -- n : }
  addr1 addr2
  u1 u2 min 0
  ?do { : s1 s2 : }
    s1 c@ s2 c@ -
    ?dup-if
    unloop exit
  then
  s1 char+ s2 char+
loop
2drop
u1 u2 - ;

```

Here it is clear from the start that `s1` has a different value in every loop iteration.

6.25.1.5 Locals implementation

Gforth uses an extra locals stack. The most compelling reason for this is that the return stack is not float-aligned; using an extra stack also eliminates the problems and restrictions of using the return stack as locals stack. Like the other stacks, the locals stack grows toward lower addresses. A few primitives allow an efficient implementation; you should not use them directly, but they appear in the output of `see`, so they are documented here:

```

@localn ( noffset - w ) gforth-internal "fetch-local-n"
f@localn ( noffset - r ) gforth-1.0 "f-fetch-local-n"
!localn ( w noffset - ) gforth-internal "store-local-n"
lp+n ( noffset - c-addr ) gforth-internal "lp-plus-n"
lp+! ( noffset - ) gforth-1.0 "lp-plus-store"

```

When used with negative *noffset* allocates memory on the local stack; when used with a positive *noffset* drops memory from the local stack

```

lp! ( c-addr - ) gforth-internal "lp-store"
>1 ( w - ) gforth-0.2 "to-l"
f>1 ( r - ) gforth-0.2 "f-to-l"

```

See also `lp@` (see `<undefined>` [Stack pointer manipulation], page `<undefined>`).

In addition to these primitives, some specializations of these primitives for commonly occurring inline arguments are provided for efficiency reasons, e.g., `@local0` as specialization of `0 @localn`.

Combinations of conditional branches and `lp+!#` like `?branch-lp+!#` (the locals pointer is only changed if the branch is taken) are provided for efficiency and correctness in loops.

A special area in the dictionary space is reserved for keeping the local variable names. `{:` switches the dictionary pointer to this area and `:}` switches it back and generates the locals initializing code. `W:` etc. are normal defining words. This special area is cleared at the start of every colon definition.

A special feature of Gforth's dictionary is used to implement the definition of locals without type specifiers: every word list (aka vocabulary) has its own methods for searching etc. (see `<undefined>` [Word Lists], page `<undefined>`). For the present purpose we defined a

word list with a special search method: When it is searched for a word, it actually creates that word using `W:`. `{:` changes the search order to first search the word list containing `}`, `W:` etc., and then the word list for defining locals without type specifiers. This implementation was designed before Gforth acquired recognizers; for a reimplementaion we would use recognizers.

The lifetime rules support a stack discipline within a colon definition: The lifetime of a local is either nested with other locals lifetimes or it does not overlap them.

At `BEGIN`, `IF`, and `AHEAD` no code for locals stack pointer manipulation is generated. Between control structure words locals definitions can push locals onto the locals stack. `AGAIN` is the simplest of the other three control flow words. It has to restore the locals stack depth of the corresponding `BEGIN` before branching. The code looks like this:

```
current-locals-size dest-locals-size - 1p+!  
branch <begin>
```

`UNTIL` is a little more complicated: If it branches back, it must adjust the stack just like `AGAIN`. But if it falls through, the locals stack must not be changed. The compiler generates the following code:

```
?branch-1p+!# <begin> current-locals-size - dest-locals-size
```

The locals stack pointer is only adjusted if the branch is taken.

`THEN` can produce somewhat inefficient code:

```
current-locals-size dest-locals-size - 1p+!  
<orig target>:  
orig-locals-size new-locals-size - 1p+!
```

The second `1p+!#` adjusts the locals stack pointer from the level at the *orig* point to the level after the `THEN`. The first `1p+!#` adjusts the locals stack pointer from the current level to the level at the *orig* point, so the complete effect is an adjustment from the current level to the right level after the `THEN`. This effect happens e.g., if there is an `ELSE` and the code before the `ELSE` defines locals, and they have a different size than those after the `ELSE`. In general we recommend not to work around this shortcoming (except in performance-critical code). We intend to eliminate this shortcoming at some point.

In a conventional Forth implementation a *dest* control-flow stack entry is just the target address and an *orig* entry is just the address to be patched. Our locals implementation adds a word list to every *orig* or *dest* item. It is the list of locals visible (or assumed visible) at the point described by the entry. Our implementation also adds a tag to identify the kind of entry, in particular to differentiate between live and dead (reachable and unreachable) *orig* entries.

A few unusual operations have to be performed on locals word lists:

```
common-list ( list1 list2 - list3 ) gforth-internal "common-list"  
sub-list? ( list1 list2 - f ) gforth-internal "sub-list?"  
list-size ( list - u ) gforth-internal "list-size"
```

Several features of our locals word list implementation make these operations easy to implement: The locals word lists are organised as linked lists; the tails of these lists are shared, if the lists contain some of the same locals; and the address of a name is greater than the address of the names behind it in the list.

Another important implementation detail is the variable **dead-code**. It is used by **BEGIN** and **THEN** to determine if they can be reached directly or only through the branch that they resolve. **dead-code** is set by **UNREACHABLE**, **AHEAD**, **EXIT** etc., and cleared at the start of a colon definition, by **BEGIN** and usually by **THEN**.

Counted loops are similar to other loops in most respects, but **LEAVE** requires special attention: It performs basically the same service as **AHEAD**, but it does not create a control-flow stack entry. Therefore the information has to be stored elsewhere; traditionally, the information was stored in the target fields of the branches created by the **LEAVEs**, by organizing these fields into a linked list. Unfortunately, this clever trick does not provide enough space for storing our extended control flow information. Therefore, we introduce another stack, the leave stack. It contains the control-flow stack entries for all unresolved **LEAVEs**.

Local names are kept until the end of the colon definition, even if they are no longer visible in any control-flow path. In a few cases this may lead to increased space needs for the locals name area, but usually less than reclaiming this space would cost in code size.

6.25.2 Standard Forth locals

The Forth-2012 standard defines a syntax for locals is restricted version of Gforth's locals:

- Locals can only be cell-sized values (no type specifiers are allowed).
- Locals can be defined only outside control structures.
- Only one locals definition is allowed per colon definition.
- Locals can interfere with explicit usage of the return stack. For the exact (and long) rules, see the standard. If you don't use return stack accessing words in a definition using locals, you will be all right. The purpose of this rule is to make locals implementation on the return stack easier.
- The whole locals definition must be in one line.

The Standard Forth locals wordset itself consists of two words: **{:** and:

(local) (*addr u -*) local “paren-local-paren”

The Forth-2012 locals extension wordset also defines a syntax using **locals|**, but it is so awful that we strongly recommend not to use it and another, better syntax (the one using **{:** was standardized). We have implemented this syntax to make porting to Gforth easy, but do not document it here. The problem with this syntax is that the locals are defined in an order reversed with respect to the standard stack comment notation, making programs harder to read, and easier to misread and miswrite.

6.26 Object-oriented Forth

Gforth comes with three packages for object-oriented programming: **objects.fs**, **oof.fs**, and **mini-oof.fs**; none of them is preloaded, so you have to **include** them before use. The most important differences between these packages (and others) are discussed in [\(undefined\)](#) [Comparison with other object models], page [\(undefined\)](#). All packages are written in Standard Forth and can be used with any other Standard Forth.

6.26.1 Why object-oriented programming?

Often we have to deal with several data structures (*objects*), that have to be treated similarly in some respects, but differently in others. Graphical objects are the textbook example:

circles, triangles, dinosaurs, icons, and others, and we may want to add more during program development. We want to apply some operations to any graphical object, e.g., **draw** for displaying it on the screen. However, **draw** has to do something different for every kind of object.

We could implement **draw** as a big CASE control structure that executes the appropriate code depending on the kind of object to be drawn. This would be not be very elegant, and, moreover, we would have to change **draw** every time we add a new kind of graphical object (say, a spaceship).

What we would rather do is: When defining spaceships, we would tell the system: “Here’s how you **draw** a spaceship; you figure out the rest”.

This is the problem that all systems solve that (rightfully) call themselves object-oriented; the object-oriented packages presented here solve this problem (and not much else).

6.26.2 Object-Oriented Terminology

This section is mainly for reference, so you don’t have to understand all of it right away. The terminology is mainly Smalltalk-inspired. In short:

<i>class</i>	a data structure definition with some extras.
<i>object</i>	an instance of the data structure described by the class definition.
<i>instance variables</i>	fields of the data structure.
<i>selector</i>	(or <i>method selector</i>) a word (e.g., draw) that performs an operation on a variety of data structures (classes). A selector describes <i>what</i> operation to perform. In C++ terminology: a (pure) virtual function.
<i>method</i>	the concrete definition that performs the operation described by the selector for a specific class. A method specifies <i>how</i> the operation is performed for a specific class.
<i>selector invocation</i>	a call of a selector. One argument of the call (the TOS (top-of-stack)) is used for determining which method is used. In Smalltalk terminology: a message (consisting of the selector and the other arguments) is sent to the object.
<i>receiving object</i>	the object used for determining the method executed by a selector invocation. In the objects.fs model, it is the object that is on the TOS when the selector is invoked. (<i>Receiving</i> comes from the Smalltalk <i>message</i> terminology.)
<i>child class</i>	a class that has (<i>inherits</i>) all properties (instance variables, selectors, methods) from a <i>parent class</i> . In Smalltalk terminology: The subclass inherits from the superclass. In C++ terminology: The derived class inherits from the base class.

6.26.3 The **objects.fs** model

This section describes the **objects.fs** package. This material also has been published in M. Anton Ertl, *Yet Another Forth Objects Package*

(<https://www.complang.tuwien.ac.at/forth/objects/objects.html>), Forth Dimensions 19(2), pages 37–43.

This section assumes that you have read [\[Structures\]](#), page [\[undefined\]](#).

The techniques on which this model is based have been used to implement the parser generator, Gray, and have also been used in Gforth for implementing the various flavours of word lists (hashed or not, case-sensitive or not, special-purpose word lists for locals etc.).

Marcel Hendrix provided helpful comments on this section.

6.26.3.1 Properties of the `objects.fs` model

- It is straightforward to pass objects on the stack. Passing selectors on the stack is a little less convenient, but possible.
- Objects are just data structures in memory, and are referenced by their address. You can create words for objects with normal defining words like `constant`. Likewise, there is no difference between instance variables that contain objects and those that contain other data.
- Late binding is efficient and easy to use.
- It avoids parsing, and thus avoids problems with state-smartness and reduced extensibility; for convenience there are a few parsing words, but they have non-parsing counterparts. There are also a few defining words that parse. This is hard to avoid, because all standard defining words parse (except `:noname`); however, such words are not as bad as many other parsing words, because they are not state-smart.
- It does not try to incorporate everything. It does a few things and does them well (IMO). In particular, this model was not designed to support information hiding (although it has features that may help); you can use a separate package for achieving this.
- It is layered; you don't have to learn and use all features to use this model. Only a few features are necessary (see [\[Basic Objects Usage\]](#), page [\[undefined\]](#), see [\[The Objects base class\]](#), page [\[undefined\]](#), see [\[Creating objects\]](#), page [\[undefined\]](#).), the others are optional and independent of each other.
- An implementation in Standard Forth is available.

6.26.3.2 Basic `objects.fs` Usage

You can define a class for graphical objects like this:

```
object class \ "object" is the parent class
  selector draw ( x y graphical -- )
end-class graphical
```

This code defines a class `graphical` with an operation `draw`. We can perform the operation `draw` on any `graphical` object, e.g.:

```
100 100 t-rex draw
```

where `t-rex` is a word (say, a constant) that produces a graphical object.

How do we create a graphical object? With the present definitions, we cannot create a useful graphical object. The class `graphical` describes graphical objects in general, but not any concrete graphical object type (C++ users would call it an *abstract class*); e.g., there is no method for the selector `draw` in the class `graphical`.

For concrete graphical objects, we define child classes of the class `graphical`, e.g.:

```
graphical class \ "graphical" is the parent class
  cell% field circle-radius

:noname ( x y circle -- )
  circle-radius @ draw-circle ;
overrides draw

:noname ( n-radius circle -- )
  circle-radius ! ;
overrides construct

end-class circle
```

Here we define a class `circle` as a child of `graphical`, with field `circle-radius` (which behaves just like a field (see `<undefined>` [Structures], page `<undefined>`)); it defines (using `overrides`) new methods for the selectors `draw` and `construct` (`construct` is defined in `object`, the parent class of `graphical`).

Now we can create a circle on the heap (i.e., allocated memory) with:

```
50 circle heap-new constant my-circle
```

`heap-new` invokes `construct`, thus initializing the field `circle-radius` with 50. We can draw this new circle at (100,100) with:

```
100 100 my-circle draw
```

Note: You can only invoke a selector if the object on the TOS (the receiving object) belongs to the class where the selector was defined or one of its descendents; e.g., you can invoke `draw` only for objects belonging to `graphical` or its descendents (e.g., `circle`). Immediately before `end-class`, the search order has to be the same as immediately after `class`.

6.26.3.3 The `object.fs` base class

When you define a class, you have to specify a parent class. So how do you start defining classes? There is one class available from the start: `object`. It is ancestor for all classes and so is the only class that has no parent. It has two selectors: `construct` and `print`.

6.26.3.4 Creating objects

You can create and initialize an object of a class on the heap with `heap-new` (... class – object) and in the dictionary (allocation with `allot`) with `dict-new` (... class – object). Both words invoke `construct`, which consumes the stack items indicated by "..." above.

If you want to allocate memory for an object yourself, you can get its alignment and size with `class-inst-size 2@` (class – align size). Once you have memory for an object, you can initialize it with `init-object` (... class object –); `construct` does only a part of the necessary work.

6.26.3.5 Object-Oriented Programming Style

This section is not exhaustive.

In general, it is a good idea to ensure that all methods for the same selector have the same stack effect: when you invoke a selector, you often have no idea which method will be invoked, so, unless all methods have the same stack effect, you will not know the stack effect of the selector invocation.

One exception to this rule is methods for the selector `construct`. We know which method is invoked, because we specify the class to be constructed at the same place. Actually, I defined `construct` as a selector only to give the users a convenient way to specify initialization. The way it is used, a mechanism different from selector invocation would be more natural (but probably would take more code and more space to explain).

6.26.3.6 Class Binding

Normal selector invocations determine the method at run-time depending on the class of the receiving object. This run-time selection is called *late binding*.

Sometimes it's preferable to invoke a different method. For example, you might want to use the simple method for `printing objects` instead of the possibly long-winded `print` method of the receiver class. You can achieve this by replacing the invocation of `print` with:

```
[bind] object print
```

in compiled code or:

```
bind object print
```

in interpreted code. Alternatively, you can define the method with a name (e.g., `print-object`), and then invoke it through the name. Class binding is just a (often more convenient) way to achieve the same effect; it avoids name clutter and allows you to invoke methods directly without naming them first.

A frequent use of class binding is this: When we define a method for a selector, we often want the method to do what the selector does in the parent class, and a little more. There is a special word for this purpose: `[parent]; [parent] selector` is equivalent to `[bind] parent selector`, where *parent* is the parent class of the current class. E.g., a method definition might look like:

```
:noname
  dup [parent] foo \ do parent's foo on the receiving object
  ... \ do some more
; overrides foo
```

In *Object-oriented programming in ANS Forth* (Forth Dimensions, March 1997), Andrew McKewan presents class binding as an optimization technique. I recommend not using it for this purpose unless you are in an emergency. Late binding is pretty fast with this model anyway, so the benefit of using class binding is small; the cost of using class binding where it is not appropriate is reduced maintainability.

While we are at programming style questions: You should bind selectors only to ancestor classes of the receiving object. E.g., say, you know that the receiving object is of class `foo` or its descendents; then you should bind only to `foo` and its ancestors.

6.26.3.7 Method conveniences

In a method you usually access the receiving object pretty often. If you define the method as a plain colon definition (e.g., with `:noname`), you may have to do a lot of stack gymnastics.

To avoid this, you can define the method with `m: ... ;m`. E.g., you could define the method for drawing a circle with

```
m: ( x y circle -- )
  ( x y ) this circle-radius @ draw-circle ;m
```

When this method is executed, the receiver object is removed from the stack; you can access it with `this` (admittedly, in this example the use of `m: ... ;m` offers no advantage). Note that I specify the stack effect for the whole method (i.e. including the receiver object), not just for the code between `m:` and `;m`. You cannot use `exit` in `m:...;m`; instead, use `exitm`.²⁶

You will frequently use sequences of the form `this field` (in the example above: `this circle-radius`). If you use the field only in this way, you can define it with `inst-var` and eliminate the `this` before the field name. E.g., the `circle` class above could also be defined with:

```
graphical class
  cell% inst-var radius

m: ( x y circle -- )
  radius @ draw-circle ;m
overrides draw

m: ( n-radius circle -- )
  radius ! ;m
overrides construct

end-class circle
```

`radius` can only be used in `circle` and its descendent classes and inside `m:...;m`.

You can also define fields with `inst-value`, which is to `inst-var` what `value` is to `variable`. You can change the value of such a field with `[to-inst]`. E.g., we could also define the class `circle` like this:

```
graphical class
  inst-value radius

m: ( x y circle -- )
  radius draw-circle ;m
overrides draw

m: ( n-radius circle -- )
  [to-inst] radius ;m
overrides construct

end-class circle
```

²⁶ Moreover, for any word that calls `catch` and was defined before loading `objects.fs`, you have to redefine it like I redefined `catch`: `: catch this >r catch r> to-this ;`

6.26.3.8 Classes and Scoping

Inheritance is frequent, unlike structure extension. This exacerbates the problem with the field name convention (see [\[Standard Structures\]](#), page [\[Standard Structures\]](#)): One always has to remember in which class the field was originally defined; changing a part of the class structure would require changes for renaming in otherwise unaffected code.

To solve this problem, I added a scoping mechanism (which was not in my original charter): A field defined with `inst-var` (or `inst-value`) is visible only in the class where it is defined and in the descendent classes of this class. Using such fields only makes sense in `m:-`defined methods in these classes anyway.

This scoping mechanism allows us to use the unadorned field name, because name clashes with unrelated words become much less likely.

Once we have this mechanism, we can also use it for controlling the visibility of other words: All words defined after `protected` are visible only in the current class and its descendents. `public` restores the compilation (i.e. `current`) word list that was in effect before. If you have several `protecteds` without an intervening `public` or `set-current`, `public` will restore the compilation word list in effect before the first of these `protecteds`.

6.26.3.9 Dividing classes

You may want to do the definition of methods separate from the definition of the class, its selectors, fields, and instance variables, i.e., separate the implementation from the definition. You can do this in the following way:

```
graphical class
  inst-value radius
end-class circle

... \ do some other stuff

circle methods \ now we are ready

m: ( x y circle -- )
  radius draw-circle ;m
overrides draw

m: ( n-radius circle -- )
  [to-inst] radius ;m
overrides construct

end-methods
```

You can use several `methods...end-methods` sections. The only things you can do to the class in these sections are: defining methods, and overriding the class's selectors. You must not define new selectors or fields.

Note that you often have to override a selector before using it. In particular, you usually have to override `construct` with a new method before you can invoke `heap-new` and friends. E.g., you must not create a circle before the `overrides construct` sequence in the example above.

6.26.3.10 Object Interfaces

In this model you can only call selectors defined in the class of the receiving objects or in one of its ancestors. If you call a selector with a receiving object that is not in one of these classes, the result is undefined; if you are lucky, the program crashes immediately.

Now consider the case when you want to have a selector (or several) available in two classes: You would have to add the selector to a common ancestor class, in the worst case to **object**. You may not want to do this, e.g., because someone else is responsible for this ancestor class.

The solution for this problem is interfaces. An interface is a collection of selectors. If a class implements an interface, the selectors become available to the class and its descendents. A class can implement an unlimited number of interfaces. For the problem discussed above, we would define an interface for the selector(s), and both classes would implement the interface.

As an example, consider an interface **storage** for writing objects to disk and getting them back, and a class **foo** that implements it. The code would look like this:

```
interface
  selector write ( file object -- )
  selector read1 ( file object -- )
end-interface storage

bar class
  storage implementation

  ... overrides write
  ... overrides read1
  ...
end-class foo
```

(I would add a word **read** (*file – object*) that uses **read1** internally, but that's beyond the point illustrated here.)

Note that you cannot use **protected** in an interface; and of course you cannot define fields.

In the Neon model, all selectors are available for all classes; therefore it does not need interfaces. The price you pay in this model is slower late binding, and therefore, added complexity to avoid late binding.

6.26.3.11 objects.fs Implementation

An object is a piece of memory, like one of the data structures described with **struct...end-struct**. It has a field **object-map** that points to the method map for the object's class.

The *method map*²⁷ is an array that contains the execution tokens (*xts*) of the methods for the object's class. Each selector contains an offset into a method map.

selector is a defining word that uses **CREATE** and **DOES>**. The body of the selector contains the offset; the **DOES>** action for a class selector is, basically:

```
( object addr ) @ over object-map @ + @ execute
```

²⁷ This is Self terminology; in C++ terminology: virtual function table.

Since **object-map** is the first field of the object, it does not generate any code. As you can see, calling a selector has a small, constant cost.

A class is basically a **struct** combined with a method map. During the class definition the alignment and size of the class are passed on the stack, just as with **structs**, so **field** can also be used for defining class fields. However, passing more items on the stack would be inconvenient, so **class** builds a data structure in memory, which is accessed through the variable **current-interface**. After its definition is complete, the class is represented on the stack by a pointer (e.g., as parameter for a child class definition).

A new class starts off with the alignment and size of its parent, and a copy of the parent's method map. Defining new fields extends the size and alignment; likewise, defining new selectors extends the method map. **overrides** just stores a new *xt* in the method map at the offset given by the selector.

Class binding just gets the *xt* at the offset given by the selector from the class's method map and **compile,s** (in the case of **[bind]**) it.

I implemented **this** as a **value**. At the start of an **m:...;m** method the old **this** is stored to the return stack and restored at the end; and the object on the TOS is stored TO **this**. This technique has one disadvantage: If the user does not leave the method via **;m**, but via **throw** or **exit**, **this** is not restored (and **exit** may crash). To deal with the **throw** problem, I have redefined **catch** to save and restore **this**; the same should be done with any word that can catch an exception. As for **exit**, I simply forbid it (as a replacement, there is **exitm**).

inst-var is just the same as **field**, with a different **DOES>** action:

```
@ this +
```

Similar for **inst-value**.

Each class also has a word list that contains the words defined with **inst-var** and **inst-value**, and its protected words. It also has a pointer to its parent. **class** pushes the word lists of the class and all its ancestors onto the search order stack, and **end-class** drops them.

An interface is like a class without fields, parent and protected words; i.e., it just has a method map. If a class implements an interface, its method map contains a pointer to the method map of the interface. The positive offsets in the map are reserved for class methods, therefore interface map pointers have negative offsets. Interfaces have offsets that are unique throughout the system, unlike class selectors, whose offsets are only unique for the classes where the selector is available (invokable).

This structure means that interface selectors have to perform one indirection more than class selectors to find their method. Their body contains the interface map pointer offset in the class method map, and the method offset in the interface method map. The **does>** action for an interface selector is, basically:

```
( object selector-body )
2dup selector-interface @ ( object selector-body object interface-offset )
swap object-map @ + @ ( object selector-body map )
swap selector-offset @ + @ execute
```

where **object-map** and **selector-offset** are first fields and generate no code.

As a concrete example, consider the following code:

```
interface
  selector if1sel1
  selector if1sel2
end-interface if1

object class
  if1 implementation
  selector cl1sel1
  cell% inst-var cl1iv1

  ' m1 overrides construct
  ' m2 overrides if1sel1
  ' m3 overrides if1sel2
  ' m4 overrides cl1sel2
end-class cl1

create obj1 object dict-new drop
create obj2 cl1 dict-new drop
```

The data structure created by this code (including the data structure for `object`) is shown in the figure (`objects-implementation.eps`), assuming a cell size of 4.

6.26.3.12 `objects.fs` Glossary

`bind (... "class" "selector" - ...)` objects “bind”

Execute the method for *selector* in *class*.

`<bind> (class selector-xt - xt)` objects “<bind>”

xt is the method for the selector *selector-xt* in *class*.

`bind' ("class" "selector" - xt)` objects “bind”

xt is the method for *selector* in *class*.

`[bind] (compile-time: "class" "selector" - ; run-time: ... object - ...)` objects “[bind]”

Compile the method for *selector* in *class*.

`class (parent-class - align offset)` objects “class”

Start a new class definition as a child of *parent-class*. *align offset* are for use by *field* etc.

`class->map (class - map)` objects “class->map”

map is the pointer to *class*’s method map; it points to the place in the map to which the selector offsets refer (i.e., where *object-maps* point to).

`class-inst-size (class - addr)` objects “class-inst-size”

Give the size specification for an instance (i.e. an object) of *class*; used as `class-inst-size 2 (class -- align size)`.

`class-override! (xt sel-xt class-map -)` objects “class-override!”

xt is the new method for the selector *sel-xt* in *class-map*.

`class-previous (class -)` objects “class-previous”

Drop *class*'s wordlists from the search order. No checking is made whether *class*'s wordlists are actually on the search order.

class>order (*class* -) objects “class>order”

Add *class*'s wordlists to the head of the search-order.

construct (... *object* -) objects “construct”

Initialize the data fields of *object*. The method for the class *object* just does nothing: (*object* --).

current' ("*selector*" - *xt*) objects “current”

xt is the method for *selector* in the current class.

[current] (*compile-time*: "*selector*" - ; *run-time*: ... *object* - ...) objects “[current]”

Compile the method for *selector* in the current class.

current-interface (- *addr*) objects “current-interface”

Variable: contains the class or interface currently being defined.

dict-new (... *class* - *object*) objects “dict-new”

allot and initialize an object of class *class* in the dictionary.

end-class (*align offset* "*name*" -) objects “end-class”

name execution: -- **class**

End a class definition. The resulting class is *class*.

end-class-noname (*align offset* - *class*) objects “end-class-noname”

End a class definition. The resulting class is *class*.

end-interface ("*name*" -) objects “end-interface”

name execution: -- **interface**

End an interface definition. The resulting interface is *interface*.

end-interface-noname (- *interface*) objects “end-interface-noname”

End an interface definition. The resulting interface is *interface*.

end-methods (-) objects “end-methods”

Switch back from defining methods of a class to normal mode (currently this just restores the old search order).

exitm (-) objects “exitm”

exit from a method; restore old **this**.

heap-new (... *class* - *object*) objects “heap-new”

allocate and initialize an object of class *class*.

implementation (*interface* -) objects “implementation”

The current class implements *interface*. I.e., you can use all selectors of the interface in the current class and its descendents.

init-object (... *class object* -) objects “init-object”

Initialize a chunk of memory (*object*) to an object of class *class*; then performs **construct**.

inst-value (*align1 offset1* "*name*" - *align2 offset2*) objects “inst-value”

name execution: -- **w**
w is the value of the field *name* in **this** object.

inst-var (*align1 offset1 align size "name" - align2 offset2*) objects “inst-var”

name execution: -- **addr**
addr is the address of the field *name* in **this** object.

interface (-) objects “interface”

Start an interface definition.

m: (- *xt colon-sys; run-time: object* -) objects “m:”

Start a method definition; *object* becomes new **this**.

:m ("*name*" - *xt; run-time: object* -) objects “:m”

Start a named method definition; *object* becomes new **this**. Has to be ended with **;m**.

;m (*colon-sys -; run-time: -*) objects “;m”

End a method definition; restore old **this**.

method (*xt "name" -*) objects “method”

name execution: ... **object** -- ...

Create selector *name* and makes *xt* its method in the current class.

methods (*class -*) objects “methods”

Makes *class* the current class. This is intended to be used for defining methods to override selectors; you cannot define new fields or selectors.

object (- *class*) objects “object”

the ancestor of all classes.

overrides (*xt "selector" -*) objects “overrides”

replace default method for *selector* in the current class with *xt*. **overrides** must not be used during an interface definition.

[parent] (*compile-time: "selector" -; run-time: ... object - ...*) objects “[parent]”

Compile the method for *selector* in the parent of the current class.

print (*object -*) objects “print”

Print the object. The method for the class *object* prints the address of the object and the address of its class.

protected (-) objects “protected”

Set the compilation wordlist to the current class’s wordlist

public (-) objects “public”

Restore the compilation wordlist that was in effect before the last **protected** that actually changed the compilation wordlist.

selector ("*name*" -) objects “selector”

name execution: ... **object** -- ...

Create selector *name* for the current class and its descendents; you can set a method for the selector in the current class with **overrides**.

this (- *object*) objects “this”

the receiving object of the current method (aka active object).

```
<to-inst> ( w xt - ) objects "<to-inst>"
  store w into the field xt in this object.
[to-inst] ( compile-time: "name" - ; run-time: w - ) objects "[to-inst]"
  store w into field name in this object.
to-this ( object - ) objects "to-this"
  Set this (used internally, but useful when debugging).
xt-new ( ... class xt - object ) objects "xt-new"
  Make a new object, using xt ( align size -- addr ) to get memory.
```

6.26.4 The oof.fs model

This section describes the `oof.fs` package.

The package described in this section has been used in bigFORTH since 1991, and used for two large applications: a chromatographic system used to create new medicaments, and a graphic user interface library (MINOS).

You can find a description (in German) of `oof.fs` in *Object oriented bigFORTH* by Bernd Paysan, published in *Vierte Dimension* 10(2), 1994.

6.26.4.1 Properties of the oof.fs model

- This model combines object oriented programming with information hiding. It helps you writing large application, where scoping is necessary, because it provides class-oriented scoping.
- Named objects, object pointers, and object arrays can be created, selector invocation uses the "object selector" syntax. Selector invocation to objects and/or selectors on the stack is a bit less convenient, but possible.
- Selector invocation and instance variable usage of the active object is straightforward, since both make use of the active object.
- Late binding is efficient and easy to use.
- State-smart objects parse selectors. However, extensibility is provided using a (parsing) selector `postpone` and a selector `'`.
- An implementation in Standard Forth is available.

6.26.4.2 Basic oof.fs Usage

This section uses the same example as for `objects` (see `<undefined>` [Basic Objects Usage], page `<undefined>`).

You can define a class for graphical objects like this:

```
object class graphical \ "object" is the parent class
  method draw ( x y -- )
class;
```

This code defines a class `graphical` with an operation `draw`. We can perform the operation `draw` on any `graphical` object, e.g.:

```
100 100 t-rex draw
```


where `t-rex` is an object or object pointer, created with e.g. `graphical : t-rex`.

How do we create a graphical object? With the present definitions, we cannot create a useful graphical object. The class `graphical` describes graphical objects in general, but not any concrete graphical object type (C++ users would call it an *abstract class*); e.g., there is no method for the selector `draw` in the class `graphical`.

For concrete graphical objects, we define child classes of the class `graphical`, e.g.:

```
graphical class circle \ "graphical" is the parent class
  cell var circle-radius
how:
  : draw ( x y -- )
    circle-radius @ draw-circle ;

  : init ( n-radius -- )
    circle-radius ! ;
class;
```

Here we define a class `circle` as a child of `graphical`, with a field `circle-radius`; it defines new methods for the selectors `draw` and `init` (`init` is defined in `object`, the parent class of `graphical`).

Now we can create a circle in the dictionary with:

```
50 circle : my-circle
: invokes init, thus initializing the field circle-radius with 50. We can draw this new
circle at (100,100) with:
100 100 my-circle draw
```

Note: You can only invoke a selector if the receiving object belongs to the class where the selector was defined or one of its descendents; e.g., you can invoke `draw` only for objects belonging to `graphical` or its descendents (e.g., `circle`). The scoping mechanism will check if you try to invoke a selector that is not defined in this class hierarchy, so you'll get an error at compilation time.

6.26.4.3 The `oof.fs` base class

When you define a class, you have to specify a parent class. So how do you start defining classes? There is one class available from the start: `object`. You have to use it as ancestor for all classes. It is the only class that has no parent. Classes are also objects, except that they don't have instance variables; class manipulation such as inheritance or changing definitions of a class is handled through selectors of the class `object`.

`object` provides a number of selectors:

- `class` for subclassing, `definitions` to add definitions later on, and `class?` to get type informations (is the class a subclass of the class passed on the stack?).

```
object-class ( "name" - ) oof "object-class"
object-definitions ( - ) oof "object-definitions"
object-class? ( o - flag ) oof "class-query"
```
- `init` and `dispose` as constructor and destructor of the object. `init` is invoked after the object's memory is allocated, while `dispose` also handles deallocation. Thus if you redefine `dispose`, you have to call the parent's `dispose` with `super dispose`, too.

- `object-init (... -)` oof “object-init”
- `object-dispose (-)` oof “object-dispose”
- `new`, `new[]`, `:`, `ptr`, `asptr`, and `[]` to create named and unnamed objects and object arrays or object pointers.
 - `object-new (- o)` oof “object-new”
 - `object-new[] (n - o)` oof “new-array”
 - `object-: ("name" -)` oof “define”
 - `object-ptr ("name" -)` oof “object-ptr”
 - `object-asptr (o "name" -)` oof “object-asptr”
 - `object-[] (n "name" -)` oof “array”
- `::` and `super` for explicit scoping. You should use explicit scoping only for super classes or classes with the same set of instance variables. Explicitly-scoped selectors use early binding.
 - `object-:: ("name" -)` oof “scope”
 - `object-super ("name" -)` oof “object-super”
- `self` to get the address of the object
 - `object-self (- o)` oof “object-self”
- `bind`, `bound`, `link`, and `is` to assign object pointers and instance defers.
 - `object-bind (o "name" -)` oof “object-bind”
 - `object-bound (class addr "name" -)` oof “object-bound”
 - `object-link ("name" - class addr)` oof “object-link”
 - `object-is (xt "name" -)` oof “object-is”
- `'` to obtain selector tokens, `send` to invoke selectors from the stack, and `postpone` to generate selector invocation code.
 - `object-' ("name" - xt)` oof “tick”
 - `object-postpone ("name" -)` oof “object-postpone”
- `with` and `endwith` to select the active object from the stack, and enable its scope. Using `with` and `endwith` also allows you to create code using selector `postpone` without being trapped by the state-smart objects.
 - `object-with (o -)` oof “object-with”
 - `object-endwith (-)` oof “object-endwith”

6.26.4.4 Class Declaration

- Instance variables
 - `var (size -)` oof “var”
 - Create an instance variable
- Object pointers
 - `ptr (-)` oof “ptr”
 - Create an instance pointer
 - `asptr (class -)` oof “asptr”
 - Create an alias to an instance pointer, cast to another class.

- Instance defers
`defer (-) oof "defer"`
 Create an instance defer
- Method selectors
`early (-) oof "early"`
 Create a method selector for early binding.
`method (-) oof "method"`
 Create a method selector.
- Class-wide variables
`static (-) oof "static"`
 Create a class-wide cell-sized variable.
- End declaration
`how: (-) oof "how-to"`
 End declaration, start implementation
`class; (-) oof "end-class"`
 End class declaration or implementation

6.26.5 The mini-oof.fs model

Gforth's third object oriented Forth package is a 12-liner. It uses a mixture of the `objects.fs` and the `oof.fs` syntax, and reduces to the bare minimum of features. This is based on a posting of Bernd Paysan in `comp.lang.forth`.

6.26.5.1 Basic mini-oof.fs Usage

There is a base class (`class`, which allocates one cell for the object pointer) plus seven other words: to define a method, a variable, a class; to end a class, to resolve binding, to allocate an object and to compile a class method.

`object (- a-addr) mini-oof "object"`

object is the base class of all objects.

`method (m v "name" - m' v') mini-oof2 "method"`

Define a selector *name*; increments the number of selectors *m* (in bytes).

`var (m v size "name" - m v') mini-oof2 "var"`

define an instance variable with *size* bytes by the name *name*, and increments the amount of storage per instance *m* by *size*.

`class (class - class methods vars) mini-oof2 "class"`

start a class definition with superclass *class*, putting the size of the methods table and instance variable space on the stack.

`end-class (class methods vars "name" -) mini-oof2 "end-class"`

finishes a class definition and assigns a name *name* to the newly created class. Inherited methods are copied from the superclass.

`defines (xt class "name" -) mini-oof "defines"`

Bind *xt* to the selector *name* in class *class*.

```
new ( class - o ) mini-oof "new"
```

Create a new incarnation of the class *class*.

```
:: ( class "name" - ) mini-oof "colon-colon"
```

Compile the method for the selector *name* of the class *class* (not immediate!).

6.26.5.2 Mini-OOF Example

A short example shows how to use this package. This example, in slightly extended form, is supplied as `moof-exm.fs`

```
object class
  method init
  method draw
end-class graphical
```

This code defines a class `graphical` with an operation `draw`. We can perform the operation `draw` on any `graphical` object, e.g.:

```
100 100 t-rex draw
```

where `t-rex` is an object or object pointer, created with e.g. `graphical new Constant t-rex`.

For concrete graphical objects, we define child classes of the class `graphical`, e.g.:

```
graphical class
  cell var circle-radius
end-class circle \ "graphical" is the parent class

:noname ( x y -- )
  circle-radius @ draw-circle ; circle defines draw
:noname ( r -- )
  circle-radius ! ; circle defines init
```

There is no implicit `init` method, so we have to define one. The creation code of the object now has to call `init` explicitly.

```
circle new Constant my-circle
50 my-circle init
```

It is also possible to add a function to create named objects with automatic call of `init`, given that all objects have `init` on the same place:

```
: new: ( .. o "name" -- )
  new dup Constant init ;
80 circle new: large-circle
```

We can draw this new circle at (100,100) with:

```
100 100 my-circle draw
```

6.26.5.3 mini-oof.fs Implementation

Object-oriented systems with late binding typically use a “vtable”-approach: the first variable in each object is a pointer to a table, which contains the methods as function pointers. The vtable may also contain other information.

So first, let's declare selectors:

```
: method ( m v "name" -- m' v ) Create over , swap cell+ swap
DOES> ( ... o -- ... ) @ over @ + @ execute ;
```

During selector declaration, the number of selectors and instance variables is on the stack (in address units). `method` creates one selector and increments the selector number. To execute a selector, it takes the object, fetches the vtable pointer, adds the offset, and executes the method *xt* stored there. Each selector takes the object it is invoked with as top of stack parameter; it passes the parameters (including the object) unchanged to the appropriate method which should consume that object.

Now, we also have to declare instance variables

```
: var ( m v size "name" -- m v' ) Create over , +
DOES> ( o -- addr ) @ + ;
```

As before, a word is created with the current offset. Instance variables can have different sizes (cells, floats, doubles, chars), so all we do is take the size and add it to the offset. If your machine has alignment restrictions, put the proper `aligned` or `faligned` before the variable, to adjust the variable offset. That's why it is on the top of stack.

We need a starting point (the base object) and some syntactic sugar:

```
Create object 1 cells , 2 cells ,
: class ( class -- class selectors vars ) dup 2@ ;
```

For inheritance, the vtable of the parent object has to be copied when a new, derived class is declared. This gives all the methods of the parent class, which can be overridden, though.

```
: end-class ( class selectors vars "name" -- )
Create here >r , dup , 2 cells ?DO ['] noop , 1 cells +LOOP
cell+ dup cell+ r> rot @ 2 cells /string move ;
```

The first line creates the vtable, initialized with noops. The second line is the inheritance mechanism, it copies the xts from the parent vtable.

We still have no way to define new methods, let's do that now:

```
: defines ( xt class "name" -- ) ' >body @ + ! ;
```

To allocate a new object, we need a word, too:

```
: new ( class -- o ) here over @ allot swap over ! ;
```

Sometimes derived classes want to access the method of the parent object. There are two ways to achieve this with Mini-OOF: first, you could use named words, and second, you could look up the vtable of the parent object.

```
: :: ( class "name" -- ) ' >body @ + @ compile, ;
```

Nothing can be more confusing than a good example, so here is one. First let's declare a text object (called `button`), that stores text and position:

```
object class
cell var text
cell var len
cell var x
cell var y
method init
```

```

    method draw
end-class button

```

Now, implement the two methods, `draw` and `init`:

```

:noname ( o -- )
  >r r@ x @ r@ y @ at-xy  r@ text @ r> len @ type ;
  button defines draw
:noname ( addr u o -- )
  >r 0 r@ x ! 0 r@ y ! r@ len ! r> text ! ;
  button defines init

```

To demonstrate inheritance, we define a class `bold-button`, with no new data and no new selectors:

```

button class
end-class bold-button

: bold 27 emit ." [1m" ;
: normal 27 emit ." [0m" ;

```

The class `bold-button` has a different `draw` method to `button`, but the new method is defined in terms of the `draw` method for `button`:

```

:noname bold [ button :: draw ] normal ; bold-button defines draw

```

Finally, create two objects and apply selectors:

```

button new Constant foo
s" thin foo" foo init
page
foo draw
bold-button new Constant bar
s" fat bar" bar init
1 bar y !
bar draw

```

6.26.6 Mini-OOF2

Mini-OOF2 is very similar to Mini-OOF in many respects, but differs significantly in a few aspects. In particular, Mini-OOF2 has a current object variable, and uses the primitives `>o` and `o>` to manipulate that object stack. All method invocations and instance variable accesses refer to the current object.

```
>o ( c-addr – r:c-old ) new “to-o”
```

Set the current object to `c-addr`, the previous current object is pushed to the return stack

```
o> ( r:c-addr – ) new “o-restore”
```

Restore the previous current object from the return stack

To ease passing an object pointer to method invocation or instance variable accesses, the additional recognizer `rec-moof2` is activated.

```
rec-moof2 ( addr u – xt translate-moof2 | 0 ) mini-oof2 “rec-moof2”
```

Very simplistic dot-parser, transforms `.selector/ivar` to `>o selector/ivar o>`.

To assign methods to selectors, use `xt class is selector`, so no `defines` necessary. For early binding of methods, `[class] defers selector` is used, no need for `::`. Instead of writing `:noname code ; class is selector`, you can also use the syntactic sugar `class :method selector code ;`.

```
:method ( class "name" - ) gforth-experimental ":method"
```

define a noname that is assigned to the deferred word *name* in *class* at `;`.

6.26.7 Comparison with other object models

Many object-oriented Forth extensions have been proposed (*A survey of object-oriented Forths* (SIGPLAN Notices, April 1996) by Bradford J. Rodriguez and W. F. S. Poehlman lists 17). This section discusses the relation of the object models described here to two well-known and two closely-related (by the use of method maps) models. Andras Zsoter helped us with this section.

The most popular model currently seems to be the Neon model (see *Object-oriented programming in ANS Forth* (Forth Dimensions, March 1997) by Andrew McKewan) but this model has a number of limitations²⁸:

- It uses a *selector object* syntax, which makes it unnatural to pass objects on the stack.
- It requires that the selector parses the input stream (at compile time); this leads to reduced extensibility and to bugs that are hard to find.
- It allows using every selector on every object; this eliminates the need for interfaces, but makes it harder to create efficient implementations.

Another well-known publication is *Object-Oriented Forth* (Academic Press, London, 1987) by Dick Pountain. However, it is not really about object-oriented programming, because it hardly deals with late binding. Instead, it focuses on features like information hiding and overloading that are characteristic of modular languages like Ada (83).

In Does late binding have to be slow? (<http://www.forth.org/oopf.html>) (Forth Dimensions 18(1) 1996, pages 31-35) Andras Zsoter describes a model that makes heavy use of an active object (like `this` in `objects.fs`): The active object is not only used for accessing all fields, but also specifies the receiving object of every selector invocation; you have to change the active object explicitly with `{ ... }`, whereas in `objects.fs` it changes more or less implicitly at `m: ... ;m`. Such a change at the method entry point is unnecessary with Zsoter's model, because the receiving object is the active object already. On the other hand, the explicit change is absolutely necessary in that model, because otherwise no one could ever change the active object. An Standard Forth implementation of this model is available through <http://www.forth.org/oopf.html>.

The `oof.fs` model combines information hiding and overloading resolution (by keeping names in various word lists) with object-oriented programming. It sets the active object implicitly on method entry, but also allows explicit changing (with `>o...o>` or with `with...endwith`). It uses parsing and state-smart objects and classes for resolving overloading and for early binding: the object or class parses the selector and determines the method from this. If the selector is not parsed by an object or class, it performs a call

²⁸ A longer version of this critique can be found in *On Standardizing Object-Oriented Forth Extensions* (Forth Dimensions, May 1997) by Anton Ertl.

to the selector for the active object (late binding), like Zsoter's model. Fields are always accessed through the active object. The big disadvantage of this model is the parsing and the state-smartness, which reduces extensibility and increases the opportunities for subtle bugs; essentially, you are only safe if you never tick or **postpone** an object or class (Bernd disagrees, but I (Anton) am not convinced).

The `mini-oof.fs` model is quite similar to a very stripped-down version of the `objects.fs` model, but syntactically it is a mixture of the `objects.fs` and `oof.fs` models.

6.27 Closures

Gforth provides flat closures (called closures in the following). Closures are similar to quotations (see `<undefined>` [Quotations], page `<undefined>`), but the execution token (xt) that represents a closure does not just refer to code, but also to data. Running the code of a closure definition creates a closure data structure (also referred to as "closure"), that is represented by an execution token. The closure data structure needs to be allocated somewhere, and in Gforth this memory is managed explicitly.

As an example, consider a word that sums up the results of a function (`n -- r`) across a range of input values:

```
: sum {: limit start xt -- r :}
  0e limit start ?do
    i xt execute f+
  loop ;
```

You can add up the values of the function $1/n$ for $n=1..10$ with:

```
11 1 [: s>f -1e f** ;] sum f.
```

Yes, you can do it shorter and more efficiently with $1/f$, but bear with me. If you want to add up $1/n^2$, you can write

```
11 1 [: s>f -2e f** ;] sum f.
```

Now if you want to deal with additional exponents and these exponents are known at compile time, you can create a new quotation for every exponent. But you may prefer to provide an exponent and produce an xt without having to write down a quotation every time. If the value of the exponent is only known at run-time, producing such an xt is possible in Forth, but even more involved, and consumes dictionary memory (with limited deallocation options). Closures come to the rescue:

```
: 1/n^r ( r -- xt; xt execution: n -- r1 )
  fnegate [f:h ( n -r ) s>f fswap f** ;] ;

11 1 3e 1/n^r dup >r sum f. r> free-closure
11 1 0.5e 1/n^r dup >r sum f. r> free-closure
```

When $1/n^r$ runs, it creates a closure that incorporates a floating-point number (indicated by the `f` in `[f:h]`), in particular the value `-r`. It also references the code between `[f:h` and `;`. The memory for the closure comes from the heap, i.e. **allocated** memory (indicated by the `h` in `[f:h]`). $1/n^r$ produces an xt representing this closure. This xt is then passed to `sum` and executed there.

When the closure is executed (in `sum`), `-r` is pushed (in addition to the `n` that has already been pushed before the `execute`) and the code of the closure is run.

The code above shows a pure-stack closure (no locals involved). Pure-stack closures start with a word with the naming scheme `[T:A` where the type `T` can be `n` (cell), `d` (double-cell), or `f` (FP). The allocator `A` can be `l` (local), `d` (dictionary), `h` (heap), or `h1`: `Allocate` the closure on the heap and `free` it after the first execution; this is used for passing data to another task with `send-event` (see `<undefined>` [Message queues], page `<undefined>`). A pure-stack closure consumes one `T` from a stack at closure creation time (when the code containing the closure definition is run), and pushes an `xt`. After creating the closure, execution continues behind the `;`.

When the `xt` is executed (directly with `execute` or indirectly through, e.g., `compile`, or a deferred word), it pushes the stack item that was consumed at closure creation time and then runs the code inside the closure definition (up to the `;`). You can deallocate heap-allocated closures with

```
free-closure ( xt - ) gforth-1.0 “free-closure”
```

Free the heap-allocated closure *xt*.

Like a quotation, a (flat) closure cannot access locals of the enclosing definition(s).

The words for starting pure-stack closure definitions are:

```
[n:l ( compilation - colon-sys; run-time: n - xt ; xt execution: - n ) gforth-1.0 “open-  
bracket-n-colon-l”
```

```
[d:l ( compilation - colon-sys; run-time: d - xt ; xt execution: - d ) gforth-1.0 “open-  
bracket-d-colon-l”
```

```
[f:l ( compilation - colon-sys; run-time: r - xt ; xt execution: - r ) gforth-1.0 “open-  
bracket-r-colon-l”
```

```
[n:d ( compilation - colon-sys; run-time: n - xt ; xt execution: - n ) gforth-1.0 “open-  
bracket-n-colon-d”
```

```
[d:d ( compilation - colon-sys; run-time: d - xt ; xt execution: - d ) gforth-1.0 “open-  
bracket-d-colon-d”
```

```
[f:d ( compilation - colon-sys; run-time: r - xt ; xt execution: - r ) gforth-1.0 “open-  
bracket-r-colon-d”
```

```
[n:h ( compilation - colon-sys; run-time: n - xt ; xt execution: - n ) gforth-1.0 “open-  
bracket-n-colon-h”
```

```
[d:h ( compilation - colon-sys; run-time: d - xt ; xt execution: - d ) gforth-1.0 “open-  
bracket-d-colon-h”
```

```
[f:h ( compilation - colon-sys; run-time: r - xt ; xt execution: - r ) gforth-1.0 “open-  
bracket-r-colon-h”
```

```
[n:h1 ( compilation - colon-sys; run-time: n - xt ; xt execution: - n ) gforth-1.0 “open-  
bracket-n-colon-h1”
```

```
[d:h1 ( compilation - colon-sys; run-time: d - xt ; xt execution: - d ) gforth-1.0 “open-  
bracket-d-colon-h1”
```

```
[f:h1 ( compilation - colon-sys; run-time: r - xt ; xt execution: - r ) gforth-1.0 “open-  
bracket-r-colon-h1”
```

If you want to pass more than one stack item from closure creation to execution time, defining more such words becomes unwieldy, and the code inside the closure definition might have to juggle many stack items, so Gforth does not provide such additional words. Instead, Gforth offers flat closures that define locals. Here's the example above, but using locals-defining closures:

```
: 1/n^r ( r -- xt; xt execution: n -- r1 )
  fnegate [{: f: -r :}h s>f -r f** ;] ;
```

The number, types, and order of the locals are used for specifying how many and which stack items are consumed at closure creation time. At closure execution time these values become the values of the locals. The locals definition ends with a word with a naming scheme `:}A`, where *A* specifies where the closure is allocated: *l* (local), *d* (dictionary), *h* (heap), or *h1* (heap, **free** on first execution).

Note that the locals are still strictly local to one execution of the *xt*, and any changes to the locals (e.g., with **to**) do not change the values stored in the closure; i.e., in the next execution of the closure the locals will be initialized with the values that closure creation consumed.

[{: (*compilation* – *haddr* *u latest wid 0* ; *instantiation* ... – *xt*) gforth-1.0 “start-closure”

Starts a closure. Closures started with `[{:` define locals for use inside the closure. The locals-definition part ends with `:}l`, `:}h`, `:}h1`, `:}d` or `:}xt`. The rest of the closure definition is Forth code. The closure ends with `;`. When the closure definition is encountered during execution (closure creation time), the values going into the locals are consumed, and an execution token (*xt*) is pushed on the stack; when that execution token is executed (with **execute**, through **compile**, or a deferred word), the code in the closure is executed (closure execution time). If the *xt* of a closure is executed multiple times, the values of the locals at the start of code execution are those from closure-creation time, unaffected by any locals-changes in earlier executions of the closure.

:}l (*haddr u latest latestnt wid 0 a-addr1 u1* ... –) gforth-1.0 “close-brace-locals”

Ends a closure's locals definition. The closure will be allocated on the locals stack.

:}d (*haddr u latest latestnt wid 0 a-addr1 u1* ... –) gforth-1.0 “colon-close-brace-d”

Ends a closure's locals definition. The closure will be allocated in the dictionary.

:}h (*haddr u latest latestnt wid 0 a-addr1 u1* ... –) gforth-1.0 “colon-close-brace-h”

Ends a closure's locals definition. At the run-time of the surrounding definition this allocates the closure on the heap; you are then responsible for deallocating it with **free-closure**.

:}h1 (*haddr u latest latestnt wid 0 a-addr1 u1* ... –) gforth-1.0 “colon-close-brace-h-one”

Ends a closure's locals definition. The closure is deallocated after the first execution, so this is a one-shot closure, particularly useful in combination with **send-event** (see [\(undefined\)](#) [Message queues], page [\(undefined\)](#)).

:}xt (*haddr u latest latestnt wid 0 a-addr1 u1* ... –) gforth-1.0 “colon-close-brace-x-t”

Ends a closure's locals definition. The closure will be allocated by the *xt* on the stack, so the closure's run-time stack effect is (... *xt-alloc* -- *xt-closure*).

>addr (... *xt* – *addr*) gforth-internal “to-addr”

Obtain the address *addr* of the addressible value-flavoured word *xt*. For some value-flavoured words, additional inputs may be consumed.

If you look at closures in other languages (e.g., Scheme), they are quite different: data is passed by accessing and possibly changing locals of enclosing definitions (lexical scoping). Gforth's closures are based on the flat closures used in the implementation of Scheme, so by writing the code appropriately (see the following subsections) you can do the same things with Gforth's closures as with lexical-scoping closures.

In our programming we have not missed lexical scoping, except when trying to convert code (usually textbook examples) coming from another language. I.e., in our experience flat closures are as useful and similarly convenient as lexical scoping. For comparison, if Gforth supported lexical scoping instead of flat closures, the definition of $1/n^r$ might look as follows:

```
\ this does not work in Gforth:
: 1/n^r ( r -- xt; xt execution: n -- r1 )
  fnegate {: -r :} [:h s>f -r f** ;] ;
```

But if you want to know how to convert lexical scoping to Gforth's flat closures, the following subsections explain it.

6.27.1 How do I read outer locals?

As long as you only read the value of locals, you can duplicate them as needed, so a way to convert an access to an outer local for flat closures is to just pass the values on the stack to the closures and define them again as locals there. Here's an example: Consider the following code for a hypothetical Gforth with a quotation-like syntax for lexical-scoping closures:

```
\ does not work; [:d would dictionary-allocate the closure
: ...
  ... {: a b :} ...
  [:d ...
    ... {: c d :} ...
    [:d ... a b c d ... ;]
  ...
;]
... ;
```

you can convert it to flat closures as follows:

```
: ...
  ... {: a b :} ...
  a b [{: a b :}d ...
    ... {: c d :} ...
    a b c d [{: a b c d :}d
      ... a b c d ... ;]
  ...
;]
... ;
```

Only those locals that are read in the closure need to be passed in.

This process is called *closure conversion* in the programming language implementation literature.

6.27.2 How do I write outer locals?

A local instance that is written and read must exist at only one location, its home location. The address of this home location is only read and can be duplicated and passed around. A textbook example might look like this in a hypothetical Gforth with lexical-scoping and explicit dictionary allocation:

```
\ does not work
: counter ( -- xt-inc xt-val )
  0 {: n :}d
  [:d n 1+ to n ;]
  [:d n ;]
;
\ for usage example see below
```

Instead, you allocate the home location, and pass its address around:

```
: counter ( -- xt-inc xt-val )
  align here {: np :} 0 , \ home location
  np [[: np :}d 1 np +! ;]
  np [[: np :}d np @ ;]
;
\ usage example
counter \ first instance
dup execute . \ prints 0
over execute
over execute
dup execute . \ prints 2
counter \ second instance
over execute
dup execute . \ prints 1
2swap \ work on first instance again
dup execute . \ prints 2
```

This introduction of a home location is called *assignment conversion* in the programming language implementation literature.

You can also use pure-stack closures in this case:

```
: counter ( -- xt-inc xt-val )
  align here {: np :} 0 , \ home location
  np [n:d 1 swap +! ;]
  np [n:d @ ;]
;
\ same usage
```

Instead of dictionary allocation you can also **allocate** on the heap. For local allocation of the home location you can use variable-flavoured locals (see [\[Gforth locals\]](#), page [\[Gforth locals\]](#)), but of course then the closures must not be used after leaving the definition in which the home location is defined. E.g.

```

: counter-example ( -- )
  0 {: w^ np :} \ home location
  np [n:d 1 swap +! ;]
  np [n:d @ ;]
  dup execute cr .
  over execute
  over execute
  dup execute cr .
  2drop
;
counter-example \ prints 0 and 2

```

There is actually rarely a reason to use home locations at all, because what the textbook examples do with closures and writable locals can be done in Gforth more directly with structs (see [\(undefined\)](#) [Structures], page [\(undefined\)](#)) or objects (see [\(undefined\)](#) [Object-oriented Forth], page [\(undefined\)](#)), or in the counter example, simply with **create**:

```

: counter ( "name" -- )
  create 0 , ;
: counter-inc ( addr -- )
  1 swap +! ;
: counter-val ( addr -- )
  @ ;
\ usage example
counter a
a counter-val . \ prints 0
a counter-inc
a counter-inc
a counter-val . \ prints 2
counter b
b counter-inc
b counter-val . \ prints 1
a counter-val . \ prints 2

```

Still, for dictionary and heap allocation Gforth has a home-location definition syntax based on the locals-definition syntax. Here's a heap-allocation version of **counter** using closures and the locals-like home-location syntax:

```

: counter ( -- handle xt-inc xt-val )
  0 <{: w^ np :}h
  np [n:h 1 swap +! ;]
  np [n:h @ ;]
  ;> -rot ;
\ usage example
counter \ first instance
dup execute . \ prints 0
over execute
over execute
dup execute . \ prints 2
counter \ second instance

```

```

over execute
dup execute . \ prints 1
free-closure free-closure free throw \ back to first instance
dup execute . \ prints 2
free-closure free-clouse free throw

```

Here <{: starts a locals scope (similar to a closure itself), then you define (variable-flavoured) locals. :}h (or :}d) finishes the locals definition. Now (and up to ;>) you can use the names of the defined locals. Finally, ;> ends the scope and pushes the start address of the allocated home-location block (also when using :}d for dictionary allocation), for freeing the home-location block later.

We have produced no uses of <{: and ;> in the first 6 years that they were present in (development) Gforth. We think that the reason is that one prefers structs or objects for modifiable data. Therefore, we intend to remove these words in the future. If you want to see them preserved, contact us and make a case for them.

<{: (*compilation – colon-sys ; run-time –*) gforth-obsolete “start-homelocation”

Starts defining a home location block.

;> (*compilation colon-sys – ; run-time – addr*) gforth-obsolete “end-homelocation”

Ends defining a home location; *addr* is the start address of the home-location block (used for deallocation).

6.28 Regular Expressions

Regular expressions are pattern matching algorithms for strings found in many contemporary languages. You can add regular expression functionality to Gforth with **require regexp.fs**.

The classical implementation for this pattern matching is a backtracking algorithm, which is also necessary if you want to have features like backreferencing. Gforth implements regular expressions by providing a language to define backtracking programs for pattern matching. Basic element is the control structure **FORK ... JOIN**, which is a forward call within a word, and therefore allows to code a lightweight try and fail control structure.

FORK (*compilation – orig ; run-time f –*) gforth-0.7 “FORK”

AHEAD-like control structure: calls the code after JOIN.

JOIN (*orig –*) gforth-0.7 “JOIN”

THEN-like control structure for FORK

You can program any sort of arbitrary checks yourself by computing a flag and **?LEAVE** when the check fails. Your regular expression code is enclosed in ((and)).

```

(( ( addr u – ) regexp-pattern “(”
  start regexp block
)) ( – flag ) regexp-pattern “)”
  end regexp block

```

Pattern matching in regular expressions have character sets as elements, so a number of functions allow you to create and modify character sets (called **charclass**). All characters here are bytes, so this doesn’t extend to unicode characters.

charclass (*–*) regexp-cg “charclass”

Create a charclass

+char (*char* –) regexp-cg “+char”

add a char to the current charclass

-char (*char* –) regexp-cg “-char”

remove a char from the current charclass

..char (*start end* –) regexp-cg “..char”

add a range of chars to the current charclass

+chars (*addr u* –) regexp-cg “+chars”

add a string of chars to the current charclass

+class (*class* –) regexp-cg “+class”

union of charclass *class* and the current charclass

-class (*class* –) regexp-cg “-class”

subtract the charclass *class* from the current charclass

There are predefined charclasses and tests for them, and generic checks. If a check fails, the next possible alternative of the regular expression is tried, or a loop is terminated.

c? (*addr class* –) regexp-pattern “c?”

check *addr* for membership in charclass *class*

-c? (*addr class* –) regexp-pattern “-c?”

check *addr* for not membership in charclass *class*

\d (*addr – addr'*) regexp-pattern “\d”

check for digit

\s (*addr – addr'*) regexp-pattern “\s”

check for blanks

.? (*addr – addr'*) regexp-pattern “.”

check for any single character

-\d (*addr – addr'*) regexp-pattern “-\d”

check for not digit

-\s (*addr – addr'*) regexp-pattern “-\s”

check for not blank

` (“*char*” –) regexp-pattern “”

check for particular char

`? (“*char*” –) regexp-pattern “?”

-` (“*char*” –) regexp-pattern “-”

check for particular char

You can certainly also check for start and end of the string, and for whole string constants.

\^ (*addr – addr*) regexp-pattern “\^”

check for string start

\\$ (*addr – addr*) regexp-pattern “\\$”

```

    check for string end
str=? ( addr1 addr u - addr2 ) regexp-pattern "str=?"
    check for a computed string on the stack (possibly a backreference)
=" ( <string> - ) regexp-pattern "="
    check for string
    Loops that check for repeated character sets can be greedy or non-greedy.
{** ( addr - addr addr ) regexp-pattern "begin-greedy-star"
    greedy zero-or-more pattern
**} ( sys - ) regexp-pattern "end-greedy-star"
    end of greedy zero-or-more pattern
{++ ( addr - addr addr ) regexp-pattern "begin-greedy-plus"
    greedy one-or-more pattern
++} ( sys - ) regexp-pattern "end-greedy-plus"
    end of greedy one-or-more pattern
{* ( addr - addr addr ) regexp-pattern "begin-non-greedy-star"
    non-greedy zero-or-more pattern
*} ( addr addr' - addr' ) regexp-pattern "end-non-greedy-star"
    end of non-greedy zero-or-more pattern
{+ ( addr - addr addr ) regexp-pattern "begin-non-greedy-plus"
    non-greedy one-or-more pattern
+} ( addr addr' - addr' ) regexp-pattern "end-non-greedy-plus"
    end of non-greedy one-or-more pattern
    Example: Searching for a substring really is a non-greedy match of anything in front of
    it.
// ( - ) regexp-pattern "/"
    search for string
    Alternatives are written with
{{ ( addr - addr addr ) regexp-pattern "begin-alternatives"
    Start of alternatives
|| ( addr addr - addr addr ) regexp-pattern "next-alternative"
    separator between alternatives
}} ( addr addr - addr ) regexp-pattern "end-alternatives"
    end of alternatives
    You can use up to 9 variables named \1 to \9 to refer to matched substrings
\ ( addr - addr ) regexp-pattern "\"
    start of matching variable; variables are referred as \\1-9
\\ ( addr - addr ) regexp-pattern "\"
    end of matching variable
\\0 ( - addr u ) regexp-pattern "\\0"

```


the whole string

Certainly, you can also write code to replace patterns you found.

```
s>> ( addr – addr ) regexp-replace “s>>”
```

Start replace pattern region

```
>> ( addr – addr ) regexp-replace “>>”
```

Start arbitrary replacement code, the code shall compute a string on the stack and pass it to <<

```
<< ( run-addr addr u – run-addr ) regexp-replace “<<”
```

Replace string from start of replace pattern region with *addr u*

```
<<" ( "string<">" – ) regexp-replace “<<”
```

Replace string from start of replace pattern region with *string*

```
s// ( addr u – ptr ) regexp-replace “s//”
```

start search/replace loop

```
//s ( ptr – ) regexp-replace “//s”
```

search end

```
//o ( ptr addr u – addr' u' ) regexp-replace “//o”
```

end search/replace single loop

```
//g ( ptr addr u – addr' u' ) regexp-replace “//g”
```

end search/replace all loop

Examples can be found in `test/regexp-test.fs`.

6.29 Programming Tools

6.29.1 Locating source code definitions

Many programming systems are organized as an integrated development environment (IDE) where the editor is the hub of the system, and allows building and running programs. If you want that, Gforth has it, too (see `<undefined>` [Emacs and Gforth], page `<undefined>`).

However, several Forth systems have a different kind of IDE: The Forth command line is the hub of the environment; you can view the source from there in various ways, and call an editor if needed.

Gforth also implements such an IDE. It mostly follows the conventions of SwiftForth where they exist, but implements features beyond them.

An advantage of this approach is that it allows you to use your favourite editor: set the environment variable `EDITOR` to your favourite editor, and the editing commands will call that editor; Gforth invokes some GUI editors in the background (so you do not need to finish editing to continue with your Forth session), terminal editors in the foreground (default for editors not known to Gforth is foreground). If you have not set `EDITOR`, the default editor is `vi`.

```
locate ( "name" – ) gforth-1.0 “locate”
```

Show the source code of the word *name* and set the current location there.

```
xt-locate ( nt/xt – ) gforth-1.0 “xt-locate”
```

Show the source code of the word *xt* and set the current location there.

The *current location* is set by a number of other words in addition to **locate**. Also, when an error happens while loading a file, the location of the error becomes the current location.

A number of words work with the current location:

l (-) gforth-1.0 “l”

Display source code lines at the current location.

n (-) gforth-1.0 “n”

Display lines behind the current location, or behind the last **n** or **b** output (whichever was later).

b (-) gforth-1.0 “b”

Display lines before the current location, or before the last **n** or **b** output (whichever was later).

g (-) gforth-0.7 “g”

Enter the editor at the current location, or at the start of the last **n** or **b** output (whichever was later).

You can control how many lines **l**, **n** and **b** show by changing the values:

before-locate (- *u*) gforth-1.0 “before-locate”

number of lines shown before current location (default 3).

after-locate (- *u*) gforth-1.0 “after-locate”

number of lines shown after current location (default 12).

Finally, you can directly go to the source code of a word in the editor with

edit ("*name*" -) gforth-1.0 “edit”

Enter the editor at the location of "*name*"

You can see the definitions of similarly-named words with

browse ("*subname*" -) gforth-1.0 “browse”

Show all places where a word with a name that contains *subname* is defined (**mwords**-like, see <undefined> [Word Lists], page <undefined>). You can then use **ww**, **nw** or **bw** (see <undefined> [Locating uses of a word], page <undefined>) to inspect specific occurrences more closely.

6.29.2 Locating uses of a word

where ("*name*" -) gforth-1.0 “where”

Show all places where *name* is used (text-interpreted). You can then use **ww**, **nw** or **bw** to inspect specific occurrences more closely. Gforth’s **where** does not show the definition of *name*; use **locate** for that.

ww (*u* -) gforth-1.0 “ww”

The next **l** or **g** shows the **where** result with index *u*

nw (-) gforth-1.0 “nw”

The next **l** or **g** shows the next **where** result; if the current one is the last one, after **nw** there is no current one. If there is no current one, after **nw** the first one is the current one.

bw (-) gforth-1.0 “bw”

The next **l** or **g** shows the previous **where** result; if the current one is the first one, after **bw** there is no current one. If there is no current one, after **bw** the last one is the current one.

gg (-) gforth-1.0 “gg”

The next **ww**, **nw**, **bw**, **bb**, **nb**, **lb** (but not **locate**, **edit**, **l** or **g**) puts its result in the editor (like **g**). Use **gg gg** to make this permanent rather than one-shot.

ll (-) gforth-1.0 “ll”

The next **ww**, **nw**, **bw**, **bb**, **nb**, **lb** (but not **locate**, **edit**, **l** or **g**) displays in the Forth system (like **l**). Use **ll ll** to make this permanent rather than one-shot.

wherereg ("name" -) gforth-1.0 “wherereg”

Like **where**, but puts the output in the editor. In Emacs, you can then use the compilation-mode commands (see Section “Compilation Mode” in *GNU Emacs Manual*) to inspect specific occurrences more closely.

short-where (-) gforth-1.0 “short-where”

Set up **where** to use a short file format (default).

expand-where (-) gforth-1.0 “expand-where”

Set up **where** to use a fully expanded file format (to pass to e.g. editors).

prepend-where (-) gforth-1.0 “prepend-where”

Set up **where** to show the file on a separate line, followed by **where** lines without file names (like SwiftForth).

The data we have on word usage also allows us to show which words have no uses:

unused-words (-) gforth-1.0 “unused-words”

list all words without usage

6.29.3 Locating exception source

tt (*u* -) gforth-1.0 “tt”

nt (-) gforth-1.0 “nt”

bt (-) gforth-1.0 “bt”

6.29.4 Examining compiled code

And finally, **see** and friends show compiled code. Some of the things in the source code are not present in the compiled code (e.g., formatting and comments), but this is useful to see what threaded code or native code is produced by macros and Gforth’s optimization features.

see ("<spaces>name" -) tools “see”

Locate *name* using the current search order. Display the definition of *name*. Since this is achieved by decompiling the definition, the formatting is mechanised and some source information (comments, interpreted sequences within definitions etc.) is lost.

xt-see (*xt* -) gforth-0.2 “xt-see”

Decompile the definition represented by *xt*.

`simple-see ("name" -) gforth-0.6 "simple-see"`

Decompile the colon definition *name*, showing a line for each cell, and try to guess a meaning for the cell, and show that.

`xt-simple-see (xt -) gforth-1.0 "xt-simple-see"`

Decompile the colon definition *xt* like `simple-see`

`simple-see-range (addr1 addr2 -) gforth-0.6 "simple-see-range"`

Decompile code in [*addr1*,*addr2*) like `simple-see`

`see-code ("name" -) gforth-0.7 "see-code"`

Like `simple-see`, but also shows the dynamic native code for the inlined primitives. For static superinstructions, it shows the primitive sequence instead of the first primitive (the other primitives of the superinstruction are shown, too). For primitives for which native code is generated, it shows the number of stack items in registers at the beginning and at the end (e.g., 1->1 means 1 stack item is in a register at the start and at the end). For each primitive or superinstruction with native code, the inline arguments and component primitives are shown first, then the native code.

`xt-see-code (xt -) gforth-1.0 "xt-see-code"`

Decompile the colon definition *xt* like `see-code`.

`see-code-range (addr1 addr2 -) gforth-0.7 "see-code-range"`

Decompile code in [*addr1*,*addr2*) like `see-code`.

As an example, consider:

```
: foo x f@ fsin drop over ;
```

This is not particularly useful, but it demonstrates the various code generation differences. Compiling this on `gforth-fast` on AMD64 and then using `see-code foo` outputs:

```
$7FD0CEE8C510 lit f@      1->1
$7FD0CEE8C518 x
$7FD0CEE8C520 f@
7FD0CEB51697:  movsd   [r12],xmm15
7FD0CEB5169D:  mov     rax,$00[r13]
7FD0CEB516A1:  sub     r12,$08
7FD0CEB516A5:  add     r13,$18
7FD0CEB516A9:  movsd   xmm15,[rax]
7FD0CEB516AE:  mov     rcx,-$08[r13]
7FD0CEB516B2:  jmp     ecx
$7FD0CEE8C528 fsin
$7FD0CEE8C530 drop      1->0
7FD0CEB516B4:  add     r13,$08
$7FD0CEE8C538 over      0->1
7FD0CEB516B8:  mov     r8,$10[r15]
7FD0CEB516BC:  add     r13,$08
$7FD0CEE8C540 ;s        1->1
7FD0CEB516C0:  mov     r10,[rbx]
7FD0CEB516C3:  add     rbx,$08
```

```

7FDOCEB516C7:  lea    r13,$08[r10]
7FDOCEB516CB:  mov    rcx,-$08[r13]
7FDOCEB516CF:  jmp    ecx

```

First, you see a threaded-code cell for a static superinstruction with the components `lit` and `f@`, starting and ending with one data stack item in a register (`1->1`); this is followed by the cell for the argument `x` of `lit`, and the cell for the `f@` component of the superinstruction; the latter cell is not used, but is there for Gforth-internal reasons.

Next, the dynamically generated native code for the superinstruction `lit f@` is shown; note that this native code is not mixed with the threaded code in memory, as you can see by comparing the addresses.

If you want to understand the native code shown here: the threaded-code instruction pointer is in `r13`, the data stack pointer in `r15`; the first data stack register is `r8` (i.e., the top of stack resides there if there is one data stack item in a register); the return stack pointer is in `rbx`, the FP stack pointer in `r12`, and the top of the floating-point stack in `xmm15`. Note that the register assignments vary between engines, so you may see a different register assignment for this code.

The dynamic native code for `lit f@` ends with a dispatch jump (aka NEXT), because the code for the next word `fsin` in the definition is not dynamically generated.

Next, you see the threaded-code cell for `fsin`. There is no dynamically-generated native code for this word, and `see-code` does not show the static native code for it (you can look at it with `see fsin`). Like all words with static native code in `gforth-fast`, the effect on the data stack representation is `1->1` (for `gforth`, `0->0`), but this is not shown.

Next, you see the threaded-code cell for `drop`; the native-code variant used here starts with one data stack item in registers, and ends with zero data stack items in registers (`1->0`). This is followed by the native code for this variant of `drop`. There is no NEXT here, because the native code falls through to the code for the next word.

Next, you see the threaded-code cell for `over` followed by the dynamically-generated native code in the `0->1` variant.

Finally, you see the threaded and native code for `;s` (the primitive compiled for `; in foo`). `;s` performs control flow (it returns), so it has to end with a NEXT.

6.29.5 Examining data

The following words inspect the stack non-destructively:

```
... ( x1 .. xn - x1 .. xn ) gforth-1.0 "..."
```

smart version of `.s`

```
.s ( - ) tools "dot-s"
```

Display the number of items on the data stack, followed by a list of the items (but not more than specified by `maxdepth-.s`; TOS is the right-most item.

```
f.s ( - ) gforth-0.2 "f-dot-s"
```

Display the number of items on the floating-point stack, followed by a list of the items (but not more than specified by `maxdepth-.s`; TOS is the right-most item.

```
f.s-precision ( - u ) gforth-1.0 "f.s-precision"
```

A **value**. *U* is the field width for f.s output. Other precision details are derived from that value.

maxdepth-.s (*- addr*) gforth-0.2 “maxdepth-dot-s”

A variable containing 9 by default. **.s** and **f.s** display at most that many stack items.

There is a word **.r** but it does *not* display the return stack! It is used for formatted numeric output (see [\[Simple numeric output\]](#), page [\(undefined\)](#)).

The following words work on the stack as a whole, either by determining the depth or by clearing them:

depth (*- +n*) core “depth”

+n is the number of values that were on the data stack before *+n* itself was placed on the stack.

fdepth (*- +n*) floating “f-depth”

+n is the current number of (floating-point) values on the floating-point stack.

clearstack (*... -*) gforth-0.2 “clear-stack”

remove and discard all/any items from the data stack.

fclearstack (*r0 .. rn -*) gforth-1.0 “f-clearstack”

clear the floating point stack

clearstacks (*... -*) gforth-0.7 “clear-stacks”

empty data and FP stack

The following words inspect memory.

? (*a-addr -*) tools “question”

Display the contents of address *a-addr* in the current number base.

dump (*addr u -*) tools “dump”

Display *u* lines of memory starting at address *addr*. Each line displays the contents of 16 bytes. When Gforth is running under an operating system you may get **Invalid memory address** errors if you attempt to access arbitrary locations.

6.29.6 Forgetting words

Forth allows you to forget words (and everything that was allotted in the dictionary after them) in a LIFO manner.

marker ("*<spaces> name*" -) core-ext “marker”

Create a definition, *name* (called a *mark*) whose execution semantics are to remove itself and everything defined after it.

The most common use of this feature is during program development: when you change a source file, forget all the words it defined and load it again (since you also forget everything defined after the source file was loaded, you have to reload that, too). Note that effects like storing to variables and destroyed system words are not undone when you forget words. With a system like Gforth, that is fast enough at starting up and compiling, I find it more convenient to exit and restart Gforth, as this gives me a clean slate.

Here’s an example of using **marker** at the start of a source file that you are debugging; it ensures that you only ever have one copy of the file’s definitions compiled at any time:

```
[IFDEF] my-code
```

```

    my-code
  [THEN]

marker my-code
init-included-files

\ .. definitions start here
\ .
\ .
\ end

```

6.29.7 Debugging

Languages with a slow edit/compile/link/test development loop tend to require sophisticated tracing/stepping debuggers to facilitate debugging.

A much better (faster) way in fast-compiling languages is to add printing code at well-selected places, let the program run, look at the output, see where things went wrong, add more printing code, etc., until the bug is found.

The simple debugging aids provided in `debugs.fs` are meant to support this style of debugging.

The word `~~` prints debugging information (by default the source location and the stack contents). It is easy to insert. If you use Emacs it is also easy to remove (`C-x ~` in the Emacs Forth mode to query-replace them with nothing). The deferred words `printdebugdata` and `.debugline` control the output of `~~`. The default source location output format works well with Emacs' compilation mode, so you can step through the program at the source level using `C-x `` (the advantage over a stepping debugger is that you can step in any direction and you know where the crash has happened or where the strange data has occurred).

`~~ (-) gforth-0.2 "tilde-tilde"`

Prints the source code location of the `~~` and the stack contents with `.debugline`.

`printdebugdata (-) gforth-0.2 "print-debug-data"`

`.debugline (nfile nline -) gforth-0.6 "print-debug-line"`

Print the source code location indicated by *nfile nline*, and additional debugging information; the default `.debugline` prints the additional information with `printdebugdata`.

`debug-fid (- file-id) gforth-1.0 "File-id"`

debugging words for output. By default it is the process's `stderr`.

`~~` (and assertions) will usually print the wrong file name if a marker is executed in the same file after their occurrence. They will print `*somewhere*` as file name if a marker is executed in the same file before their occurrence.

`once (-) gforth-1.0 "once"`

do the following up to THEN only once

`~~bt (-) gforth-1.0 "~~bt"`

print stackdump and backtrace

`~~1bt (-) gforth-1.0 "~~1bt"`

```

    print stackdump and backtrace once
    ??? ( - ) gforth-0.2 "???"
    Open a debugging shell
    WTF?? ( - ) gforth-1.0 "WTF??"
    Open a debugging shell with backtrace and stack dump
    !!FIXME!! ( - ) gforth-1.0 "!!FIXME!!"
    word that should never be reached
    replace-word ( xt1 xt2 - ) gforth-1.0 "replace-word"
    make xt2 do xt1, both need to be colon definitions
    ~~Variable ( "name" - ) gforth-1.0 "~~Variable"
    Variable that will be watched on every access
    ~~Value ( n "name" - ) gforth-1.0 "~~Value"
    Value that will be watched on every access
    +ltrace ( - ) gforth-1.0 "+ltrace"
    turn on line tracing
    -ltrace ( - ) gforth-1.0 "-ltrace"
    turn off line tracing
    #loc ( nline nchar "file" - ) gforth-1.0 "#loc"
    set next word's location to nline nchar in "file"

```

6.29.8 Assertions

It is a good idea to make your programs self-checking, especially if you make an assumption that may become invalid during maintenance (for example, that a certain field of a data structure is never zero). Gforth supports *assertions* for this purpose. They are used like this:

```
assert( flag )
```

The code between **assert**(and) should compute a flag, that should be true if everything is alright and false otherwise. It should not change anything else on the stack. The overall stack effect of the assertion is (--). E.g.

```

assert( 1 1 + 2 = ) \ what we learn in school
assert( dup 0<> ) \ assert that the top of stack is not zero
assert( false ) \ this code should not be reached

```

The need for assertions is different at different times. During debugging, we want more checking, in production we sometimes care more for speed. Therefore, assertions can be turned off, i.e., the assertion becomes a comment. Depending on the importance of an assertion and the time it takes to check it, you may want to turn off some assertions and keep others turned on. Gforth provides several levels of assertions for this purpose:

```
assert0( ( - ) gforth-0.2 "assert-zero"
```

Important assertions that should always be turned on.

```
assert1( ( - ) gforth-0.2 "assert-one"
```


Normal assertions; turned on by default.

```
assert2( ( - ) gforth-0.2 "assert-two"
```

Debugging assertions.

```
assert3( ( - ) gforth-0.2 "assert-three"
```

Slow assertions that you may not want to turn on in normal debugging; you would turn them on mainly for thorough checking.

```
assert( ( - ) gforth-0.2 "assert("
```

Equivalent to `assert1(`

```
) ( - ) gforth-0.2 "close-paren"
```

End an assertion. Generic end, can be used for other similar purposes

The variable `assert-level` specifies the highest assertions that are turned on. I.e., at the default `assert-level` of one, `assert0(` and `assert1(` assertions perform checking, while `assert2(` and `assert3(` assertions are treated as comments.

The value of `assert-level` is evaluated at compile-time, not at run-time. Therefore you cannot turn assertions on or off at run-time; you have to set the `assert-level` appropriately before compiling a piece of code. You can compile different pieces of code at different `assert-levels` (e.g., a trusted library at level 1 and newly-written code at level 3).

```
assert-level ( - a-addr ) gforth-0.2 "assert-level"
```

All assertions above this level are turned off.

If an assertion fails, a message compatible with Emacs' compilation mode is produced and the execution is aborted (currently with `ABORT"`. If there is interest, we will introduce a special throw code. But if you intend to `catch` a specific condition, using `throw` is probably more appropriate than an assertion).

Assertions (and `~~`) will usually print the wrong file name if a marker is executed in the same file after their occurrence. They will print `'*somewhere*` as file name if a marker is executed in the same file before their occurrence.

Definitions in Standard Forth for these assertion words are provided in `compat/assert.fs`.

6.29.9 Singlestep Debugger

The singlestep debugger works only with the engine `gforth-itc`.

When you create a new word there's often the need to check whether it behaves correctly or not. You can do this by typing `dbg badword`. A debug session might look like this:

```
: badword 0 DO i . LOOP ; ok
2 dbg badword
: badword
Scanning code...
```

Nesting debugger ready!

```
400D4738 8049BC4 0          -> [ 2 ] 00002 00000
400D4740 8049F68 DO        -> [ 0 ]
400D4744 804A0C8 i         -> [ 1 ] 00000
```

```

400D4748 400C5E60 .          -> 0 [ 0 ]
400D474C 8049D0C LOOP        -> [ 0 ]
400D4744 804A0C8 i           -> [ 1 ] 00001
400D4748 400C5E60 .          -> 1 [ 0 ]
400D474C 8049D0C LOOP        -> [ 0 ]
400D4758 804B384 ;           -> ok

```

Each line displayed is one step. You always have to hit return to execute the next word that is displayed. If you don't want to execute the next word in a whole, you have to type *n* for **nest**. Here is an overview what keys are available:

RET	Next; Execute the next word.
<i>n</i>	Nest; Single step through next word.
<i>u</i>	Unnest; Stop debugging and execute rest of word. If we got to this word with nest, continue debugging with the calling word.
<i>d</i>	Done; Stop debugging and execute rest.
<i>s</i>	Stop; Abort immediately.

Debugging large application with this mechanism is very difficult, because you have to nest very deeply into the program before the interesting part begins. This takes a lot of time.

To do it more directly put a **BREAK:** command into your source code. When program execution reaches **BREAK:** the single step debugger is invoked and you have all the features described above.

If you have more than one part to debug it is useful to know where the program has stopped at the moment. You can do this by the **BREAK" string"** command. This behaves like **BREAK:** except that string is typed out when the "breakpoint" is reached.

```
dbg ( "name" - ) gforth-0.2 "dbg"
```

```
break: ( - ) gforth-0.4 "break:"
```

```
break" ( 'ccc' - ) gforth-0.4 "break"
```

6.29.10 Code Coverage and Execution Frequency

If you run extensive tests on your code, you often want to figure out if the tests exercise all parts of the code. This is called (test) coverage. The file **coverage.fs** contains tools for measuring the coverage as well as execution frequency.

Code coverage inserts counting code in every basic block (straight-line code sequence) loaded after **coverage.fs**. Each time that code is run, it increments the counter for that basic block. Later you can show the source file with the counts inserted in these basic blocks.

```
nocov[ ( - ) gforth-1.0 "nocov-bracket"
```

(Immediate) Turn coverage off temporarily.

```
]nocov ( - ) gforth-1.0 "bracket-nocov"
```

(Immediate) End of temporary turned off coverage.

```
coverage? ( - f ) gforth-internal "coverage?"
```

Value: Coverage check on/off

cov+ (-) gforth-experimental “cov+”

(Immediate) Place a coverage counter here.

?cov+ (*flag* - *flag*) gforth-experimental “?cov+”

(Immediate) A coverage counter for a flag; in the coverage output you see three numbers behind **?cov**: The first is the number of executions where the top-of-stack was non-zero; the second is the number of executions where it was zero; the third is the total number of executions.

.coverage (-) gforth-experimental “.coverage”

Show code with execution frequencies.

annotate-cov (-) gforth-experimental “annotate-cov”

For every file with coverage information, produce a **.cov** file that has the execution frequencies inserted. We recommend to use **bw-cover** first (with the default **color-cover** you get escape sequences in the files).

cov% (-) gforth-experimental “cov-percent”

Print the percentage of basic blocks loaded after **coverage.fs** that are executed at least once.

.cover-raw (-) gforth-experimental “.cover-raw”

Print raw execution counts.

By default, the counts are shown in colour (using ANSI escape sequences), but you can use **bw-cover** to show them in parenthesized form without escape sequences.

bw-cover (-) gforth-1.0 “bw-cover”

Print execution counts in parentheses (source-code compatible).

color-cover (-) gforth-1.0 “color-cover”

Print execution counts in colours (default).

You can save and reload the coverage counters in binary format, to aggregate coverage counters across several test runs of the same program.

save-cov (-) gforth-experimental “save-cov”

Save coverage counters.

load-cov (-) gforth-experimental “load-cov”

Load coverage counters.

cover-filename (- *c-addr u*) gforth-experimental “cover-filename”

C-addr u is the file name of the file that is used by **save-cov** and **load-cov**. The file name depends on the code compiled since **coverage.fs** was loaded.

6.30 Multitasker

Gforth offers two multitaskers: a traditional, cooperative round-robin multitasker, and a pthread-based multitasker which allows to run several threads concurrently on multi-core machines. The pthread-based is now marked as experimental feature, as standardization of Forth multitaskers will likely change the names of words without changing their semantics.

6.30.1 Pthreads

Posix threads can run in parallel on several cores, or with pre-emptive multitasking on onecore. However, many of the following words are the same as in the traditional cooperative multi-tasker.

In addition, there are words that allow you to make sure that only one task at a time changes something, and for communicating between tasks. These words are necessary for pre-emptive and multi-core multi-tasking, because the cooperative-multitasking way of performing transactions between calls to `pause` does not work in this environment.

6.30.1.1 Basic multi-tasking

Tasks can be created with `newtask` or `newtask4` with a given amount of stack space (either all the same or each stack's size specified).

newtask (*stacksize* – *task*) gforth-experimental “newtask”

creates *task*; each stack (data, return, FP, locals) has size *stacksize*.

task (*ustacksize* “*name*” –) gforth-experimental “task”

creates a task *name*; each stack (data, return, FP, locals) has size *ustacksize*.

name execution: (– *task*)

newtask4 (*u-data* *u-return* *u-fp* *u-locals* – *task*) gforth-experimental “newtask4”

creates *task* with data stack size *u-data*, return stack size *u-return*, FP stack size *u-fp* and locals stack size *u-locals*.

If you don't know which stack sizes to use for the task, you can use the size(s) of the main task:

stacksize (– *u*) gforth-experimental “stacksize”

u is the data stack size of the main task.

stacksize4 (– *u-data* *u-return* *u-fp* *u-locals*) gforth-experimental “stacksize4”

Pushes the data, return, FP, and locals stack sizes of the main task.

A task is created in an inactive state. To let it run, you have to activate it with one of the following words:

initiate (*xt* *task* –) gforth-experimental “initiate”

Let *task* execute *xt*. Upon return from the *xt*, the task terminates itself (VFX compatible). Use one-time executable closures to pass arbitrary parameters to a task.

The following legacy words provide the same functionality as `initiate`, but with a different interface: Like `does>`, they split their containing colon definition in two parts: The part before `activate/pass` runs in the activating task, and returns to its caller after activating the task. The part behind `activate/pass` is executed in the activated target task.

activate (*run-time nest-sys1* *task* –) gforth-experimental “activate”

Let *task* perform the code behind `activate`, and return to the caller of the word containing `activate`. When the task returns from the code behind `activate`, it terminates itself.

pass (*x1* .. *xn* *n* *task* –) gforth-experimental “pass”

Pull $x1 \dots xn$ from the current task's data stack and push $x1 \dots xn$ on *task*'s data stack. Let *task* perform the code behind **pass**, and return to the caller of the word containing **pass**. When the task returns from the code behind **pass**, it terminates itself.

You can also do creation and activation in one step:

execute-task (*xt* – *task*) gforth-experimental “execute-task”

Create a new task *task* with the same stack sizes as the main task. Let *task* execute *xt*. Upon return from the *xt*, the task terminates itself.

Apart from terminating by running to the end, a task can terminate itself with **kill-task**. Other tasks can terminate it with **kill**.

kill-task (–) gforth-experimental “kill-task”

Terminate the current task.

kill (*task* –) gforth-experimental “kill”

Terminate *task*.

Tasks can also temporarily stop themselves or be stopped:

halt (*task* –) gforth-experimental “halt”

Stop *task* (no difference from **sleep**)

sleep (*task* –) gforth-experimental “sleep”

Stop *task* (no difference from **halt**)

stop (–) gforth-experimental “stop”

stops the current task, and waits for events (which may restart it)

stop-ns (*timeout* –) gforth-experimental “stop-ns”

Stop with timeout (in nanoseconds), better replacement for **ms**

stop-dns (*dtimeout* –) gforth-experimental “stop-dns”

Stop with timeout (in nanoseconds), better replacement for **ms** Stop with *dtimeout* (in nanoseconds), better replacement for **ms**

thread-deadline (*d* –) gforth-experimental “thread-deadline”

stop until absolute time *d* in nanoseconds, base is 1970-1-1 0:00 UTC, but you usually will want to base your deadlines on a time you get with **ntime**.

Using **stop-dns** is easier to code, but if you want your task to wake up at regular intervals rather than some time after it finished its last piece of work, the way to go is to work with deadlines.

A task restarts when the timeout is over or when another task wakes it with:

wake (*task* –) gforth-experimental “wake”

Wake *task*

restart (*task* –) gforth-experimental “restart”

Wake *task* (no difference from **wake**)

There is also:

pause (–) gforth-experimental “pause”

voluntarily switch to the next waiting task (**pause** is the traditional cooperative task switcher; in the pthread multitasker, you don't need **pause** for cooperation, but you still can use it e.g. when you have to resort to polling for some reason). This also checks for events in the queue.

6.30.1.2 Task-local data

In Forth every task has essentially the same task-local data, called “user” area (early Forth systems were multi-user systems and there often was one user per task). The *task* result of, e.g. `newtask` is the start address of its user area. Each task gets the user data defined by the system (e.g., `base`). You can define additional user data with:

`User ("name" -) gforth-0.2 “User”`

Name is a user variable (1 cell).

Name execution: (*- addr*)

Addr is the address of the user variable in the current task.

`AUser ("name" -) gforth-0.2 “AUser”`

Name is a user variable containing an address (this only makes a difference in the cross-compiler).

`uallot (n1 - n2) gforth-0.3 “uallot”`

Reserve *n1* bytes of user data. *n2* is the offset of the start of the reserved area within the user area.

`UValue ("name" -) gforth-1.0 “UValue”`

Name is a user value.

Name execution: (*- x*)

`UDefer ("name" -) gforth-1.0 “UDefer”`

Name is a task-local deferred word.

Name execution: (... - ...)

There are also the following words for dealing with user data.

`up@ (- a-addr) new “up-fetch”`

Addr is the start of the user area of the current task (*addr* also serves as the *task* identifier of the current task).

`user' ("name" - u) gforth-experimental “user”`

U is the offset of the user variable *name* in the user area of each task.

`'s (addr1 task - addr2) gforth-experimental “s”`

With *addr1* being an address in the user data of the current task, *addr2* is the corresponding address in *task*’s user data.

The pictured numeric output buffer is also task-local, but other areas like dictionary or PAD are shared.

6.30.1.3 Semaphores

A cooperative multitasker can ensure that there is no other task interacting between two invocations of `pause`. Pthreads however are really concurrent tasks (at least on a multi-core CPU), and therefore, several techniques to avoid conflicts when accessing the same resources.

Semaphores can only be acquired by one thread, all other threads have to wait until the semaphore is released.

`semaphore ("name" -) gforth-experimental “semaphore”`

```

    create a named semaphore name
name execution: ( - semaphore )
lock ( semaphore - ) gforth-experimental "lock"
    lock the semaphore
unlock ( semaphore - ) gforth-experimental "unlock"
    unlock the semaphore

```

The other approach to prevent concurrent access is the critical section. Here, we implement a critical section with a semaphore, so you have to specify the semaphore which is used for the critical section. Only those critical sections which use the same semaphore are mutually exclusive.

```
critical-section ( xt semaphore - ) gforth-experimental "critical-section"
```

Execute *xt* while locking *semaphore*. After leaving *xt*, *semaphore* is unlocked even if an exception is thrown.

6.30.1.4 Hardware operations for multi-tasking

Atomic hardware operations perform the whole operation, without any other task seeing an intermediate state. These operations can be used to synchronize tasks without using slow OS primitives, but compared to the non-atomic sequences of operations they tend to be slow. Atomic operations only work correctly on aligned addresses, even on hardware that otherwise does not require alignment.

```
atomic!@ ( w1 a-addr - w2 ) gforth-experimental "atomic-store-fetch"
```

Fetch *w2* from *a-addr*, then store *w1* there, combined into an atomic operation.

```
atomic+!@ ( u1 a-addr - u2 ) gforth-experimental "atomic-plus-store-fetch"
```

Fetch *w2* from *a-addr*, then increment this location by *u1*. This atomic operation is commonly known as fetch-and-add.

```
atomic?!@ ( unew uold a-addr - uprev ) gforth-experimental "atomic-question-store-fetch"
```

Fetch *uprev* from *a-addr*, compare it to *uold*, and if equal, store *unew* there. This atomic operation is commonly known as compare-and-swap.

There are also the non-atomic !@ and +!@ (otherwise the same behaviour, see [\(undefined\)](#) [Memory Access], page [\(undefined\)](#)).

Another hardware operation is the memory barrier. Unfortunately modern hardware often can reorder memory operations relative to other memory operations (as seen by a different core), and the memory barrier suppresses this reordering for one point in the execution of the task.

```
barrier ( - ) gforth-experimental "barrier"
```

All memory operations before the barrier are performed before any memory operation after the barrier.

6.30.1.5 Message queues

Gforth's message queues are a variant of the actor model.

The sending task tells the receiving task to execute an *xt* with the stack effect (--) (an *event* in the name of the words below; the actor model would call these *xts* *messages*),

and when the receiving task is ready, it will execute the xt, possibly after other xts from its message queue.

The execution order between xts from different tasks is arbitrary, the order between xts from the same task is the sending order.

In many cases you do not just want to pass the xts of existing words, but also parameters. You can construct execute-once closures (defined using `:}h1`, see [\[Closures\]](#), page [\[undefined\]](#)) to achieve that, e.g., with

```
: .-in-task ( n task -- )
  >r [{: n :}h1 n . ;] r> send-event ;
```

```
5 my-task .-in-task \ my-task prints 5
send-event ( xt task - ) gforth-experimental "send-event"
```

Inter-task communication: `send xt (--) to task`. *task* executes the xt at some later point in time. To pass parameters, construct a one-shot closure that contains the parameters (see [\[Closures\]](#), page [\[undefined\]](#)) and pass the xt of that closure.

In order to execute xts received from other tasks, perform one of the following words in the receiving task:

```
?events ( - ) gforth-experimental "question-events"
```

Execute all event xts in the current task's message queue, one xt at a time.

```
event-loop ( - ) gforth-experimental "event-loop"
```

Wait for event xts and execute these xts when they arrive, one at a time. Return to waiting if no event xts are in the queue. This word never returns.

Alternatively, when a task is **stopped**, it is also ready for receiving xts, and receiving an xt will not just execute the xt, but also continue execution after the **stop**.

6.30.2 Cilk

Gforth's Cilk is a framework for dividing work between multiple tasks running on several cores, inspired by the programming language of the same name. Use `require cilk.fs` if you want to use Cilk.

The idea is that you identify subproblems that can be solved in parallel, and the framework assigns worker tasks to these subproblems. In particular, you use one of the **spawn** words for each subtask. Eventually you need to wait with **cilk-sync** for the subproblems to be solved.

Currently all the spawning has to happen from one task, and **cilk-sync** waits for all subproblems to complete, so using the current Gforth Cilk for recursive algorithms is not straightforward.

Do not divide the subproblems too finely, in order to avoid overhead; how fine is too fine depends on how uniform the run-time for the subproblems is, but for problems with substantial run-time, having `5*cores` subproblems is probably a good starting point.

```
cores ( - u ) cilk "cores"
```

A value containing the number of worker tasks to use. By default this is the number of hardware threads (with SMT/HT), if we can determine that, otherwise 1. If you want to use a different number, change **cores** before calling **cilk-init**.

```
cilk-init ( - ) cilk "cilk-init"
```


Start the worker tasks if not already done.

```
spawn ( xt - ) cilk "spawn"
```

Execute *xt* (-) in a worker task. Use one-time executable closures to pass heap-allocated closures, allowing to pass arbitrary data from the spawner to the code running in the worker.

E.g.: (n r) [{ : n f : r : } h1 code ;] spawn

```
spawn1 ( x xt - ) cilk "spawn1"
```

Execute *xt* (x -) in a worker task.

```
spawn2 ( x1 x2 xt - ) cilk "spawn2"
```

Execute *xt* (x1 x2 -) in a worker task.

```
cilk-sync ( - ) cilk "cilk-sync"
```

Wait for all subproblems to complete.

```
cilk-bye ( - ) cilk "cilk-bye"
```

Terminate all workers.

6.31 C Interface

Gforth's C interface works by compiling a wrapper library that contains C functions which take parameters from the Forth stacks and calls the C functions. This wrapper library is compiled by the C compiler. Compilation results are cached, so that Gforth only needs to rerun the C compilation if the wrapper library has to change. This build process is automatic, and done at the end of a interface declaration. Gforth uses libtool and GCC for that process.

The C interface is now mostly complete, callbacks have been added, but for structs, we use Forth2012 structs, which don't have independent scopes. The offsets of those structs are extracted from header files with a SWIG plugin.

6.31.1 Calling C functions

Once a C function is declared (see see <undefined> [Declaring C Functions], page <undefined>), you can call it as follows: You push the arguments on the stack(s), and then call the word for the C function. The arguments have to be pushed in the same order as the arguments appear in the C documentation (i.e., the first argument is deepest on the stack). Integer and pointer arguments have to be pushed on the data stack, floating-point arguments on the FP stack; these arguments are consumed by the called C function.

On returning from the C function, the return value, if any, resides on the appropriate stack: an integer return value is pushed on the data stack, an FP return value on the FP stack, and a void return value results in not pushing anything. Note that most C functions have a return value, even if that is often not used in C; in Forth, you have to **drop** this return value explicitly if you do not use it.

The C interface automatically converts between the C type and the Forth type as necessary, on a best-effort basis (in some cases, there may be some loss).

As an example, consider the POSIX function `lseek()`:

```
off_t lseek(int fd, off_t offset, int whence);
```

This function takes three integer arguments, and returns an integer argument, so a Forth call for setting the current file offset to the start of the file could look like this:

```
fd @ 0 SEEK_SET lseek -1 = if
... \ error handling
then
```

You might be worried that an `off_t` does not fit into a cell, so you could not pass larger offsets to `lseek`, and might get only a part of the return values. In that case, in your declaration of the function (see [\(undefined\)](#) [Declaring C Functions], page [\(undefined\)](#)) you should declare it to use double-cells for the `off_t` argument and return value, and maybe give the resulting Forth word a different name, like `dlseek`; the result could be called like this:

```
fd @ 0. SEEK_SET dlseek -1. d= if
... \ error handling
then
```

Passing and returning structs or unions is currently not supported by our interface²⁹.

Calling functions with a variable number of arguments (*variadic* functions, e.g., `printf()`) is only supported by having you declare one function-calling word for each argument pattern, and calling the appropriate word for the desired pattern.

6.31.2 Declaring C Functions

Before you can call `lseek` or `dlseek`, you have to declare it. The declaration consists of two parts:

The C part

is the C declaration of the function, or more typically and portably, a C-style `#include` of a file that contains the declaration of the C function.

The Forth part

declares the Forth types of the parameters and the Forth word name corresponding to the C function.

For the words `lseek` and `dlseek` mentioned earlier, the declarations are:

```
\c #define _FILE_OFFSET_BITS 64
\c #include <sys/types.h>
\c #include <unistd.h>
c-function lseek lseek n n n -- n
c-function dlseek lseek n d n -- d
```

The C part of the declarations is prefixed by `\c`, and the rest of the line is ordinary C code. You can use as many lines of C declarations as you like, and they are visible for all further function declarations.

The Forth part declares each interface word with `c-function`, followed by the Forth name of the word, the C name of the called function, and the stack effect of the word. The stack effect contains an arbitrary number of types of parameters, then `--`, and then exactly one type for the return value. The possible types are:

n single-cell integer

²⁹ If you know the calling convention of your C compiler, you usually can call such functions in some way, but that way is usually not portable between platforms, and sometimes not even between C compilers.

a	address (single-cell)
d	double-cell integer
r	floating-point value
func	C function pointer
void	no value (used as return type for void functions)

To deal with variadic C functions, you can declare one Forth word for every pattern you want to use, e.g.:

```
\c #include <stdio.h>
c-function printf-nr printf a n r -- n
c-function printf-rn printf a r n -- n
```

Note that with C functions declared as variadic (or if you don't provide a prototype), the C interface has no C type to convert to, so no automatic conversion happens, which may lead to portability problems in some cases. You can add the C type cast in curly braces after the Forth type. This also allows to pass e.g. structs to C functions, which in Forth cannot live on the stack.

```
c-function printfll printf a n{(long long)} -- n
c-function pass-struct pass_struct a{*(struct foo *)} -- n
```

This typecasting is not available to return values, as C does not allow typecasts for lvalues.

```
\c ( "rest-of-line" - ) gforth-0.7 "backslash-c"
```

One line of C declarations for the C interface

```
c-function ( "forth-name" "c-name" "{type}" "—" "type" - ) gforth-0.7 "c-function"
```

Define a Forth word *forth-name*. *Forth-name* has the specified stack effect and calls the C function *c-name*.

```
c-value ( "forth-name" "c-name" "—" "type" - ) gforth-1.0 "c-value"
```

Define a Forth word *forth-name*. *Forth-name* has the specified stack effect and gives the C value of *c-name*.

```
c-variable ( "forth-name" "c-name" - ) gforth-1.0 "c-variable"
```

Define a Forth word *forth-name*. *Forth-name* returns the address of *c-name*.

In order to work, this C interface invokes GCC at run-time and uses dynamic linking. If these features are not available, there are other, less convenient and less portable C interfaces in *lib.fs* and *oldlib.fs*. These interfaces are mostly undocumented and mostly incompatible with each other and with the documented C interface; you can find some examples for the *lib.fs* interface in *lib.fs*.

6.31.3 Calling C function pointers from Forth

If you come across a C function pointer (e.g., in some C-constructed structure) and want to call it from your Forth program, you could use the structures as described above by defining a macro. Or you use *c-funptr*.

```
c-funptr ( "forth-name" <{>"c-typecast"<}> "{type}" "—" "type" - ) gforth-1.0 "c-funptr"
```

Define a Forth word *forth-name*. *Forth-name* has the specified stack effect plus the called pointer on top of stack, i.e. ({type} ptr -- type) and calls the C function pointer *ptr* using the typecast or struct access *c-typecast*.

Let us assume that there is a C function pointer type *func1* defined in some header file *func1.h*, and you know that these functions take one integer argument and return an integer result; and you want to call functions through such pointers. Just define

```
\c #include <func1.h>
c-funptr call-func1 {((func1)ptr)} n -- n
```

and then you can call a function pointed to by, say *func1a* as follows:

```
-5 func1a call-func1 .
```

The Forth word *call-func1* is similar to *execute*, except that it takes a C *func1* pointer instead of a Forth execution token, and it is specific to *func1* pointers. For each type of function pointer you want to call from Forth, you have to define a separate calling word.

6.31.4 Defining library interfaces

You can give a name to a bunch of C function declarations (a library interface), as follows:

```
c-library lseek-lib
\c #define _FILE_OFFSET_BITS 64
...
end-c-library
```

The effect of giving such a name to the interface is that the names of the generated files will contain that name, and when you use the interface a second time, it will use the existing files instead of generating and compiling them again, saving you time. The generated file contains a 128 bit hash (not cryptographically safe, but good enough for that purpose) of the source code, so changing the declarations will cause a new compilation. Normally these files are cached in *\$HOME/.gforth/architecture/libcc-named*, so if you experience problems or have other reasons to force a recompilation, you can delete the files there.

Note that you should use *c-library* before everything else having anything to do with that library, as it resets some setup stuff. The idea is that the typical use is to put each *c-library...end-c-library* unit in its own file, and to be able to include these files in any order. All other words dealing with the C interface are hidden in the vocabulary *c-lib*, which is put on top of the search stack by *c-library* and removed by *end-c-library*.

Note that the library name is not allocated in the dictionary and therefore does not shadow dictionary names. It is used in the file system, so you have to use naming conventions appropriate for file systems. The name is also used as part of the C symbols, but characters outside the legal C symbol names are replaced with underscores. Also, you shall not call a function you declare after *c-library* before you perform *end-c-library*.

A major benefit of these named library interfaces is that, once they are generated, the tools used to generate them (in particular, the C compiler and *libtool*) are no longer needed, so the interface can be used even on machines that do not have the tools installed. The build system of Gforth can even cross-compile these libraries, so that the libraries are available for platforms on which build tools aren't installed.

```
c-library-name ( c-addr u - ) gforth-0.7 "c-library-name"
```

Start a C library interface with name *c-addr u*.

```
c++-library-name ( c-addr u - ) gforth-1.0 "c++-library-name"
```

Start a C++ library interface with name *c-addr u*.

```
c-library ( "name" - ) gforth-0.7 "c-library"
```

Parsing version of *c-library-name*

```
c++-library ( "name" - ) gforth-1.0 "c++-library"
```

Parsing version of *c++-library-name*

```
end-c-library ( - ) gforth-0.7 "end-c-library"
```

Finish and (if necessary) build the latest C library interface.

6.31.5 Declaring OS-level libraries

For calling some C functions, you need to link with a specific OS-level library that contains that function. E.g., the `sin` function requires linking a special library by using the command line switch `-lm`. In our C interface you do the equivalent thing by calling `add-lib` as follows:

```
clear-libs
s" m" add-lib
\c #include <math.h>
c-function sin sin r -- r
```

First, you clear any libraries that may have been declared earlier (you don't need them for `sin`); then you add the `m` library (actually `libm.so` or `somesuch`) to the currently declared libraries; you can add as many as you need. Finally you declare the function as shown above. Typically you will use the same set of library declarations for many function declarations; you need to write only one set for that, right at the beginning.

Note that you must not call `clear-libs` inside `c-library...end-c-library`; however, `c-library` performs the function of `clear-libs`, so `clear-libs` is not necessary, and you usually want to put `add-lib` calls inside `c-library...end-c-library`.

```
clear-libs ( - ) gforth-0.7 "clear-libs"
```

Clear the list of libs

```
add-lib ( c-addr u - ) gforth-0.7 "add-lib"
```

Add library *libstring* to the list of libraries, where *string* is represented by *c-addr u*.

```
add-libpath ( c-addr u - ) gforth-0.7 "add-libpath"
```

Add path *string* to the list of library search pathes, where *string* is represented by *c-addr u*.

```
add-framework ( c-addr u - ) gforth-1.0 "add-framework"
```

Add framework *libstring* to the list of frameworks, where *string* is represented by *c-addr u*.

```
add-incdir ( c-addr u - ) gforth-1.0 "add-incdir"
```

Add path *c-addr u* to the list of include search pathes

```
add-cflags ( c-addr u - ) gforth-1.0 "add-cflags"
```

add any kind of cflags to compilation

```
add-ldflags ( c-addr u - ) gforth-1.0 "add-ldflags"
```

add flag to linker

6.31.6 Callbacks

In some cases you have to pass a function pointer to a C function, i.e., the library wants to call back to your application (and the pointed-to function is called a callback function). You can pass the address of an existing C function (that you get with `lib-sym`, see [\(undefined\)](#) [Low-Level C Interface Words], page [\(undefined\)](#)), but if there is no appropriate C function, you probably want to define the function as a Forth word. Then you need to generate a callback as described below:

You can generate C callbacks from Forth code with `c-callback`.

```
c-callback ( "forth-name" "{type}" "—" "type" - ) gforth-1.0 "c-callback"
```

Define a callback instantiator with the given signature. The callback instantiator *forth-name* (`xt -- addr`) takes an *xt*, and returns the *address* of the C function handling that callback.

```
c-callback-thread ( "forth-name" "{type}" "—" "type" - ) gforth-1.0 "c-callback-thread"
```

Define a callback instantiator with the given signature. The callback instantiator *forth-name* (`xt -- addr`) takes an *xt*, and returns the *address* of the C function handling that callback. This callback is safe when called from another thread

This precompiles a number of callback functions (up to the value `callback#`). The prototype of the C function is deduced from its Forth signature. If this is not sufficient, you can add types in curly braces after the Forth type.

```
c-callback vector4double: f f f f -- void
c-callback vector4single: f{float} f{float} f{float} f{float} -- void
```

6.31.7 How the C interface works

The documented C interface works by generating a C code out of the declarations.

In particular, for every Forth word declared with `c-function`, it generates a wrapper function in C that takes the Forth data from the Forth stacks, and calls the target C function with these data as arguments. The C compiler then performs an implicit conversion between the Forth type from the stack, and the C type for the parameter, which is given by the C function prototype. After the C function returns, the return value is likewise implicitly converted to a Forth type and written back on the stack.

The `\c` lines are literally included in the C code (but without the `\c`), and provide the necessary declarations so that the C compiler knows the C types and has enough information to perform the conversion.

These wrapper functions are eventually compiled and dynamically linked into Gforth, and then they can be called.

The libraries added with `add-lib` are used in the compile command line to specify dependent libraries with `-llib`, causing these libraries to be dynamically linked when the wrapper function is linked.

6.31.8 Low-Level C Interface Words

```
open-lib ( c-addr1 u1 - u2 ) gforth-0.4 "open-lib"
```

```
lib-sym ( c-addr1 u1 u2 - u3 ) gforth-0.4 "lib-sym"
```

```
lib-error ( - c-addr u ) gforth-0.7 "lib-error"
```

Error message for last failed `open-lib` or `lib-sym`.

`call-c (... w - ...) gforth-0.2 "call-c"`

Call the C function pointed to by *w*. The C function has to access the stack itself. The stack pointers are exported into a `ptrpair` structure passed to the C function, and returned in that form.

6.31.9 Automated interface generation using SWIG

SWIG, the Simple Wrapper Interface Generator, is used to create C interfaces for a lot of programming languages. The SWIG version extended with a Forth module can be found on github (<https://github.com/GeraldWodni/swig>).

6.31.9.1 Basic operation

C-headers are parsed and converted to Forth-Sourcecode which uses the previously describe C interface functions.

6.31.9.2 Detailed operation:

1. Select a target, in this example we are using `example.h`
2. Create an interface file for the header. This can be used to pass options, switches and define variables. In the simplest case it just instructs to translate all of `example.h`:

```
%module example
%insert("include")
{
    #include "example.h"
}
%include "example.h"
```

3. Use SWIG to create a `.fsi-c` file.


```
swig -forth -stackcomments -use-structs -enumcomments -o example-fsi.c
example.i.
```

 FSI stands “Forth Source Independent” meaning it can be transferred to any host having a C-compiler. SWIG is not required past this point.
4. On the target machine compile the `.fsi-c` file to a `.fsx` (x stands for executable)


```
gcc -o example.fsx example-fsi.c
```

 The compilation will resolve all constants to the values on the target.
5. The last step is to run the executable and capture its output to a `.fs` “Forth Source” file.


```
./example.fsx -gforth > example.fs
```

 This code can now be used on the target platform.

6.31.9.3 Examples

You can find some examples in SWIG’s Forth Example section (<https://github.com/GeraldWodni/swig/tree/master/Examples/forth>).

A lot of interface files can be found in Forth Posix C-Interface (<https://github.com/GeraldWodni/posix>) and Forth C-Interface Modules (<https://github.com/GeraldWodni/forth-c-interfaces>).

Contribution to the Forth C-Interface Module repository (<https://github.com/GeraldWodni/forth-c-interfaces>) is always welcome.

6.31.10 Migrating from Gforth 0.7

In this version, you can use `\c`, `c-function` and `add-lib` only inside `c-library...end-c-library`. `add-lib` now always starts from a clean slate inside a `c-library`, so you don't need to use `clear-libs` in most cases.

If you have a program that uses these words outside `c-library...end-c-library`, just wrap them in `c-library...end-c-library`. You may have to add some instances of `add-lib`, however.

6.32 Assembler and Code Words

6.32.1 Definitions in assembly language

Gforth provides ways to implement words in assembly language (using `abi-code...end-code`), and also ways to define defining words with arbitrary run-time behaviour (like `does>`), where (unlike `does>`) the behaviour is not defined in Forth, but in assembly language (with `;code`).

However, the machine-independent nature of Gforth poses a few problems: First of all, Gforth runs on several architectures, so it can provide no standard assembler. It does provide assemblers for several of the architectures it runs on, though. Moreover, you can use a system-independent assembler in Gforth, or compile machine code directly with `,` and `c,.`

Another problem is that the virtual machine registers of Gforth (the stack pointers and the virtual machine instruction pointer) depend on the installation and engine. Also, which registers are free to use also depend on the installation and engine. So any code written to run in the context of the Gforth virtual machine is essentially limited to the installation and engine it was developed for (it may run elsewhere, but you cannot rely on that).

Fortunately, you can define `abi-code` words in Gforth that are portable to any Gforth running on a platform with the same calling convention (ABI); typically this means portability to the same architecture/OS combination, sometimes crossing OS boundaries).

assembler (-) tools-ext “assembler”

A vocabulary: Replaces the wordlist at the top of the search order with the assembler wordlist.

init-asm (-) gforth-0.2 “init-asm”

Pushes the assembler wordlist on the search order.

abi-code ("name" - colon-sys) gforth-1.0 “abi-code”

Start a native code definition that is called using the platform's ABI conventions corresponding to the C-prototype:

```
Cell *function(Cell *sp, Float **fpp);
```

The FP stack pointer is passed in by providing a reference to a memory location containing the FP stack pointer and is passed out by storing the changed FP stack pointer there (if necessary).

;abi-code (-) gforth-1.0 “semicolon-abi-code”

Ends the colon definition, but at run-time also changes the last defined word *X* (which must be a **created** word) to call the following native code using the platform's ABI convention corresponding to the C prototype:

```
Cell *function(Cell *sp, Float **fpp, Address body);
```

The FP stack pointer is passed in by providing a reference to a memory location containing the FP stack pointer and is passed out by storing the changed FP stack pointer there (if necessary). The parameter *body* is the body of *X*.

```
end-code ( colon-sys - ) gforth-0.2 "end-code"
```

End a code definition. Note that you have to assemble the return from the ABI call (for **abi-code**) or the dispatch to the next VM instruction (for **code** and **;code**) yourself.

```
code ( "name" - colon-sys ) tools-ext "code"
```

Start a native code definition that runs in the context of the Gforth virtual machine (engine). Such a definition is not portable between Gforth installations, so we recommend using **abi-code** instead of **code**. You have to end a **code** definition with a dispatch to the next virtual machine instruction.

```
;code ( compilation. colon-sys1 - colon-sys2 ) tools-ext "semicolon-code"
```

The code after **;code** becomes the behaviour of the last defined word (which must be a **created** word). The same caveats apply as for **code**, so we recommend using **;abi-code** instead.

```
flush-icache ( c-addr u - ) gforth-0.2 "flush-icache"
```

Make sure that the instruction cache of the processor (if there is one) does not contain stale data at *c-addr* and *u* bytes afterwards. **END-CODE** performs a **flush-icache** automatically. Caveat: **flush-icache** might not work on your installation; this is usually the case if direct threading is not supported on your machine (take a look at your **machine.h**) and your machine has a separate instruction cache. In such cases, **flush-icache** does nothing instead of flushing the instruction cache.

If **flush-icache** does not work correctly, **abi-code** words etc. will not work (reliably), either.

The typical usage of these words can be shown most easily by analogy to the equivalent high-level defining words:

<pre>: foo <high-level Forth words> ;</pre>	<pre>abi-code foo <assembler> end-code</pre>
<pre>: bar <high-level Forth words> CREATE <high-level Forth words> DOES> <high-level Forth words> ;</pre>	<pre>: bar <high-level Forth words> CREATE <high-level Forth words> ;code <assembler> end-code</pre>

For using **abi-code**, take a look at the ABI documentation of your platform to see how the parameters are passed (so you know where you get the stack pointers) and how the return value is passed (so you know where the data stack pointer is returned). The ABI

documentation also tells you which registers are saved by the caller (caller-saved), so you are free to destroy them in your code, and which registers have to be preserved by the called word (callee-saved), so you have to save them before using them, and restore them afterwards. For some architectures and OSs we give short summaries of the parts of the calling convention in the appropriate sections. More reverse-engineering oriented people can also find out about the passing and returning of the stack pointers through `see abi-call`.

Most ABIs pass the parameters through registers, but some (in particular the most common 386 (aka IA-32) calling conventions) pass them on the architectural stack. The common ABIs all pass the return value in a register.

Other things you need to know for using `abi-code` is that both the data and the FP stack grow downwards (towards lower addresses) in Gforth, with `1 cells` size per cell, and `1 floats` size per FP value.

Here's an example of using `abi-code` on the 386 architecture:

```
abi-code my+ ( n1 n2 -- n )
4 sp d) ax mov \ sp into return reg
ax )      cx mov \ tos
4 #       ax add \ update sp (pop)
cx      ax ) add \ sec = sec+tos
ret              \ return from my+
end-code
```

An AMD64 variant of this example can be found in `<undefined>` [AMD64 Assembler], page `<undefined>`.

Here's a 386 example that deals with FP values:

```
abi-code my-f+ ( r1 r2 -- r )
8 sp d) cx mov \ load address of fp
cx )      dx mov \ load fp
.fl dx )   fld \ r2
8 #       dx add \ update fp
.fl dx )   fadd \ r1+r2
.fl dx )   fstp \ store r
dx      cx ) mov \ store new fp
4 sp d) ax mov \ sp into return reg
ret              \ return from my-f+
end-code
```

6.32.2 Common Assembler

The assemblers in Gforth generally use a postfix syntax, i.e., the instruction name follows the operands.

The operands are passed in the usual order (the same that is used in the manual of the architecture). Since they all are Forth words, they have to be separated by spaces; you can also use Forth words to compute the operands.

The instruction names usually end with a `,`. This makes it easier to visually separate instructions if you put several of them on one line; it also avoids shadowing other Forth words (e.g., `and`).

Registers are usually specified by number; e.g., (decimal) 11 specifies registers R11 and F11 on the Alpha architecture (which one, depends on the instruction). The usual names are also available, e.g., `s2` for R11 on Alpha.

Control flow is specified similar to normal Forth code (see `<undefined>` [Arbitrary control structures], page `<undefined>`), with `if,, ahead,, then,, begin,, until,, again,, cs-roll, cs-pick, else,, while,,` and `repeat,.` The conditions are specified in a way specific to each assembler.

The rest of this section is of interest mainly for those who want to define `code` words (instead of the more portable `abi-code` words).

Note that the register assignments of the Gforth engine can change between Gforth versions, or even between different compilations of the same Gforth version (e.g., if you use a different GCC version). If you are using `CODE` instead of `ABI-CODE`, and you want to refer to Gforth's registers (e.g., the stack pointer or TOS), I recommend defining your own words for referring to these registers, and using them later on; then you can adapt to a changed register assignment.

The most common use of these registers is to end a `code` definition with a dispatch to the next word (the `next` routine). A portable way to do this is to jump to '`noop >code-address`' (of course, this is less efficient than integrating the `next` code and scheduling it well). When using `ABI-CODE`, you can just assemble a normal subroutine return (but make sure you return the data stack pointer).

Another difference between Gforth versions is that the top of stack is kept in memory in `gforth` and, on most platforms, in a register in `gforth-fast`. For `ABI-CODE` definitions, any stack caching registers are guaranteed to be flushed to the stack, allowing you to reliably access the top of stack in memory.

6.32.3 Common Disassembler

You can disassemble a `code` word with `see` (see `<undefined>` [Debugging], page `<undefined>`). You can disassemble a section of memory with

```
discode ( addr u - ) gforth-0.2 "discode"
```

hook for the disassembler: disassemble u bytes of code at addr

There are two kinds of disassembler for Gforth: The Forth disassembler (available on some CPUs) and the gdb disassembler (available on platforms with `gdb` and `mktemp`). If both are available, the Forth disassembler is used by default. If you prefer the gdb disassembler, say

```
' disasm-gdb is discode
```

If neither is available, `discode` performs `dump`.

The Forth disassembler generally produces output that can be fed into the assembler (i.e., same syntax, etc.). It also includes additional information in comments. In particular, the address of the instruction is given in a comment before the instruction.

The gdb disassembler produces output in the same format as the gdb `disassemble` command (see Section "Source and machine code" in *Debugging with GDB*), in the default flavour (AT&T syntax for the 386 and AMD64 architectures).

`See` may display more or less than the actual code of the word, because the recognition of the end of the code is unreliable. You can use `discode` if it did not display enough. It

may display more, if the code word is not immediately followed by a named word. If you have something else there, you can follow the word with `align latest`, to ensure that the end is recognized.

6.32.4 386 Assembler

The 386 assembler included in Gforth was written by Bernd Paysan, it's available under GPL, and originally part of bigFORTH.

The 386 disassembler included in Gforth was written by Andrew McKewan and is in the public domain.

The disassembler displays code in an Intel-like prefix syntax.

The assembler uses a postfix syntax with AT&T-style parameter order (i.e., destination last).

The assembler includes all instruction of the Athlon, i.e. 486 core instructions, Pentium and PPro extensions, floating point, MMX, 3Dnow!, but not ISSE. It's an integrated 16- and 32-bit assembler. Default is 32 bit, you can switch to 16 bit with `.86` and back to 32 bit with `.386`.

There are several prefixes to switch between different operation sizes, `.b` for byte accesses, `.w` for word accesses, `.d` for double-word accesses. Addressing modes can be switched with `.wa` for 16 bit addresses, and `.da` for 32 bit addresses. You don't need a prefix for byte register names (AL et al).

For floating point operations, the prefixes are `.fs` (IEEE single), `.fl` (IEEE double), `.fx` (extended), `.fw` (word), `.fd` (double-word), and `.fq` (quad-word). The default is `.fx`, so you need to specify `.fl` explicitly when dealing with Gforth FP values.

The MMX opcodes don't have size prefixes, they are spelled out like in the Intel assembler. Instead of move from and to memory, there are PLDQ/PLDD and PSTQ/PSTD.

The registers lack the 'e' prefix; even in 32 bit mode, `eax` is called `ax`. Immediate values are indicated by postfixing them with `#`, e.g., `3 #`. Here are some examples of addressing modes in various syntaxes:

Gforth	Intel (NASM)	AT&T (gas)	Name
<code>.w ax</code>	<code>ax</code>	<code>%ax</code>	register (16 bit)
<code>ax</code>	<code>eax</code>	<code>%eax</code>	register (32 bit)
<code>3 #</code>	<code>offset 3</code>	<code>\$3</code>	immediate
<code>1000 #)</code>	<code>byte ptr 1000</code>	<code>1000</code>	displacement
<code>bx)</code>	<code>[ebx]</code>	<code>(%ebx)</code>	base
<code>100 di d)</code>	<code>100[edi]</code>	<code>100(%edi)</code>	base+displacement
<code>20 ax *4 i#)</code>	<code>20[<i>eax</i>*4]</code>	<code>20(,<i>eax</i>,4)</code>	(index*scale)+displacement
<code>di ax *4 i)</code>	<code>[edi][<i>eax</i>*4]</code>	<code>(%edi,<i>eax</i>,4)</code>	base+(index*scale)
<code>4 bx cx di)</code>	<code>4[ebx][ecx]</code>	<code>4(%ebx,%ecx)</code>	base+index+displacement
<code>12 sp ax *2 di)</code>	<code>12[esp][<i>eax</i>*2]</code>	<code>12(%esp,<i>eax</i>,2)</code>	base+(index*scale)+displacement

You can use `L)` and `LI)` instead of `D)` and `DI)` to enforce 32-bit displacement fields (useful for later patching).

Some example of instructions are:

```
ax bx mov      \ move ebx,eax
3 # ax mov     \ mov eax,3
```

```

100 di d) ax mov      \ mov eax,100[edi]
4 bx cx di) ax mov    \ mov eax,4[ebx][ecx]
.w ax bx mov          \ mov bx,ax

```

The following forms are supported for binary instructions:

```

<reg> <reg> <inst>
<n> # <reg> <inst>
<mem> <reg> <inst>
<reg> <mem> <inst>
<n> # <mem> <inst>

```

The shift/rotate syntax is:

```

<reg/mem> 1 # shl \ shortens to shift without immediate
<reg/mem> 4 # shl
<reg/mem> cl shl

```

Precede string instructions (`movs` etc.) with `.b` to get the byte version.

The control structure words `IF` `UNTIL` etc. must be preceded by one of these conditions: `vs vc u< u>= 0= 0<> u<= u> 0< 0>= ps pc < >= <= >`. (Note that most of these words shadow some Forth words when `assembler` is in front of `forth` in the search path, e.g., in `code` words). Currently the control structure words use one stack item, so you have to use `roll` instead of `cs-roll` to shuffle them (you can also use `swap` etc.).

Based on the Intel ABI (used in Linux), `abi-code` words can find the data stack pointer at `4 sp d`), and the address of the FP stack pointer at `8 sp d`); the data stack pointer is returned in `ax`; `Ax`, `Cx`, and `Dx` are caller-saved, so you do not need to preserve their values inside the word. You can return from the word with `ret`, the parameters are cleaned up by the caller.

For examples of 386 `abi-code` words, see [\[Assembler Definitions\]](#), page [\(undefined\)](#).

6.32.5 AMD64 (x86_64) Assembler

The AMD64 assembler is a slightly modified version of the 386 assembler, and as such shares most of the syntax. Two new prefixes, `.q` and `.qa`, are provided to select 64-bit operand and address sizes respectively. 64-bit sizes are the default, so normally you only have to use the other prefixes. Also there are additional register operands `R8-R15`.

The registers lack the 'e' or 'r' prefix; even in 64 bit mode, `rax` is called `ax`. Additional register operands are available to refer to the lowest-significant byte of all registers: `R8L-R15L`, `SPL`, `BPL`, `SIL`, `DIL`.

The Linux-AMD64 calling convention is to pass the first 6 integer parameters in `rdi`, `rsi`, `rdx`, `rcx`, `r8` and `r9` and to return the result in `rax` and `rdx`; to pass the first 8 FP parameters in `xmm0-xmm7` and to return FP results in `xmm0-xmm1`. So `abi-code` words get the data stack pointer in `di` and the address of the FP stack pointer in `si`, and return the data stack pointer in `ax`. The other caller-saved registers are: `r10`, `r11`, `xmm8-xmm15`. This calling convention reportedly is also used in other non-Microsoft OSs.

Windows x64 passes the first four integer parameters in `rcx`, `rdx`, `r8` and `r9` and return the integer result in `rax`. The other caller-saved registers are `r10` and `r11`.

On the Linux platform, according to https://uclibc.org/docs/psABI-x86_64.pdf page 21 the registers AX CX DX SI DI R8 R9 R10 R11 are available for scratch.

The addressing modes for the AMD64 are:

```
\ running word A produces a memory error as the registers are not initialised ;-)\
ABI-CODE A ( -- )
    500      #                AX MOV      \ immediate
        DX                AX MOV      \ register
    200      AX MOV      \ direct addressing
        DX )            AX MOV      \ indirect addressing
    40  DX D)            AX MOV      \ base with displacement
        DX CX          I) AX MOV      \ scaled index
        DX CX *4 I) AX MOV      \ scaled index
    40  DX CX *4 DI) AX MOV      \ scaled index with displacement

        DI                AX MOV      \ SP Out := SP in
                        RET
```

END-CODE

Here are a few examples of an AMD64 abi-code words:

```
abi-code my+ ( n1 n2 -- n3 )
\ SP passed in di, returned in ax, address of FP passed in si
8 di d) ax lea          \ compute new sp in result reg
di )    dx mov          \ get old tos
dx  ax ) add           \ add to new tos
ret
end-code
```

\ Do nothing

```
ABI-CODE aNOP ( -- )
    DI )    AX          LEA          \ SP out := SP in
                        RET
```

END-CODE

\ Drop TOS

```
ABI-CODE aDROP ( n -- )
    8  DI D)    AX          LEA          \ SPout := SPin - 1
                        RET
```

END-CODE

\ Push 5 on the data stack

```
ABI-CODE aFIVE ( -- 5 )
    -8 DI D)    AX          LEA          \ SPout := SPin + 1
    5  #        AX )    MOV          \ TOS := 5
                        RET
```

END-CODE

\ Push 10 and 20 into data stack

```
ABI-CODE aTOS2 ( -- n n )
    -16 DI D)    AX          LEA          \ SPout := SPin + 2
    10 #        8  AX D)    MOV          \ TOS - 1 := 10
```

```

    20 #          AX )  MOV          \ TOS := 20
                                RET

END-CODE

\ Get Time Stamp Counter as two 32 bit integers
\ The TSC is incremented every CPU clock pulse
ABI-CODE aRDTSC  ( -- TSC1 TSCh )

                                RDTSC          \ DX:AX := TSC
    $FFFFFFFF #      AX      AND          \ Clear upper 32 bit AX
    0xFFFFFFFF #     DX      AND          \ Clear upper 32 bit DX
    AX              R8      MOV          \ Temporary save AX
    -16 DI D)       AX      LEA          \ SPout := SPin + 2
    R8              8  AX D)  MOV          \ TOS-1 := saved AX = TSC low
    DX              AX )  MOV          \ TOS := Dx = TSC high
                                RET

END-CODE

\ Get Time Stamp Counter as 64 bit integer
ABI-CODE RDTSC  ( -- TSC )

                                RDTSC          \ DX:AX := TSC
    $FFFFFFFF #      AX      AND          \ Clear upper 32 bit AX
    32 #            DX      SHL          \ Move lower 32 bit DX to upper 32 bit
    AX              DX      OR           \ Combine AX wit DX in DX
    -8 DI D)       AX      LEA          \ SPout := SPin + 1
    DX              AX )  MOV          \ TOS := DX
                                RET

END-CODE

VARIABLE V

\ Assign 4 to variable V
ABI-CODE V=4 ( -- )

    BX              PUSH          \ Save BX, used by gforth
    V #            BX      MOV          \ BX := address of V
    4 #            BX )  MOV          \ Write 4 to V
    BX              POP           \ Restore BX
    DI )          AX      LEA          \ SPout := SPin
                                RET

END-CODE

VARIABLE V

\ Assign 5 to variable V
ABI-CODE V=5 ( -- )

    V #            CX      MOV          \ CX := address of V
    5 #            CX )  MOV          \ Write 5 to V
    DI )          AX      LEA          \ SPout := SPin
                                RET

END-CODE

ABI-CODE TEST2  ( -- n n )

```

```

-16 DI D) AX      LEA      \ SPout := SPin + 2
5  #      CX      MOV      \ CX := 5
5  #      CX      CMP
0= IF
  1  # 8 AX D)      MOV      \ If CX = 5 then TOS - 1 := 1 <--■
ELSE
  2  # 8 AX D)      MOV      \ else TOS - 1 := 2
THEN
6  #      CX      CMP
0= IF
  3  #      AX )      MOV      \ If CX = 6 then TOS := 3
ELSE
  4  #      AX )      MOV      \ else TOS := 4 <--
THEN
                                RET
END-CODE

\ Do four loops. Expect : ( 4 3 2 1 -- )
ABI-CODE LOOP4 ( -- n n n n )
  DI      AX      MOV      \ SPout := SPin
  4  #      DX      MOV      \ DX := 4 loop counter
  BEGIN
    8  #      AX      SUB      \ SP := SP + 1
      DX      AX ) MOV      \ TOS := DX
    1  #      DX      SUB      \ DX := DX - 1
  0= UNTIL
                                RET
END-CODE

```

Here's a AMD64 example that deals with FP values:

```

abi-code my-f+ ( r1 r2 -- r )
\ SP passed in di, returned in ax, address of FP passed in si
si )      dx mov      \ load fp
8 dx d) xmm0 movsd    \ r2
dx )      xmm0 addsd   \ r1+r2
xmm0 8 dx d) movsd    \ store r
8 #      si ) add      \ update fp
di      ax mov      \ sp into return reg
ret
end-code

```

6.32.6 Alpha Assembler

The Alpha assembler and disassembler were originally written by Bernd Thallner.

The register names **a0–a5** are not available to avoid shadowing hex numbers.

Immediate forms of arithmetic instructions are distinguished by a **#** just before the **,**, e.g., **and#**, (note: **lda**, does not count as arithmetic instruction).

You have to specify all operands to an instruction, even those that other assemblers consider optional, e.g., the destination register for `br,,` or the destination register and hint for `jmp,,`.

You can specify conditions for `if`, by removing the first `b` and the trailing `,` from a branch with a corresponding name; e.g.,

```
11 fgt if, \ if F11>0e
...
endif,
fbgt, gives fgt.
```

6.32.7 MIPS assembler

The MIPS assembler was originally written by Christian Pirker.

Currently the assembler and disassembler covers most of the MIPS32 architecture and doesn't support FP instructions.

The register names `$a0-$a3` are not available to avoid shadowing hex numbers. Use register numbers `$4-$7` instead.

Nothing distinguishes registers from immediate values. Use explicit opcode names with the `i` suffix for instructions with immediate argument. E.g. `addiu`, in place of `addu,,`.

Where the architecture manual specifies several formats for the instruction (e.g., for `jalr,,`), use the one with more arguments (i.e. two for `jalr,,`). When in doubt, see `arch/mips/testasm.fs` for an example of correct use.

Branches and jumps in the MIPS architecture have a delay slot. You have to fill it manually (the simplest way is to use `nop,,`), the assembler does not do it for you (unlike `as`). Even `if,,`, `ahead,,`, `until,,`, `again,,`, `while,,`, `else,,` and `repeat,,` need a delay slot. Since `begin,,` and `then,,` just specify branch targets, they are not affected. For branches the argument specifying the target is a relative address. Add the address of the delay slot to get the absolute address.

Note that you must not put branches nor jumps (nor control-flow instructions) into the delay slot. Also it is a bad idea to put pseudo-ops such as `li`, into a delay slot, as these may expand to several instructions. The MIPS I architecture also had load delay slots, and newer MIPSes still have restrictions on using `mfhi`, and `mflo,,`. Be careful to satisfy these restrictions, the assembler does not do it for you.

Some example of instructions are:

```
$ra 12 $sp sw,      \ sw    ra,12(sp)
$4   8 $s0 lw,      \ lw     a0,8(s0)
$v0  $0 lui,        \ lui    v0,0x0
$s0  $s4 $12 addiu,  \ addiu  s0,s4,0x12
$s0  $s4 $4 addu,    \ addu   s0,s4,$a0
$ra  $t9 jalr,      \ jalr   t9
```

You can specify the conditions for `if`, etc. by taking a conditional branch and leaving away the `b` at the start and the `,` at the end. E.g.,

```
4 5 eq if,
... \ do something if $4 equals $5
then,
```

The calling conventions for 32-bit MIPS machines is to pass the first 4 arguments in registers \$4..\$7, and to use \$v0-\$v1 for return values. In addition to these registers, it is ok to clobber registers \$t0-\$t8 without saving and restoring them.

If you use `jalr`, to call into dynamic library routines, you must first load the called function's address into \$t9, which is used by position-indirect code to do relative memory accesses.

Here is an example of a MIPS32 abi-code word:

```
abi-code my+ ( n1 n2 -- n3 )
  \ SP passed in $4, returned in $v0
  $t0 4 $4 lw,      \ load n1, n2 from stack
  $t1 0 $4 lw,
  $t0 $t0 $t1 addu,  \ add n1+n2, result in $t0
  $t0 4 $4 sw,      \ store result (overwriting n1)
  $ra jr,           \ return to caller
  $v0 $4 4 addiu,    \ (delay slot) return updated SP in $v0
end-code
```

6.32.8 PowerPC assembler

The PowerPC assembler and disassembler were contributed by Michal Revucky.

This assembler does not follow the convention of ending mnemonic names with a “,”, so some mnemonic names shadow regular Forth words (in particular: `and` or `xor` `fabs`); so if you want to use the Forth words, you have to make them visible first, e.g., with `also forth`.

Registers are referred to by their number, e.g., 9 means the integer register 9 or the FP register 9 (depending on the instruction).

Because there is no way to distinguish registers from immediate values, you have to explicitly use the immediate forms of instructions, i.e., `addi`, not just `add`.

The assembler and disassembler usually support the most general form of an instruction, but usually not the shorter forms (especially for branches).

6.32.9 ARM Assembler

The ARM assembler includes all instruction of ARM architecture version 4, and the BLX instruction from architecture 5. It does not (yet) have support for Thumb instructions. It also lacks support for any co-processors.

The assembler uses a postfix syntax with the same operand order as used in the ARM Architecture Reference Manual. Mnemonics are suffixed by a comma.

Registers are specified by their names `r0` through `r15`, with the aliases `pc`, `lr`, `sp`, `ip` and `fp` provided for convenience. Note that `ip` refers to the “intra procedure call scratch register” (`r12`) and does not refer to an instruction pointer. `sp` refers to the ARM ABI stack pointer (`r13`) and not the Forth stack pointer.

Condition codes can be specified anywhere in the instruction, but will be most readable if specified just in front of the mnemonic. The ‘S’ flag is not a separate word, but encoded into instruction mnemonics, ie. just use `adds`, instead of `add`, if you want the status register to be updated.

The following table lists the syntax of operands for general instructions:

Gforth	normal assembler	description
123 #	#123	immediate
r12	r12	register
r12 4 #LSL	r12, LSL #4	shift left by immediate
r12 r1 LSL	r12, LSL r1	shift left by register
r12 4 #LSR	r12, LSR #4	shift right by immediate
r12 r1 LSR	r12, LSR r1	shift right by register
r12 4 #ASR	r12, ASR #4	arithmetic shift right
r12 r1 ASR	r12, ASR r1	... by register
r12 4 #ROR	r12, ROR #4	rotate right by immediate
r12 r1 ROR	r12, ROR r1	... by register
r12 RRX	r12, RRX	rotate right with extend by 1

Memory operand syntax is listed in this table:

Gforth	normal assembler	description
r4]	[r4]	register
r4 4 #]	[r4, #+4]	register with immediate offset
r4 -4 #]	[r4, #-4]	with negative offset
r4 r1 +]	[r4, +r1]	register with register offset
r4 r1 -]	[r4, -r1]	with negated register offset
r4 r1 2 #LSL -]	[r4, -r1, LSL #2]	with negated and shifted offset
r4 4 #]!	[r4, #+4]!	immediate preincrement
r4 r1 +]!	[r4, +r1]!	register preincrement
r4 r1 -]!	[r4, +r1]!	register predecrement
r4 r1 2 #LSL +]!	[r4, +r1, LSL #2]!	shifted preincrement
r4 -4]#	[r4], #-4	immediate postdecrement
r4 r1]+	[r4], r1	register postincrement
r4 r1]-	[r4], -r1	register postdecrement
r4 r1 2 #LSL]-	[r4], -r1, LSL #2	shifted postdecrement
' xyz >body [#]	xyz	PC-relative addressing

Register lists for load/store multiple instructions are started and terminated by using the words { and } respectively. Between braces, register names can be listed one by one or register ranges can be formed by using the postfix operator r-r. The ^ flag is not encoded in the register list operand, but instead directly encoded into the instruction mnemonic, ie. use ^ldm, and ^stm,.

Addressing modes for load/store multiple are not encoded as instruction suffixes, but instead specified like an addressing mode. Use one of DA, IA, DB, IB, DA!, IA!, DB! or IB!.

The following table gives some examples:

Gforth	normal assembler
r4 ia { r0 r7 r8 } stm,	stmia r4, {r0,r7,r8}
r4 db! { r0 r7 r8 } ldm,	ldmdb r4!, {r0,r7,r8}
sp ia! { r0 r15 r-r } ^ldm,	ldmfd sp!, {r0-r15}^

Control structure words typical for Forth assemblers are available: if, ahead, then, else, begin, until, again, while, repeat, repeat-until,. Conditions are specified in front of these words:

```

r1 r2 cmp,    \ compare r1 and r2
eq if,        \ equal?
...           \ code executed if r1 == r2
then,

```

Example of a definition using the ARM assembler:

```

abi-code my+ ( n1 n2 -- n3 )
  \ arm abi: r0=SP, r1=&FP, r2,r3,r12 saved by caller
  r0 IA! { r2 r3 } ldm,    \ pop r2 = n2, r3 = n1
  r3 r2 r3          add,    \ r3 = n1+n1
  r3 r0 -4 #]!      str,    \ push r3
  pc lr            mov,    \ return to caller, new SP in r0
end-code

```

6.32.10 Other assemblers

If you want to contribute another assembler/disassembler, please contact us (anton@mips.complang.tuwien.ac.at) to check if we have such an assembler already. If you are writing them from scratch, please use a similar syntax style as the one we use (i.e., postfix, commas at the end of the instruction names, see [\[Common Assembler\]](#), page [\[undefined\]](#)); make the output of the disassembler be valid input for the assembler, and keep the style similar to the style we used.

Hints on implementation: The most important part is to have a good test suite that contains all instructions. Once you have that, the rest is easy. For actual coding you can take a look at `arch/mips/disasm.fs` to get some ideas on how to use data for both the assembler and disassembler, avoiding redundancy and some potential bugs. You can also look at that file (and see [\[Advanced does> usage example\]](#), page [\[undefined\]](#)) to get ideas how to factor a disassembler.

Start with the disassembler, because it's easier to reuse data from the disassembler for the assembler than the other way round.

For the assembler, take a look at `arch/alpha/asm.fs`, which shows how simple it can be.

6.33 Carnal words

These words deal with the mechanics of Gforth (in Forth circles called “carnal knowledge” of a Forth system), but we consider them stable enough to document them.

6.33.1 Header fields

In Gforth 1.0 we switched to a new word header layout. For a detailed description, read: Bernd Paysan and M. Anton Ertl. *The new Gforth header* (<http://www.euroforth.org/ef19/papers/paysan.pdf>). In 35th EuroForth Conference, pages 5-20, 2019. Since this paper was published, xt and nt have been changed to point to the parameter field, like the body, but otherwise it is still up-to-date.

This section explains just the data structure and the words used to access it. A header has the following fields:

```

name

```

```

>f+c
>link
>cfa
>namehm
>body

```

Currently Gforth has the names shown above for getting from the xt/nt/body to the field, but apart from the standard **>body** they are not stable Gforth words. Instead, we provide access words. Note that the documented access words have survived the reorganization of the header layout.

Some of the words expect an nt, some expect an xt. Given that both nt and xt point to the body of a word, what is the difference? For most words, the xt and nt use the same header, and with nt=xt, they point to the same place. However, for a synonym (see [\(undefined\)](#) [Synonyms], page [\(undefined\)](#)) there is a difference; consider the example

```

create x
synonym y x
synonym z y

```

In this case the nt of **z** points to the body of **z**, while the xt of **z** points to the body of **x**. Words defined with **alias** or **forward** (see [\(undefined\)](#) [Calls and returns], page [\(undefined\)](#)) also have different nts and xts.

The name field is variable-length and is accessed with **name>string** (see [\(undefined\)](#) [Name token], page [\(undefined\)](#)).

The **>f+c** field contains flags and the name length (count). You read the count with **name>string**, and the flags with

compile-only? (*nt* – *flag*) gforth-1.0 “compile-only?”

true if *nt* is marked as compile-only.

The **>link** field contains a link to the previous word in the same word list. You can read it with **name>link** (see [\(undefined\)](#) [Name token], page [\(undefined\)](#)).

The name, **>f+c** and **>link** fields are not present for **noname** words, but **name>string** and **name>link** work nevertheless, producing 0 0 and 0, respectively.

The **>cfa** field (aka code field) contains the code address used for **execute**ing the word; you can read it with **>code-address** and write it with **code-address!** (see [\(undefined\)](#) [Threading Words], page [\(undefined\)](#)).

The **>namehm** field contains the address of the header methods table, described below. You access it by performing or accessing header methods (see [\(undefined\)](#) [Header methods], page [\(undefined\)](#)).

The **>body** (aka parameter) field contains data or threaded code specific to the word type; its length depends on the word type. E.g., for a **constant** it contains a cell with the value of the constant. You can access it through **>body** (see [\(undefined\)](#) [CREATE..DOES> details], page [\(undefined\)](#)), but this is only standard for words you defined with **create**.

6.33.2 Header methods

The new Gforth word header is object-oriented and supports the following methods (method selectors):

.hm label method	overrider	field
-------------------------	------------------	--------------

	execute	set-execute	>cfa
opt:	opt-compile,	set-optimizer	>hmcompile,
to:	(to)	set-to	>hmto
extra:			>hmextra
>int:	name>interpret	set->int	>hm>int
>comp:	name>compile	set->comp	>hm>comp
>string:	name>string	set-name>string	>hm>string
>link:	name>link	set-name>link	>hm>link

Many of these words are not stable Gforth words, but Gforth has stable higher-level words that we mention below.

You can look at the header methods of a word with

```
.hm ( nt - ) gforth-1.0 "dot-h-m"
```

print the header methods of *nt*

Overrider (setter) words change the method implementation for the most recent definition. Quotations or closures restore the previous most recent definition when they are completed, so they are not considered most recent, and you can do things like:

```
: my2dup over over ;
[: drop ] over over [[: ] set-optimizer
```

The **execute** method is actually stored in the **>cfa** field in the header rather than in the header-methods table for performance reasons; also it is implemented through a native-code address, while the other methods are implemented by calling an xt. The high-level way to set this method is

```
set-execute ( ca - ) gforth-1.0 "set-execute"
```

Changes the current word such that it jumps to the native code at *ca*. Also changes the **compile**, implementation to the most general (and slowest) one. Call **set-optimizer** afterwards if you want a more efficient **compile**, implementation.

To get a code address for use with **set-execute**, you can use words like **docol:** or **>code-address**, See [\(undefined\)](#) [Threading Words], page [\(undefined\)](#).

As an alternative to **set-execute**, there is also **set-does>** (see [\(undefined\)](#) [User-defined Defining Words], page [\(undefined\)](#)), which takes an xt.

Moreover, there are the low-level **code-address!** and **definer!** (see [\(undefined\)](#) [Threading Words], page [\(undefined\)](#)).

The **opt-compile**, method is what **compile**, does on most Gforth engines (**gforth-itc** uses **,** instead). You can define a more efficient implementation of **compile**, for the current word with **set-optimizer** (see [\(undefined\)](#) [User-defined compile-comma], page [\(undefined\)](#)). Note that the end result must be equivalent to **postpone literal postpone execute**.

As an example of the use of **set-optimizer**, consider the following definition of **constant**:

```
: constant ( n "name" -- ; name: -- n )
  create ,
  ['] @ set-does>
;
```

```
5 constant five
: foo five ; see foo
```

The Forth system does not know that the value of a constant must not be changed, and just sees a **created** word (which can be changed with **>body**), and **foo** first pushes the body address of **five** and then fetches from there. With **set-optimizer** the definition of **constant** can be optimized as follows:

```
: constant ( n "name" -- ; name: -- n )
  create ,
  ['] @ set-does>
  [: >body @ postpone literal ;] set-optimizer
;
```

Now **foo** contains the literal 5 rather than a call to **five**.

Note that **set-execute** and **set-does>** perform **set-optimizer** themselves in order to ensure that **execute** and **compile**, agree, so if you want to add your own optimizer, you should add it afterwards.

The **(to)** method and **set-to** are used for implementing **to name** semantics etc. (see **<undefined>** [Words with user-defined TO etc.], page **<undefined>**).

The **>hmextra** field is used for cases where additional data needs to be stored in the header methods table. In particular, it stores the xt passed to **set-does>** (and **does>** calls **set-does>**) and the code address behind **;abi-code**.

The methods above all consume an xt, not an nt, but the override words work on the most recent definition. This means that if you use, e.g., **set-optimizer** on a synonym, the effect will probably not be what you intended: When **compile**,ing the xt of the word, the **opt-compile**, implementation of the original word will be used, not the freshly-set one of the synonym.

The following methods consume an nt.

The **name>interpret** method is implemented as noop for most words, except synonyms and similar words.

```
set->int ( xt - ) gforth-1.0 "set-to-int"
```

Sets the implementation of the **name>interpret (nt -- xt2)** method of the current word to *xt*.

The **name>compile** method produces the compilation semantics of the nt. By changing it with **set->comp**, you can change the compilation semantics, but it's not as simple as just pushing the xt of the desired compilation semantics, because of the stack effect of **name>compile**. Generally you should avoid changing the compilation semantics, and if you do, use a higher-level word like **immediate** or **interpret/compile:**, See **<undefined>** [Combined words], page **<undefined>**.

```
set->comp ( xt - ) gforth-1.0 "set-to-comp"
```

Sets the implementation of the **name>compile (nt -- w xt2)** method of the current word to *xt*.

```
immediate? ( nt - flag ) gforth-1.0 "immediate?"
```

true if the word *nt* has non-default compilation semantics (that's not quite according to the definition of immediacy, but many people mean that when they call a word "immediate").

Name>string and **Name>link** are methods in order to make it possible to eliminate the name, **>f+c** and **link** fields from noname headers, but still produce meaningful results when using these words. You will typically not change the implementations of these methods except with **noname**, but we still have

set-name>string (*xt* -) gforth-1.0 "set-name-to-string"

Sets the implementation of the **name>string** (*nt* -- *addr u*) method of the current word to *xt*.

set-name>link (*xt* -) gforth-1.0 "set-name-to-link"

Sets the implementation of the **name>link** (*nt1* -- *nt2|0*) method of the current word to *xt*.

6.33.3 Threading Words

The terminology used here stems from indirect threaded Forth systems; in such a system, the XT of a word is represented by the CFA (code field address) of a word; the CFA points to a cell that contains the code address. The code address is the address of some machine code that performs the run-time action of invoking the word (e.g., the **dovar:** routine pushes the address of the body of the word (a variable) on the stack).

These words provide access to code fields, code addresses and other threading stuff in Gforth. It more or less abstracts away the differences between direct and indirect threading.

Up to and including Gforth 0.7, the code address (plus, for **does>**-defined words, the address returned by **>does-code**) was sufficient to know the type of the word. However, since Gforth-1.0 the behaviour or at least implementation of words like **compile**, and **name>compile** can be determined independently as described in [\(undefined\)](#) [Header methods], page [\(undefined\)](#).

To create a code field and at the same time initialize the header methods use **create-from** (see [\(undefined\)](#) [Creating from a prototype], page [\(undefined\)](#)).

The following words were designed before the introduction of header methods, and are therefore not the best (and recommended) way to deal with different word types in Gforth.

In an indirect threaded Forth, you can get the code address of *name* with ' **name @**; in Gforth you can get it with ' **name >code-address**, independent of the threading method.

threading-method (- *n*) gforth-0.2 "threading-method"

0 if the engine is direct threaded. Note that this may change during the lifetime of an image.

>code-address (*xt* - *c_addr*) gforth-0.2 ">code-address"

c_addr is the code address of the word *xt*.

code-address! (*c_addr xt* -) gforth-obsolete "code-address!"

Change a code field with code address *c_addr* at *xt*.

The code addresses produced by various defining words are produced by the following words:

docol: (- *addr*) gforth-0.2 "docol:"

The code address of a colon definition.

`docon: (- addr) gforth-0.2 “docon:”`

The code address of a `CONSTANT`.

`dovar: (- addr) gforth-0.2 “dovar:”`

The code address of a `CREATED` word.

`douser: (- addr) gforth-0.2 “douser:”`

The code address of a `USER` variable.

`dodefer: (- addr) gforth-0.2 “dodefer:”`

The code address of a `deferred` word.

`dofield: (- addr) gforth-0.2 “dofield:”`

The code address of a `field`.

`dovalue: (- addr) gforth-0.7 “dovalue:”`

The code address of a `CONSTANT`.

`dodoes: (- addr) gforth-0.6 “dodoes:”`

The code address of a `DOES>`-defined word.

`doabicode: (- addr) gforth-1.0 “doabicode:”`

The code address of a `ABI-CODE` definition.

For a word *X* defined with `set-does>`, the code address points to `dodoes:`, and the `>hmextra` field of the header methods contains the xt of the word that is called after pushing the body address of *X*.

If you want to know whether a word is a `DOES>`-defined word, and what Forth code it executes, `>does-code` tells you that:

`>does-code (xt1 - xt2) gforth-0.2 “>does-code”`

If *xt1* is the execution token of a child of a `set-does>`-defined word, *xt2* is the xt passed to `set-does>`, i.e, the xt of the word that is executed when executing *xt1* (but first the body address of *xt1* is pushed). If *xt1* does not belong to a `set-does>`-defined word, *xt2* is 0.

You can use the resulting *xt2* with `set-does>` (preferred) to change the latest word or with

`does-code! (xt2 xt1 -) gforth-0.2 “does-code!”`

Change *xt1* to be a *xt2* `set-does>`-defined word.

to change an arbitrary word.

The following two words generalize `>code-address`, `>does-code`, `code-address!`, and `does-code!`:

`>definer (xt - definer) gforth-0.2 “>definer”`

Definer is a unique identifier for the way the *xt* was defined. Words defined with different `does>`-codes have different definers. The definer can be used for comparison and in `definer!`.

`definer! (definer xt -) gforth-obsolete “definer!”`

The word represented by *xt* changes its behaviour to the behaviour associated with *definer*.

`Code-address!`, `does-code!`, and `definer!` update the `opt-compile`, method to a somewhat generic compiler for that word type (in particular, primitives get the slow `general-compile`, method rather than the primitive-specific `peephole-compile`,).

6.34 Passing Commands to the Operating System

Gforth allows you to pass an arbitrary string to the host operating system shell (if such a thing exists) for execution.

`sh ("... " -) gforth-0.2 "sh"`

Execute the rest of the command line as shell command(s). Afterwards, `$?` produces the exit status of the command.

`system (c-addr u -) gforth-0.2 "system"`

Pass the string specified by `c-addr u` to the host operating system for execution in a sub-shell. Afterwards, `$?` produces the exit status of the command. The value of the environment variable `GFORTHSYSTEMPREFIX` (or its default value) is prepended to the string (mainly to support using `command.com` as shell in Windows instead of whatever shell Cygwin uses by default; see [\(undefined\) \[Environment variables\]](#), page [\(undefined\)](#)).

`sh-get (c-addr u - c-addr2 u2) gforth-1.0 "sh-get"`

Run the shell command `addr u`; `c-addr2 u2` is the output of the command. The exit code is in `$?`, the output also in `sh$ 20`.

`$? (- n) gforth-0.2 "dollar-question"`

Value – the exit status returned by the most recently executed `system` command.

`getenv (c-addr1 u1 - c-addr2 u2) gforth-0.2 "getenv"`

The string `c-addr1 u1` specifies an environment variable. The string `c-addr2 u2` is the host operating system’s expansion of that environment variable. If the environment variable does not exist, `c-addr2 u2` specifies a string 0 characters in length.

6.35 Keeping track of Time

`ms (n -) facility-ext "ms"`

`ns (d -) gforth-1.0 "ns"`

`time&date (- nsec nmin nhour nday nmonth nyear) facility-ext "time-and-date"`

Report the current time of day. Seconds, minutes and hours are numbered from 0. Months are numbered from 1.

`>time&date&tz (udtime - nsec nmin nhour nday nmonth nyear fdst ndstoffs c-addr tz) gforth-1.0 "to-time-and-date"`

Convert time in seconds since 1.1.1970 0:00Z to the current time of day. Seconds, minutes and hours are numbered from 0. Months are numbered from 1.

`utime (- dtime) gforth-0.5 "utime"`

Report the current time in microseconds since some epoch. Use `#1000000 um/mod nip` to convert to seconds

`ntime (- dtime) gforth-1.0 "ntime"`

Report the current time in nanoseconds since some epoch.

`cputime (- duser dsystem) gforth-0.5 "cputime"`

duser and dsystem are the respective user- and system-level CPU times used since the start of the Forth system (excluding child processes), in microseconds (the granularity may be much larger, however). On platforms without the getrusage call, it reports elapsed time (since some epoch) for duser and 0 for dsystem.

6.36 Miscellaneous Words

This section lists the Standard Forth words that are not documented elsewhere in this manual. Ultimately, they all need proper homes.

quit (?? - ??) core “quit”

Empty the return stack, make the user input device the input source, enter interpret state and start the text interpreter.

The following Standard Forth words are not currently supported by Gforth (see <undefined> [Standard conformance], page <undefined>):

EDITOR EMIT? FORGET

7 Error messages

A typical Gforth error message looks like this:

```
in file included from \evaluated string/:-1
in file included from ./yyy.fs:1
./xxx.fs:4: Invalid memory address
>>>bar<<<
Backtrace:
$400E664C @
$400E6664 foo
```

The message identifying the error is **Invalid memory address**. The error happened when text-interpreting line 4 of the file `./xxx.fs`. This line is given (it contains `bar`), and the word on the line where the error happened, is pointed out (with `>>>` and `<<<`).

The file containing the error was included in line 1 of `./yyy.fs`, and `yyy.fs` was included from a non-file (in this case, by giving `yyy.fs` as command-line parameter to Gforth).

At the end of the error message you find a return stack dump that can be interpreted as a backtrace (possibly empty). On top you find the top of the return stack when the **throw** happened, and at the bottom you find the return stack entry just above the return stack of the topmost text interpreter.

To the right of most return stack entries you see a guess for the word that pushed that return stack entry as its return address. This gives a backtrace. In our case we see that `bar` called `foo`, and `foo` called `@` (and `@` had an *Invalid memory address* exception).

Note that the backtrace is not perfect: We don't know which return stack entries are return addresses (so we may get false positives); and in some cases (e.g., for **abort**) we cannot determine from the return address the word that pushed the return address, so for some return addresses you see no names in the return stack dump.

The return stack dump represents the return stack at the time when a specific **throw** was executed. In programs that make use of **catch**, it is not necessarily clear which **throw** should be used for the return stack dump (e.g., consider one **throw** that indicates an error, which is caught, and during recovery another error happens; which **throw** should be used for the stack dump?). Gforth presents the return stack dump for the first **throw** after the last executed (not returned-to) **catch** or **nothrow**; this works well in the usual case. To get the right backtrace, you usually want to insert **nothrow** or `['] false catch 2drop` after a **catch** if the error is not rethrown.

Gforth is able to do a return stack dump for throws generated from primitives (e.g., invalid memory address, stack empty etc.); **gforth-fast** is only able to do a return stack dump from a directly called **throw** (including **abort** etc.). Given an exception caused by a primitive in **gforth-fast**, you will typically see no return stack dump at all; however, if the exception is caught by **catch** (e.g., for restoring some state), and then **thrown** again, the return stack dump will be for the first such **throw**.

gforth-fast also does not attempt to differentiate between division by zero and division overflow, because that costs time in every division.

8 Tools

See also [\[Emacs and Gforth\]](#), page [\[undefined\]](#).

8.1 `ans-report.fs`: Report the words used, sorted by wordset

If you want to label a Forth program as Standard Program, you must document which wordsets the program uses.

The `ans-report.fs` tool makes it easy for you to determine which words from which wordset and which non-standard words your application uses. You simply have to include `ans-report.fs` before loading the program you want to check. After loading your program, you can get the report with `print-ans-report`. A typical use is to run this as batch job like this:

```
gforth ans-report.fs myprog.fs -e "print-ans-report bye"
```

The output looks like this (for `compat/control.fs`):

```
The program uses the following words
from CORE :
: POSTPONE THEN ; immediate ?dup IF 0=
from BLOCK-EXT :
\
from FILE :
(
```

`ans-report.fs` reports both Forth-94 and Forth-2012 wordsets. For words that are in both standards, it reports the wordset without suffix (e.g., `CORE-EXT`). For Forth-2012-only words, it reports the wordset with a `-2012` suffix (e.g., `CORE-EXT-2012`); and likewise for the words that are Forth-94-only (i.e., that have been removed in Forth-2012).

8.1.1 Caveats

Note that `ans-report.fs` just checks which words are used, not whether they are used in a standard-conforming way!

Some words are defined in several wordsets in the standard. `ans-report.fs` reports them for only one of the wordsets, and not necessarily the one you expect. It depends on usage which wordset is the right one to specify. E.g., if you only use the compilation semantics of `S`, it is a Core word; if you also use its interpretation semantics, it is a File word.

8.2 Stack depth changes during interpretation

Sometimes you notice that, after loading a file, there are items left on the stack. The tool `depth-changes.fs` helps you find out quickly where in the file these stack items are coming from.

The simplest way of using `depth-changes.fs` is to include it before the file(s) you want to check, e.g.:

```
gforth depth-changes.fs my-file.fs
```

This will compare the stack depths of the data and FP stack at every empty line (in interpretation state) against these depths at the last empty line (in interpretation state). If the depths are not equal, the position in the file and the stack contents are printed with `~~` (see [\[Debugging\]](#), page [\(undefined\)](#)). This indicates that a stack depth change has occurred in the paragraph of non-empty lines before the indicated line. It is a good idea to leave an empty line at the end of the file, so the last paragraph is checked, too.

Checking only at empty lines usually works well, but sometimes you have big blocks of non-empty lines (e.g., when building a big table), and you want to know where in this block the stack depth changed. You can check all interpreted lines with

```
gforth depth-changes.fs -e "" all-lines is depth-changes-filter" my-file.fs■
```

This checks the stack depth at every end-of-line. So the depth change occurred in the line reported by the `~~` (not in the line before).

Note that, while this offers better accuracy in indicating where the stack depth changes, it will often report many intentional stack depth changes (e.g., when an interpreted computation stretches across several lines). You can suppress the checking of some lines by putting backslashes at the end of these lines (not followed by white space), and using

```
gforth depth-changes.fs -e "" most-lines is depth-changes-filter" my-file.fs■
```

9 Standard conformance

To the best of our knowledge, Gforth is a

ANS Forth System and a Forth-2012 System

- providing the Core Extensions word set
- providing the Block word set
- providing the Block Extensions word set
- providing the Double-Number word set
- providing the Double-Number Extensions word set
- providing the Exception word set
- providing the Exception Extensions word set
- providing the Facility word set
- providing the Facility Extensions word set, except `EMIT?`
- providing the File Access word set
- providing the File Access Extensions word set
- providing the Floating-Point word set
- providing the Floating-Point Extensions word set
- providing the Locals word set
- providing the Locals Extensions word set
- providing the Memory-Allocation word set
- providing the Memory-Allocation Extensions word set
- providing the Programming-Tools word set
- providing the Programming-Tools Extensions word set, except `EDITOR` and `FORGET`
- providing the Search-Order word set
- providing the Search-Order Extensions word set
- providing the String word set
- providing the String Extensions word set
- providing the Extended-Character wordset

Gforth has the following environmental restrictions:

- While processing the OS command line, if an exception is not caught, Gforth exits with a non-zero exit code instead of performing `QUIT`.
- When an `throw` is performed after a `query`, Gforth does not always restore the input source specification in effect at the corresponding catch.

In addition, Standard Forth systems are required to document certain implementation choices. This chapter tries to meet these requirements for the Forth-94 standard. For the Forth-2012 standard, we decided to produce the additional documentation only if there is demand. So if you are really missing this documentation, please let us know.

In many cases, the following documentation gives a way to ask the system for the information instead of providing the information directly, in particular, if the information depends on the processor, the operating system or the installation options chosen, or if they are likely to change during the maintenance of Gforth.

9.1 The Core Words

9.1.1 Implementation Defined Options

(Cell) aligned addresses:

processor-dependent. Gforth's alignment words perform natural alignment (e.g., an address aligned for a datum of size 8 is divisible by 8). Unaligned accesses usually result in a `-23 THROW`.

EMIT and *non-graphic characters*:

The character is output using the C library function (actually, macro) `putc`.

character editing of ACCEPT and EXPECT:

This is modeled on the GNU readline library (see Section “Command Line Editing” in *The GNU Readline Library*) with Emacs-like key bindings. **Tab** deviates a little by producing a full word completion every time you type it (instead of producing the common prefix of all completions). See `<undefined>` [Command-line editing], page `<undefined>`.

character set:

The character set of your computer and display device. Gforth is 8-bit-clean (but some other component in your system may make trouble).

Character-aligned address requirements:

installation-dependent. Currently a character is represented by a C **unsigned char**; in the future we might switch to **wchar_t** (Comments on that requested).

character-set extensions and matching of names:

Any character except the ASCII NUL character can be used in a name. Matching is case-insensitive (except in **TABLES**). The matching is performed using the C library function `strncasecmp`, whose function is probably influenced by the locale. E.g., the C locale does not know about accents and umlauts, so they are matched case-sensitively in that locale. For portability reasons it is best to write programs such that they work in the C locale. Then one can use libraries written by a Polish programmer (who might use words containing ISO Latin-2 encoded characters) and by a French programmer (ISO Latin-1) in the same program (of course, **WORDS** will produce funny results for some of the words (which ones, depends on the font you are using)). Also, the locale you prefer may not be available in other operating systems. Hopefully, Unicode will solve these problems one day.

conditions under which control characters match a space delimiter:

If **word** is called with the space character as a delimiter, all white-space characters (as identified by the C macro `isspace()`) are delimiters. **Parse**, on the other hand, treats space like other delimiters. **Parse-name**, which is used by the outer interpreter (aka text interpreter) by default, treats all white-space characters as delimiters.

format of the control-flow stack:

The data stack is used as control-flow stack. The size of a control-flow stack item in cells is given by the constant `cs-item-size`. At the time of this writing,

an item consists of a (pointer to a) locals list (third), an address in the code (second), and a tag for identifying the item (TOS). The following tags are used: `defstart`, `live-orig`, `dead-orig`, `dest`, `do-dest`, `scopestart`.

conversion of digits > 35

The characters `[\]^_'` are the digits with the decimal value 36–41. There is no way to input many of the larger digits.

display after input terminates in ACCEPT and EXPECT:

The cursor is moved to the end of the entered string. If the input is terminated using the **Return** key, a space is typed.

exception abort sequence of ABORT":

The error string is stored into the variable `abort-string` and a `-2 throw` is performed.

input line terminator:

For interactive input, `C-m` (CR) and `C-j` (LF) terminate lines. One of these characters is typically produced when you type the **Enter** or **Return** key.

maximum size of a counted string:

`s" /counted-string" environment? drop ..` Currently 255 characters on all platforms, but this may change.

maximum size of a parsed string:

Given by the constant `/line`. Currently 255 characters.

maximum size of a definition name, in characters:

`MAXU/8`

maximum string length for ENVIRONMENT?, in characters:

`MAXU/8`

method of selecting the user input device:

The user input device is the standard input. There is currently no way to change it from within Gforth. However, the input can typically be redirected in the command line that starts Gforth.

method of selecting the user output device:

`EMIT` and `TYPE` output to the file-id stored in the value `outfile-id` (`stdout` by default). Gforth uses unbuffered output when the user output device is a terminal, otherwise the output is buffered.

methods of dictionary compilation:

What are we expected to document here?

number of bits in one address unit:

`s" address-units-bits" environment? drop ..` 8 in all current platforms.

number representation and arithmetic:

Processor-dependent. Binary two's complement on all current platforms.

ranges for integer types:

Installation-dependent. Make environmental queries for `MAX-N`, `MAX-U`, `MAX-D` and `MAX-UD`. The lower bounds for unsigned (and positive) types is 0. The lower

bound for signed types on two's complement and one's complement machines can be computed by adding 1 to the upper bound.

read-only data space regions:

The whole Forth data space is writable.

size of buffer at WORD:

PAD HERE - .. 104 characters on 32-bit machines. The buffer is shared with the pictured numeric output string. If overwriting **PAD** is acceptable, it is as large as the remaining dictionary space, although only as much can be sensibly used as fits in a counted string.

size of one cell in address units:

1 cells ..

size of one character in address units:

1 chars .. 1 on all current platforms.

size of the keyboard terminal buffer:

Varies. You can determine the size at a specific time using **lp@tib** - .. It is shared with the locals stack and TIBs of files that include the current file. You can change the amount of space for TIBs and locals stack at Gforth startup with the command line option **-l**.

size of the pictured numeric output buffer:

PAD HERE - .. 104 characters on 32-bit machines. The buffer is shared with **WORD**.

size of the scratch area returned by PAD:

The remainder of dictionary space. **unused pad here** - - ..

system case-sensitivity characteristics:

Dictionary searches are case-insensitive (except in **TABLEs**). However, as explained above under *character-set extensions*, the matching for non-ASCII characters is determined by the locale you are using. In the default **C** locale all non-ASCII characters are matched case-sensitively.

system prompt:

ok in interpret state, **compiled** in compile state.

division rounding:

The ordinary division words **/mod** **/mod*** ***/mod** perform floored division (with the default installation of Gforth). You can check this with **s" floored" environment? drop** .. If you write programs that need a specific division rounding, best use **fm/mod** or **sm/rem** for portability.

values of STATE when true:

-1.

values returned after arithmetic overflow:

On two's complement machines, arithmetic is performed modulo $2^{**}\text{bits-per-cell}$ for single arithmetic and $4^{**}\text{bits-per-cell}$ for double arithmetic (with appropriate mapping for signed types). Division by zero typically results in a **-55 throw** (Floating-point unidentified fault) or **-10 throw** (divide by zero). Integer

division overflow can result in these throws, or in `-11 throw`; in `gforth-fast` division overflow and divide by zero may also result in returning bogus results without producing an exception.

whether the current definition can be found after DOES>:

No.

9.1.2 Ambiguous conditions

a name is neither a word nor a number:

`-13 throw` (Undefined word).

a definition name exceeds the maximum length allowed:

`-19 throw` (Word name too long)

addressing a region not inside the various data spaces of the forth system:

The stacks, code space and header space are accessible. Machine code space is typically readable. Accessing other addresses gives results dependent on the operating system. On decent systems: `-9 throw` (Invalid memory address).

argument type incompatible with parameter:

This is usually not caught. Some words perform checks, e.g., the control flow words, and issue a `ABORT` or `-12 THROW` (Argument type mismatch).

attempting to obtain the execution token of a word with undefined execution semantics:

The execution token represents the interpretation semantics of the word. Gforth defines interpretation semantics for all words; for words where the standard does not define interpretation semantics, but defines the execution semantics (except `LEAVE`), the interpretation semantics are to perform the execution semantics. For words where the standard defines no interpretation semantics, but defined compilation semantics (plus `LEAVE`), the interpretation semantics are to perform the compilation semantics. Some words are marked as compile-only, and ' gives a warning for these words.

dividing by zero:

On some platforms, this produces a `-10 throw` (Division by zero); on other systems, this typically results in a `-55 throw` (Floating-point unidentified fault).

insufficient data stack or return stack space:

Depending on the operating system, the installation, and the invocation of Gforth, this is either checked by the memory management hardware, or it is not checked. If it is checked, you typically get a `-3 throw` (Stack overflow), `-5 throw` (Return stack overflow), or `-9 throw` (Invalid memory address) (depending on the platform and how you achieved the overflow) as soon as the overflow happens. If it is not checked, overflows typically result in mysterious illegal memory accesses, producing `-9 throw` (Invalid memory address) or `-23 throw` (Address alignment exception); they might also destroy the internal data structure of `ALLOCATE` and friends, resulting in various errors in these words.

insufficient space for loop control parameters:

Like other return stack overflows.

insufficient space in the dictionary:

If you try to allot (either directly with `allot`, or indirectly with `,`, `create` etc.) more memory than available in the dictionary, you get a `-8 throw` (Dictionary overflow). If you try to access memory beyond the end of the dictionary, the results are similar to stack overflows.

interpreting a word with undefined interpretation semantics:

Gforth defines interpretation semantics for all words; for words where the standard defines execution semantics (except `LEAVE`), the interpretation semantics are to perform the execution semantics. For words where the standard defines no interpretation semantics, but defined compilation semantics (plus `LEAVE`), the interpretation semantics are to perform the compilation semantics. Some words are marked as compile-only, and text-interpreting them gives a warning.

modifying the contents of the input buffer or a string literal:

These are located in writable memory and can be modified.

overflow of the pictured numeric output string:

`-17 throw` (Pictured numeric output string overflow).

parsed string overflow:

`PARSE` cannot overflow. `WORD` does not check for overflow.

producing a result out of range:

On two's complement machines, arithmetic is performed modulo $2^{\text{bits-per-cell}}$ for single arithmetic and $4^{\text{bits-per-cell}}$ for double arithmetic (with appropriate mapping for signed types). Division by zero typically results in a `-10 throw` (divide by zero) or `-55 throw` (floating point unidentified fault). Overflow on division may result in these errors or in `-11 throw` (result out of range). `Gforth-fast` may silently produce bogus results on division overflow or division by zero. `Convert` and `>number` currently overflow silently.

reading from an empty data or return stack:

The data stack is checked by the outer (aka text) interpreter after every word executed. If it has underflowed, a `-4 throw` (Stack underflow) is performed. Apart from that, stacks may be checked or not, depending on operating system, installation, and invocation. If they are caught by a check, they typically result in `-4 throw` (Stack underflow), `-6 throw` (Return stack underflow) or `-9 throw` (Invalid memory address), depending on the platform and which stack underflows and by how much. Note that even if the system uses checking (through the MMU), your program may have to underflow by a significant number of stack items to trigger the reaction (the reason for this is that the MMU, and therefore the checking, works with a page-size granularity). If there is no checking, the symptoms resulting from an underflow are similar to those from an overflow. Unbalanced return stack errors can result in a variety of symptoms, including `-9 throw` (Invalid memory address) and Illegal Instruction (typically `-260 throw`).

unexpected end of the input buffer, resulting in an attempt to use a zero-length string as a name:

`Create` and its descendants perform a `-16 throw` (Attempt to use zero-length string as a name). Words like `'` probably will not find what they search. Note that it is possible to create zero-length names with `nextname` (should it not?).

>IN greater than input buffer:

The next invocation of a parsing word returns a string with length 0.

RECURSE appears after DOES>:

Compiles a recursive call to the code after `DOES>`.

argument input source different than current input source for RESTORE-INPUT:

`-12 THROW`. Note that, once an input file is closed (e.g., because the end of the file was reached), its source-id may be reused. Therefore, restoring an input source specification referencing a closed file may lead to unpredictable results instead of a `-12 THROW`.

In the future, Gforth may be able to restore input source specifications from other than the current input source.

data space containing definitions gets de-allocated:

Deallocation with `allot` is not checked. This typically results in memory access faults or execution of illegal instructions.

data space read/write with incorrect alignment:

Processor-dependent. Typically results in a `-23 throw` (Address alignment exception). Under Linux-Intel on a 486 or later processor with alignment turned on, incorrect alignment results in a `-9 throw` (Invalid memory address). There are reportedly some processors with alignment restrictions that do not report violations.

data space pointer not properly aligned, ,, C,:

Like other alignment errors.

less than u+2 stack items (PICK and ROLL):

Like other stack underflows.

loop control parameters not available:

Not checked. The counted loop words simply assume that the top of return stack items are loop control parameters and behave accordingly.

most recent definition does not have a name (IMMEDIATE):

`abort` "last word was headerless".

name not defined by VALUE used by TO:

`-32 throw` (Invalid name argument) (unless name is a local or was defined by `CONSTANT`; in the latter case it just changes the constant).

name not found (' , POSTPONE, ['], [COMPILE]):

`-13 throw` (Undefined word)

parameters are not of the same type (DO, ?DO, WITHIN):

Gforth behaves as if they were of the same type. I.e., you can predict the behaviour by interpreting all parameters as, e.g., signed.

POSTPONE or **[COMPILE]** *applied to TO*:

Assume : X **POSTPONE TO** ; **IMMEDIATE**. X performs the compilation semantics of TO.

String longer than a counted string returned by WORD:

Not checked. The string will be ok, but the count will, of course, contain only the least significant bits of the length.

u greater than or equal to the number of bits in a cell (LSHIFT, RSHIFT):

Processor-dependent. Typical behaviours are returning 0 and using only the low bits of the shift count.

word not defined via CREATE:

>**BODY** produces the PFA of the word no matter how it was defined.

DOES> changes the execution semantics of the last defined word no matter how it was defined. E.g., **CONSTANT DOES>** is equivalent to **CREATE , DOES>**.

words improperly used outside <# and #>:

Not checked. As usual, you can expect memory faults.

9.1.3 Other system documentation

nonstandard words using PAD:

None.

operator's terminal facilities available:

After processing the OS's command line, Gforth goes into interactive mode, and you can give commands to Gforth interactively. The actual facilities available depend on how you invoke Gforth.

program data space available:

UNUSED . gives the remaining dictionary space. The total dictionary space can be specified with the **-m** switch (see <undefined> [Invoking Gforth], page <undefined>) when Gforth starts up.

return stack space available:

You can compute the total return stack space in cells with **s" RETURN-STACK-CELLS" environment? drop ..** You can specify it at startup time with the **-r** switch (see <undefined> [Invoking Gforth], page <undefined>).

stack space available:

You can compute the total data stack space in cells with **s" STACK-CELLS" environment? drop ..** You can specify it at startup time with the **-d** switch (see <undefined> [Invoking Gforth], page <undefined>).

system dictionary space required, in address units:

Type **here forthstart - .** after startup. At the time of this writing, this gives 80080 (bytes) on a 32-bit system.

9.2 The optional Block word set

9.2.1 Implementation Defined Options

the format for display by LIST:

First the screen number is displayed, then 16 lines of 64 characters, each line preceded by the line number.

the length of a line affected by \:

64 characters.

9.2.2 Ambiguous conditions

correct block read was not possible:

Typically results in a **throw** of some OS-derived value (between -512 and -2048). If the blocks file was just not long enough, blanks are supplied for the missing portion.

I/O exception in block transfer:

Typically results in a **throw** of some OS-derived value (between -512 and -2048).

invalid block number:

-35 **throw** (Invalid block number)

a program directly alters the contents of BLK:

The input stream is switched to that other block, at the same position. If the storing to BLK happens when interpreting non-block input, the system will get quite confused when the block ends.

no current block buffer for UPDATE:

UPDATE has no effect.

9.2.3 Other system documentation

any restrictions a multiprogramming system places on the use of buffer addresses:

No restrictions (yet).

the number of blocks available for source and data:

depends on your disk space.

9.3 The optional Double Number word set

9.3.1 Ambiguous conditions

d outside of range of n in D>S:

The least significant cell of *d* is produced.

9.4 The optional Exception word set

9.4.1 Implementation Defined Options

THROW-codes used in the system:

The codes -256--511 are used for reporting signals. The mapping from OS signal numbers to throw codes is -256--*signal*. The codes -512--2047 are used

for OS errors (for file and memory allocation operations). The mapping from OS error numbers to throw codes is `-512-errno`. One side effect of this mapping is that undefined OS errors produce a message with a strange number; e.g., `-1000 THROW` results in `Unknown error 488` on my system.

9.5 The optional Facility word set

9.5.1 Implementation Defined Options

encoding of keyboard events (EKEY):

Keys corresponding to ASCII characters are encoded as ASCII characters. Other keys are encoded with the constants `k-left`, `k-right`, `k-up`, `k-down`, `k-home`, `k-end`, `k1`, `k2`, `k3`, `k4`, `k5`, `k6`, `k7`, `k8`, `k9`, `k10`, `k11`, `k12`, `k-winch`, `k-eof`.

duration of a system clock tick:

System dependent. With respect to `MS`, the time is specified in microseconds. How well the OS and the hardware implement this, is another question.

repeatability to be expected from the execution of MS:

System dependent. On Unix, a lot depends on load. If the system is lightly loaded, and the delay is short enough that Gforth does not get swapped out, the performance should be acceptable. Under MS-DOS and other single-tasking systems, it should be good.

9.5.2 Ambiguous conditions

AT-XY can't be performed on user output device:

Largely terminal dependent. No range checks are done on the arguments. No errors are reported. You may see some garbage appearing, you may see simply nothing happen.

9.6 The optional File-Access word set

9.6.1 Implementation Defined Options

file access methods used:

`R/O`, `R/W` and `BIN` work as you would expect. `W/O` translates into the C file opening mode `w` (or `wb`): The file is cleared, if it exists, and created, if it does not (with both `open-file` and `create-file`). Under Unix `create-file` creates a file with 666 permissions modified by your `umask`.

file exceptions:

The file words do not raise exceptions (except, perhaps, memory access faults when you pass illegal addresses or file-ids).

file line terminator:

System-dependent. Gforth uses C's newline character as line terminator. What the actual character code(s) of this are is system-dependent.

file name format:

System dependent. Gforth just uses the file name format of your OS.

information returned by FILE-STATUS:

FILE-STATUS returns the most powerful file access mode allowed for the file: Either R/O, W/O or R/W. If the file cannot be accessed, R/O BIN is returned. BIN is applicable along with the returned mode.

input file state after an exception when including source:

All files that are left via the exception are closed.

ior values and meaning:

The *iors* returned by the file and memory allocation words are intended as throw codes. They typically are in the range -512--2047 of OS errors. The mapping from OS error numbers to *iors* is -512-*errno*.

maximum depth of file input nesting:

limited by the amount of return stack, locals/TIB stack, and the number of open files available. This should not give you troubles.

maximum size of input line:

/line. Currently 255.

methods of mapping block ranges to files:

By default, blocks are accessed in the file `blocks.fb` in the current working directory. The file can be switched with USE.

number of string buffers provided by S":

As many as memory available; the strings are stored in memory blocks allocated with ALLOCATE indefinitely.

size of string buffer used by S":

/line. currently 255.

9.6.2 Ambiguous conditions

attempting to position a file outside its boundaries:

REPOSITION-FILE is performed as usual: Afterwards, FILE-POSITION returns the value given to REPOSITION-FILE.

attempting to read from file positions not yet written:

End-of-file, i.e., zero characters are read and no error is reported.

file-id is invalid (INCLUDE-FILE):

An appropriate exception may be thrown, but a memory fault or other problem is more probable.

I/O exception reading or closing file-id (INCLUDE-FILE, INCLUDED):

The *ior* produced by the operation, that discovered the problem, is thrown.

named file cannot be opened (INCLUDED):

The *ior* produced by `open-file` is thrown.

requesting an unmapped block number:

There are no unmapped legal block numbers. On some operating systems, writing a block with a large number may overflow the file system and have an error message as consequence.

using source-id when blk is non-zero:

source-id performs its function. Typically it will give the id of the source which loaded the block. (Better ideas?)

9.7 The optional Floating-Point word set

9.7.1 Implementation Defined Options

format and range of floating point numbers:

System-dependent; the `double` type of C.

results of REPRESENT when float is out of range:

System dependent; REPRESENT is implemented using the C library function `ecvt()` and inherits its behaviour in this respect.

rounding or truncation of floating-point numbers:

System dependent; the rounding behaviour is inherited from the hosting C compiler. IEEE-FP-based (i.e., most) systems by default round to nearest, and break ties by rounding to even (i.e., such that the last bit of the mantissa is 0).

size of floating-point stack:

`s" FLOATING-STACK" environment? drop .` gives the total size of the floating-point stack (in floats). You can specify this on startup with the command-line option `-f` (see `<undefined>` [Invoking Gforth], page `<undefined>`).

width of floating-point stack:

1 floats.

9.7.2 Ambiguous conditions

df@ or df! used with an address that is not double-float aligned:

System-dependent. Typically results in a `-23 THROW` like other alignment violations.

f@ or f! used with an address that is not float aligned:

System-dependent. Typically results in a `-23 THROW` like other alignment violations.

floating-point result out of range:

System-dependent. Can result in a `-43 throw` (floating point overflow), `-54 throw` (floating point underflow), `-41 throw` (floating point inexact result), `-55 THROW` (Floating-point unidentified fault), or can produce a special value representing, e.g., Infinity.

sf@ or sf! used with an address that is not single-float aligned:

System-dependent. Typically results in an alignment fault like other alignment violations.

base is not decimal (REPRESENT, F., FE., FS.):

The floating-point number is converted into decimal nonetheless.

Both arguments are equal to zero (FATAN2):

System-dependent. FATAN2 is implemented using the C library function `atan2()`.

Using FTAN on an argument $r1$ where $\cos(r1)$ is zero:

System-dependent. Anyway, typically the cos of $r1$ will not be zero because of small errors and the tan will be a very large (or very small) but finite number.

d cannot be presented precisely as a float in D>F:

The result is rounded to the nearest float.

dividing by zero:

Platform-dependent; can produce an Infinity, NaN, `-42 throw` (floating point divide by zero) or `-55 throw` (Floating-point unidentified fault).

exponent too big for conversion (DF!, DF@, SF!, SF@):

System dependent. On IEEE-FP based systems the number is converted into an infinity.

float<1 (FACOSH):

Platform-dependent; on IEEE-FP systems typically produces a NaN.

float<=-1 (FLNP1):

Platform-dependent; on IEEE-FP systems typically produces a NaN (or a negative infinity for $float=-1$).

float<=0 (FLN, FLOG):

Platform-dependent; on IEEE-FP systems typically produces a NaN (or a negative infinity for $float=0$).

float<0 (FASINH, FSQRT):

Platform-dependent; for `fsqrt` this typically gives a NaN, for `fasinh` some platforms produce a NaN, others a number (bug in the C library?).

|float|>1 (FACOS, FASIN, FATANH):

Platform-dependent; IEEE-FP systems typically produce a NaN.

integer part of float cannot be represented by d in F>D:

Platform-dependent; typically, some double number is produced and no error is reported.

string larger than pictured numeric output area (f., fe., fs.):

`Precision` characters of the numeric output area are used. If `precision` is too high, these words will smash the data or code close to `here`.

9.8 The optional Locals word set

9.8.1 Implementation Defined Options

maximum number of locals in a definition:

`s" #locals" environment? drop ..` Currently 15. This is a lower bound, e.g., on a 32-bit machine there can be 41 locals of up to 8 characters. The number of locals in a definition is bounded by the size of `locals-buffer`, which contains the names of the locals.

9.8.2 Ambiguous conditions

executing a named local in interpretation state:

Compiles the local into the current definition (just as in compile state); in addition text-interpreting a local in interpretation state gives an “is compile-only” warning.

name not defined by VALUE or (LOCAL) (T0):

-32 **throw** (Invalid name argument)

9.9 The optional Memory-Allocation word set

9.9.1 Implementation Defined Options

values and meaning of ior:

The *iors* returned by the file and memory allocation words are intended as throw codes. They typically are in the range -512--2047 of OS errors. The mapping from OS error numbers to *iors* is -512-*errno*.

9.10 The optional Programming-Tools word set

9.10.1 Implementation Defined Options

ending sequence for input following ;CODE and CODE:

END-CODE

manner of processing input following ;CODE and CODE:

The **ASSEMBLER** vocabulary is pushed on the search order stack, and the input is processed by the text interpreter, (starting) in interpret state.

search order capability for EDITOR and ASSEMBLER:

The Search-Order word set.

source and format of display by SEE:

The source for **see** is the executable code used by the inner interpreter. The current **see** tries to output Forth source code (and on some platforms, assembly code for primitives) as well as possible.

9.10.2 Ambiguous conditions

deleting the compilation word list (FORGET):

Not implemented (yet).

fewer than u+1 items on the control-flow stack (CS-PICK, CS-ROLL):

This typically results in an **abort** with a descriptive error message (may change into a -22 **throw** (Control structure mismatch) in the future). You may also get a memory access error. If you are unlucky, this ambiguous condition is not caught.

name can't be found (FORGET):

Not implemented (yet).

name not defined via CREATE:

;CODE behaves like DOES> in this respect, i.e., it changes the execution semantics of the last defined word no matter how it was defined.

POSTPONE *applied to* [IF]:

After defining : X POSTPONE [IF] ; IMMEDIATE. X is equivalent to [IF].

reaching the end of the input source before matching [ELSE] or [THEN]:

Continue in the same state of conditional compilation in the next outer input source. Currently there is no warning to the user about this.

removing a needed definition (FORGET):

Not implemented (yet).

9.11 The optional Search-Order word set

9.11.1 Implementation Defined Options

maximum number of word lists in search order:

s" wordlists" environment? drop .. Currently 16.

minimum search order:

root root.

9.11.2 Ambiguous conditions

changing the compilation word list (during compilation):

The word is entered into the word list that was the compilation word list at the start of the definition. Any changes to the name field (e.g., `immediate`) or the code field (e.g., when executing DOES>) are applied to the latest defined word (as reported by `latest` or `latesttxt`), if possible, irrespective of the compilation word list.

search order empty (previous):

abort" Vocstack empty".

too many word lists in search order (also):

abort" Vocstack full".

10 Should I use Gforth extensions?

As you read through the rest of this manual, you will see documentation for *Standard* words, and documentation for some appealing Gforth *extensions*. You might ask yourself the question: “*Should I restrict myself to the standard, or should I use the extensions?*”

The answer depends on the goals you have for the program you are working on:

- Is it just for yourself or do you want to share it with others?
- If you want to share it, do the others all use Gforth?
- If it is just for yourself, do you want to restrict yourself to Gforth?

If restricting the program to Gforth is ok, then there is no reason not to use extensions. It is still a good idea to keep to the standard where it is easy, in case you want to reuse these parts in another program that you want to be portable.

If you want to be able to port the program to other Forth systems, there are the following points to consider:

- Most Forth systems that are being maintained support Standard Forth. So if your program complies with the standard, it will be portable among many systems.
- A number of the Gforth extensions can be implemented in Standard Forth using public-domain files provided in the `compat/` directory. These are mentioned in the text in passing. There is no reason not to use these extensions, your program will still be Standard Forth compliant; just include the appropriate `compat` files with your program.
- The tool `ans-report.fs` (see `<undefined>` [Standard Report], page `<undefined>`) makes it easy to analyse your program and determine what non-Standard words it relies upon. However, it does not check whether you use standard words in a non-standard way.
- Some techniques are not standardized by Standard Forth, and are hard or impossible to implement in a standard way, but can be implemented in most Forth systems easily, and usually in similar ways (e.g., accessing word headers). Forth has a rich historical precedent for programmers taking advantage of implementation-dependent features of their tools (for example, relying on a knowledge of the dictionary structure). Sometimes these techniques are necessary to extract every last bit of performance from the hardware, sometimes they are just a programming shorthand.
- Does using a Gforth extension save more work than the porting this part to other Forth systems (if any) will cost?
- Is the additional functionality worth the reduction in portability and the additional porting problems?

In order to perform these considerations, you need to know what’s standard and what’s not. This manual generally states if something is non-standard, but the authoritative source is the standard document (<https://forth-standard.org/standard/words>). Appendix A of the Standard (*Rationale*) provides a valuable insight into the thought processes of the technical committee.

Note also that portability between Forth systems is not the only portability issue; there is also the issue of portability between different platforms (processor/OS combinations).

11 Model

This chapter has yet to be written. It will contain information, on which internal structures you can rely.

12 Integrating Gforth into C programs

Several people like to use Forth as scripting language for applications that are otherwise written in C, C++, or some other language.

The Forth system ATLAST provides facilities for embedding it into applications; unfortunately it has several disadvantages: most importantly, it is not based on Standard Forth, and it is apparently dead (i.e., not developed further and not supported). The facilities provided by Gforth in this area are inspired by ATLAST's facilities, so making the switch should not be hard.

We also tried to design the interface such that it can easily be implemented by other Forth systems, so that we may one day arrive at a standardized interface. Such a standard interface would allow you to replace the Forth system without having to rewrite C code.

You embed the Gforth interpreter by linking with the library `libgforth.a` or `libgforth.so` (give the compiler the option `-lgforth`, or for one of the other engines `-lgforth-fast`, `-lgforth-itc`, or `-lgforth-ditc`). All global symbols in this library that belong to the interface, have the prefix `gforth_`; if a common interface emerges, the functions may also be available through `#defines` with the prefix `forth_`.

You can include the declarations of Forth types, the functions and variables of the interface with `#include <gforth.h>`.

You can now run a Gforth session by either calling `gforth_main` or using the components:

```
Cell gforth_main(int argc, char **argv, char **env)
{
    Cell retvalue=gforth_start(argc, argv);

    if(retvalue == -56) { /* throw-code for quit */
        retvalue = gforth_bootmessage();    // show boot message
        if(retvalue == -56)
            retvalue = gforth_quit(); // run quit loop
    }
    gforth_cleanup();
    gforth_printmetrics();
    // gforth_free_dict(); // if you want to restart, do this

    return retvalue;
}
```

To interact with the Forth interpreter, there's `Xt gforth_find(Char * name)` and `Cell gforth_execute(Xt xt)`.

More documentation needs to be put here.

12.1 Types

`Cell`, `UCell`: data stack elements.

`Float`: float stack element.

`Address`, `Xt`, `Label`: pointer typies to memory, Forth words, and Forth instructions inside the VM.

12.2 Variables

Data and FP Stack pointer. Area sizes. Accessing the Stacks

`gforth_SP`, `gforth_FP`.

12.3 Functions

```
void *gforth_engine(Xt *, stackpointers *);
Cell gforth_main(int argc, char **argv, char **env);
int gforth_args(int argc, char **argv, char **path, char **imagename);
ImageHeader* gforth_loader(char* imagename, char* path);
user_area* gforth_stacks(Cell dsize, Cell rsize, Cell fsize, Cell lsize);
void gforth_free_stacks(user_area* t);
void gforth_setstacks(user_area * t);
void gforth_free_dict();
Cell gforth_go(Xt* ip0);
Cell gforth_boot(int argc, char** argv, char* path);
void gforth_bootmessage();
Cell gforth_start(int argc, char ** argv);
Cell gforth_quit();
Xt gforth_find(Char * name);
Cell gforth_execute(Xt xt);
void gforth_cleanup();
void gforth_printmetrics();
void gforth_setwinch();
```

12.4 Signals

Gforth sets up signal handlers to catch exceptions and window size changes. This may interfere with your C program.

13 Emacs and Gforth

Gforth comes with `gforth.el`, an improved version of `forth.el` by Goran Rydqvist (included in the TILE package). The improvements are:

- A better handling of indentation.
- A custom highlighting engine for Forth-code.
- Comment paragraph filling (*M-q*)
- Commenting (*C-x *) and uncommenting (*C-u C-x *) of regions
- Removal of debugging tracers (*C-x ~*, see [\[Debugging\]](#), page [\(undefined\)](#)).
- Support of the `info-lookup` feature for looking up the documentation of a word.
- Support for reading and writing blocks files.

To get a basic description of these features, enter Forth mode and type *C-h m*.

In addition, Gforth supports Emacs quite well: The source code locations given in error messages, debugging output (from `~~`) and failed assertion messages are in the right format for Emacs' compilation mode (see Section “Running Compilations under Emacs” in *Emacs Manual*) so the source location corresponding to an error or other message is only a few keystrokes away (*C-x `* for the next error, *C-c C-c* for the error under the cursor).

Moreover, for words documented in this manual, you can look up the glossary entry quickly by using *C-h TAB* (`info-lookup-symbol`, see Section “Documentation Commands” in *Emacs Manual*). This feature requires Emacs 20.3 or later and does not work for words containing `:`.

13.1 Installing gforth.el

To make the features from `gforth.el` available in Emacs, add the following lines to your `.emacs` file:

```
(autoload 'forth-mode "gforth.el")
(setq auto-mode-alist (cons '("\\.fs\\\\" . forth-mode)
  auto-mode-alist))
(autoload 'forth-block-mode "gforth.el")
(setq auto-mode-alist (cons '("\\.fb\\\\" . forth-block-mode)
  auto-mode-alist))
(add-hook 'forth-mode-hook (function (lambda ()
  ;; customize variables here:
  (setq forth-indent-level 4)
  (setq forth-minor-indent-level 2)
  (setq forth-highlight-level 3)
  ;;; ...
)))
```

13.2 Emacs Tags

If you require `etags.fs`, a new TAGS file will be produced (see Section “Tags Tables” in *Emacs Manual*) that contains the definitions of all words defined afterwards. You can then find the source for a word using *M-..* Note that Emacs can use several tags files

at the same time (e.g., one for the Gforth sources and one for your program, see Section “Selecting a Tags Table” in *Emacs Manual*). The TAGS file for the preloaded words is `$(datadir)/gforth/$(VERSION)/TAGS` (e.g., `/usr/local/share/gforth/0.2.0/TAGS`). To get the best behaviour with `etags.fs`, you should avoid putting definitions both before and after `require` etc., otherwise you will see the same file visited several times by commands like `tags-search`.

13.3 Hilighting

`gforth.el` comes with a custom source hilighting engine. When you open a file in `forth-mode`, it will be completely parsed, assigning faces to keywords, comments, strings etc. While you edit the file, modified regions get parsed and updated on-the-fly.

Use the variable ‘`forth-hil提高-level`’ to change the level of decoration from 0 (no hilighting at all) to 3 (the default). Even if you set the hilighting level to 0, the parser will still work in the background, collecting information about whether regions of text are “compiled” or “interpreted”. Those information are required for auto-indentation to work properly. Set ‘`forth-disable-parser`’ to non-nil if your computer is too slow to handle parsing. This will have an impact on the smartness of the auto-indentation engine, though.

Sometimes Forth sources define new features that should be hilighted, new control structures, defining-words etc. You can use the variable ‘`forth-custom-words`’ to make `forth-mode` hilight additional words and constructs. See the docstring of ‘`forth-words`’ for details (in Emacs, type `C-h v forth-words`).

‘`forth-custom-words`’ is meant to be customized in your `.emacs` file. To customize hilighting in a file-specific manner, set ‘`forth-local-words`’ in a local-variables section at the end of your source file (see Section “Variables” in *Emacs Manual*).

Example:

```
0 [IF]
  Local Variables:
  forth-local-words:
    (((("t:") definition-starter (font-lock-keyword-face . 1)
        "[ \t\n]" t name (font-lock-function-name-face . 3))
      ((";t") definition-ender (font-lock-keyword-face . 1)))
  End:
[THEN]
```

13.4 Auto-Indentation

`forth-mode` automatically tries to indent lines in a smart way, whenever you type `TAB` or break a line with `C-m`.

Simple customization can be achieved by setting ‘`forth-indent-level`’ and ‘`forth-minor-indent-level`’ in your `.emacs` file. For historical reasons `gforth.el` indents per default by multiples of 4 columns. To use the more traditional 3-column indentation, add the following lines to your `.emacs`:

```
(add-hook 'forth-mode-hook (function (lambda ()
;; customize variables here:
(setq forth-indent-level 3)
```

```
(setq forth-minor-indent-level 1)
)))
```

If you want indentation to recognize non-default words, customize it by setting ‘forth-custom-indent-words’ in your `.emacs`. See the docstring of ‘forth-indent-words’ for details (in Emacs, type `C-h v forth-indent-words`).

To customize indentation in a file-specific manner, set ‘forth-local-indent-words’ in a local-variables section at the end of your source file (see Section “Local Variables in Files” in *Emacs Manual*).

Example:

```
0 [IF]
  Local Variables:
  forth-local-indent-words:
    (((("t:") (0 . 2) (0 . 2))
      ((";t") (-2 . 0) (0 . -2)))
  End:
[THEN]
```

13.5 Blocks Files

`forth-mode` Autodetects blocks files by checking whether the length of the first line exceeds 1023 characters. It then tries to convert the file into normal text format. When you save the file, it will be written to disk as normal stream-source file.

If you want to write blocks files, use `forth-blocks-mode`. It inherits all the features from `forth-mode`, plus some additions:

- Files are written to disk in blocks file format.
- Screen numbers are displayed in the mode line (enumerated beginning with the value of ‘forth-block-base’)
- Warnings are displayed when lines exceed 64 characters.
- The beginning of the currently edited block is marked with an overlay-arrow.

There are some restrictions you should be aware of. When you open a blocks file that contains tabulator or newline characters, these characters will be translated into spaces when the file is written back to disk. If tabs or newlines are encountered during blocks file reading, an error is output to the echo area. So have a look at the ‘*Messages*’ buffer, when Emacs’ bell rings during reading.

Please consult the docstring of `forth-blocks-mode` for more information by typing `C-h v forth-blocks-mode`).

14 Image Files

An image file is a file containing an image of the Forth dictionary, i.e., compiled Forth code and data residing in the dictionary. By convention, we use the extension `.fi` for image files.

14.1 Image Licensing Issues

An image created with `gforthmi` (see [gforthmi](#), page [gforthmi](#)) or `savesystem` (see [Non-Relocatable Image Files](#), page [Non-Relocatable Image Files](#)) includes the original image; i.e., according to copyright law it is a derived work of the original image.

Since Gforth is distributed under the GNU GPL, the newly created image falls under the GNU GPL, too. In particular, this means that if you distribute the image, you have to make all of the sources for the image available, including those you wrote. For details see [GNU General Public License \(Section 3\)](#), page [GNU General Public License \(Section 3\)](#).

If you create an image with `cross` (see [cross.fs](#), page [cross.fs](#)), the image contains only code compiled from the sources you gave it; if none of these sources is under the GPL, the terms discussed above do not apply to the image. However, if your image needs an engine (a gforth binary) that is under the GPL, you should make sure that you distribute both in a way that is at most a *mere aggregation*, if you don't want the terms of the GPL to apply to the image.

14.2 Image File Background

Gforth consists not only of primitives (in the engine), but also of definitions written in Forth. Since the Forth compiler itself belongs to those definitions, it is not possible to start the system with the engine and the Forth source alone. Therefore we provide the Forth code as an image file in nearly executable form. When Gforth starts up, a C routine loads the image file into memory, optionally relocates the addresses, then sets up the memory (stacks etc.) according to information in the image file, and (finally) starts executing Forth code.

The default image file is `gforth.fi` (in the `GFORTHPATH`). You can use a different image by using the `-i`, `--image-file` or `--appl-image` options (see [Invoking Gforth](#), page [Invoking Gforth](#)), e.g.:

```
gforth-fast -i myimage.fi
```

There are different variants of image files, and they represent different compromises between the goals of making it easy to generate image files and making them portable.

Win32Forth 3.4 and Mitch Bradley's `cforth` use relocation at run-time. This avoids many of the complications discussed below (image files are data relocatable without further ado), but costs performance (one addition per memory access) and makes it difficult to pass addresses between Forth and library calls or other programs.

By contrast, the Gforth loader performs relocation at image load time. The loader also has to replace tokens that represent primitive calls with the appropriate code-field addresses (or code addresses in the case of direct threading).

There are three kinds of image files, with different degrees of relocatability: non-relocatable, data-relocatable, and fully relocatable image files.

These image file variants have several restrictions in common; they are caused by the design of the image file loader:

- There is only one segment; in particular, this means, that an image file cannot represent **ALLOCATED** memory chunks (and pointers to them). The contents of the stacks are not represented, either.
- The only kinds of relocation supported are: adding the same offset to all cells that represent data addresses; and replacing special tokens with code addresses or with pieces of machine code.

If any complex computations involving addresses are performed, the results cannot be represented in the image file. Several applications that use such computations come to mind:

- Hashing addresses (or data structures which contain addresses) for table lookup. If you use Gforth's **tables** or **wordlists** for this purpose, you will have no problem, because the hash tables are recomputed automatically when the system is started. If you use your own hash tables, you will have to do something similar.
- There's a cute implementation of doubly-linked lists that uses **XORed** addresses. You could represent such lists as singly-linked in the image file, and restore the doubly-linked representation on startup.¹
- The code addresses of run-time routines like **docol:** cannot be represented in the image file (because their tokens would be replaced by machine code in direct threaded implementations). As a workaround, compute these addresses at run-time with **>code-address** from the executions tokens of appropriate words (see the definitions of **docol:** and friends in **kernel/getdoers.fs**).
- On many architectures addresses are represented in machine code in some shifted or mangled form. You cannot put **CODE** words that contain absolute addresses in this form in a relocatable image file. Workarounds are representing the address in some relative form (e.g., relative to the CFA, which is present in some register), or loading the address from a place where it is stored in a non-mangled form.

14.3 Non-Relocatable Image Files

These files are simple memory dumps of the dictionary. They are specific to the executable (i.e., **gforth** file) they were created with. What's worse, they are specific to the place on which the dictionary resided when the image was created. Now, there is no guarantee that the dictionary will reside at the same place the next time you start Gforth, so there's no guarantee that a non-relocatable image will work the next time (Gforth will complain instead of crashing, though). Indeed, on OSs with (enabled) address-space randomization non-relocatable images are unlikely to work.

You can create a non-relocatable image file with **savesystem**, e.g.:

```
gforth app.fs -e "savesystem app.fi bye"
savesystem ( "image" - ) gforth-0.2 "savesystem"
```

¹ In my opinion, though, you should think thrice before using a doubly-linked list (whatever implementation).

14.4 Data-Relocatable Image Files

These files contain relocatable data addresses, but fixed code addresses (instead of tokens). They are specific to the executable (i.e., `gforth` file) they were created with. Also, they disable dynamic native code generation (typically a factor of 2 in speed). You get a data-relocatable image, if you pass the engine you want to use through the `GFORTHHD` environment variable to `gforthmi` (see `<undefined> [gforthmi]`, page `<undefined>`), e.g.

```
GFORTHHD="/usr/bin/gforth-fast --no-dynamic" gforthmi myimage.fi source.fs
```

Note that the `--no-dynamic` is required here for the image to work (otherwise it will contain references to dynamically generated code that is not saved in the image).

14.5 Fully Relocatable Image Files

These image files have relocatable data addresses, and tokens for code addresses. They can be used with different binaries (e.g., with and without debugging) on the same machine, and even across machines with the same data formats (byte order, cell size, floating point format), and they work with dynamic native code generation. However, they are usually specific to the version of Gforth they were created with. The files `gforth.fi` and `kernl*.fi` are fully relocatable.

There are two ways to create a fully relocatable image file:

14.5.1 `gforthmi`

You will usually use `gforthmi`. If you want to create an image *file* that contains everything you would load by invoking Gforth with `gforth options`, you simply say:

```
gforthmi file options
```

E.g., if you want to create an image `asm.fi` that has the file `asm.fs` loaded in addition to the usual stuff, you could do it like this:

```
gforthmi asm.fi asm.fs
```

`gforthmi` is implemented as a sh script and works like this: It produces two non-relocatable images for different addresses and then compares them. Its output reflects this: first you see the output (if any) of the two Gforth invocations that produce the non-relocatable image files, then you see the output of the comparing program: It displays the offset used for data addresses and the offset used for code addresses; moreover, for each cell that cannot be represented correctly in the image files, it displays a line like this:

```
78DC          BFFFFA50          BFFFFA40
```

This means that at offset `$78dc` from `forthstart`, one input image contains `$bffffa50`, and the other contains `$bffffa40`. Since these cells cannot be represented correctly in the output image, you should examine these places in the dictionary and verify that these cells are dead (i.e., not read before they are written).

If you insert the option `--application` in front of the image file name, you will get an image that uses the `--appl-image` option instead of the `--image-file` option (see `<undefined> [Invoking Gforth]`, page `<undefined>`). When you execute such an image on Unix (by typing the image name as command), the Gforth engine will pass all options to the image instead of trying to interpret them as engine options.

If you type `gforthmi` with no arguments, it prints some usage instructions.

There are a few wrinkles: After processing the passed *options*, the words **savesystem** and **bye** must be visible. A special doubly indirect threaded version of the **gforth** executable is used for creating the non-relocatable images; you can pass the exact filename of this executable through the environment variable **GFORTH** (default: **gforth-ditc**); if you pass a version that is not doubly indirect threaded, you will not get a fully relocatable image, but a data-relocatable image (see [\[Data-Relocatable Image Files\]](#), page [\(undefined\)](#)), because there is no code address offset). The normal **gforth** executable is used for creating the relocatable image; you can pass the exact filename of this executable through the environment variable **GFORTH**.

14.5.2 cross.fs

You can also use **cross**, a batch compiler that accepts a Forth-like programming language (see [\[Cross Compiler\]](#), page [\(undefined\)](#)).

cross allows you to create image files for machines with different data sizes and data formats than the one used for generating the image file. You can also use it to create an application image that does not contain a Forth compiler. These features are bought with restrictions and inconveniences in programming. E.g., addresses have to be stored in memory with special words (**A!**, **A,**, etc.) in order to make the code relocatable.

14.6 Stack and Dictionary Sizes

If you invoke Gforth with a command line flag for the size (see [\[Invoking Gforth\]](#), page [\(undefined\)](#)), the size you specify is stored in the dictionary. If you save the dictionary with **savesystem** or create an image with **gforthmi**, this size will become the default for the resulting image file. E.g., the following will create a fully relocatable version of **gforth.fi** with a 1MB dictionary:

```
gforthmi gforth.fi -m 1M
```

In other words, if you want to set the default size for the dictionary and the stacks of an image, just invoke **gforthmi** with the appropriate options when creating the image.

Note: For cache-friendly behaviour (i.e., good performance), you should make the sizes of the stacks modulo, say, 2K, somewhat different. E.g., the default stack sizes are: data: 16k (mod 2k=0); fp: 15.5k (mod 2k=1.5k); return: 15k(mod 2k=1k); locals: 14.5k (mod 2k=0.5k).

14.7 Running Image Files

You can invoke Gforth with an image file *image* instead of the default **gforth.fi** with the **-i** flag (see [\[Invoking Gforth\]](#), page [\(undefined\)](#)):

```
gforth -i image
```

If your operating system supports starting scripts with a line of the form **#! ...**, you just have to type the image file name to start Gforth with this image file (note that the file extension **.fi** is just a convention). I.e., to run Gforth with the image file *image*, you can just type *image* instead of **gforth -i image**. This works because every **.fi** file starts with a line of this format:

```
#! /usr/local/bin/gforth-0.4.0 -i
```


The file and pathname for the Gforth engine specified on this line is the specific Gforth executable that it was built against; i.e. the value of the environment variable `GFORTH` at the time that `gforthmi` was executed.

You can make use of the same shell capability to make a Forth source file into an executable. For example, if you place this text in a file:

```
#! /usr/local/bin/gforth

." Hello, world" CR
bye
```

and then make the file executable (`chmod +x` in Unix), you can run it directly from the command line. The sequence `#!` is used in two ways; firstly, it is recognised as a “magic sequence” by the operating system² secondly it is treated as a comment character by Gforth. Because of the second usage, a space is required between `#!` and the path to the executable (moreover, some Unixes require the sequence `#! /`).

Most Unix systems (including Linux) support exactly one option after the binary name. If that is not enough, you can use the following trick:

```
#! /bin/sh
: ## ; 0 [if]
exec gforth -m 10M -d 1M $0 "$@"
[then]
." Hello, world" cr
bye \ caution: this prevents (further) processing of "$@"
```

First this script is interpreted as shell script, which treats the first two lines as (mostly) comments, then performs the third line, which invokes `gforth` with this script (`$0`) as parameter and its parameters as additional parameters (`"$@"`). Then this script is interpreted as Forth script, which first defines a colon definition `##`, then ignores everything up to `[then]` and finally processes the following Forth code. You can also use

```
#0 [if]
```

in the second line, but this works only in Gforth-0.7.0 and later.

The `gforthmi` approach is the fastest one, the shell-based one is slowest (needs to start an additional shell). An additional advantage of the shell approach is that it is unnecessary to know where the Gforth binary resides, as long as it is in the `$PATH`.

`#! (-) gforth-0.2 “hash-bang”`

An alias for \

14.8 Modifying the Startup Sequence

You can add your own initialization to the startup sequence of an image through the deferred word `'cold`. `'cold` is invoked just before the image-specific command line processing (i.e., loading files and evaluating `(-e)` strings) starts.

² The Unix kernel actually recognises two types of files: executable files and files of data, where the data is processed by an interpreter that is specified on the “interpreter line” – the first line of the file, starting with the sequence `#!`. There may be a small limit (e.g., 32) on the number of characters that may be specified on the interpreter line.

A sequence for adding your initialization usually looks like this:

```
:noname
  Defers 'cold \ do other initialization stuff (e.g., rehashing wordlists)
  ... \ your stuff
; IS 'cold
```

After 'cold, Gforth processes the image options (see [\[Invoking Gforth\]](#), page [\[undefined\]](#)), and then it performs **bootmessage**, another deferred word. This normally prints Gforth's startup message and does nothing else.

So, if you want to make a turnkey image (i.e., an image for an application instead of an extended Forth system), you can do this in several ways:

- If you want to do your interpretation of the OS command-line arguments, hook into 'cold. In that case you probably also want to build the image with **gforthmi --application** (see [\[gforthmi\]](#), page [\[undefined\]](#)) to keep the engine from processing OS command line options. You can then do your own command-line processing with **next-arg**.
- If you want to have the normal Gforth processing of OS command-line arguments, but specify your own command-line options, hook into **process-option**.
- If you want to have more options in addition to the ones that come with Gforth, define words into the **options** vocabulary.
- If you want to display your own boot message, hook into **bootmessage**.

In either case, you probably do not want the word that you execute in these hooks to exit normally, but use **bye** or **throw**. Otherwise the Gforth startup process would continue and eventually present the Forth command line to the user.

'cold (-) gforth-0.2 “tick-cold”

Hook (deferred word) for things to do right before interpreting the OS command-line arguments. Normally does some initializations that you also want to perform.

bootmessage (-) gforth-0.4 “bootmessage”

Hook (deferred word) executed right after interpreting the OS command-line arguments. Normally prints the Gforth startup message.

process-option (*addr u* - ... *xt* | 0) gforth-0.7 “process-option”

Recognizer that processes an option, returns an execute-only xt to process the option

15 Engine

Reading this chapter is not necessary for programming with Gforth. It may be helpful for finding your way in the Gforth sources.

The ideas in this section have also been published in the following papers: Bernd Paysan, *ANS fig/GNU/??? Forth* (in German), Forth-Tagung '93; M. Anton Ertl, *A Portable Forth Engine* (<https://www.complang.tuwien.ac.at/papers/ertl93.ps.Z>), EuroForth '93; M. Anton Ertl, *Threaded code variations and optimizations (extended version)* (<https://www.complang.tuwien.ac.at/papers/ertl02.ps.gz>), Forth-Tagung '02.

15.1 Portability

An important goal of the Gforth Project is availability across a wide range of personal machines. fig-Forth, and, to a lesser extent, F83, achieved this goal by manually coding the engine in assembly language for several then-popular processors. This approach is very labor-intensive and the results are short-lived due to progress in computer architecture.

Others have avoided this problem by coding in C, e.g., Mitch Bradley (cforth), Mikael Patel (TILE) and Dirk Zoller (pfe). This approach is particularly popular for UNIX-based Forths due to the large variety of architectures of UNIX machines. Unfortunately an implementation in C does not mix well with the goals of efficiency and with using traditional techniques: Indirect or direct threading cannot be expressed in C, and switch threading, the fastest technique available in C, is significantly slower. Another problem with C is that it is very cumbersome to express double integer arithmetic.

Fortunately, there is a portable language that does not have these limitations: GNU C, the version of C processed by the GNU C compiler (see Section “Extensions to the C Language Family” in *GNU C Manual*). Its labels as values feature (see Section “Labels as Values” in *GNU C Manual*) makes direct and indirect threading possible, its `long long` type (see Section “Double-Word Integers” in *GNU C Manual*) corresponds to Forth’s double numbers on many systems. GNU C is freely available on all important (and many unimportant) UNIX machines, VMS, 80386s running MS-DOS, the Amiga, and the Atari ST, so a Forth written in GNU C can run on all these machines.

Writing in a portable language has the reputation of producing code that is slower than assembly. For our Forth engine we repeatedly looked at the code produced by the compiler and eliminated most compiler-induced inefficiencies by appropriate changes in the source code.

However, register allocation cannot be portably influenced by the programmer, leading to some inefficiencies on register-starved machines. We use explicit register declarations (see Section “Variables in Specified Registers” in *GNU C Manual*) to improve the speed on some machines. They are turned on by using the configuration flag `--enable-force-reg` (gcc switch `-DFORCE_REG`). Unfortunately, this feature not only depends on the machine, but also on the compiler version: On some machines some compiler versions produce incorrect code when certain explicit register declarations are used. So by default `-DFORCE_REG` is not used.

15.2 Threading

GNU C's labels as values extension (available since `gcc-2.0`, see Section "Labels as Values" in *GNU C Manual*) makes it possible to take the address of *label* by writing `&&label`. This address can then be used in a statement like `goto *address`. I.e., `goto *&&x` is the same as `goto x`.

With this feature an indirect threaded NEXT looks like:

```
cfa = *ip++;
ca = *cfa;
goto *ca;
```

For those unfamiliar with the names: `ip` is the Forth instruction pointer; the `cfa` (code-field address) corresponds to Standard Forth's execution token and points to the code field of the next word to be executed; The `ca` (code address) fetched from there points to some executable code, e.g., a primitive or the colon definition handler `docol`.

Direct threading is even simpler:

```
ca = *ip++;
goto *ca;
```

Of course we have packaged the whole thing neatly in macros called `NEXT` and `NEXT1` (the part of `NEXT` after fetching the `cfa`).

15.2.1 Scheduling

There is a little complication: Pipelined and superscalar processors, i.e., RISC and some modern CISC machines can process independent instructions while waiting for the results of an instruction. The compiler usually reorders (schedules) the instructions in a way that achieves good usage of these delay slots. However, on our first tries the compiler did not do well on scheduling primitives. E.g., for `+` implemented as

```
n=sp[0]+sp[1];
sp++;
sp[0]=n;
NEXT;
```

the `NEXT` comes strictly after the other code, i.e., there is nearly no scheduling. After a little thought the problem becomes clear: The compiler cannot know that `sp` and `ip` point to different addresses (and the version of `gcc` we used would not know it even if it was possible), so it could not move the load of the `cfa` above the store to the TOS. Indeed the pointers could be the same, if code on or very near the top of stack were executed. In the interest of speed we chose to forbid this probably unused "feature" and helped the compiler in scheduling: `NEXT` is divided into several parts: `NEXT_P0`, `NEXT_P1` and `NEXT_P2`). `+` now looks like:

```
NEXT_P0;
n=sp[0]+sp[1];
sp++;
NEXT_P1;
sp[0]=n;
NEXT_P2;
```

There are various schemes that distribute the different operations of NEXT between these parts in several ways; in general, different schemes perform best on different processors. We use a scheme for most architectures that performs well for most processors of this architecture; in the future we may switch to benchmarking and choosing the scheme on installation time.

15.2.2 Direct or Indirect Threaded?

Threaded forth code consists of references to primitives (simple machine code routines like `+`) and to non-primitives (e.g., colon definitions, variables, constants); for a specific class of non-primitives (e.g., variables) there is one code routine (e.g., `dovar`), but each variable needs a separate reference to its data.

Traditionally Forth has been implemented as indirect threaded code, because this allows to use only one cell to reference a non-primitive (basically you point to the data, and find the code address there).

However, threaded code in Gforth (since 0.6.0) uses two cells for non-primitives, one for the code address, and one for the data address; the data pointer is an immediate argument for the virtual machine instruction represented by the code address. We call this *primitive-centric* threaded code, because all code addresses point to simple primitives. E.g., for a variable, the code address is for `lit` (also used for integer literals like `99`).

Primitive-centric threaded code allows us to use (faster) direct threading as dispatch method, completely portably (direct threaded code in Gforth before 0.6.0 required architecture-specific code). It also eliminates the performance problems related to I-cache consistency that 386 implementations have with direct threaded code, and allows additional optimizations.

There is a catch, however: the `xt` parameter of `execute` can occupy only one cell, so how do we pass non-primitives with their code *and* data addresses to them? Our answer is to use indirect threaded dispatch for `execute` and other words that use a single-cell `xt`. So, normal threaded code in colon definitions uses direct threading, and `execute` and similar words, which dispatch to `xts` on the data stack, use indirect threaded code. We call this *hybrid direct/indirect* threaded code.

The engines `gforth` and `gforth-fast` use hybrid direct/indirect threaded code. This means that with these engines you cannot use `,` to compile an `xt`. Instead, you have to use `compile,.`

If you want to compile `xts` with `,`, use `gforth-itc`. This engine uses plain old indirect threaded code. It still compiles in a primitive-centric style, so you cannot use `compile,`, instead of `,` (e.g., for producing tables of `xts` with `] word1 word2 ... [`). If you want to do that, you have to use `gforth-itc` and execute `' , is compile,.` Your program can check if it is running on a hybrid direct/indirect threaded engine or a pure indirect threaded engine with `threading-method` (see `<undefined>` [Threading Words], page `<undefined>`).

15.2.3 Dynamic Superinstructions

The engines `gforth` and `gforth-fast` use another optimization: Dynamic superinstructions with replication. As an example, consider the following colon definition:

```
: squared ( n1 -- n2 )
  dup * ;
```

Gforth compiles this into the threaded code sequence

```
dup
*
;s
```

Use `simple-see` (see `<undefined>` [Examining compiled code], page `<undefined>`) to see the threaded code of a colon definition.

In normal direct threaded code there is a code address occupying one cell for each of these primitives. Each code address points to a machine code routine, and the interpreter jumps to this machine code in order to execute the primitive. The routines for these three primitives are (in `gforth-fast` on the 386):

```
Code dup
( $804B950 ) add    esi , # -4 \ $83 $C6 $FC
( $804B953 ) add    ebx , # 4  \ $83 $C3 $4
( $804B956 ) mov    dword ptr 4 [esi] , ecx \ $89 $4E $4
( $804B959 ) jmp    dword ptr FC [ebx] \ $FF $63 $FC
end-code
Code *
( $804ACC4 ) mov    eax , dword ptr 4 [esi] \ $8B $46 $4
( $804ACC7 ) add    esi , # 4  \ $83 $C6 $4
( $804ACCA ) add    ebx , # 4  \ $83 $C3 $4
( $804ACCD ) imul   ecx , eax \ $F $AF $C8
( $804ACD0 ) jmp    dword ptr FC [ebx] \ $FF $63 $FC
end-code
Code ;s
( $804A693 ) mov    eax , dword ptr [edi] \ $8B $7
( $804A695 ) add    edi , # 4  \ $83 $C7 $4
( $804A698 ) lea    ebx , dword ptr 4 [eax] \ $8D $58 $4
( $804A69B ) jmp    dword ptr FC [ebx] \ $FF $63 $FC
end-code
```

With dynamic superinstructions and replication the compiler does not just lay down the threaded code, but also copies the machine code fragments, usually without the jump at the end.

```
( $4057D27D ) add    esi , # -4 \ $83 $C6 $FC
( $4057D280 ) add    ebx , # 4  \ $83 $C3 $4
( $4057D283 ) mov    dword ptr 4 [esi] , ecx \ $89 $4E $4
( $4057D286 ) mov    eax , dword ptr 4 [esi] \ $8B $46 $4
( $4057D289 ) add    esi , # 4  \ $83 $C6 $4
( $4057D28C ) add    ebx , # 4  \ $83 $C3 $4
( $4057D28F ) imul   ecx , eax \ $F $AF $C8
( $4057D292 ) mov    eax , dword ptr [edi] \ $8B $7
( $4057D294 ) add    edi , # 4  \ $83 $C7 $4
( $4057D297 ) lea    ebx , dword ptr 4 [eax] \ $8D $58 $4
( $4057D29A ) jmp    dword ptr FC [ebx] \ $FF $63 $FC
```

Only when a threaded-code control-flow change happens (e.g., in `;s`), the jump is appended. This optimization eliminates many of these jumps and makes the rest much more

predictable. The speedup depends on the processor and the application; on the Athlon and Pentium III this optimization typically produces a speedup by a factor of 2.

The code addresses in the direct-threaded code are set to point to the appropriate points in the copied machine code, in this example like this:

```
primitive  code address
dup        $4057D27D
*          $4057D286
;s         $4057D292
```

Thus there can be threaded-code jumps to any place in this piece of code. This also simplifies decompilation quite a bit.

See-code (see `<undefined>` [Examining compiled code], page `<undefined>`) shows the threaded code intermingled with the native code of dynamic superinstructions. These days some additional optimizations are applied for the dynamically-generated native code, so the output of **see-code squared** on **gforth-fast** on one particular AMD64 installation looks like this:

```
$7FB689C678C8 dup    1->2
7FB68990C1B2:  mov    r15,r8
$7FB689C678D0 *      2->1
7FB68990C1B5:  imul   r8,r15
$7FB689C678D8 ;s     1->1
7FB68990C1B9:  mov    rbx,[r14]
7FB68990C1BC:  add    r14,$08
7FB68990C1C0:  mov    rax,[rbx]
7FB68990C1C3:  jmp    eax
```

You can disable this optimization with **--no-dynamic**. You can use the copying without eliminating the jumps (i.e., dynamic replication, but without superinstructions) with **--no-super**; this gives the branch prediction benefit alone; the effect on performance depends on the CPU; on the Athlon and Pentium III the speedup is a little less than for dynamic superinstructions with replication.

One use of these options is if you want to patch the threaded code. With superinstructions, many of the dispatch jumps are eliminated, so patching often has no effect. These options preserve all the dispatch jumps.

On some machines dynamic superinstructions are disabled by default, because it is unsafe on these machines. However, if you feel adventurous, you can enable it with **--dynamic**.

15.2.4 DOES>

One of the most complex parts of a Forth engine is **dodoes**, i.e., the chunk of code executed by every word defined by a **CREATE...DOES>** pair; actually with primitive-centric code, this is only needed if the xt of the word is **executed**. The main problem here is: How to find the Forth code to be executed, i.e. the code after the **DOES>** (the **DOES>-code**)? There are two solutions:

In fig-Forth the code field points directly to the **dodoes** and the **DOES>-code** address is stored in the cell after the code address (i.e. at **CFA cell+**). It may seem that this solution is illegal in the Forth-79 and all later standards, because in fig-Forth this address lies in the body (which is illegal in these standards). However, by making the code field larger for all

words this solution becomes legal again. We use this approach. Leaving a cell unused in most words is a bit wasteful, but on the machines we are targeting this is hardly a problem.

15.3 Primitives

15.3.1 Automatic Generation

Since the primitives are implemented in a portable language, there is no longer any need to minimize the number of primitives. On the contrary, having many primitives has an advantage: speed. In order to reduce the number of errors in primitives and to make programming them easier, we provide a tool, the primitive generator (`prims2x.fs` aka `Vmgen`, see Section “Introduction” in `Vmgen`), that automatically generates most (and sometimes all) of the C code for a primitive from the stack effect notation. The source for a primitive has the following form:

```
Forth-name ( stack-effect )      category   [pronounc.]
["glossary entry"]
C code
[:
Forth code]
```

The items in brackets are optional. The category and glossary fields are there for generating the documentation, the Forth code is there for manual implementations on machines without GNU C. E.g., the source for the primitive `+` is:

```
+      ( n1 n2 -- n )   core    plus
n = n1+n2;
```

This looks like a specification, but in fact `n = n1+n2` is C code. Our primitive generation tool extracts a lot of information from the stack effect notations¹: The number of items popped from and pushed on the stack, their type, and by what name they are referred to in the C code. It then generates a C code prelude and postlude for each primitive. The final C code for `+` looks like this:

```
I_plus: /* + ( n1 n2 -- n ) */ /* label, stack effect */
/* */ /* documentation */
NAME("+") /* debugging output (with -DDEBUG) */
{
  DEF_CA /* definition of variable ca (indirect threading) */
  Cell n1; /* definitions of variables */
  Cell n2;
  Cell n;
  NEXT_P0; /* NEXT part 0 */
  n1 = (Cell) sp[1]; /* input */
  n2 = (Cell) TOS;
  sp += 1; /* stack adjustment */
  {
    n = n1+n2; /* C code taken from the source */
  }
```

¹ We use a one-stack notation, even though we have separate data and floating-point stacks; The separate notation can be generated easily from the unified notation.


```

NEXT_P1;                                /* NEXT part 1 */
TOS = (Cell)n;                          /* output */
NEXT_P2;                                /* NEXT part 2 */
}

```

This looks long and inefficient, but the GNU C compiler optimizes quite well and produces optimal code for + on, e.g., the R3000 and the HP RISC machines: Defining the `ns` does not produce any code, and using them as intermediate storage also adds no cost.

There are also other optimizations that are not illustrated by this example: assignments between simple variables are usually for free (copy propagation). If one of the stack items is not used by the primitive (e.g. in `drop`), the compiler eliminates the load from the stack (dead code elimination). On the other hand, there are some things that the compiler does not do, therefore they are performed by `prims2x.fs`: The compiler does not optimize code away that stores a stack item to the place where it just came from (e.g., `over`).

While programming a primitive is usually easy, there are a few cases where the programmer has to take the actions of the generator into account, most notably `?dup`, but also words that do not (always) fall through to `NEXT`.

For more information

15.3.2 TOS Optimization

An important optimization for stack machine emulators, e.g., Forth engines, is keeping one or more of the top stack items in registers. If a word has the stack effect *in1...inx -- out1...outy*, keeping the top *n* items in registers

- is better than keeping *n-1* items, if $x \geq n$ and $y \geq n$, due to fewer loads from and stores to the stack.
- is slower than keeping *n-1* items, if $x < y$ and $x < n$ and $y < n$, due to additional moves between registers.

In particular, keeping one item in a register is never a disadvantage, if there are enough registers. Keeping two items in registers is a disadvantage for frequent words like `?branch`, constants, variables, literals and `i`. Therefore our generator only produces code that keeps zero or one items in registers. The generated C code covers both cases; the selection between these alternatives is made at C-compile time using the switch `-DUSE_TOS`. `TOS` in the C code for + is just a simple variable name in the one-item case, otherwise it is a macro that expands into `sp[0]`. Note that the GNU C compiler tries to keep simple variables like `TOS` in registers, and it usually succeeds, if there are enough registers.

The primitive generator performs the TOS optimization for the floating-point stack, too (`-DUSE_FTOS`). For floating-point operations the benefit of this optimization is even larger: floating-point operations take quite long on most processors, but can be performed in parallel with other operations as long as their results are not used. If the FP-TOS is kept in a register, this works. If it is kept on the stack, i.e., in memory, the store into memory has to wait for the result of the floating-point operation, lengthening the execution time of the primitive considerably.

The TOS optimization makes the automatic generation of primitives a bit more complicated. Just replacing all occurrences of `sp[0]` by `TOS` is not sufficient. There are some special cases to consider:

- In the case of `dup (w -- w w)` the generator must not eliminate the store to the original location of the item on the stack, if the TOS optimization is turned on.
- Primitives with stack effects of the form `-- out1...outy` must store the TOS to the stack at the start. Likewise, primitives with the stack effect `in1...inx --` must load the TOS from the stack at the end. But for the null stack effect `--` no stores or loads should be generated.

15.3.3 Produced code

To see what assembly code is produced for the primitives on your machine with your compiler and your flag settings, type `make engine.s` and look at the resulting file `engine.s`. Alternatively, you can also disassemble the code of primitives with `see` on some architectures.

15.4 Performance

On RISCs the Gforth engine is very close to optimal; i.e., it is usually impossible to write a significantly faster threaded-code engine.

On register-starved machines like the 386 architecture processors improvements are possible, because `gcc` does not utilize the registers as well as a human, even with explicit register declarations; e.g., Bernd Beuster wrote a Forth system fragment in assembly language and hand-tuned it for the 486; this system is 1.19 times faster on the Sieve benchmark on a 486DX2/66 than Gforth compiled with `gcc-2.6.3` with `-DFORCE_REG`. The situation has improved with `gcc-2.95` and `gforth-0.4.9`; now the most important virtual machine registers fit in real registers (and we can even afford to use the TOS optimization), resulting in a speedup of 1.14 on the sieve over the earlier results. And dynamic superinstructions provide another speedup (but only around a factor 1.2 on the 486).

The potential advantage of assembly language implementations is not necessarily realized in complete Forth systems: We compared Gforth-0.5.9 (direct threaded, compiled with `gcc-2.95.1` and `-DFORCE_REG`) with Win32Forth 1.2093 (newer versions are reportedly much faster), LMI's NT Forth (Beta, May 1994) and Eforth (with and without peephole (aka pinhole) optimization of the threaded code); all these systems were written in assembly language. We also compared Gforth with three systems written in C: PFE-0.9.14 (compiled with `gcc-2.6.3` with the default configuration for Linux: `-O2 -fomit-frame-pointer -DUSE_REGS -DUNROLL_NEXT`), ThisForth Beta (compiled with `gcc-2.6.3 -O3 -fomit-frame-pointer`; ThisForth employs peephole optimization of the threaded code) and TILE (compiled with `make opt`). We benchmarked Gforth, PFE, ThisForth and TILE on a 486DX2/66 under Linux. Kenneth O'Heskin kindly provided the results for Win32Forth and NT Forth on a 486DX2/66 with similar memory performance under Windows NT. Marcel Hendrix ported Eforth to Linux, then extended it to run the benchmarks, added the peephole optimizer, ran the benchmarks and reported the results.

We used four small benchmarks: the ubiquitous Sieve; bubble-sorting and matrix multiplication come from the Stanford integer benchmarks and have been translated into Forth by Martin Fraeman; we used the versions included in the TILE Forth package, but with bigger data set sizes; and a recursive Fibonacci number computation for benchmarking calling performance. The following table shows the time taken for the benchmarks scaled by

the time taken by Gforth (in other words, it shows the speedup factor that Gforth achieved over the other systems).

relative time	Win32- Gforth	Win32- Forth	NT Forth	eforth eforth	eforth +opt	This- PFE	This- Forth	TILE
sieve	1.00	2.16	1.78	2.16	1.32	2.46	4.96	13.37
bubble	1.00	1.93	2.07	2.18	1.29	2.21		5.70
matmul	1.00	1.92	1.76	1.90	0.96	2.06		5.32
fib	1.00	2.32	2.03	1.86	1.31	2.64	4.55	6.54

You may be quite surprised by the good performance of Gforth when compared with systems written in assembly language. One important reason for the disappointing performance of these other systems is probably that they are not written optimally for the 486 (e.g., they use the `lods` instruction). In addition, Win32Forth uses a comfortable, but costly method for relocating the Forth image: like `cforth`, it computes the actual addresses at run time, resulting in two address computations per `NEXT` (see `<undefined>` [Image File Background], page `<undefined>`).

The speedup of Gforth over PFE, ThisForth and TILE can be easily explained with the self-imposed restriction of the latter systems to standard C, which makes efficient threading impossible (however, the measured implementation of PFE uses a GNU C extension: see Section “Defining Global Register Variables” in *GNU C Manual*). Moreover, current C compilers have a hard time optimizing other aspects of the ThisForth and the TILE source.

The performance of Gforth on 386 architecture processors varies widely with the version of `gcc` used. E.g., `gcc-2.5.8` failed to allocate any of the virtual machine registers into real machine registers by itself and would not work correctly with explicit register declarations, giving a significantly slower engine (on a 486DX2/66 running the Sieve) than the one measured above.

Note that there have been several releases of Win32Forth since the release presented here, so the results presented above may have little predictive value for the performance of Win32Forth today (results for the current release on an i486DX2/66 are welcome).

In *Translating Forth to Efficient C* (<https://www.complang.tuwien.ac.at/papers/ertl&maierhofer95.pdf>) by M. Anton Ertl and Martin Maierhofer (presented at EuroForth '95), an indirect threaded version of Gforth is compared with Win32Forth, NT Forth, PFE, ThisForth, and several native code systems; that version of Gforth is slower on a 486 than the version used here. You can find a newer version of these measurements at <https://www.complang.tuwien.ac.at/forth/performance.html>. You can find numbers for Gforth on various machines in `Benchres`.

16 Cross Compiler

The cross compiler is used to bootstrap a Forth kernel. Since Gforth is mostly written in Forth, including crucial parts like the outer interpreter and compiler, it needs compiled Forth code to get started. The cross compiler allows to create new images for other architectures, even running under another Forth system.

16.1 Using the Cross Compiler

The cross compiler uses a language that resembles Forth, but isn't. The main difference is that you can execute Forth code after definition, while you usually can't execute the code compiled by cross, because the code you are compiling is typically for a different computer than the one you are compiling on.

The Makefile is already set up to allow you to create kernels for new architectures with a simple make command. The generic kernels using the GCC compiled virtual machine are created in the normal build process with **make**. To create an embedded Gforth executable for e.g. the 8086 processor (running on a DOS machine), type

```
make kernl-8086.fi
```

This will use the machine description from the **arch/8086** directory to create a new kernel. A machine file may look like that:

```
\ Parameter for target systems                                06oct92py

4 Constant cell                \ cell size in bytes
2 Constant cell<<              \ cell shift to bytes
5 Constant cell>bit            \ cell shift to bits
8 Constant bits/char           \ bits per character
8 Constant bits/byte           \ bits per byte [default: 8]
8 Constant float               \ bytes per float
8 Constant /maxalign           \ maximum alignment in bytes
false Constant bigendian       \ byte order
( true=big, false=little )

include machpc.fs            \ feature list
```

This part is obligatory for the cross compiler itself, the feature list is used by the kernel to conditionally compile some features in and out, depending on whether the target supports these features.

There are some optional features, if you define your own primitives, have an assembler, or need special, nonstandard preparation to make the boot process work. **asm-include** includes an assembler, **prims-include** includes primitives, and **>boot** prepares for booting.

```
: asm-include    ." Include assembler" cr
  s" arch/8086/asm.fs" included ;

: prims-include  ." Include primitives" cr
  s" arch/8086/prim.fs" included ;
```

```
: >boot      ." Prepare booting" cr
s" ' boot >body into-forth 1+ !" evaluate ;
```

These words are used as sort of macro during the cross compilation in the file `kernel/main.fs`. Instead of using these macros, it would be possible — but more complicated — to write a new kernel project file, too.

`kernel/main.fs` expects the machine description file name on the stack; the cross compiler itself (`cross.fs`) assumes that either `mach-file` leaves a counted string on the stack, or `machine-file` leaves an address, count pair of the filename on the stack.

The feature list is typically controlled using `SetValue`, generic files that are used by several projects can use `DefaultValue` instead. Both functions work like `Value`, when the value isn't defined, but `SetValue` works like `to` if the value is defined, and `DefaultValue` doesn't set anything, if the value is defined.

```
\ generic mach file for pc gforth                                03sep97jaw

true DefaultValue NIL \ relocating

>ENVIRON

true DefaultValue file      \ controls the presence of the
                             \ file access wordset
true DefaultValue OS        \ flag to indicate a operating system

true DefaultValue prims     \ true: primitives are c-code

true DefaultValue floating  \ floating point wordset is present

true DefaultValue glocals   \ gforth locals are present
                             \ will be loaded
true DefaultValue dcomps    \ double number comparisons

true DefaultValue hash      \ hashing primitives are loaded/present

true DefaultValue xconds    \ used together with glocals,
                             \ special conditionals supporting gforths'
                             \ local variables
true DefaultValue header    \ save a header information

true DefaultValue backtrace \ enables backtrace code

false DefaultValue ec
false DefaultValue crlf

cell 2 = [IF] &32 [ELSE] &256 [THEN] KB DefaultValue kernel-size

&16 KB      DefaultValue stack-size
&15 KB &512 + DefaultValue fstack-size
```

```
&15 KB          DefaultValue rstack-size
&14 KB &512 +    DefaultValue lstack-size
```

16.2 How the Cross Compiler Works

17 MINOS2, a GUI library

17.1 MINOS2 object framework

MINOS2 is a GUI library, written in `mini-oof2.fs`'s object model. It has two main class hierarchies:

```
actor ( - class ) minos2 "actor"
    class for the actions bound to a component.
widget ( - class ) minos2 "widget"
    class for visual components
```

17.1.1 actor methods:

```
caller-w ( - optr ) minos2 "caller-w"
    pointer back to the widget embedding the actor
active-w ( - optr ) minos2 "active-w"
    pointer to the active subwidget embedding the actor
act-name$ ( - addr u ) minos2 "act-name-string"
    Debugging aid: name of the actor
clicked ( rx ry bmask n - ) minos2 "clicked"
    processed clicks
scrolled ( axis dir - ) minos2 "scrolled"
    process scrolling
touchdown ( $rxy*n bmask - ) minos2 "touchdown"
    raw click down
touchup ( $rxy*n bmask - ) minos2 "touchup"
    raw click up
ukeyed ( addr u - ) minos2 "ukeyed"
    key event, string of printable unicode characters
ekeyed ( ekey - ) minos2 "ekeyed"
    key event, non-printable key
?inside ( rx ry - act / 0 ) minos2 "query-inside"
    check if coordinates are inside the widget
focus ( - ) minos2 "focus"
    put widget into focus
defocus ( - ) minos2 "defocus"
    put widget out of focus
entered ( - ) minos2 "entered"
    react on cursor entering the widget area
left ( - ) minos2 "left"
```

react on cursor leaving the widget area
show (*-*) minos2 “show”
 widget is shown
hide (*-*) minos2 “hide”
 widget is hidden
get (*- something*) minos2 “get”
 getter for the value behind the widget
set (*something -*) minos2 “set”
 setter for the value behind the widget
show-you (*-*) minos2 “show-you”
 make widget visible

17.1.2 widget methods:

parent-w (*- optr*) minos2 “parent-w”
 pointer to parent widget
act (*- optr*) minos2 “act”
 pointer to actor
name\$ (*- addr u*) minos2 “name-string”
 Widget name for debugging and searching
x (*- r*) minos2 “x”
 widget x coordinate
y (*- r*) minos2 “y”
 widget y coordinate
w (*- r*) minos2 “w”
 widget width
h (*- r*) minos2 “h”
 widget height above baseline
d (*- r*) minos2 “d”
 widget depth below baseline
gap (*- r*) minos2 “gap”
 gap between lines
baseline (*- r*) minos2 “baseline”
 minimum skip per line
kerning (*- r*) minos2 “kerning”
 add kerning
raise (*- r*) minos2 “raise”
 raise/lower box
border (*- r*) minos2 “border”

surrounding border, all directions
borderv (*- r*) minos2 “borderv”
 vertical border offset
bordert (*- r*) minos2 “bordert”
 top border offset
borderl (*- r*) minos2 “borderl”
 left border offset
w-color (*- r*) minos2 “w-color”
 widget color index (into color map), if any
draw-init (*-*) minos2 “draw-init”
 init draw
draw (*-*) minos2 “draw”
 draw widget
split (*firstflag rstart1 rx - o rstart2*) minos2 “split”
 split a widget into parts for typesetting paragraphs
lastfit (*-*) minos2 “lastfit”
 fit last widget element in a box
hglue (*- rtyp rsub radd*) minos2 “hglue”
 calculate horizontal glue
dglue (*- rtyp rsub radd*) minos2 “dglue”
 calculate vertical glue below baseline
vglue (*- rtyp rsub radd*) minos2 “vglue”
 calculate vertical glue above baseline
hglue@ (*- rtyp rsub radd*) minos2 “hglue-fetch”
 cached variant of **hglue**
dglue@ (*- rtyp rsub radd*) minos2 “dglue-fetch”
 cached variant of **dglue**
vglue@ (*- rtyp rsub radd*) minos2 “vglue-fetch”
 cached variant of **vglue**
xywh (*- rx0 ry0 rw rh*) minos2 “xywh”
 widget bounding box, starting at the top left corner
xywhd (*- rx ry rw rh rd*) minos2 “xywhd”
 widget bounding box, starting at the left baseline point
!resize (*rx ry rw rh rd -*) minos2 “store-resize”
 resize a widget
!size (*-*) minos2 “store-size”
 let the widget self-determine its size
dispose-widget (*-*) minos2 “dispose-widget”

get rid of a widget
.widget (*-*) minos2 “print-widget”
 debugging: Print informations about the widget
par-split (*rw -*) minos2 “par-split”
 split a paragraph by width *rw*
resized (*-*) minos2 “resized”
 widget is resized

Components are composed using a boxes&glue model similar to L^AT_EX, including paragraph breaking. For the sake of simplicity and portability, MINOS2 only supports a single window, and uses OpenGL for rendering.

MINOS2 furthermore supports animations with the **animation** class. A color index texture is used for different color schemes, and transition between neighboring schemes can also be animated.

>animate (*rdelta addr xt -*) minos2 “to-animate”

create a new animation, calling *xt* with stack effect (**addr** *r0..1 --*) repeatedly, until the *rdelta* timeout expired; last call is always with argument *1e* for the time.

You can create named color indexes and assign them color values for the currently active color scheme.

color: (*rgba "name" -*) minos2 “color:”

Create a (possibly shared) color index initialized with *rgba*

new-color: (*rgba "name" -*) minos2 “new-color:”

Create a unique color index initialized with *rgba*

text-color: (*rgba "name" -*) minos2 “text-color:”

Create a unique text color index initialized with *rgba*, the corresponding emoji color is set to white.

text-emoji-color: (*rgbatext rgbaemoji "name" -*) minos2 “text-emoji-color:”

Create a unique text color index initialized with *rgbatext*, the corresponding emoji color is set to *rgbaemoji*.

fade-color: (*rgba1 rgba2 "name" -*) minos2 “fade-color:”

Create a unique pair of text color index initialized with *rgba1* and *rgba2*, the corresponding emoji color is set to white. By slowly shifting the index from one to the next index, the object will shift its color using a linear interpolation when redrawn.

text-emoji-fade-color: (*rgbatext1 ~2 rgbaemoji1 ~2 "name" -*) minos2 “text-emoji-fade-color:”

Create a unique pair of text color index initialized with *rgbatext1* and *~2*, the corresponding emoji color pair is set to *rgbaemoji1* to *~2*. By slowly shifting the index from one to the next index, the object will shift its color using a linear interpolation when redrawn.

re-color (*rgba "name" -*) minos2 “re-color”

assign the named color index “*name*” in the current color scheme with the value *rgba*.

re-text-color (*rgba "name" -*) minos2 “re-text-color”

assign the named text color index "*name*" in the current color scheme with the value *rgba*.

```
re-emoji-color ( rbatext rgbaemoji "name" - ) minos2 "re-emoji-color"
```

assign the named text and emoji color index "*name*" in the current color scheme with the value *rbatext* and *rgbaemoji*.

```
re-fade-color ( rgba1 rgba2 "name" - ) minos2 "re-fade-color"
```

assign the named color index pair "*name*" in the current color scheme with the value *rgba1* and *rgba2*.

```
re-text-emoji-fade-color ( rbatext1 ~2 rgbaemoji1 ~2 "name" - ) minos2 "re-text-emoji-fade-color"
```

assign the named color index pair "*name*" in the current color scheme with the value *rbatext1* and *~2* resp. *rgbaemoji1* and *~2*.

For a number of specific objects, there are early bound methods, that only work on these objects

- Viewport

```
vp-top ( o:vp - ) minos2 "vp-top"
```

scroll viewport to top

```
vp-bottom ( o:vp - ) minos2 "vp-bottom"
```

scroll viewport to bottom

```
vp-left ( o:vp - ) minos2 "vp-left"
```

scroll viewport to left

```
vp-right ( o:vp - ) minos2 "vp-right"
```

scroll viewport to right

```
vp-reslide ( o:vp - ) minos2 "vp-reslide"
```

Adjust the sliders of a viewport after scrolling

```
vp-needed ( xt - ) minos2 "vp-needed"
```

collect needs in viewport's vp-need

17.2 MINOS2 tutorial

Tutorials are small files, each showing a bit of MINOS2. For the common framework, the file `minos2/tutorial/tutorial.fs` needs to be loaded first; all other tutorials in the command line argument are included from within that file. Scroll wheel or previous/next mouse buttons as well as clicking on the left or right edge of the window allow navigation between the different tutorials loaded.

I.e. to load the buttons tutorial, you start Gforth with

```
gforth minos2/tutorial/tutorial.fs buttons.fs
```

Available tutorials:

- `buttons.fs`: Clickable buttons
- `plots.fs`: Plot functions
- `markdown.fs`: Markdown document viewer
- `screenshot.fs`: Screenshot function

Appendix A Bugs

Known bugs are described in the file `BUGS` in the Gforth distribution.

If you find a bug, please submit a bug report through <https://savannah.gnu.org/bugs/?func=addbug&group=gforth>.

- A program (or a sequence of keyboard commands) that reproduces the bug.
- A description of what you think constitutes the buggy behaviour.
- The Gforth version used (it is announced at the start of an interactive Gforth session).
- The machine and operating system (on Unix systems `uname -a` will report this information).
- The installation options (you can find the configure options at the start of `config.status`) and configuration (`configure` output or `config.cache`).
- A complete list of changes (if any) you (or your installer) have made to the Gforth sources.

For a thorough guide on reporting bugs read Section “How to Report Bugs” in *GNU C Manual*.

Appendix B Authors and Ancestors of Gforth

B.1 Authors and Contributors

The Gforth project was started in mid-1992 by Bernd Paysan and Anton Ertl. The third major author was Jens Wilke. Neal Crook contributed a lot to the manual. Assemblers and disassemblers were contributed by Andrew McKewan, Christian Pirker, Bernd Thallner, and Michal Revucky. Lennart Benschop (who was one of Gforth's first users, in mid-1993) and Stuart Ramsden inspired us with their continuous feedback. Lennart Benschop contributed `glosgen.fs`, while Stuart Ramsden has been working on automatic support for calling C libraries. Helpful comments also came from Paul Kleinrubatscher, Christian Pirker, Dirk Zoller, Marcel Hendrix, John Wavrik, Barrie Stott, Marc de Groot, Jorge Acerada, Bruce Hoyt, Robert Epprecht, Dennis Ruffer and David N. Williams. Since the release of Gforth-0.2.1 there were also helpful comments from many others; thank you all, sorry for not listing you here (but digging through my mailbox to extract your names is on my to-do list).

Gforth also owes a lot to the authors of the tools we used (GCC, CVS, and autoconf, among others), and to the creators of the Internet: Gforth was developed across the Internet, and its authors did not meet physically for the first 4 years of development.

B.2 Pedigree

Gforth descends from bigFORTH (1993) and fig-Forth. Of course, a significant part of the design of Gforth was prescribed by Standard Forth.

Bernd Paysan wrote bigFORTH, a descendent from TurboForth, an unreleased 32 bit native code version of VolksForth for the Atari ST, written mostly by Dietrich Weineck.

VolksForth was written by Klaus Schleisiek, Bernd Pennemann, Georg Rehfeld and Dietrich Weineck for the C64 (called UltraForth there) in the mid-80s and ported to the Atari ST in 1986. It descends from fig-Forth.

A team led by Bill Ragsdale implemented fig-Forth on many processors in 1979. Robert Selzer and Bill Ragsdale developed the original implementation of fig-Forth for the 6502 based on microForth.

The principal architect of microForth was Dean Sanderson. microForth was FORTH, Inc.'s first off-the-shelf product. It was developed in 1976 for the 1802, and subsequently implemented on the 8080, the 6800 and the Z80.

All earlier Forth systems were custom-made, usually by Charles Moore, who discovered (as he puts it) Forth during the late 60s. The first full Forth existed in 1971.

A part of the information in this section comes from *The Evolution of Forth* (<https://www.forth.com/resources/evolution/index.html>) by Elizabeth D. Rather, Donald R. Colburn and Charles H. Moore, presented at the HOPL-II conference and preprinted in SIGPLAN Notices 28(3), 1993. You can find more historical and genealogical information about Forth there. For a more general (and graphical) Forth family tree look see <https://www.complang.tuwien.ac.at/forth/family-tree/>, *Forth Family Tree and Timeline*.

Appendix C Other Forth-related information

There is an active news group (`comp.lang.forth`) discussing Forth (including Gforth) and Forth-related issues. Its FAQs (<https://www.complang.tuwien.ac.at/forth/faq/faq-general-2.html>) (frequently asked questions and their answers) contains a lot of information on Forth. You should read it before posting to `comp.lang.forth`.

The Forth standard is most usable in its HTML form (<https://forth-standard.org/>).

Appendix D Licenses

D.1 GNU Free Documentation License

Version 1.2, November 2002

Copyright © 2000,2001,2002 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any,

- be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
 - C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
 - D. Preserve all the copyright notices of the Document.
 - E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
 - F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
 - G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
 - H. Include an unaltered copy of this License.
 - I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
 - J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
 - K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
 - L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
 - M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
 - N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
 - O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their

titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

D.1.1 ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts.  A copy of the license is included in the section entitled ``GNU
Free Documentation License''.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

D.2 GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright © 2007 Free Software Foundation, Inc. <http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program—to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes

copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To “convey” a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays “Appropriate Legal Notices” to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The “source code” for a work means the preferred form of the work for making modifications to it. “Object code” means any non-source form of a work.

A “Standard Interface” means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The “System Libraries” of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A “Major Component”, in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The “Corresponding Source” for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work’s System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its

content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a. The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b. The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c. You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any

applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

- d. If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an “aggregate” if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation’s users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c. Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d. Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

- e. Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A “User Product” is either (1) a “consumer product”, which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, “normally used” refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

“Installation Information” for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

“Additional permissions” are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permis-

sions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a. Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b. Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c. Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d. Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e. Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f. Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered “further restrictions” within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will

automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An “entity transaction” is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party’s predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A “contributor” is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor’s “contributor version”.

A contributor’s “essential patent claims” are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, “control” includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor’s essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a “patent license” is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To “grant” such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. “Knowingly relying” means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient’s use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is “discriminatory” if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License “or any later version” applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFEC-

TIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the “copyright” line and a pointer to where the full notice is found.

one line to give the program's name and a brief idea of what it does.
Copyright (C) year name of author

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
program Copyright (C) year name of author
This program comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type 'show c' for details.
```

The hypothetical commands ‘show w’ and ‘show c’ should show the appropriate parts of the General Public License. Of course, your program’s commands might be different; for a GUI interface, you would use an “about box”.

You should also get your employer (if you work as a programmer) or school, if any, to sign a “copyright disclaimer” for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

Word Index

This index is a list of Forth words that have “glossary” entries within this manual. Each word is listed with its stack effect and wordset.

!

! (w a-addr --) core 81
 !!FIXME!! (--) gforth-1.0 245
 !@ (w1 a-addr -- w2) gforth-experimental. 81
 !localn (w noffset --) gforth-internal. 207
 !resize (rx ry rw rh rd --) minos2 326
 !size (--) minos2 326

#

(ud1 -- ud2) core 184
 #! (--) gforth-0.2 310
 #> (xd -- addr u) core 184
 #>> (--) gforth-0.5 184
 #bell (-- c) gforth-0.2 90
 #bs (-- c) gforth-0.2 90
 #cr (-- c) gforth-0.2 90
 #del (-- c) gforth-0.2 90
 #eof (-- c) gforth-0.7 90
 #esc (-- c) gforth-0.5 90
 #ff (-- c) gforth-0.2 90
 #lf (-- c) gforth-0.2 90
 #line ("u" ["file"] --) gforth-1.0 ... 159
 #loc (nline nchar "file" --) gforth-1.0. 245
 #locals (-- n) environment 170
 #s (ud -- 0 0) core 184
 #tab (-- c) gforth-0.2 90
 #tib (-- addr) core-ext-obsolescent 156

\$

\$! (addr1 u \$addr --) gforth-0.7 93
 \$!len (u \$addr --) gforth-0.7 93
 \$+! (addr1 u \$addr --) gforth-0.7 93
 \$+!len (u \$addr -- addr) gforth-1.0 93
 \$+[]! (c-addr u \$[]addr --) gforth-1.0... 94
 \$+slurp (fid \$addr --) gforth-1.0 94
 \$+slurp-file (c-addr u \$addr --)
 gforth-1.0 94
 \$. (\$addr --) gforth-1.0 94
 \$? (-- n) gforth-0.2 279
 \$[] (u \$[]addr -- addr') gforth-1.0 94
 \$[]! (c-addr u n \$[]addr --) gforth-1.0.. 94
 \$[]# (\$[]addr -- len) gforth-1.0 94
 \$[]+! (c-addr u n \$[]addr --) gforth-1.0. 94
 \$[] . (\$[]addr --) gforth-1.0 95
 \$[]@ (n \$[]addr -- addr u) gforth-1.0 94
 \$[]free (\$[]addr --) gforth-1.0 95
 \$[]map (\$[]addr xt --) gforth-1.0 94

\$[]slurp (fid \$[]addr --) gforth-1.0..... 94
 \$[]slurp-file (addr u \$[]addr --)
 gforth-1.0 94
 \$[]Variable ("name" --) gforth-1.0..... 95
 \$@ (\$addr -- addr2 u) gforth-0.7 93
 \$@len (\$addr -- u) gforth-0.7 93
 \$del (\$addr off u --) gforth-0.7 93
 \$exec (xt \$addr --) gforth-1.0 94
 \$free (\$addr --) gforth-1.0 93
 \$init (\$addr --) gforth-1.0 93
 \$ins (addr1 u \$addr off --) gforth-0.7 ... 93
 \$iter (.. \$addr char xt -- ..)
 gforth-0.7 93
 \$over (addr u \$addr off --) gforth-1.0... 93
 \$slurp (fid \$addr --) gforth-1.0 94
 \$slurp-file (c-addr u \$addr --)
 gforth-1.0 94
 \$split (c-addr u char -- c-addr u1 c-addr2 u2
) gforth-0.7 91
 \$substitute (addr1 len1 -- addr2 len2 n/ior
) gforth-experimental 198
 \$tmp (xt -- addr u) gforth-1.0 92
 \$unescape (addr1 u1 -- addr2 u2)
 gforth-experimental 198
 \$value: (u1 "name" -- u2)
 gforth-experimental 137
 \$value[]: (u1 "name" -- u2)
 gforth-experimental 138
 \$Variable ("name" --) gforth-1.0 95

%

%align (align size --) gforth-0.4 141
 %alignment (align size -- align)
 gforth-0.4 141
 %alloc (align size -- addr) gforth-0.4.. 141
 %allocate (align size -- addr ior)
 gforth-0.4 141
 %allot (align size -- addr) gforth-0.4.. 141
 %size (align size -- size) gforth-0.4... 141

,

' ("name" -- xt) core 145
 'cold (--) gforth-0.2 311
 's (addr1 task -- addr2)
 gforth-experimental 251

- (
 ((compilation 'ccc<close-paren>' -- ;
 run-time --) core,file..... 59
 (((addr u --) regexp-pattern..... 235
 (local) (addr u --) local 209
)
) (--) gforth-0.2..... 246
)) (-- flag) regexp-pattern 235
- *
- * (n1 n2 -- n) core..... 61
 **} (sys --) regexp-pattern 237
 */ ((n1 n2 n3 -- n4) core 63
 */f (n1 n2 n3 -- n4) gforth-1.0..... 63
 */mod (n1 n2 n3 -- n4 n5) core..... 63
 */modf (n1 n2 n3 -- n4 n5) gforth-1.0..... 63
 */mods (n1 n2 n3 -- n4 n5) gforth-1.0..... 63
 */s (n1 n2 n3 -- n4) gforth-1.0..... 63
 *} (addr addr' -- addr') regexp-pattern. 237
 *align (n --) gforth-1.0..... 86
 *aligned (addr1 n -- addr2) gforth-1.0... 86
- +
- + (n1 n2 -- n) core..... 60
 +! (n a-addr --) core..... 81
 +!@ (u1 a-addr -- u2)
 gforth-experimental..... 81
 ++} (sys --) regexp-pattern 237
 +} (addr addr' -- addr') regexp-pattern. 237
 +after (x1 x2 stack --)
 gforth-experimental..... 142
 +char (char --) regexp-cg..... 236
 +chars (addr u --) regexp-cg..... 236
 +class (class --) regexp-cg..... 236
 +DO (compilation -- do-sys ; run-time n1 n2
 -- | loop-sys) gforth-0.2..... 100
 +field (noffset1 nsize "name" -- noffset2)
 facility-ext..... 136
 +fmode (fam1 rwxrwxrwx -- fam2)
 gforth-1.0..... 174
 +load (i*x n -- j*x) gforth-0.2..... 182
 +LOOP (compilation do-sys -- ; run-time
 loop-sys1 n -- | loop-sys2) core 101
 +ltrace (--) gforth-1.0..... 245
 +thru (i*x n1 n2 -- j*x) gforth-0.2..... 182
 +T0 (value "name" --) gforth-1.0..... 114
 +x/string (xc-addr1 u1 -- xc-addr2 u2)
 xchar-ext..... 196
- ,
 , (w --) core..... 77
-
- (n1 n2 -- n) core..... 61
 -- (haddr u wid 0 ... --) local-ext..... 202
 --> (--) gforth-0.2..... 182
 ->here (addr --) gforth-1.0..... 76
 -[do (compilation -- do-sys ; run-time n1 n2
 -- | loop-sys) gforth-experimental.... 100
 -` ("char" --) regexp-pattern..... 236
 -\d (addr -- addr') regexp-pattern..... 236
 -\s (addr -- addr') regexp-pattern..... 236
 -c? (addr class --) regexp-pattern..... 236
 -char (char --) regexp-cg..... 236
 -class (class --) regexp-cg..... 236
 -DO (compilation -- do-sys ; run-time n1 n2
 -- | loop-sys) gforth-0.2..... 100
 -inf (-- r) gforth-1.0..... 71
 -infinity (-- r) gforth-1.0..... 71
 -LOOP (compilation do-sys -- ; run-time
 loop-sys1 u -- | loop-sys2) gforth-0.2. 101
 -ltrace (--) gforth-1.0..... 245
 -rot (w1 w2 w3 -- w3 w1 w2) gforth-0.2.... 72
 -stack (x stack --)
 gforth-experimental..... 142
 -trailing (c_addr u1 -- c_addr u2)
 string..... 91
 -trailing-garbage (xc-addr u1 -- xc-addr u2
) xchar-ext..... 196
- .
- . (n --) core..... 182
 ." (compilation 'ccc'" -- ; run-time --)
 core..... 188
 .((compilation&interpretation
 'ccc<close-paren>' --) core-ext 188
 ... (x1 .. xn -- x1 .. xn) gforth-1.0.... 242
 ..char (start end --) regexp-cg..... 236
 .? (addr -- addr') regexp-pattern..... 236
 .\" (compilation 'ccc'" -- ; run-time --)
 gforth-0.6..... 188
 .cover-raw (--) gforth-experimental.... 248
 .coverage (--) gforth-experimental.... 248
 .debugline (nfile nline --) gforth-0.6. 244
 .fpath (--) gforth-0.4..... 178
 .hm (nt --) gforth-1.0..... 275
 .id (nt --) gforth-0.6..... 147
 .included (--) gforth-0.5..... 174
 .locale-csv (--) gforth-experimental... 197
 .path (path-addr --) gforth-0.4..... 178
 .quoted-csv (c-addr u --)
 gforth-experimental..... 199

- .r (n1 n2 --) core-ext..... 183
- .recognizers (--) gforth-experimental.. 160
- .s (--) tools..... 242
- .sections (--) gforth-1.0..... 79
- .substitute (addr1 len1 -- n / ior)
 - gforth-experimental..... 198
- .unresolved (--) gforth-1.0..... 106
- .voc (wid --) gforth-0.2..... 166
- .widget (--) minos2..... 327

- /
 - (n1 n2 -- n) core..... 62
 - ((--) regexp-pattern..... 237
 - (ptr addr u -- addr' u')
 - regexp-replace..... 238
 - (ptr addr u -- addr' u')
 - regexp-replace..... 238
 - (ptr --) regexp-replace..... 238
 - /COUNTED-STRING (-- n) environment..... 169
 - /f (n1 n2 -- n) gforth-1.0..... 62
 - /f-stage1m (n a-reci --) gforth-1.0..... 65
 - /f-stage2m (n1 a-reci -- nquotient)
 - gforth-1.0..... 65
 - /HOLD (-- n) environment..... 170
 - /l (-- u) gforth-0.7..... 86
 - /mod (n1 n2 -- n3 n4) core..... 62
 - /modf (n1 n2 -- n3 n4) gforth-1.0..... 63
 - /modf-stage2m (n1 a-reci -- umodulus
 - nquotient) gforth-1.0..... 65
 - /mods (n1 n2 -- n3 n4) gforth-1.0..... 62
 - /PAD (-- n) environment..... 170
 - /s (n1 n2 -- n) gforth-1.0..... 62
 - /string (c-addr1 u1 n -- c-addr2 u2)
 - string..... 91
 - /w (-- u) gforth-0.7..... 86
 - /x (-- u) gforth-1.0..... 86

- :
 - ("name" -- colon-sys) core..... 115
 - :: (class "name" --) mini-oof..... 225
 - } (haddr u wid 0 xt1 ... xtn --)
 - gforth-1.0..... 202
 - }d (haddr u latest latestnt wid 0 a-addr1
 - u1 ... --) gforth-1.0..... 231
 - }h (haddr u latest latestnt wid 0 a-addr1
 - u1 ... --) gforth-1.0..... 231
 - }h1 (haddr u latest latestnt wid 0 a-addr1
 - u1 ... --) gforth-1.0..... 231
 - }l (haddr u latest latestnt wid 0 a-addr1
 - u1 ... --) gforth-1.0..... 231
 - }xt (haddr u latest latestnt wid 0 a-addr1
 - u1 ... --) gforth-1.0..... 231
 - :is ("name" --) gforth-experimental.... 131

- :m ("name" -- xt; run-time: object --)
 - objects..... 220
- :method (class "name" --)
 - gforth-experimental..... 228
- :noname (-- xt colon-sys) core-ext..... 116

- ;
 - (compilation colon-sys -- ; run-time
 - nest-sys --) core..... 115
 - > (compilation colon-sys -- ; run-time --
 - addr) gforth-obsolete..... 235
 -] (compile-time: quotation-sys -- ;
 - run-time: -- xt) gforth-1.0..... 118
 - ;abi-code (--) gforth-1.0..... 261
 - ;code (compilation. colon-sys1 -- colon-sys2
 -) tools-ext..... 262
 - ;inline (inline:-sys --)
 - gforth-experimental..... 116
 - ;m (colon-sys --; run-time: --) objects. 220

- <
 - (n1 n2 -- f) core..... 68
 - <# (--) core..... 184
 - << (run-addr addr u -- run-addr)
 - regexp-replace..... 238
 - <<" ("string<">" --) regexp-replace.... 238
 - <<# (--) gforth-0.5..... 184
 - <= (n1 n2 -- f) gforth-0.2..... 68
 - <> (n1 n2 -- f) core-ext..... 68
 - <{: (compilation -- colon-sys ; run-time --
 -) gforth-obsolete..... 235
 - <bind> (class selector-xt -- xt)
 - objects..... 218
 - <to-inst> (w xt --) objects..... 221

- =
 - = (n1 n2 -- f) core..... 68
 - = " (<string>" --) regexp-pattern..... 237
 - =mkdir (c-addr u wmode -- wior)
 - gforth-0.7..... 177

```

>
> ( n1 n2 -- f ) core..... 68
>= ( n1 n2 -- f ) gforth-0.2..... 68
>> ( addr -- addr ) regexp-replace..... 238
>addr ( ... xt -- addr ) gforth-internal.. 231
>animate ( rdelta addr xt -- ) minus2..... 327
>back ( x stack -- ) gforth-experimental. 142
>body ( xt -- a-addr ) core..... 122
>code-address ( xt -- c-addr )
    gforth-0.2..... 277
>definer ( xt -- definer ) gforth-0.2..... 278
>does-code ( xt1 -- xt2 ) gforth-0.2..... 278
>float ( c-addr u -- f:... flag )
    floating..... 194
>float1 ( c-addr u c -- f:... flag )
    gforth-1.0..... 194
>in ( -- addr ) core..... 156
>l ( w -- ) gforth-0.2..... 207
>name ( xt -- nt|0 ) gforth-0.2..... 147
>number ( ud1 c-addr1 u1 -- ud2 c-addr2 u2 )
    core..... 193
>o ( c-addr -- r:c-old ) new..... 227
>order ( wid -- ) gforth-0.5..... 166
>pow2 ( u1 -- u2 ) gforth-1.0..... 67
>r ( w -- R:w ) core..... 74
>stack ( x stack -- )
    gforth-experimental..... 142
>string-execute ( ... xt -- ... c-addr u )
    gforth-1.0..... 92
>time&date&tz ( udtim -- nsec nmin nhour
    nday nmonth nyear fdst ndstoffs c-addrtz utz
    ) gforth-1.0..... 279
>uvalue ( xt -- addr ) gforth-internal... 127

?
? ( a-addr -- ) tools..... 243
??? ( -- ) gforth-0.2..... 245
?cov+ ( flag -- flag )
    gforth-experimental..... 248
?DO ( compilation -- do-sys ; run-time w1 w2
    -- | loop-sys ) core-ext..... 100
?dup ( w -- S:... w ) core..... 73
?dup-IF ( compilation -- orig ; run-time n --
    n| ) gforth-0.2..... 106
?DUP-0=-IF ( compilation -- orig ; run-time n
    -- n| ) gforth-0.2..... 106
?errno-throw ( f -- ) gforth-1.0..... 108
?events ( -- ) gforth-experimental..... 253
?EXIT ( -- ) gforth-0.2..... 107
?found ( token|0 -- token|never )
    gforth-experimental..... 162
?inside ( rx ry -- act / 0 ) minus2..... 324
?ior ( x -- ) gforth-1.0..... 108
?LEAVE ( compilation -- ; run-time f | f
    loop-sys -- ) gforth-0.2..... 101

```

```

?of ( compilation -- of-sys ; run-time f -- )
    gforth-1.0..... 104

[
[ ( -- ) core..... 149
['] ( compilation. "name" -- ; run-time. -- xt
    ) core..... 145
[+LOOP] ( n -- ) gforth-0.2..... 159
[: ( compile-time: -- quotation-sys flag
    colon-sys ) gforth-1.0..... 117
[?DO] ( n-limit n-index -- ) gforth-0.2.. 159
[{: ( compilation -- haddr u latest wid 0 ;
    instantiation ... -- xt ) gforth-1.0... 231
[AGAIN] ( -- ) gforth-0.2..... 159
[BEGIN] ( -- ) gforth-0.2..... 159
[bind] ( compile-time: "class" "selector" --
    ; run-time: ... object -- ... ) objects. 218
[char] ( compilation '<spaces>ccc' -- ;
    run-time -- c ) core,xchar-ext..... 90
[COMP'] ( compilation "name" -- ; run-time --
    w xt ) gforth-0.2..... 148
[compile] ( compilation "name" -- ; run-time
    ? -- ? ) core-ext..... 153
[current] ( compile-time: "selector" -- ;
    run-time: ... object -- ... ) objects... 219
[d:d ( compilation -- colon-sys; run-time: d
    -- xt ; xt execution: -- d ) gforth-1.0. 230
[d:h ( compilation -- colon-sys; run-time: d
    -- xt ; xt execution: -- d ) gforth-1.0. 230
[d:h1 ( compilation -- colon-sys; run-time: d
    -- xt ; xt execution: -- d ) gforth-1.0. 230
[d:l ( compilation -- colon-sys; run-time: d
    -- xt ; xt execution: -- d ) gforth-1.0. 230
[defined] ( "<spaces>name" -- flag )
    tools-ext..... 158
[DO] ( n-limit n-index -- ) gforth-0.2... 159
[ELSE] ( -- ) tools-ext..... 158
[ENDIF] ( -- ) gforth-0.2..... 158
[f:d ( compilation -- colon-sys; run-time: r
    -- xt ; xt execution: -- r ) gforth-1.0. 230
[f:h ( compilation -- colon-sys; run-time: r
    -- xt ; xt execution: -- r ) gforth-1.0. 230
[f:h1 ( compilation -- colon-sys; run-time: r
    -- xt ; xt execution: -- r ) gforth-1.0. 230
[f:l ( compilation -- colon-sys; run-time: r
    -- xt ; xt execution: -- r ) gforth-1.0. 230
[FOR] ( n -- ) gforth-0.2..... 159
[I] ( run-time -- n ) gforth-0.2..... 159
[IF] ( flag -- ) tools-ext..... 158
[IFDEF] ( "<spaces>name" -- ) gforth-0.2. 158
[IFUNDEF] ( "<spaces>name" -- )
    gforth-0.2..... 158
[LOOP] ( -- ) gforth-0.2..... 159
[n:d ( compilation -- colon-sys; run-time: n
    -- xt ; xt execution: -- n ) gforth-1.0. 230

```

- [n:h (compilation -- colon-sys; run-time: n
-- xt ; xt execution: -- n) gforth-1.0. 230
[n:h1 (compilation -- colon-sys; run-time: n
-- xt ; xt execution: -- n) gforth-1.0. 230
[n:l (compilation -- colon-sys; run-time: n
-- xt ; xt execution: -- n) gforth-1.0. 230
[NEXT] (n --) gforth-0.2..... 159
[noop] (--) gforth-experimental 126
[parent] (compile-time: "selector" -- ;
run-time: ... object -- ...) objects... 220
[REPEAT] (--) gforth-0.2..... 159
[THEN] (--) tools-ext..... 158
[to-inst] (compile-time: "name" -- ;
run-time: w --) objects..... 221
[undefined] ("<spaces>name" -- flag)
tools-ext..... 158
[UNTIL] (flag --) gforth-0.2..... 159
[WHILE] (flag --) gforth-0.2..... 159
-]
-] (--) core..... 149
]] (--) gforth-0.6..... 151
]L (compilation: n -- ; run-time: -- n)
gforth-0.5..... 150
]nocov (--) gforth-1.0..... 247
- ,
- ` ("char" --) regexp-pattern..... 236
`? ("char" --) regexp-pattern..... 236
- @
- @ (a-addr -- w) core..... 81
@localn (noffset -- w) gforth-internal. 207
- \
- \ (compilation 'ccc<newline>' -- ; run-time
--) core-ext,block-ext..... 60
\\$ (addr -- addr) regexp-pattern..... 236
\\ (addr -- addr) regexp-pattern..... 237
\\ (addr -- addr) regexp-pattern..... 237
\\^ (addr -- addr) regexp-pattern..... 236
\\\\ (--) gforth-1.0..... 174
\\0 (-- addr u) regexp-pattern..... 237
\\c ("rest-of-line" --) gforth-0.7..... 256
\\d (addr -- addr') regexp-pattern..... 236
\\G (compilation 'ccc<newline>' -- ; run-time
--) gforth-0.2..... 60
\\s (addr -- addr') regexp-pattern..... 236
- {
- { (-- haddr u wid 0) gforth-0.2..... 202
{* (addr -- addr addr) regexp-pattern... 237
{** (addr -- addr addr) regexp-pattern... 237
{+ (addr -- addr addr) regexp-pattern... 237
{++ (addr -- addr addr) regexp-pattern... 237
{: (-- haddr u wid 0) local-ext..... 202
{{ (addr -- addr addr) regexp-pattern... 237
- }
- } (haddr u wid 0 xt1 ... xtn --)
gforth-0.2..... 202
}} (addr addr -- addr) regexp-pattern... 237
- |
- | (--) local-ext..... 202
|| (addr addr -- addr addr)
regexp-pattern..... 237
- ~
- ~~ (--) gforth-0.2..... 244
~~1bt (--) gforth-1.0..... 244
~~bt (--) gforth-1.0..... 244
~~Value (n "name" --) gforth-1.0..... 245
~~Variable ("name" --) gforth-1.0..... 245
- 0
- 0< (n -- f) core..... 68
0<= (n -- f) gforth-0.2..... 68
0<> (n -- f) core-ext..... 68
0= (n -- f) core..... 68
0> (n -- f) core-ext..... 68
0>= (n -- f) gforth-0.2..... 68
- 1
- 1+ (n1 -- n2) core..... 60
1- (n1 -- n2) core..... 61
1/f (r1 -- r2) gforth-0.2..... 70

2

2! (w1 w2 a-addr --) core..... 82
 2* (n1 -- n2) core..... 67
 2, (w1 w2 --) gforth-0.2..... 77
 2/ (n1 -- n2) core..... 67
 2>r (w1 w2 -- R:w1 R:w2) core-ext..... 74
 2@ (a-addr -- w1 w2) core..... 82
 2compile, (xt1 xt2 --)
 gforth-experimental..... 153
 2Constant (w1 w2 "name" --) double..... 114
 2drop (w1 w2 --) core..... 73
 2dup (w1 w2 -- w1 w2 w1 w2) core..... 73
 2field: (u1 "name" -- u2) gforth-0.7.... 135
 2Literal (compilation w1 w2 -- ; run-time --
 w1 w2) double..... 150
 2nip (w1 w2 w3 w4 -- w3 w4) gforth-0.2.... 73
 2over (w1 w2 w3 w4 -- w1 w2 w3 w4 w1 w2)
 core..... 73
 2r> (R:w1 R:w2 -- w1 w2) core-ext..... 74
 2r@ (R:w1 R:w2 -- R:w1 R:w2 w1 w2)
 core-ext..... 74
 2rdrop (R:w1 R:w2 --) gforth-0.2..... 74
 2rot (w1 w2 w3 w4 w5 w6 -- w3 w4 w5 w6 w1 w2)
 double-ext..... 73
 2swap (w1 w2 w3 w4 -- w3 w4 w1 w2) core.... 73
 2tuck (w1 w2 w3 w4 -- w3 w4 w1 w2 w3 w4)
 gforth-0.2..... 73
 2Value (w1 w2 "name" --) double-ext..... 114
 2value: (u1 "name" -- u2)
 gforth-experimental..... 137
 2Variable ("name" --) double..... 113

A

A, (addr --) gforth-0.2..... 77
 abi-code ("name" -- colon-sys)
 gforth-1.0..... 261
 abort (?? -- ??) core,exception-ext..... 111
 ABORT" (compilation 'ccc' -- ; run-time ...
 f --) core,exception-ext..... 111
 abs (n -- u) core..... 61
 absolute-file? (addr u -- flag)
 gforth-1.0..... 177
 accept (c-addr +n1 -- +n2) core..... 193
 AConstant (addr "name" --) gforth-0.2.. 113
 act (-- optr) minos2..... 325
 act-name\$ (-- addr u) minos2..... 324
 action-of (interpretation "name" -- xt;
 compilation "name" -- ; run-time -- xt)
 core-ext..... 131
 activate (run-time nest-sys1 task --)
 gforth-experimental..... 249
 active-w (-- optr) minos2..... 324
 actor (-- class) minos2..... 324
 add-cflags (c-addr u --) gforth-1.0.... 258
 add-framework (c-addr u --) gforth-1.0. 258

add-incdir (c-addr u --) gforth-1.0.... 258
 add-ldflags (c-addr u --) gforth-1.0... 258
 add-lib (c-addr u --) gforth-0.7..... 258
 add-libpath (c-addr u --) gforth-0.7... 258
 addr ("name" -- addr) gforth-1.0..... 115
 ADDRESS-UNIT-BITS (-- n) environment... 169
 addressable: (--) gforth-experimental.. 115
 adjust-buffer (u addr --)
 gforth-experimental..... 81
 after-locate (-- u) gforth-1.0..... 239
 AGAIN (compilation dest -- ; run-time --)
 core-ext..... 105
 AHEAD (compilation -- orig ; run-time --)
 tools-ext..... 105
 Alias (xt "name" --) gforth-0.2..... 133
 align (--) core..... 77
 aligned (c-addr -- a-addr) core..... 85
 ALiteral (compilation addr -- ; run-time --
 addr) gforth-0.2..... 149
 allocate (u -- a-addr wior) memory..... 80
 allot (n --) core..... 76
 also (--) search-ext..... 166
 also-path (c-addr len path-addr --)
 gforth-0.4..... 178
 and (w1 w2 -- w) core..... 66
 annotate-cov (--) gforth-experimental.. 248
 append (c-addr1 u1 c-addr2 u2 -- c-addr u)
 gforth-0.7..... 92
 arg (u -- addr count) gforth-0.2..... 199
 argc (-- addr) gforth-0.2..... 200
 argv (-- addr) gforth-0.2..... 200
 array>mem (uelements uelemsize -- ubytes
 uelemsize) gforth-experimental..... 100
 arshift (n1 u -- n2) gforth-1.0..... 66
 asptr (class --) oof..... 223
 assembler (--) tools-ext..... 261
 assert((--) gforth-0.2..... 246
 assert-level (-- a-addr) gforth-0.2.... 246
 assert0((--) gforth-0.2..... 245
 assert1((--) gforth-0.2..... 245
 assert2((--) gforth-0.2..... 246
 assert3((--) gforth-0.2..... 246
 ASSUME-LIVE (orig -- orig) gforth-0.2.. 205
 at-deltax (dx dy --) gforth-0.7..... 189
 at-xy (x y --) facility..... 189
 atomic!@ (w1 a-addr -- w2)
 gforth-experimental..... 252
 atomic+!@ (u1 a-addr -- u2)
 gforth-experimental..... 252
 atomic?!@ (unew uold a-addr -- uprev)
 gforth-experimental..... 252
 AUser ("name" --) gforth-0.2..... 251
 authors (--) gforth-1.0..... 10
 AValue (w "name" --) gforth-0.6..... 114
 AVariable ("name" --) gforth-0.2..... 113

B

b (--) gforth-1.0..... 239
 back> (stack -- x) gforth-experimental. 142
 barrier (--) gforth-experimental..... 252
 base (-- a-addr) core..... 157
 base-execute (i*x xt u -- j*x)
 gforth-0.7..... 157
 baseline (-- r) minos2..... 325
 basename (c-addr1 u1 -- c-addr2 u2)
 gforth-0.7..... 176
 before-line (--) gforth-1.0..... 163
 before-locate (-- u) gforth-1.0..... 239
 before-word (--) gforth-0.7..... 163
 begin-structure ("name" -- struct-sys 0)
 facility-ext..... 135
 BEGIN (compilation -- dest ; run-time --)
 core..... 105
 bin (fam1 -- fam2) file..... 174
 bind (... "class" "selector" -- ...)
 objects..... 218
 bind' ("class" "selector" -- xt)
 objects..... 218
 bl (-- c-char) core..... 90
 blank (c-addr u --) string..... 87
 blk (-- addr) block..... 156
 block (u -- a-addr) block..... 181
 block-included (a-addr u --)
 gforth-0.2..... 182
 block-offset (-- addr) gforth-0.5..... 181
 block-position (u --) block..... 181
 bootmessage (--) gforth-0.4..... 311
 border (-- r) minos2..... 325
 borderl (-- r) minos2..... 326
 bordert (-- r) minos2..... 326
 borderv (-- r) minos2..... 326
 bounds (u1 u2 -- u3 u1) gforth-0.2..... 100
 break" ('ccc' --) gforth-0.4..... 247
 break: (--) gforth-0.4..... 247
 broken-pipe-error (-- n) gforth-0.6..... 194
 browse ("subname" --) gforth-1.0..... 239
 bt (--) gforth-1.0..... 240
 buffer (u -- a-addr) block..... 181
 buffer% (u1 u2 --) gforth-experimental.. 81
 buffer: (u "name" --) core-ext..... 113
 bw (--) gforth-1.0..... 240
 bw-cover (--) gforth-1.0..... 248
 bye (--) tools-ext..... 9

C

c! (c c-addr --) core..... 81
 c\$+! (char \$addr --) gforth-1.0..... 93
 c++-library ("name" --) gforth-1.0..... 258
 c++-library-name (c-addr u --)
 gforth-1.0..... 258
 c, (c --) core..... 76
 c-callback ("forth-name" "{type}" "----"
 "type" --) gforth-1.0..... 259
 c-callback-thread ("forth-name" "{type}"
 "----" "type" --) gforth-1.0..... 259
 c-function ("forth-name" "c-name" "{type}"
 "----" "type" --) gforth-0.7..... 256
 c-funptr ("forth-name" <{>"c-typecast"<}>
 "{type}" "----" "type" --) gforth-1.0.. 256
 c-library ("name" --) gforth-0.7..... 258
 c-library-name (c-addr u --)
 gforth-0.7..... 257
 c-value ("forth-name" "c-name" "----" "type"
 --) gforth-1.0..... 256
 c-variable ("forth-name" "c-name" --)
 gforth-1.0..... 256
 c>s (x -- n) gforth-1.0..... 84
 c? (addr class --) regexp-pattern..... 236
 c@ (c-addr -- c) core..... 81
 C" (compilation "ccc<quote>" -- ; run-time
 -- c-addr) core-ext..... 95
 C: (compilation "name" -- a-addr xt;
 run-time c --) gforth-0.2..... 202
 C^ (compilation "name" -- a-addr xt;
 run-time c --) gforth-0.2..... 202
 call-c (... w -- ...) gforth-0.2..... 260
 caller-w (-- optr) minos2..... 324
 capscompare (c-addr1 u1 c-addr2 u2 -- n)
 gforth-0.7..... 92
 capssearch (c-addr1 u1 c-addr2 u2 -- c-addr3
 u3 flag) gforth-1.0..... 92
 capsstring-prefix? (c-addr1 u1 c-addr2 u2 --
 f) gforth-1.0..... 92
 case (compilation -- case-sys ; run-time --
) core-ext..... 104
 catch (x1 .. xn xt -- y1 .. ym 0 / z1 .. zn
 error) exception..... 108
 catch-nobt (x1 .. xn xt -- y1 .. ym 0 / z1 ..
 zn error) gforth-experimental..... 108
 cell (-- u) gforth-0.2..... 85
 cell% (-- align size) gforth-0.4..... 141
 cell+ (a-addr1 -- a-addr2) core..... 85
 cell- (a-addr1 -- a-addr2) core..... 85
 cell/ (n1 -- n2) gforth-1.0..... 85
 cells (n1 -- n2) core..... 85
 cfield: (u1 "name" -- u2) facility-ext.. 135
 char ('<spaces>ccc' -- c)
 core,xchar-ext..... 90
 char% (-- align size) gforth-0.4..... 141
 char+ (c-addr1 -- c-addr2) core..... 85
 char- (c-addr1 -- c-addr2) gforth-0.7... 85

- charclass (--) regexp-cg 235
 - chars (n1 -- n2) core 85
 - cilk-bye (--) cilk 254
 - cilk-init (--) cilk 253
 - cilk-sync (--) cilk 254
 - class (parent-class -- align offset)
 - objects 218, 224
 - class->map (class -- map) objects 218
 - class-inst-size (class -- addr)
 - objects 218
 - class-override! (xt sel-xt class-map --)
 - objects 218
 - class-previous (class --) objects 218
 - class; (--) oof 224
 - class>order (class --) objects 219
 - clear-libs (--) gforth-0.7 258
 - clear-path (path-addr --) gforth-0.5... 178
 - clearstack (... --) gforth-0.2 243
 - clearstacks (... --) gforth-0.7 243
 - clicked (rx ry bmask n --) minos2 324
 - close-dir (wdirid -- wior) gforth-0.5.. 177
 - close-file (wfileid -- wior) file 174
 - close-pipe (wfileid -- wretval wior)
 - gforth-0.2 194
 - cmove (c-from c-to u --) string 87
 - cmove> (c-from c-to u --) string 87
 - code ("name" -- colon-sys) tools-ext ... 262
 - code-address! (c_addr xt --)
 - gforth-obsolete 277
 - color-cover (--) gforth-1.0 248
 - color: (rgba "name" --) minos2 327
 - common-list (list1 list2 -- list3)
 - gforth-internal 208
 - COMP' ("name" -- w xt) gforth-0.2 148
 - compare (c-addr1 u1 c-addr2 u2 -- n)
 - string 90
 - compile, (xt --) core-ext 153
 - compile-color (--) gforth-1.0 190
 - compile-only (--) gforth-0.2 143
 - compile-only? (nt -- flag) gforth-1.0.. 274
 - compiling (translator --)
 - gforth-experimental 163
 - compsem: (--) gforth-experimental 144
 - const-does> (run-time: w*uw r*ur uw ur
 - "name" --) gforth-obsolete 129
 - Constant (w "name" --) core 113
 - construct (... object --) objects 219
 - context (-- addr) gforth-0.2 167
 - contof (compilation case-sys1 of-sys --
 - case-sys2 ; run-time --) gforth-1.0... 104
 - convert (ud1 c-addr1 -- ud2 c-addr2)
 - core-ext-obsolete 194
 - CORE (-- f) environment 170
 - CORE-EXT (-- f) environment 170
 - cores (-- u) cilk 253
 - count (c-addr1 -- c-addr2 u) core 95
 - Country (<lang> "name" --)
 - gforth-experimental 197
 - cov% (--) gforth-experimental 248
 - cov+ (--) gforth-experimental 248
 - cover-filename (-- c-addr u)
 - gforth-experimental 248
 - coverage? (-- f) gforth-internal 247
 - cputime (-- duser dsystem) gforth-0.5.. 279
 - cr (--) core 187
 - Create ("name" --) core 112
 - create-file (c-addr u wfam -- wfileid wior)
 - file 174
 - create-from (nt "name" --) gforth-1.0.. 129
 - critical-section (xt semaphore --)
 - gforth-experimental 252
 - cs-vocabulary ("name" --) gforth-1.0... 166
 - cs-wordlist (-- wid) gforth-1.0 166
 - CS-DROP (dest/orig --) gforth-1.0 105
 - CS-PICK (dest0/orig0 dest1/orig1 ...
 - destu/origu u -- ... dest0/orig0)
 - tools-ext 105
 - CS-ROLL (destu/origu .. dest0/orig0 u -- ..
 - dest0/orig0 destu/origu) tools-ext 105
 - cstring>sstring (c-addr -- c-addr u)
 - gforth-0.2 92
 - csv-quote (-- c) gforth-experimental... 199
 - csv-separator (-- c)
 - gforth-experimental 198
 - ctz (x -- u) gforth-1.0 67
 - current (-- addr) gforth-0.2 167
 - current' ("selector" -- xt) objects 219
 - current-interface (-- addr) objects 219
 - cvalue: (u1 "name" -- u2)
 - gforth-experimental 137
- ## D
- d (-- r) minos2 325
 - d+ (ud1 ud2 -- ud) double 61
 - d- (d1 d2 -- d) double 61
 - d. (d --) double 183
 - d.r (d n --) double 183
 - d< (d1 d2 -- f) double 68
 - d<= (d1 d2 -- f) gforth-0.2 68
 - d<> (d1 d2 -- f) gforth-0.2 68
 - d= (d1 d2 -- f) double 68
 - d> (d1 d2 -- f) gforth-0.2 68
 - d>= (d1 d2 -- f) gforth-0.2 68
 - d>f (d -- r) floating 69
 - d>s (d -- n) double 61
 - d0< (d -- f) double 68
 - d0<= (d -- f) gforth-0.2 68
 - d0<> (d -- f) gforth-0.2 68
 - d0= (d -- f) double 68
 - d0> (d -- f) gforth-0.2 69
 - d0>= (d -- f) gforth-0.2 69
 - d2* (d1 -- d2) double 67
 - d2/ (d1 -- d2) double 67

D: (*compilation* "name" -- a-addr xt;
 run-time x1 x2 --) gforth-0.2 202
 D^ (*compilation* "name" -- a-addr xt;
 run-time x1 x2 --) gforth-0.2 202
 dabs (d -- ud) double 61
 dark-mode (--) gforth-1.0 190
 darshift (d1 u -- d2) gforth-1.0 67
 dbg ("name" --) gforth-0.2 247
 debug-fid (-- file-id) gforth-1.0 244
 dec. (n --) gforth-0.2 182
 dec.r (u n --) gforth-0.5 183
 decimal (--) core 157
 default-color (--) gforth-1.0 189
 default-input (--) gforth-1.0 190
 defer (--) oof 224
 Defer ("name" --) core-ext 131
 defer! (xt xt-deferred --) core-ext 132
 defer: (u1 "name" -- u2)
 gforth-experimental 139
 defer@ (... xt-deferred -- xt) core-ext 132
 defers (*compilation* "name" -- ; *run-time* ...
 -- ...) gforth-0.2 131
 definer! (definer xt --)
 gforth-obsolete 278
 defines (xt class "name" --) mini-oof 224
 definitions (--) search 165
 defocus (--) minos2 324
 delete (c-addr u u1 --) gforth-0.7 92
 delete-file (c-addr u -- wior) file 174
 delta-i (r:ulimit r:u -- r:ulimit r:u u2)
 gforth-1.0 101
 depth (-- +n) core 243
 df! (r df-addr --) floating-ext 82
 df@ (df-addr -- r) floating-ext 82
 dfloat (--) floating-ext 77
 dfloat (c-addr -- df-addr)
 floating-ext 86
 dffield: (u1 "name" -- u2) floating-ext 135
 dfloat% (-- align size) gforth-0.4 141
 dfloat+ (df-addr1 -- df-addr2)
 floating-ext 86
 dfloat/ (n1 -- n2) gforth-1.0 86
 dfloats (n1 -- n2) floating-ext 85
 dfvalue: (u1 "name" -- u2)
 gforth-experimental 137
 dglue (-- rtyp rsub radd) minos2 326
 dglue@ (-- rtyp rsub radd) minos2 326
 dict-new (... class -- object) objects 219
 dirname (c-addr1 u1 -- c-addr1 u2)
 gforth-0.7 176
 discode (addr u --) gforth-0.2 264
 dispose-widget (--) minos2 326
 dishift (ud1 u -- ud2) gforth-1.0 66
 dmax (d1 d2 -- d) double 61
 dmin (d1 d2 -- d) double 61
 dnegate (d1 -- d2) double 61
 DO (*compilation* -- do-sys ; *run-time* w1 w2 --
 loop-sys) core 101

doabicode: (-- addr) gforth-1.0 278
 docol: (-- addr) gforth-0.2 277
 docon: (-- addr) gforth-0.2 278
 dodefer: (-- addr) gforth-0.2 278
 dodoes: (-- addr) gforth-0.6 278
 does-code! (xt2 xt1 --) gforth-0.2 278
 DOES> (*compilation* colon-sys1 -- colon-sys2
) core 121
 dofield: (-- addr) gforth-0.2 278
 DONE (*compilation* do-sys -- ; *run-time* --)
 gforth-0.2 101
 double% (-- align size) gforth-0.4 141
 douser: (-- addr) gforth-0.2 278
 dovalue: (-- addr) gforth-0.7 278
 dovar: (-- addr) gforth-0.2 278
 dpl (-- a-addr) gforth-0.2 157
 draw (--) minos2 326
 draw-init (--) minos2 326
 drol (ud1 u -- ud2) gforth-1.0 67
 drop (w --) core 72
 dror (ud1 u -- ud2) gforth-1.0 68
 drshift (ud1 u -- ud2) gforth-1.0 66
 du/mod (d u -- n u1) gforth-1.0 63
 du< (ud1 ud2 -- f) double-ext 69
 du<= (ud1 ud2 -- f) gforth-0.2 69
 du> (ud1 ud2 -- f) gforth-0.2 69
 du>= (ud1 ud2 -- f) gforth-0.2 69
 dump (addr u --) tools 243
 dup (w -- w w) core 72

E

early (--) oof 224
 edit ("name" --) gforth-1.0 239
 edit-line (c-addr n1 n2 -- n3)
 gforth-0.6 193
 ekey (-- u) facility-ext 191
 ekey>char (u -- u false | c true)
 facility-ext 191
 ekey>fkey (u1 -- u2 f) facility-ext 191
 ekey>xchar (u -- u false | xc true)
 xchar-ext 191
 ekey? (-- flag) facility-ext 191
 ekeyed (ekey --) minos2 324
 ELSE (*compilation* orig1 -- orig2 ; *run-time*
 --) core 105
 emit (c --) core 189
 emit-file (c wfileid -- wior)
 gforth-0.2 175
 empty-buffer (buffer --) gforth-0.2 181
 empty-buffers (--) block-ext 181
 end-c-library (--) gforth-0.7 258
 end-class (align offset "name" --)
 objects 219, 224
 end-class-noname (align offset -- class)
 objects 219
 end-code (colon-sys --) gforth-0.2 262

end-interface ("name" --) objects..... 219
 end-interface-noname (-- interface)
 objects..... 219
 end-methods (--) objects..... 219
 end-struct (align size "name" --)
 gforth-0.2..... 141
 end-structure (struct-sys +n --)
 facility-ext..... 135
 endcase (compilation case-sys -- ; run-time
 x --) core-ext..... 104
 ENDIF (compilation orig -- ; run-time --)
 gforth-0.2..... 105
 endof (compilation case-sys1 of-sys --
 case-sys2 ; run-time --) core-ext..... 104
 endscope (compilation scope -- ; run-time --
) gforth-0.2..... 203
 endtry (compilation -- ; run-time R:sys1 --
) gforth-0.5..... 109
 entry-iferror (compilation orig1 -- orig2 ;
 run-time R:sys1 --) gforth-0.7..... 110
 entered (--) minos2..... 324
 environment (--) gforth-0.6..... 172
 environment-wordlist (-- wid)
 gforth-0.2..... 172
 environment? (c-addr u -- false / ... true)
 core..... 169
 erase (addr u --) core-ext..... 87
 error-color (--) gforth-1.0..... 189
 error-hl-inv (--) gforth-1.0..... 189
 error-hl-ul (--) gforth-1.0..... 189
 evaluate (... addr u -- ...) core,block. 156
 event-loop (--) gforth-experimental.... 253
 exception (addr u -- n) gforth-0.2..... 107
 exceptions (xt n1 -- n2) gforth-1.0..... 107
 execute (xt --) core..... 146
 execute-exit (compilation -- ; run-time xt
 nest-sys --) gforth-1.0..... 146
 execute-parsing (... addr u xt -- ...)
 gforth-0.6..... 164
 execute-parsing-file (i*x fileid xt -- j*x)
 gforth-0.6..... 165
 execute-task (xt -- task)
 gforth-experimental..... 250
 EXIT (compilation -- ; run-time nest-sys --
) core..... 107
 exitm (--) objects..... 219
 expand-where (--) gforth-1.0..... 240
 expect (c-addr +n --)
 core-ext-obsolescent..... 194
 extend-mem (addr1 u1 u -- addr addr2 u2)
 gforth-experimental..... 80
 extend-structure (n "name" -- struct-sys n)
 gforth-1.0..... 139
 extra-section (use "name" --)
 gforth-1.0..... 79

F

f! (r f-addr --) floating..... 82
 f* (r1 r2 -- r3) floating..... 69
 f** (r1 r2 -- r3) floating-ext..... 70
 f+ (r1 r2 -- r3) floating..... 69
 f, (f --) gforth-0.2..... 76
 f- (r1 r2 -- r3) floating..... 69
 f-rot (r1 r2 r3 -- r3 r1 r2) gforth-1.0... 73
 f. (r --) floating-ext..... 186
 f.rdp (rf +nr +nd +np --) gforth-0.6.... 186
 f.s (--) gforth-0.2..... 242
 f.s-precision (-- u) gforth-1.0..... 242
 f/ (r1 r2 -- r3) floating..... 69
 f< (r1 r2 -- f) floating..... 72
 f<= (r1 r2 -- f) gforth-0.2..... 72
 f<> (r1 r2 -- f) gforth-0.2..... 72
 f= (r1 r2 -- f) gforth-0.2..... 72
 f> (r1 r2 -- f) gforth-0.2..... 72
 f>= (r1 r2 -- f) gforth-0.2..... 72
 f>buf-rdp (rf c-addr +nr +nd +np --)
 gforth-0.6..... 187
 f>d (r -- d) floating..... 69
 f>l (r --) gforth-0.2..... 207
 f>r (r --) gforth-experimental..... 74
 f>s (r -- n) floating-ext..... 69
 f>str-rdp (rf +nr +nd +np -- c-addr nr)
 gforth-0.6..... 187
 f@ (f-addr -- r) floating..... 82
 f@localn (noffset -- r) gforth-1.0..... 207
 f~ (r1 r2 r3 -- flag) floating-ext..... 72
 f~abs (r1 r2 r3 -- flag) gforth-0.5..... 71
 f~rel (r1 r2 r3 -- flag) gforth-0.5..... 71
 f0< (r -- f) floating..... 72
 f0<= (r -- f) gforth-0.2..... 72
 f0<> (r -- f) gforth-0.2..... 72
 f0= (r -- f) floating..... 72
 f0> (r -- f) gforth-0.2..... 72
 f0>= (r -- f) gforth-0.2..... 72
 f2* (r1 -- r2) gforth-0.2..... 70
 f2/ (r1 -- r2) gforth-0.2..... 70
 F: (compilation "name" -- a-addr xt;
 run-time r --) gforth-0.2..... 202
 F~ (compilation "name" -- a-addr xt;
 run-time r --) gforth-0.2..... 202
 fabs (r1 -- r2) floating-ext..... 69
 facos (r1 -- r2) floating-ext..... 71
 facosh (r1 -- r2) floating-ext..... 71
 fade-color: (rgba1 rgba2 "name" --)
 minos2..... 327
 falign (--) floating..... 77
 faligned (c-addr -- f-addr) floating.... 85
 falog (r1 -- r2) floating-ext..... 70
 false (-- f) core-ext..... 60
 fasin (r1 -- r2) floating-ext..... 71
 fasinh (r1 -- r2) floating-ext..... 71
 fast-throw (... nerror -- ... nerror)
 gforth-experimental..... 107

- fatana (r1 -- r2) floating-ext..... 71
- fatana2 (r1 r2 -- r3) floating-ext..... 71
- fatana (r1 -- r2) floating-ext..... 71
- faxpy (ra f-x nstridey f-y nstridey ucount --) gforth-0.5..... 70
- fclearstack (r0 .. rn --) gforth-1.0.... 243
- fconstant (r "name" --) floating..... 114
- fcopysign (r1 r2 -- r3) gforth-1.0..... 69
- fcos (r1 -- r2) floating-ext..... 70
- fcosh (r1 -- r2) floating-ext..... 71
- fdepth (-- +n) floating..... 243
- fdrop (r --) floating..... 73
- fdup (r -- r r) floating..... 73
- fe. (r --) floating-ext..... 186
- fexp (r1 -- r2) floating-ext..... 70
- fexpm1 (r1 -- r2) floating-ext..... 70
- ffield: (u1 "name" -- u2) floating-ext.. 135
- ffourth (r1 r2 r3 r4 -- r1 r2 r3 r4 r1) gforth-1.0..... 73
- field (align1 offset1 align size "name" -- align2 offset2) gforth-0.2..... 141
- field: (u1 "name" -- u2) facility-ext... 135
- file-eof? (wfileid -- flag) gforth-0.6. 175
- file-position (wfileid -- ud wior) file. 175
- file-size (wfileid -- ud wior) file.... 175
- file-status (c-addr u -- wfam wior) file-ext..... 175
- file>fpath (addr1 u1 -- addr2 u2) gforth-1.0..... 178
- file>path (c-addr1 u1 path-addr -- c-addr2 u2) gforth-1.0..... 178
- filename-match (c-addr1 u1 c-addr2 u2 -- flag) gforth-0.5..... 177
- fill (c-addr u c --) core..... 87
- find (c-addr -- xt +1 | c-addr 0) core,search..... 166
- find-name (c-addr u -- nt | 0) gforth-0.2..... 147
- find-name-in (c-addr u wid -- nt | 0) gforth-1.0..... 147
- fkey. (u --) gforth-1.0..... 193
- FLiteral (compilation r -- ; run-time -- r) floating..... 150
- fln (r1 -- r2) floating-ext..... 70
- flnp1 (r1 -- r2) floating-ext..... 70
- float (-- u) gforth-0.3..... 85
- float% (-- align size) gforth-0.4..... 141
- float+ (f-addr1 -- f-addr2) floating.... 85
- float/ (n1 -- n2) gforth-1.0..... 85
- floating-stack (-- n) environment..... 170
- floats (n1 -- n2) floating..... 85
- flog (r1 -- r2) floating-ext..... 70
- floor (r1 -- r2) floating..... 69
- FLOORED (-- f) environment..... 170
- flush (--) block..... 182
- flush-file (wfileid -- wior) file-ext.. 175
- flush-icache (c-addr u --) gforth-0.2.. 262
- fm/mod (d1 n1 -- n2 n3) core..... 63
- fmax (r1 r2 -- r3) floating..... 69
- fmin (r1 r2 -- r3) floating..... 69
- fnegate (r1 -- r2) floating..... 69
- fnip (r1 r2 -- r2) gforth-0.2..... 73
- focus (--) minos2..... 324
- FOR (compilation -- do-sys ; run-time u -- loop-sys) gforth-0.2..... 101
- FORK (compilation -- orig ; run-time f --) gforth-0.7..... 235
- form (-- nlines ncols) gforth-0.2..... 189
- Forth (--) search-ext..... 166
- forth-recognize (c-addr u -- ... translate-xt) recognizer..... 162
- forth-recognizer (-- xt) gforth-obsolete..... 162
- forth-wordlist (-- wid) search..... 165
- forward ("name" --) gforth-1.0..... 106
- fourth (w1 w2 w3 w4 -- w1 w2 w3 w4 w1) gforth-1.0..... 72
- fover (r1 r2 -- r1 r2 r1) floating..... 73
- fp! (f-addr -- f:...) gforth-0.2..... 75
- fp. (r --) floating-ext..... 186
- fp@ (f:... -- f-addr) gforth-0.2..... 75
- fp0 (-- a-addr) gforth-0.4..... 75
- fpath (-- path-addr) gforth-0.4..... 178
- fpick (f:... u -- f:... r) gforth-0.4.... 73
- fr> (-- r) gforth-experimental..... 74
- fr@ (-- r) gforth-experimental..... 74
- free (a-addr -- wior) memory..... 80
- free-closure (xt --) gforth-1.0..... 230
- free-mem-var (addr --) gforth-experimental..... 80
- frot (r1 r2 r3 -- r2 r3 r1) floating..... 73
- fround (r1 -- r2) floating..... 70
- fs. (r --) floating-ext..... 186
- fsin (r1 -- r2) floating-ext..... 70
- fsincos (r1 -- r2 r3) floating-ext..... 70
- fsinh (r1 -- r2) floating-ext..... 71
- fsqrt (r1 -- r2) floating-ext..... 70
- fswap (r1 r2 -- r2 r1) floating..... 73
- ftan (r1 -- r2) floating-ext..... 71
- ftanh (r1 -- r2) floating-ext..... 71
- fthird (r1 r2 r3 -- r1 r2 r3 r1) gforth-1.0..... 73
- ftrunc (r1 -- r2) floating-ext..... 70
- ftuck (r1 r2 -- r2 r1 r2) gforth-0.2..... 73
- fvalue (r "name" --) floating-ext..... 114
- fvalue: (u1 "name" -- u2) gforth-experimental..... 137
- fvariable ("name" --) floating..... 113

G

g (--) gforth-0.7..... 239
gap (-- r) minos2..... 325
get (-- *something*) minos2..... 325
get-block-fid (-- *wfileid*) gforth-0.2.. 181
get-current (-- *wid*) search..... 165
get-dir (*c-addr1 u1* -- *c-addr2 u2*)
 gforth-0.7..... 177
get-order (-- *widn* .. *wid1 n*) search.... 165
get-recognizers (-- *xt1* .. *xtn n*)
 gforth-obsolete..... 162
get-stack (*stack* -- *x1* .. *xn n*)
 gforth-experimental..... 142
get-state (-- *xt*) gforth-experimental.. 163
getenv (*c-addr1 u1* -- *c-addr2 u2*)
 gforth-0.2..... 279
gforth (-- *c-addr u*)
 gforth-environment..... 171
gg (--) gforth-1.0..... 240

H

h (-- r) minos2..... 325
h. (*u* --) gforth-1.0..... 182
halt (*task* --) gforth-experimental.... 250
heap-new (... *class* -- *object*) objects.. 219
help ("rest-of-line" --) gforth-1.0..... 9
here (-- *addr*) core..... 76
hex (--) core-ext..... 157
hex. (*u* --) gforth-0.2..... 182
hglue (-- *rtyp rsub radd*) minos2..... 326
hglue@ (-- *rtyp rsub radd*) minos2..... 326
hide (--) minos2..... 325
hold (*char* --) core..... 184
holds (*addr u* --) core-ext..... 184
how: (--) oof..... 224

I

i (*R:n* -- *R:n n*) core..... 101
i' (*R:w R:w2* -- *R:w R:w2 w*) gforth-0.2.. 101
id. (*nt* --) gforth-0.6..... 147
IF (*compilation* -- *orig* ; *run-time f* --)
 core..... 104
iferror (*compilation orig1* -- *orig2* ;
 run-time --) gforth-0.7..... 109
immediate (--) core..... 143
immediate? (*nt* -- *flag*) gforth-1.0..... 276
implementation (*interface* --) objects.. 219
in ("voc" "defining-word" --)
 gforth-experimental..... 165
in-colon-def? (-- *flag*)
 gforth-experimental..... 153
in-wordlist (*wordlist* "defining-word" --)
 gforth-experimental..... 165

include (... "file" -- ...) file-ext.... 173
include-file (*i*x wfileid* -- *j*x*) file.. 173
include-locale ("name" --)
 gforth-experimental..... 197
included (*i*x c-addr u* -- *j*x*) file.... 173
included-locale (*addr u* --)
 gforth-experimental..... 197
included? (*c-addr u* -- *f*) gforth-0.2.... 173
inf (-- r) gforth-1.0..... 71
infile-execute (... *xt file-id* -- ...)
 gforth-0.7..... 176
infile-id (-- *file-id*) gforth-0.4..... 176
infinity (-- r) gforth-1.0..... 71
info-color (--) gforth-1.0..... 190
init-asm (--) gforth-0.2..... 261
init-buffer (*addr* --)
 gforth-experimental..... 81
init-object (... *class object* --)
 objects..... 219
initiate (*xt task* --)
 gforth-experimental..... 249
inline: ("name" -- *inline:-sys*)
 gforth-experimental..... 115
input-color (--) gforth-1.0..... 190
insert (*c-addr1 u1 c-addr2 u2* --)
 gforth-0.7..... 91
inst-value (*align1 offset1* "name" -- *align2*
 offset2) objects..... 219
inst-var (*align1 offset1 align size* "name"
 -- *align2 offset2*) objects..... 220
INT-[I] (-- *n*) gforth-1.0..... 159
interface (--) objects..... 220
interpret (... -- ...) gforth-0.2..... 156
interpret/compile: (*interp-xt comp-xt*
 "name" --) gforth-0.2..... 143
interpreting (*translator* --)
 gforth-experimental..... 163
intsem: (--) gforth-experimental..... 144
invert (*w1* -- *w2*) core..... 66
IS (*xt* "name" --) core-ext..... 131

J

j (*R:n R:w1 R:w2* -- *n R:n R:w1 R:w2*)
 core..... 101
JOIN (*orig* --) gforth-0.7..... 235

K

k (R:n R:w1 R:w2 R:w3 R:w4 -- n R:n R:w1 R:w2
 R:w3 R:w4) gforth-0.3..... 101
 k-alt-mask (-- u) facility-ext..... 192
 k-backspace (-- u) gforth-1.0..... 192
 k-ctrl-mask (-- u) facility-ext..... 192
 k-delete (-- u) facility-ext..... 192
 k-down (-- u) facility-ext..... 191
 k-end (-- u) facility-ext..... 191
 k-enter (-- u) gforth-1.0..... 192
 k-eof (-- u) gforth-1.0..... 192
 k-f1 (-- u) facility-ext..... 192
 k-f10 (-- u) facility-ext..... 192
 k-f11 (-- u) facility-ext..... 192
 k-f12 (-- u) facility-ext..... 192
 k-f2 (-- u) facility-ext..... 192
 k-f3 (-- u) facility-ext..... 192
 k-f4 (-- u) facility-ext..... 192
 k-f5 (-- u) facility-ext..... 192
 k-f6 (-- u) facility-ext..... 192
 k-f7 (-- u) facility-ext..... 192
 k-f8 (-- u) facility-ext..... 192
 k-f9 (-- u) facility-ext..... 192
 k-home (-- u) facility-ext..... 191
 k-insert (-- u) facility-ext..... 192
 k-left (-- u) facility-ext..... 191
 k-mute (-- u) gforth-1.0..... 192
 k-next (-- u) facility-ext..... 192
 k-pause (-- u) gforth-1.0..... 192
 k-prior (-- u) facility-ext..... 191
 k-right (-- u) facility-ext..... 191
 k-sel (-- u) gforth-1.0..... 192
 k-shift-mask (-- u) facility-ext..... 192
 k-tab (-- u) gforth-1.0..... 192
 k-up (-- u) facility-ext..... 191
 k-voldown (-- u) gforth-1.0..... 192
 k-volup (-- u) gforth-1.0..... 192
 k-winch (-- u) gforth-1.0..... 192
 kerning (-- r) minos2..... 325
 key (-- char) core..... 190
 key-file (fd -- key) gforth-0.4..... 175
 key-ior (-- char|ior) gforth-1.0..... 190
 key? (-- flag) facility..... 190
 key?-file (wfileid -- f) gforth-0.4..... 175
 kill (task --) gforth-experimental..... 250
 kill-task (--) gforth-experimental..... 250

L

l (--) gforth-1.0..... 239
 l! (w c-addr --) gforth-0.7..... 83
 l, (l --) gforth-1.0..... 77
 l>s (x -- n) gforth-1.0..... 84
 l@ (c-addr -- u) gforth-0.7..... 83
 L" ("lsid<">" -- lsid)
 gforth-experimental..... 197

lalign (--) gforth-1.0..... 86
 laligned (addr -- addr') gforth-1.0..... 86
 Language ("name" --)
 gforth-experimental..... 197
 lastfit (--) minos2..... 326
 latest (-- nt) gforth-0.6..... 147
 latestnt (-- nt) gforth-1.0..... 147
 latestxt (-- xt) gforth-0.6..... 117
 lbe (u1 -- u2) gforth-1.0..... 83
 LEAVE (compilation -- ; run-time loop-sys --
) core..... 101
 left (--) minos2..... 324
 lfield: (u1 "name" -- u2) gforth-1.0.... 135
 lib-error (-- c-addr u) gforth-0.7..... 259
 lib-sym (c-addr1 u1 u2 -- u3)
 gforth-0.4..... 259
 license (--) gforth-0.2..... 10
 light-mode (--) gforth-1.0..... 190
 line-end-hook (--) gforth-0.7..... 163
 list (u --) block-ext..... 181
 list-size (list -- u) gforth-internal.. 208
 Literal (compilation n -- ; run-time -- n)
 core..... 149
 ll (--) gforth-1.0..... 240
 lle (u1 -- u2) gforth-1.0..... 83
 load (i*x u -- j*x) block..... 182
 load-cov (--) gforth-experimental..... 248
 locale! (addr u lsid --)
 gforth-experimental..... 197
 locale-csv ("name" --)
 gforth-experimental..... 197
 locale-csv-out ("name" --)
 gforth-experimental..... 198
 locale-file (fid --)
 gforth-experimental..... 197
 locale@ (lsid -- addr u)
 gforth-experimental..... 197
 locate ("name" --) gforth-1.0..... 238
 lock (semaphore --)
 gforth-experimental..... 252
 log2 (u -- n) gforth-1.0..... 67
 LOOP (compilation do-sys -- ; run-time
 loop-sys1 -- | loop-sys2) core..... 101
 lp! (c-addr --) gforth-internal..... 75, 207
 lp+! (noffset --) gforth-1.0..... 207
 lp+n (noffset -- c-addr)
 gforth-internal..... 207
 lp@ (-- c-addr) gforth-0.2..... 75
 lp0 (-- a-addr) gforth-0.4..... 75
 lrol (u1 u -- u2) gforth-1.0..... 67
 lror (u1 u -- u2) gforth-1.0..... 67
 lshift (u1 u -- u2) core..... 66
 LU" ("lsid<">" -- lsid)
 gforth-experimental..... 197
 lvalue: (u1 "name" -- u2)
 gforth-experimental..... 137

M

m* (*n1 n2 -- d*) core 61
 m*/ (*d1 n2 u3 -- dquot*) double 64
 m+ (*d1 n -- d2*) double 61
 m: (*-- xt colon-sys; run-time: object --*)
 objects 220
 macros-wordlist (*-- wid*)
 gforth-experimental 198
 magenta-input (*--*) gforth-1.0 190
 make-latest (*nt --*) gforth-1.0 129
 map-vocs (*... xt -- ...*) gforth-1.0 167
 marker (*"<spaces> name" --*) core-ext ... 243
 max (*n1 n2 -- n*) core 61
 max-float (*-- r*) environment 170
 MAX-CHAR (*-- u*) environment 169
 MAX-D (*-- d*) environment 170
 MAX-N (*-- n*) environment 170
 MAX-U (*-- u*) environment 170
 MAX-UD (*-- ud*) environment 170
 MAX-XCHAR (*-- xchar*) environment 170
 maxalign (*--*) gforth-0.2 77
 maxaligned (*addr1 -- addr2*) gforth-0.2 .. 86
 maxdepth-.s (*-- addr*) gforth-0.2 243
 mem+do (*compilation -- w xt do-sys; run-time*
 addr ubytes +nstride --)
 gforth-experimental 101
 mem, (*addr u --*) gforth-0.6 77
 mem-do (*compilation -- w xt do-sys; run-time*
 addr ubytes +nstride --)
 gforth-experimental 101
 method (*xt "name" --*) objects 220, 224
 methods (*class --*) objects 220
 min (*n1 n2 -- n*) core 61
 mkdir-parents (*c-addr u mode -- ior*)
 gforth-0.7 177
 mod (*n1 n2 -- n*) core 62
 modf (*n1 n2 -- n*) gforth-1.0 62
 modf-stage2m (*n1 a-rci -- umodulus*)
 gforth-1.0 65
 mods (*n1 n2 -- n*) gforth-1.0 62
 move (*c-from c-to ucount --*) core 87
 ms (*n --*) facility-ext 279
 mux (*u1 u2 u3 -- u*) gforth-1.0 66
 mwords (*["pattern"] --*) gforth-1.0 167

N

n (*--*) gforth-1.0 239
 n/a (*--*) gforth-experimental 126
 n>r (*x1 .. xn n -- R:xn..R:x1 R:n*)
 tools-ext 74
 name (*-- c-addr u*) gforth-obsolete 164
 name\$ (*-- addr u*) minos2 325
 name>compile (*nt -- w xt*) tools-ext 147
 name>interpret (*nt -- xt*) tools-ext 147
 name>link (*nt1 -- nt2 / 0*) gforth-1.0 ... 147

name>string (*nt -- addr u*) tools-ext 147
 NaN (*-- r*) gforth-1.0 71
 native@ (*lsid -- addr u*)
 gforth-experimental 197
 needs (*... "name" -- ...*) gforth-0.2 174
 negate (*n1 -- n2*) core 61
 new (*class -- o*) mini-oof 225
 new-color: (*rgba "name" --*) minos2 327
 newline (*-- c-addr u*) gforth-0.5 90
 newtask (*stacksize -- task*)
 gforth-experimental 249
 newtask4 (*u-data u-return u-fp u-locals --*
 task) gforth-experimental 249
 next-arg (*-- addr u*) gforth-0.7 199
 next-case (*compilation case-sys --* ;
 run-time --) gforth-1.0 104
 next-section (*--*) gforth-1.0 79
 NEXT (*compilation do-sys -- ; run-time*
 loop-sys1 -- | loop-sys2) gforth-0.2 .. 101
 nextname (*c-addr u --*) gforth-0.2 118
 nip (*w1 w2 -- w2*) core-ext 72
 nocov[(*--*) gforth-1.0 247
 noname (*--*) gforth-0.2 117
 noname-from (*xt --*) gforth-1.0 129
 noop (*--*) gforth-0.2 146
 nosplit? (*addr1 u1 addr2 u2 -- addr1 u1 addr2*
 u2 flag) gforth-experimental 91
 nothrow (*--*) gforth-0.7 108
 nr> (*R:xn..R:x1 R:n -- x1 .. xn n*)
 tools-ext 74
 ns (*d --*) gforth-1.0 279
 nt (*--*) gforth-1.0 240
 ntime (*-- dtime*) gforth-1.0 279
 nw (*--*) gforth-1.0 239

O

o> (*r:c-addr --*) new 227
 object (*-- class*) objects 220, 224
 object-' (*"name" -- xt*) oof 223
 object-: (*"name" --*) oof 223
 object-:: (*"name" --*) oof 223
 object-[] (*n "name" --*) oof 223
 object-asptr (*o "name" --*) oof 223
 object-bind (*o "name" --*) oof 223
 object-bound (*class addr "name" --*) oof 223
 object-class (*"name" --*) oof 222
 object-class? (*o -- flag*) oof 222
 object-definitions (*--*) oof 222
 object-dispose (*--*) oof 223
 object-endwith (*--*) oof 223
 object-init (*... --*) oof 222
 object-is (*xt "name" --*) oof 223
 object-link (*"name" -- class addr*) oof .. 223
 object-new (*-- o*) oof 223
 object-new[] (*n -- o*) oof 223
 object-postpone (*"name" --*) oof 223

object-ptr ("name" --) oof..... 223
 object-self (-- o) oof..... 223
 object-super ("name" --) oof..... 223
 object-with (o --) oof..... 223
 obsolete? (nt -- flag) gforth-1.0..... 147
 of (compilation -- of-sys ; run-time x1 x2 --
 |x1) core-ext..... 104
 off (a-addr --) gforth-0.2..... 60
 on (a-addr --) gforth-0.2..... 60
 once (--) gforth-1.0..... 244
 Only (--) search-ext..... 166
 open-blocks (c-addr u --) gforth-0.2... 181
 open-dir (c-addr u -- wdirid wior)
 gforth-0.5..... 176
 open-file (c-addr u wfam -- wfileid wior)
 file..... 174
 open-lib (c-addr1 u1 -- u2) gforth-0.4.. 259
 open-path-file (addr1 u1 path-addr --
 wfileid addr2 u2 0 | ior) gforth-0.2... 178
 open-pipe (c-addr u wfam -- wfileid wior)
 gforth-0.2..... 194
 opt: (compilation -- colon-sys2 ; run-time
 -- nest-sys) gforth-1.0..... 127
 or (w1 w2 -- w) core..... 66
 order (--) search-ext..... 166
 os-class (-- c-addr u)
 gforth-environment..... 171
 os-type (-- c-addr u)
 gforth-environment..... 171
 out (-- addr) gforth-1.0..... 188
 outfile-execute (... xt file-id -- ...)
 gforth-0.7..... 176
 outfile-id (-- file-id) gforth-0.2..... 176
 over (w1 w2 -- w1 w2 w1) core..... 72
 overrides (xt "selector" --) objects... 220

P

pad (-- c-addr) core-ext..... 87
 page (--) facility..... 189
 par-split (rw --) minos2..... 327
 parent-w (-- optr) minos2..... 325
 parse (xchar "ccc<xchar>" -- c-addr u)
 core-ext,xchar-ext..... 164
 parse-name ("name" -- c-addr u)
 core-ext..... 164
 parse-word (-- c-addr u)
 gforth-obsolete..... 164
 pass (x1 .. xn n task --)
 gforth-experimental..... 249
 path+ (path-addr "dir" --) gforth-0.4.. 178
 path= (path-addr "dir1|dir2|dir3" --)
 gforth-0.4..... 178
 pause (--) gforth-experimental..... 250
 perform (a-addr --) gforth-0.2..... 146
 pi (-- r) gforth-0.2..... 71
 pick (S:... u -- S:... w) core-ext..... 72

place (c-addr1 u c-addr2 --)
 gforth-experimental..... 95
 postpone ("name" --) core..... 150
 postpone, (w xt --) gforth-0.2..... 149
 postponing (translator --)
 gforth-experimental..... 163
 pow2? (u -- f) gforth-1.0..... 67
 precision (-- u) floating-ext..... 186
 prepend-where (--) gforth-1.0..... 240
 preserve (compilation "name" -- ; run-time
 --) gforth-1.0..... 132
 previous (--) search-ext..... 166
 previous-section (--) gforth-1.0..... 79
 print (object --) objects..... 220
 printdebugdata (--) gforth-0.2..... 244
 process-option (addr u -- ... xt | 0)
 gforth-0.7..... 311
 protected (--) objects..... 220
 ptr (--) oof..... 223
 public (--) objects..... 220

Q

query (--) core-ext-obsolescent..... 156
 quit (?? -- ??) core..... 280

R

r'@ (r:w r:w2 -- r:w r:w2 w) gforth-1.0.. 74
 r/o (-- fam) file..... 174
 r/w (-- fam) file..... 174
 r> (R:w -- w) core..... 74
 r@ (R:w -- R:w w) core..... 74
 raise (-- r) minos2..... 325
 rdop (R:w --) gforth-0.2..... 74
 re-color (rgba "name" --) minos2..... 327
 re-emoji-color (rgbatext rgbaemoji "name" --
) minos2..... 328
 re-fade-color (rgba1 rgba2 "name" --)
 minos2..... 328
 re-text-color (rgba "name" --) minos2.. 327
 re-text-emoji-fade-color (rgbatext1 ~2
 rgbaemoji1 ~2 "name" --) minos2..... 328
 read-csv (addr u xt --)
 gforth-experimental..... 198
 read-dir (c-addr u1 wdirid -- u2 flag wior)
 gforth-0.5..... 176
 read-file (c-addr u1 wfileid -- u2 wior)
 file..... 174
 read-line (c-addr u1 wfileid -- u2 flag wior
) file..... 174
 rec-body (addr u -- xt translate-num | 0)
 gforth-experimental..... 161
 rec-complex (addr u -- z translate-complex |
 0) gforth-1.0..... 161

rec-dtick (addr u -- nt translate-num | 0)
 gforth-experimental..... 161
 rec-env (addr u -- addr u translate-env | 0)
 gforth-1.0..... 161
 rec-float (addr u -- r translate-float | 0)
 gforth-experimental..... 161
 rec-meta (addr u -- xt translate-to | 0)
 gforth-1.0..... 162
 rec-moof2 (addr u -- xt translate-moof2 | 0)
) mini-oof2 227
 rec-nt (addr u -- nt translate-nt | 0)
 gforth-experimental..... 161
 rec-num (addr u -- n/d table | 0)
 gforth-experimental..... 161
 rec-scope (addr u -- nt rectype-nt | 0)
 gforth-experimental..... 161
 rec-string (addr u -- addr u'
 scan-translate-string | 0)
 gforth-experimental..... 161
 rec-tick (addr u -- xt translate-num | 0)
 gforth-experimental..... 161
 rec-to (addr u -- xt n translate-to | 0)
 gforth-experimental..... 161
 recognize (addr u rec-addr -- ... rectype)
 gforth-experimental..... 162
 recognizer-sequence: (xt1 .. xtn n "name" --
) gforth-experimental..... 162
 recurse (... -- ...) core..... 106
 recursive (compilation -- ; run-time --)
 gforth-0.2..... 106
 refill (-- flag)
 core-ext,block-ext,file-ext..... 164
 rename-file (c-addr1 u1 c-addr2 u2 -- wior)
 file-ext 174
 REPEAT (compilation orig dest -- ; run-time
 --) core..... 105
 replace-word (xt1 xt2 --) gforth-1.0... 245
 replacer: ("name" --)
 gforth-experimental..... 198
 replaces (addr1 len1 addr2 len2 --)
 string-ext..... 198
 reposition-file (ud wfileid -- wior)
 file..... 175
 represent (r c-addr u -- n f1 f2)
 floating 187
 require (... "file" -- ...) file-ext.... 173
 required (i*x addr u -- i*x) file-ext... 173
 resize (a_addr1 u -- a_addr2 wior)
 memory..... 80
 resize-file (ud wfileid -- wior) file... 175
 resized (--) minos2..... 327
 restart (task --) gforth-experimental.. 250
 restore (compilation orig1 -- ; run-time --
) gforth-0.7..... 110
 restore-input (x1 .. xn n -- flag)
 core-ext 156
 restrict (--) gforth-0.2 143
 return-stack-cells (-- n) environment.. 170

reveal (--) gforth-0.2..... 129
 reveal! (xt wid --) core-ext..... 129
 rol (u1 u -- u2) gforth-1.0..... 67
 roll (x0 x1 .. xn n -- x1 .. xn x0)
 core-ext..... 73
 Root (--) gforth-0.2..... 167
 ror (u1 u -- u2) gforth-1.0..... 67
 rot (w1 w2 w3 -- w2 w3 w1) core..... 72
 rp! (a-addr --) gforth-0.2..... 75
 rp@ (-- a-addr) gforth-0.2..... 75
 rp0 (-- a-addr) gforth-0.4..... 75
 rpick (R:wu ... R:w0 u -- R:wu ... R:w0 wu)
 gforth-1.0..... 74
 rshift (u1 u -- u2) core..... 66

S

s+ (c-addr1 u1 c-addr2 u2 -- c-addr u)
 gforth-0.7 92
 s// (addr u -- ptr) regexp-replace..... 238
 s>> (addr -- addr) regexp-replace..... 238
 s>d (n -- d) core..... 61
 s>f (n -- r) floating-ext 69
 s>number? (addr u -- d f) gforth-0.5.... 193
 s>unnumber? (c-addr u -- ud flag)
 gforth-0.5..... 193
 s\" (Interpretation 'ccc' -- c-addr u)
 core-ext,file-ext 89
 S\" (Interpretation 'ccc' -- c-addr u)
 core,file 89
 safe/string (c-addr1 u1 n -- c-addr2 u2)
 gforth-1.0..... 91
 save-buffer (buffer --) gforth-0.2..... 182
 save-buffers (--) block..... 182
 save-cov (--) gforth-experimental..... 248
 save-input (-- x1 .. xn n) core-ext 156
 save-mem (addr1 u -- addr2 u) gforth-0.2. 80
 save-mem-dict (addr1 u -- addr2 u)
 gforth-0.7 77
 savesystem ("image" --) gforth-0.2..... 307
 scan (c-addr1 u1 c -- c-addr2 u2)
 gforth-0.2..... 91
 scan-back (c-addr u1 c -- c-addr u2)
 gforth-0.7 91
 scope (compilation -- scope ; run-time --)
 gforth-0.2..... 203
 scr (-- a-addr) block-ext..... 181
 scrolled (axis dir --) minos2..... 324
 scvalue: (u1 "name" -- u2)
 gforth-experimental..... 137
 seal (--) gforth-0.2..... 167
 search (c-addr1 u1 c-addr2 u2 -- c-addr3 u3
 flag) string..... 91
 search-wordlist (c-addr count wid -- 0 | xt
 +-1) search..... 167
 see ("<spaces>name" --) tools 240
 see-code ("name" --) gforth-0.7..... 241

- see-code-range (addr1 addr2 --)
 gforth-0.7 241
 select (u1 u2 f -- u) gforth-1.0 60
 selector ("name" --) objects 220
 semaphore ("name" --)
 gforth-experimental 251
 send-event (xt task --)
 gforth-experimental 253
 set (something --) minos2 325
 set->comp (xt --) gforth-1.0 276
 set->int (xt --) gforth-1.0 276
 set-compsem (xt --)
 gforth-experimental 144
 set-current (wid --) search 165
 set-dir (c-addr u -- wior) gforth-0.7... 177
 set-does> (xt --) gforth-1.0 122
 set-execute (ca --) gforth-1.0 275
 set-forth-recognize (xt --)
 gforth-obsolete 162
 set-name>link (xt --) gforth-1.0 277
 set-name>string (xt --) gforth-1.0 277
 set-optimizer (xt --) gforth-1.0 127
 set-order (widn .. wid1 n --) search 165
 set-precision (u --) floating-ext 186
 set-recognizers (xt1 .. xtn n --)
 gforth-obsolete 162
 set-stack (x1 .. xn n stack --)
 gforth-experimental 142
 set-state (xt --) gforth-experimental.. 163
 set-to (to-xt --) gforth-1.0 127
 sf! (r sf-addr --) floating-ext 82
 sf@ (sf-addr -- r) floating-ext 82
 sfalign (--) floating-ext 77
 sfaligned (c-addr -- sf-addr)
 floating-ext 85
 sffield: (u1 "name" -- u2) floating-ext. 135
 sfloat% (-- align size) gforth-0.4 141
 sfloat+ (sf-addr1 -- sf-addr2)
 floating-ext 85
 sfloat/ (n1 -- n2) gforth-1.0 85
 sfloats (n1 -- n2) floating-ext 85
 sfvalue: (u1 "name" -- u2)
 gforth-experimental 137
 sh ("... " --) gforth-0.2 279
 sh-get (c-addr u -- c-addr2 u2)
 gforth-1.0 279
 shift-args (--) gforth-0.7 199
 short-where (--) gforth-1.0 240
 show (--) minos2 325
 show-you (--) minos2 325
 sign (n --) core 184
 simple-fkey-string (u1 -- c-addr u)
 gforth-1.0 193
 simple-see ("name" --) gforth-0.6 241
 simple-see-range (addr1 addr2 --)
 gforth-0.6 241
 skip (c-addr1 u1 c -- c-addr2 u2)
 gforth-0.2 91
 sleep (task --) gforth-experimental... 250
 SLiteral (Compilation c-addr1 u ; run-time
 -- c-addr2 u) string 150
 slurp-fid (fid -- addr u) gforth-0.6... 175
 slurp-file (c-addr1 u1 -- c-addr2 u2)
 gforth-0.6 175
 slvalue: (u1 "name" -- u2)
 gforth-experimental 137
 sm/rem (d1 n1 -- n2 n3) core 63
 source (-- addr u) core 156
 source-id (-- 0 | -1 | fileid)
 core-ext,file 156
 sourcefilename (-- c-addr u)
 gforth-0.2 174
 sourceline# (-- u) gforth-0.2 174
 sp! (a-addr -- S:...) gforth-0.2 75
 sp@ (S:... -- a-addr) gforth-0.2 75
 sp0 (-- a-addr) gforth-0.4 75
 space (--) core 188
 spaces (u --) core 188
 span (-- c-addr) core-ext-obsolescent.. 194
 spawn (xt --) cilk 254
 spawn1 (x xt --) cilk 254
 spawn2 (x1 x2 xt --) cilk 254
 split (firstflag rstart1 rx -- o rstart2)
 minos2 326
 stack (n -- stack) gforth-experimental. 142
 stack-cells (-- n) environment 170
 stack: (n "name" --)
 gforth-experimental 142
 stack> (stack -- x)
 gforth-experimental 142
 stacksize (-- u) gforth-experimental... 249
 stacksize4 (-- u-data u-return u-fp u-locals
) gforth-experimental 249
 staged/-divisor (addr1 -- addr2)
 gforth-1.0 66
 staged/-size (-- u) gforth-1.0 65
 static (--) oof 224
 status-color (--) gforth-1.0 190
 stderr (-- wfileid) gforth-0.2 175
 stdin (-- wfileid) gforth-0.4 175
 stdout (-- wfileid) gforth-0.2 175
 stop (--) gforth-experimental 250
 stop-dns (dtimeout --)
 gforth-experimental 250
 stop-ns (timeout --)
 gforth-experimental 250
 str< (c-addr1 u1 c-addr2 u2 -- f)
 gforth-0.6 91
 str= (c-addr1 u1 c-addr2 u2 -- f)
 gforth-0.6 91
 str=? (addr1 addr u -- addr2)
 regex-pattern 237
 string, (c-addr u --) gforth-0.2 95
 string-parse (c-addr1 u1 "ccc<string>" --
 c-addr2 u2) gforth-1.0 164

string-prefix? (c-addr1 u1 c-addr2 u2 -- f)
 gforth-0.6 91
string-suffix? (c-addr1 u1 c-addr2 u2 -- f)
 gforth-1.0 91
struct (-- align size) gforth-0.2 141
sub-list? (list1 list2 -- f)
 gforth-internal 208
substitute (addr1 len1 addr2 len2 -- addr2
 len3 n/ior) string-ext 198
success-color (--) gforth-1.0 190
swap (w1 w2 -- w2 w1) core 72
swvalue: (u1 "name" -- u2)
 gforth-experimental 137
Synonym ("name" "oldname" --)
 tools-ext 133
system (c-addr u --) gforth-0.2 279

T

table (-- wid) gforth-0.2 166
task (ustacksize "name" --)
 gforth-experimental 249
text-color: (rgba "name" --) minos2 327
text-emoji-color: (rgbatext rgbaemoji
 "name" --) minos2 327
text-emoji-fade-color: (rgbatext1 ~2
 rgbaemoji1 ~2 "name" --) minos2 327
THEN (compilation orig -- ; run-time --)
 core 105
third (w1 w2 w3 -- w1 w2 w3 w1)
 gforth-1.0 72
this (-- object) objects 220
thread-deadline (d --)
 gforth-experimental 250
threading-method (-- n) gforth-0.2 277
throw (y1 .. ym nerror -- y1 .. ym / z1 .. zn
 nerror) exception 107
thru (i*x n1 n2 -- j*x) block-ext 182
tib (-- addr) core-ext-obsolescent 156
time&date (-- nsec nmin nhour nday nmonth
 nyear) facility-ext 279
to-class: (xt table "name" --)
 gforth-experimental 126
to-table: ("name" "to-word" "+to-word"
 "addr-word" "action-of-word" "is-word" --
) gforth-experimental 126
to-this (object --) objects 221
TO (value "name" --) core-ext 114
touchdown (\$rxy*n bmask --) minos2 324
touchup (\$rxy*n bmask --) minos2 324
toupper (c1 -- c2) gforth-0.2 88
translate-dnum (dx -- | dx)
 gforth-experimental 162
translate-float (r -- | r)
 gforth-experimental 162
translate-method: ("name" --)
 gforth-experimental 163

translate-nt (i*x nt -- j*x)
 gforth-experimental 162
translate-num (x -- | x)
 gforth-experimental 162
translate: (int-xt comp-xt post-xt "name" --
) gforth-experimental 162
traverse-wordlist (... xt wid -- ...)
 tools-ext 147
true (-- f) core-ext 60
try (compilation -- orig ; run-time -- R:sys1
) gforth-0.5 109
try-recognize (addr u xt -- results | false
) gforth-experimental 162
tt (u --) gforth-1.0 240
tuck (w1 w2 -- w2 w1 w2) core-ext 72
type (c-addr u --) core 189
typewhite (addr n --) gforth-0.2 189

U

u*/ (u1 u2 u3 -- u4) gforth-1.0 63
u*/mod (u1 u2 u3 -- u4 u5) gforth-1.0 63
u-[do (compilation -- do-sys ; run-time u1 u2
 -- | loop-sys) gforth-experimental 100
u. (u --) core 183
u.r (u n --) core-ext 183
u/ (u1 u2 -- u) gforth-1.0 62
u/-stage1m (u a-reci --) gforth-1.0 65
u/-stage2m (u1 a-reci -- uquotient)
 gforth-1.0 65
u/mod (u1 u2 -- u3 u4) gforth-1.0 63
u/mod-stage2m (u1 a-reci -- umodulus
 uquotient) gforth-1.0 65
u< (u1 u2 -- f) core 68
u<= (u1 u2 -- f) gforth-0.2 68
u> (u1 u2 -- f) core-ext 68
u>= (u1 u2 -- f) gforth-0.2 68
U+D0 (compilation -- do-sys ; run-time u1 u2
 -- | loop-sys) gforth-0.2 100
U-D0 (compilation -- do-sys ; run-time u1 u2
 -- | loop-sys) gforth-0.2 100
uallot (n1 -- n2) gforth-0.3 251
ud. (ud --) gforth-0.2 183
ud.r (ud n --) gforth-0.2 183
ud/mod (ud1 u2 -- urem udquot)
 gforth-0.2 63
UDefer ("name" --) gforth-1.0 251
ukeyed (addr u --) minos2 324
um* (u1 u2 -- ud) core 61
um/mod (ud u1 -- u2 u3) core 63
umax (u1 u2 -- u) gforth-1.0 61
umin (u1 u2 -- u) gforth-0.5 61
umod (u1 u2 -- u) gforth-1.0 62
umod-stage2m (u1 a-reci -- umodulus)
 gforth-1.0 65
uncolored-mode (--) gforth-1.0 190
under+ (n1 n2 n3 -- n n2) gforth-0.3 61

unescape (addr1 u1 dest -- dest u2)
 string-ext 198
 unlock (semaphore --)
 gforth-experimental 252
 unloop (R:w1 R:w2 --) core 101
 UNREACHABLE (--) gforth-0.2 203
 UNTIL (compilation dest -- ; run-time f --)
 core 105
 unused (-- u) core-ext 76
 unused-words (--) gforth-1.0 240
 up@ (-- a-addr) new 251
 update (--) block 181
 updated? (n -- f) gforth-0.2 181
 use ("file" --) gforth-0.2 181
 User ("name" --) gforth-0.2 251
 user' ("name" -- u)
 gforth-experimental 251
 utime (-- dtim) gforth-0.5 279
 UValue ("name" --) gforth-1.0 251

V

v* (f-addr1 nstride1 f-addr2 nstride2 ucount
 -- r) gforth-0.5 70
 Value (w "name" --) core-ext 114
 value: (u1 "name" -- u2)
 gforth-experimental 137
 value[]: (u1 "name" -- u2)
 gforth-experimental 138
 var (size --) oof 223, 224
 Variable ("name" --) core 113
 vglue (-- rtyp rsub radd) minos2 326
 vglue@ (-- rtyp rsub radd) minos2 326
 vlist (--) gforth-0.2 167
 Vocabulary ("name" --) gforth-0.2 167
 vocs (--) gforth-0.2 167
 vp-bottom (o:vp --) minos2 328
 vp-left (o:vp --) minos2 328
 vp-needed (xt --) minos2 328
 vp-reslide (o:vp --) minos2 328
 vp-right (o:vp --) minos2 328
 vp-top (o:vp --) minos2 328

W

w (-- r) minos2 325
 w! (w c-addr --) gforth-0.7 82
 w, (x --) gforth-1.0 77
 w-color (-- r) minos2 326
 w/o (-- fam) file 174
 w>s (x -- n) gforth-1.0 84
 w@ (c-addr -- u) gforth-0.5 82
 W: (compilation "name" -- a-addr xt;
 run-time x --) gforth-0.2 202
 W^ (compilation "name" -- a-addr xt;
 run-time x --) gforth-0.2 202

wake (task --) gforth-experimental 250
 walign (--) gforth-1.0 86
 waligned (addr -- addr') gforth-1.0 86
 warning-color (--) gforth-1.0 189
 WARNING" (compilation 'ccc' -- ; run-time f
 --) gforth-1.0 111
 warnings (-- addr) gforth-0.2 111
 wbe (u1 -- u2) gforth-1.0 83
 wfield: (u1 "name" -- u2) gforth-1.0 135
 where ("name" --) gforth-1.0 239
 whereg ("name" --) gforth-1.0 240
 WHILE (compilation dest -- orig dest ;
 run-time f --) core 105
 widget (-- class) minos2 324
 within (u1 u2 u3 -- f) core-ext 68
 wle (u1 -- u2) gforth-1.0 83
 word (char "<chars>ccc<char>-- c-addr)
 core 164
 wordlist (-- wid) search 166
 wordlist-words (wid --) gforth-0.6 167
 wordlists (-- n) environment 170
 words (--) tools 167
 wrap-xt (... xt1 xt2 xt3 -- ...)
 gforth-1.0 132
 write-file (c-addr u1 wfileid -- wior)
 file 175
 write-line (c-addr u wfileid -- ior)
 file 175
 wrol (u1 u -- u2) gforth-1.0 67
 wror (u1 u -- u2) gforth-1.0 67
 WTF?? (--) gforth-1.0 245
 wvalue: (u1 "name" -- u2)
 gforth-experimental 137
 ww (u --) gforth-1.0 239

X

x (-- r) minos2 325
 x! (w c-addr --) gforth-1.0 83
 x, (x --) gforth-1.0 77
 x-size (xc-addr u1 -- u2) xchar 195
 x-width (xc-addr u -- n) xchar-ext 196
 x>s (x -- n) gforth-1.0 84
 x@ (c-addr -- u) gforth-1.0 83
 x\string- (xc-addr u1 -- xc-addr u2)
 xchar-ext 196
 xalign (--) gforth-1.0 86
 xaligned (addr -- addr') gforth-1.0 86
 xbe (u1 -- u2) gforth-1.0 83
 xc!+ (xc xc-addr1 -- xc-addr2) xchar 196
 xc!+? (xc xc-addr1 u1 -- xc-addr2 u2 f)
 xchar 195
 xc, (xchar --) xchar 196
 xc-size (xc -- u) xchar 195
 xc-width (xc -- n) xchar-ext 196
 xc@ (xc-addr -- xc) xchar-ext 195
 xc@+ (xc-addr1 -- xc-addr2 xc) xchar 195

<code>xc@+?</code> (<code>xc-addr1 u1 -- xc-addr2 u2 xc</code>)	
<code>gforth-experimental</code>	195
<code>xchar+</code> (<code>xc-addr1 -- xc-addr2</code>) <code>xchar</code>	196
<code>xchar-</code> (<code>xc-addr1 -- xc-addr2</code>)	
<code>xchar-ext</code>	196
<code>XCHAR-ENCODING</code> (<code>-- addr u</code>) <code>environment</code>	170
<code>XCHAR-MAXMEM</code> (<code>-- u</code>) <code>environment</code>	171
<code>xd!</code> (<code>ud c-addr --</code>) <code>gforth-1.0</code>	83
<code>xd</code> , (<code>xd --</code>) <code>gforth-1.0</code>	77
<code>xd>s</code> (<code>xd -- d</code>) <code>gforth-1.0</code>	84
<code>xd@</code> (<code>c-addr -- ud</code>) <code>gforth-1.0</code>	83
<code>xdbe</code> (<code>ud1 -- ud2</code>) <code>gforth-1.0</code>	83
<code>xdle</code> (<code>ud1 -- ud2</code>) <code>gforth-1.0</code>	83
<code>xemit</code> (<code>xc --</code>) <code>xchar</code>	189
<code>xfield:</code> (<code>u1 "name" -- u2</code>) <code>gforth-1.0</code>	135
<code>xhold</code> (<code>xc --</code>) <code>xchar-ext</code>	196
<code>xkey</code> (<code>-- xc</code>) <code>xchar</code>	196
<code>xkey?</code> (<code>-- flag</code>) <code>xchar</code>	191
<code>xle</code> (<code>u1 -- u2</code>) <code>gforth-1.0</code>	83
<code>xor</code> (<code>w1 w2 -- w</code>) <code>core</code>	66
<code>xt-locate</code> (<code>nt/xt --</code>) <code>gforth-1.0</code>	238
<code>xt-new</code> (<code>... class xt -- object</code>) <code>objects</code>	221
<code>xt-see</code> (<code>xt --</code>) <code>gforth-0.2</code>	240
<code>xt-see-code</code> (<code>xt --</code>) <code>gforth-1.0</code>	241
<code>xt-simple-see</code> (<code>xt --</code>) <code>gforth-1.0</code>	241
<code>xt>name</code> (<code>xt -- nt</code>) <code>gforth-1.0</code>	147
<code>XT:</code> (<code>compilation "name" -- a-addr xt;</code>	
<code>run-time xt1 --</code>) <code>gforth-1.0</code>	202
<code>xywh</code> (<code>-- rx0 ry0 rw rh</code>) <code>minos2</code>	326
<code>xywhd</code> (<code>-- rx ry rw rh rd</code>) <code>minos2</code>	326
Y	
<code>y</code> (<code>-- r</code>) <code>minos2</code>	325
Z	
<code>z:</code> (<code>compilation "name" -- a-addr xt;</code>	
<code>run-time z --</code>) <code>gforth-1.0</code>	202
<code>zvalue:</code> (<code>u1 "name" -- u2</code>)	
<code>gforth-experimental</code>	137

Concept and Word Index

Not all entries listed in this index are present verbatim in the text. This index also duplicates, in abbreviated form, all of the words listed in the Word Index (only the names are listed for the words here).

!		<code>\$[]</code>	94
<code>!</code>	81	<code>\$[]!</code>	94
<code>!!FIXME!!</code>	245	<code>\$[]#</code>	94
<code>!@</code>	81	<code>\$[]+!</code>	94
<code>!localn</code>	207	<code>\$[]</code>	95
<code>!resize</code>	326	<code>\$[]@</code>	94
<code>!size</code>	326	<code>\$[]free</code>	95
		<code>\$[]map</code>	94
		<code>\$[]slurp</code>	94
		<code>\$[]slurp-file</code>	94
		<code>\$[]Variable</code>	95
"		<code>\$@</code>	93
<code>", stack item type</code>	59	<code>\$@len</code>	93
		<code>\$del</code>	93
		<code>\$exec</code>	94
#		<code>\$free</code>	93
<code>#</code>	184	<code>\$init</code>	93
<code>#!</code>	310	<code>\$ins</code>	93
<code>#-prefix for decimal numbers</code>	54	<code>\$iter</code>	93
<code>#></code>	184	<code>\$over</code>	93
<code>#>></code>	184	<code>\$slurp</code>	94
<code>#bell</code>	90	<code>\$slurp-file</code>	94
<code>#bs</code>	90	<code>\$split</code>	91
<code>#cr</code>	90	<code>\$substitute</code>	198
<code>#del</code>	90	<code>\$tmp</code>	92
<code>#eof</code>	90	<code>\$unescape</code>	198
<code>#esc</code>	90	<code>\$value:</code>	137
<code>#ff</code>	90	<code>\$value[]:</code>	138
<code>#lf</code>	90	<code>\$Variable</code>	95
<code>#line</code>	159		
<code>#loc</code>	245	%	
<code>#locals</code>	170	<code>%-prefix for binary numbers</code>	54
<code>#s</code>	184	<code>%align</code>	141
<code>#tab</code>	90	<code>%alignment</code>	141
<code>#tib</code>	156	<code>%alloc</code>	141
		<code>%allocate</code>	141
\$		<code>%allot</code>	141
<code>\$!</code>	93	<code>%size</code>	141
<code>\$!len</code>	93		
<code>\$+!</code>	93	&	
<code>\$+!len</code>	93	<code>&-prefix for decimal numbers</code>	54
<code>\$+[]!</code>	94		
<code>\$+slurp</code>	94		
<code>\$+slurp-file</code>	94		
<code>\$-prefix for hexadecimal numbers</code>	54		
<code>\$</code>	94		
<code>\$?</code>	279		

-[do.....	100	.included.....	174
-`.....	236	.locale-csv.....	197
-\d.....	236	.path.....	178
-\s.....	236	.quoted-csv.....	199
-c?.....	236	.r.....	183
-char.....	236	.recognizers.....	160
-class.....	236	.s.....	242
-d, command-line option.....	5	.sections.....	79
-D, command-line option.....	5	.substitute.....	198
-DFORCE_REG.....	312	.unresolved.....	106
-DO.....	100	.voc.....	166
-DUSE_FTOS.....	318	.widget.....	327
-DUSE_NO_FTOS.....	318		
-DUSE_NO_TOS.....	318		
-DUSE_TOS.....	318		
-f, command-line option.....	5	/	
-h, command-line option.....	5	/.....	62
-i, command-line option.....	4	//.....	237
-i, invoke image file.....	309	//g.....	238
-inf.....	71	//o.....	238
-infinity.....	71	//s.....	238
-l, command-line option.....	5	/COUNTED-STRING.....	169
-LOOP.....	101	/f.....	62
-ltrace.....	245	/f-stage1m.....	65
-m, command-line option.....	4	/f-stage2m.....	65
-p, command-line option.....	4	/HOLD.....	170
-r, command-line option.....	5	/l.....	86
-rot.....	72	/mod.....	62
-stack.....	142	/modf.....	63
-trailing.....	91	/modf-stage2m.....	65
-trailing-garbage.....	196	/mods.....	62
-v, command-line option.....	5	/PAD.....	170
-W, command-line option.....	9	/s.....	62
-Wall, command-line option.....	9	/string.....	91
-Werror, command-line option.....	9	/w.....	86
-Won, command-line option.....	9	/x.....	86
-Wpedantic, command-line option.....	9		
.		:	
.....	182	:.....	115
.".....	188	:, passing data across.....	150
.", how it works.....	51	::.....	225
.(.....	188	:}.....	202
.....	242	:}d.....	231
.char.....	236	:}h.....	231
.?.....	236	:}h1.....	231
.\n.....	188	:}l.....	231
.cover-raw.....	248	:}xt.....	231
.coverage.....	248	:is.....	131
.debugline.....	244	:m.....	220
.emacs.....	303	:method.....	228
.fi files.....	306	:noname.....	116
.fpath.....	178		
.gforth-history.....	10		
.hm.....	275		
.id.....	147		

[IF] and POSTPONE	298
[IF], end of the input source before matching [ELSE] or [THEN]	298
[IFDEF]	158
[IFUNDEF]	158
[LOOP]	159
[n:d]	230
[n:h]	230
[n:h1]	230
[n:l]	230
[NEXT]	159
[noop]	126
[parent]	220
[parent] usage	213
[REPEAT]	159
[THEN]	158
[to-inst]	221
[undefined]	158
[UNTIL]	159
[WHILE]	159

]	
] .	149
]]	151
]L	150
]nocov	247

‘	236
˘	236
˘ prefix	145
˘ prefix of word	56
?	236
˘˘ prefix of word	56

@	
@	81
@localn	207

<code>\</code>	60
<code>\\$</code>	236
<code>\(</code>	237
<code>\)</code>	237
<code>\, editing with Emacs</code>	303
<code>\, line length in blocks</code>	292
<code>\^</code>	236
<code>\\</code>	174
<code>\0</code>	237
<code>\c</code>	256
<code>\d</code>	236

<code>\G</code>	60
<code>\s</code>	236

{	202
{	202
{*	237
{**	237
{+	237
{++	237
{:	202
{{	237
}	
}	202
}}	237

 202
 237

```

~
~~
~~. . . . . 244
~~, removal with Emacs . . . . . 303
~~1bt . . . . . 244
~~bt . . . . . 244
~~Value . . . . . 245
~~Variable . . . . . 245

```

0	
0<.....	68
0<=.....	68
0<>.....	68
0=.....	68
0>.....	68
0>=.....	68
0x-prefix for hexadecimal numbers	54

1	
1+.....	60
1-.....	61
1/f.....	70

2

2!	82
2*	67
2,	77
2/	67
2>r	74
2@	82
2compile,	153
2Constant	114
2drop	73
2dup	73
2field:	135
2Literal	150
2nip	73
2over	73
2r>	74
2r@	74
2rdrop	74
2rot	73
2swap	73
2tuck	73
2Value	114
2value:	137
2Variable	113

A

a_, stack item type	59
A,	77
abi-code	261
abort	111
ABORT"	111
ABORT", exception abort sequence	286
abs	61
absolute-file?	177
abstract class	211, 222
accept	193
ACCEPT, display after end of input	286
ACCEPT, editing	285
ACONSTANT	113
act	325
act-name\$	324
action-of	131
action-of name semantics, changing them	125
activate	249
active-w	324
actor	324
add-cflags	258
add-framework	258
add-incdir	258
add-ldflags	258
add-lib	258
add-libpath	258
addr	115
addr name semantics, changing them	125
address alignment exception	290

address alignment exception, stack overflow ...	288
address arithmetic words	84
address unit	84
address unit, size in bits	286
ADDRESS-UNIT-BITS	169
addressable:	115
adjust-buffer	81
after-locate	239
AGAIN	105
AHEAD	105
Alias	133
aliases	133
align	77
aligned	85
aligned addresses	285
alignment faults	290
alignment of addresses for types	84
alignment tutorial	30
ALiteral	149
allocate	80
allot	76
also	166
also, too many word lists in search order	298
also-path	178
ambiguous conditions, block words	292
ambiguous conditions, core words	288
ambiguous conditions, double words	292
ambiguous conditions, facility words	293
ambiguous conditions, file words	294
ambiguous conditions, floating-point words	295
ambiguous conditions, locals words	297
ambiguous conditions, programming-tools words	297
ambiguous conditions, search-order words	298
and	66
angles in trigonometric operations	70
annotate-cov	248
ans-report.fs	282
append	92
arg	199
argc	200
argument input source different than current input source for RESTORE-INPUT	290
argument type mismatch	288
argument type mismatch, RESTORE-INPUT	290
arguments, OS command line	199
argv	200
arithmetic words	60
arithmetics tutorial	15
array, iterating over	99
array>mem	100
arrays	112
arrays tutorial	38
arshift	66
asptr	223
assembler	261
ASSEMBLER, search order capability	297
assert(246

assert-level	246
assert0 (.....	245
assert1 (.....	245
assert2 (.....	246
assert3 (.....	246
assertions	245
assignment conversion	233
ASSUME-LIVE	205
at-deltaxy	189
at-xy	189
AT-XY can't be performed on user output device.....	293
atomic operations	252
atomic!@	252
atomic+!@	252
atomic?!@	252
Attempt to use zero-length string as a name	290
au (address unit)	84
AUser	251
authors	10
authors of Gforth	330
auto-indentation of Forth code in Emacs	304
AValue	114
AVariable	113

B

b	239
back>	142
backtrace	281
backtrace examination	240
backtraces with gforth-fast	281
barrier	252
base	157
base is not decimal (REPRESENT, F., FE., FS.)	295
base-execute	157
baseline	325
basename	176
basic objects usage	211
batch processing with Gforth	9
before-line	163
before-locate	239
before-word	163
begin-structure	135
BEGIN	105
benchmarking Forth systems	319
Benchres	320
big-endian	82
bin	174
bind	218
bind usage	213
bind'	218
bitwise operation words	66
bl	90
blank	87
blk	156
BLK, altering BLK	292
block	181

block buffers	179
block number invalid	292
block read not possible	292
block transfer, I/O exception	292
block words, ambiguous conditions	292
block words, implementation-defined options ..	292
block words, other system documentation	292
block words, system documentation	291
block-included	182
block-offset	181
block-position	181
blocks	179
blocks file	179
blocks files, use with Emacs	305
blocks in files	294
blocks.fb	179
body-relative address input format	56
Boolean flags	60
bootmessage	311
border	325
borderl	326
bordert	326
borderv	326
bounds	100
break "	247
break:	247
broken-pipe-error	194
browse	239
bt	240
buffer	181
buffer%	81
buffer:	113
bug reporting	329
bw	240
bw-cover	248
bye	9
bye during gforthmi	308
byte order	82

C

c!	81
c\$+!	93
c++-library	258
c++-library-name	258
c,	76
c, stack item type	58
c-callback	259
c-callback-thread	259
c-function	256
c-funptr	256
c-library	258
c-library-name	257
c-value	256
c-variable	256
c>s	84
c?	236

<code>c_</code> , stack item type.....	59	characters tutorial.....	29
<code>c@</code>	81	<code>charclass</code>	235
C function pointers to Forth words.....	259	<code>chars</code>	85
C function pointers, calling from Forth.....	256	child class.....	210
C functions, calls to.....	254	child words.....	119
C functions, declarations.....	255	<code>cilk-bye</code>	254
C interface.....	254	<code>cilk-init</code>	253
<code>C"</code>	95	<code>cilk-sync</code>	254
C, using C for the engine.....	312	<code>class</code>	210, 218, 224
<code>C:</code>	202	class binding.....	213
<code>C^</code>	202	class binding as optimization.....	213
<code>call-c</code>	260	class binding, alternative to.....	213
Callback functions written in Forth.....	259	class binding, implementation.....	217
<code>caller-w</code>	324	class declaration.....	223
calling a definition.....	106	class definition, restrictions.....	212, 222
calling C functions.....	254	class implementation and representation.....	217
<code>capscompare</code>	92	class scoping implementation.....	217
<code>capssearch</code>	92	<code>class usage</code>	211, 221
<code>capsstring-prefix?</code>	92	<code>class->map</code>	218
<code>case</code>	104	<code>class-inst-size</code>	218
<code>case</code> as generalized control structure.....	103	<code>class-inst-size</code> discussion.....	212
case sensitivity.....	59	<code>class-override!</code>	218
case-sensitivity characteristics.....	287	<code>class-previous</code>	218
case-sensitivity for name lookup.....	285	<code>class;</code>	224
CASE control structure.....	96	<code>class;</code> usage.....	221
<code>catch</code>	108	<code>class>order</code>	219
<code>catch</code> and backtraces.....	281	classes and scoping.....	215
<code>catch</code> and <code>this</code>	217	clear screen.....	189
<code>catch in m: ... ;m</code>	214	<code>clear-libs</code>	258
<code>catch-nobt</code>	108	<code>clear-path</code>	178
<code>cell</code>	85	<code>clearstack</code>	243
cell size.....	287	<code>clearstacks</code>	243
<code>cell%</code>	141	<code>clicked</code>	324
<code>cell+</code>	85	clock tick duration.....	293
<code>cell-</code>	85	<code>close-dir</code>	177
cell-aligned addresses.....	285	<code>close-file</code>	174
<code>cell/</code>	85	<code>close-pipe</code>	194
<code>cells</code>	85	closure conversion.....	232
CFA.....	277	closures.....	229
<code>cfield:</code>	135	<code>cmove</code>	87
changing the compilation word list (during compilation).....	298	<code>cmove></code>	87
<code>char</code>	90	<code>code</code>	262
char size.....	287	code address.....	277
<code>char%</code>	141	code coverage.....	247
<code>char+</code>	85	code field.....	277
<code>char-</code>	85	code space.....	75
character editing of <code>ACCEPT</code> and <code>EXPECT</code>	285	code words.....	261
character encoding.....	87	<code>code-address!</code>	277
character literals.....	88	CODE ending sequence.....	297
character set.....	285	CODE, processing input.....	297
character strings - displaying.....	189	colon definitions.....	115, 116
character strings - moving and copying.....	87	colon definitions, nesting.....	117
character strings - representations.....	88	colon definitions, tutorial.....	18
character-aligned address requirements.....	285	colon-sys, passing data across :.....	150
character-set extensions and matching of names.....	285	<code>color-cover</code>	248
Characters - chars/bytes vs. extended characters.....	87	<code>color:</code>	327
characters - displaying.....	189	combined words.....	143
		command line arguments, OS.....	199

command-line editing	10
command-line options	4
comment editing commands	303
comments	59
comments tutorial	17
common-list	208
comp-i.fs	308
comp.lang.forth	331
COMP'	148
compare	90
compare and swap	252
comparison of object models	228
comparison tutorial	23
compilation semantics	50, 142
compilation semantics tutorial	33
compilation token	148
compilation tokens, tutorial	41
compilation word list	165
compilation word list, change before definition ends	298
compile state	154
compile,	153
compile-color	190
compile-only	143
compile-only warning, for ' etc.	288
compile-only words	143
compile-only?	274
compiled code examination	240
compiling	163
compiling compilation semantics	150
compiling words	149
complex numbers, input format	55
compsem:	144
conditional compilation	158
conditionals, tutorial	22
const-does>	129
Constant	113
constants	113
construct	219
construct discussion	212
context	167
context-sensitive help	303
contiguous region	76
contiguous regions and heap allocation	80
contiguous regions in dictionary allocation	76
contiguous regions and sections	78
contof	104
contributors to Gforth	330
control characters as delimiters	285
control structures	95
control structures for selection	96
control structures, user-defined	104
control-flow stack	104
control-flow stack items, locals information	208
control-flow stack underflow	297
control-flow stack, format	285
convert	194
convertin strings to numbers	193
core words, ambiguous conditions	288
core words, implementation-defined options ...	285
core words, other system documentation	291
core words, system documentation	285
CORE	170
CORE-EXT	170
cores	253
count	95
counted loops	97
counted loops with negative increment	98
counted string, maximum size	286
counted strings	88
Country	197
cov%	248
cov+	248
cover-filename	248
coverage?	247
cputime	279
cr	187
Create	112
create-file	174
create-from	129
create...does> tutorial	37
CREATE ... DOES>	119
CREATE ... DOES>, applications	120
CREATE ... DOES>, details	121
CREATE ... SET-DOES>	120
CREATE and alignment	84
creating objects	212
critical-section	252
cross-compiler	309, 321
cross.fs	309, 321
cs-vocabulary	166
cs-wordlist	166
CS-DROP	105
CS-PICK	105
CS-PICK, fewer than <i>u</i> +1 items on the control flow-stack	297
CS-ROLL	105
CS-ROLL, fewer than <i>u</i> +1 items on the control flow-stack	297
cstring>sstring	92
csv-quote	199
csv-separator	198
ct (compilation token)	148
CT, tutorial	41
ctz	67
current	167
current'	219
current-interface	219
current-interface discussion	217
currying	121
cursor positioning	189
cvalue:	137

D

d	325	Defer	131
d+	61	defer	224
d, stack item type	59	defer!	132
d-	61	defer:	139
d	183	defer@	132
d.r	183	deferred words	130
d<	68	defers	131
d<=	68	definer	278
d<>	68	definer!	278
d=	68	defines	224
d>	68	defining defining words	118
d>=	68	defining words	111
d>f	69	defining words tutorial	37
d>s	61	defining words without name	116
d0<	68	defining words, name given in a string	118
d0<=	68	defining words, simple	112
d0<>	68	defining words, user-defined	118
d0=	68	definition	44
d0>	69	definitions	165
d0>=	69	definitions, tutorial	18
d2*	67	defocus	324
d2/	67	delete	92
D:	202	delete-file	174
D>F, <i>d</i> cannot be presented precisely as a float	296	delta-i	101
D>S, <i>d</i> out of range of <i>n</i>	292	depth	243
D~	202	depth changes during interpretation	282
dabs	61	depth-changes.fs	282
dark-mode	190	deque	142
darshift	67	design of stack effects, tutorial	21
data space	75	dest, control-flow stack item	104
data space - reserving some	76	df!	82
data space available	291	df_, stack item type	59
data space containing definitions gets		df@	82
de-allocated	290	df@ or df! used with an address that is not	
data space pointer not properly aligned, ,, C, .	290	double-float aligned	295
data space read/write with incorrect alignment	290	dfalign	77
data stack	72	dfaligned	86
data stack manipulation words	72	dffield:	135
data structure locals	201	dfloat%	141
data-relocatable image files	308	dfloat+	86
data-space, read-only regions	287	dfloat/	86
dbg	247	dfloats	85
debug tracer editing commands	303	dfvalue:	137
debug-fid	244	dglue	326
debugging	244	dglue@	326
debugging output, finding the source location in		dict-new	219
Emacs	303	dict-new discussion	212
debugging Singlestep	246	dictionary	154
dec	182	dictionary allocation direction	76
dec.r	183	dictionary in persistent form	306
decimal	157	dictionary memory	75
declaring C functions	255	dictionary overflow	289
decompilation tutorial	18	dictionary size default	309
default type of locals	201	digits > 35	286
default-color	189	direct threaded inner interpreter	313
default-input	190	Directories	176
		dirname	176
		disassembler, general	264

discode 264
dispose-widget 326
 dividing by zero 288
 dividing by zero, floating-point 296
 Dividing classes 215
 dividing integers 62
 dividing many integers with the same divisor ... 64
 Division by zero 62, 64
 division rounding 287
 division with potentially negative operands 60
dlshift 66
dmax 61
dmin 61
dnegate 61
 DO loops 97
doabicode: 278
docol: 277
docon: 278
dodefer: 278
 dodoes routine 316
dodoes: 278
does-code! 278
does> tutorial 37
does>-code 278
DOES> 121
DOES> implementation 316
DOES> in a separate definition 121
DOES> in interpretation state 122
DOES> of non-CREATED words 291
DOES>, visibility of current definition 288
DOES>-code 316
DOES>-parts, stack effect 120
dofield: 278
DONE 101
 double precision arithmetic words 61
 double words, ambiguous conditions 292
 double words, system documentation 292
double% 141
 double-cell numbers, input format 54
 double-ended queue 142
 doubly indirect threaded code 308
douser: 278
dovalue: 278
dovar: 278
DO 101
dpl 157
draw 326
draw-init 326
drcl 67
drop 72
dror 68
drshift 66
du/mod 63
du< 69
du<= 69
du> 69
du>= 69
dump 243

dup 72
 duration of a system clock tick 293
 dynamic allocation of memory 80
 Dynamic superinstructions with replication 314
 Dynamically linked libraries in C interface 258

E

early 224
 early binding 213
edit 239
edit-line 193
 editing in ACCEPT and EXPECT 285
 eforth performance 319
ekey 191
ekey>char 191
ekey>fkey 191
ekey>xchar 191
ekey? 191
 EKEY, encoding of keyboard events 293
ekeyed 324
 elements of a Forth system 52
ELSE 105
 Emacs and Gforth 303
emit 189
emit-file 175
 EMIT and non-graphic characters 285
empty-buffer 181
empty-buffers 181
end-c-library 258
end-class 219, 224
end-class usage 211
end-class-noname 219
end-code 262
end-interface 219
end-interface usage 216
end-interface-noname 219
end-methods 219
end-struct 141
end-struct usage 140
end-structure 135
endcase 104
ENDIF 105
 endless loop 97
endof 104
endscope 203
endtry 109
endtry-iferror 110
engine 312
 engine performance 319
 engine portability 312
engine.s 319
 engines, gforth vs. gforth-fast vs. gforth-itc 314
entered 324
environment 172
 environment variable input format 55
 environment variables 11, 308

environment wordset.....	58
environment-wordlist	172
environment?	169
ENVIRONMENT? string length, maximum	286
environmental queries.....	169
environmental restrictions.....	284
equality of floats.....	71
erase.....	87
error messages.....	281
error output, finding the source location in Emacs.....	303
error-color.....	189
error-hl-inv	189
error-hl-ul.....	189
etags.fs.....	303
evaluate.....	156
event-loop.....	253
examining data.....	242
exception.....	107
exception abort sequence of ABORT"	286
exception source code.....	240
exception when including source	294
exception words, implementation-defined options	292
exception words, system documentation	292
exceptions.....	107
exceptions tutorial.....	36
executable image file.....	309
execute.....	146
execute-exit	146
execute-parsing.....	164
execute-parsing-file	165
execute-task	250
executing code on startup.....	9
execution frequency.....	247
execution semantics.....	143
execution token	44, 145
execution token input format.....	56
execution token of last defined word.....	117
execution token of words with undefined execution semantics.....	288
execution tokens tutorial.....	35
exercises.....	53
exit in m: ... ;m.....	214
exitm.....	219
exitm discussion.....	214
EXIT.....	107
expand-where	240
expect	194
EXPECT, display after end of input	286
EXPECT, editing	285
explicit register declarations.....	312
exponent too big for conversion (DF!, DF@, SF!, SF@).....	296
extend-mem.....	80
extend-structure.....	139
extended records.....	139
extra-section	79

F

f!	82
f! used with an address that is not float aligned	295
f*.....	69
f**.....	70
f+.....	69
f,	76
f, stack item type.....	58
f-.....	69
f-rot.....	73
f.....	186
f.rdp.....	186
f.s.....	242
f.s-precision	242
f/.....	69
f<.....	72
f<=.....	72
f<>.....	72
f=.....	72
f>.....	72
f>=.....	72
f>buf-rdp.....	187
f>d.....	69
f>l.....	207
f>r.....	74
f>s.....	69
f>str-rdp.....	187
f_, stack item type.....	59
f@.....	82
f@ used with an address that is not float aligned	295
f@localn.....	207
f~	72
f~abs.....	71
f~rel.....	71
f0<.....	72
f0<=.....	72
f0<>.....	72
f0=.....	72
f0>.....	72
f0>=.....	72
f2*.....	70
f2/.....	70
F:	202
F>D, integer part of float cannot be represented by d	296
F~	202
fabs.....	69
facility words, ambiguous conditions.....	293
facility words, implementation-defined options	293
facility words, system documentation.....	293
facos.....	71
FACOS, float >1	296
facosh.....	71
FACOSH, float<1	296
factoring.....	43
factoring similar colon definitions	120
factoring tutorial.....	20

<code>fade-color:</code>	327	files containing Forth code, tutorial.....	17
<code>falign</code>	77	files tutorial.....	32
<code>faligned</code>	85	<code>fill</code>	87
<code>falog</code>	70	<code>find</code>	166
<code>false</code>	60	<code>find-name</code>	147
<code>fam</code> (file access method)	174	<code>find-name-in</code>	147
<code>fasin</code>	71	first definition.....	48
<code>FASIN</code> , <code> float >1</code>	296	first field optimization	136
<code>fasinh</code>	71	<code>fkey</code>	193
<code>FASINH</code> , <code>float<0</code>	296	flags on the command line.....	4
<code>fast-throw</code>	107	flags tutorial.....	23
<code>fatan</code>	71	flat address space.....	76
<code>fatan2</code>	71	flat closures.....	229
<code>FATAN2</code> , both arguments are equal to zero	295	flavours of locals.....	200
<code>fatanh</code>	71	<code>FLiteral</code>	150
<code>FATANH</code> , <code> float >1</code>	296	<code>fln</code>	70
<code>faxpy</code>	70	<code>FLN</code> , <code>float<=0</code>	296
<code>fclearstack</code>	243	<code>flnp1</code>	70
<code>fconstant</code>	114	<code>FLNP1</code> , <code>float<=-1</code>	296
<code>fcopysign</code>	69	<code>float</code>	85
<code>fcos</code>	70	<code>float%</code>	141
<code>fcosh</code>	71	<code>float+</code>	85
<code>fdepth</code>	243	<code>float/</code>	85
<code>FDL</code> , GNU Free Documentation License	332	floating point arithmetic words.....	69
<code>fdrop</code>	73	floating point numbers, format and range	295
<code>fdup</code>	73	floating point tutorial.....	31
<code>fe</code>	186	floating point unidentified fault, integer division.....	288
fetch and add.....	252	floating-point arithmetic, pitfalls	69
<code>fexp</code>	70	floating-point comparisons	71
<code>fexpm1</code>	70	floating-point constants.....	71
<code>ffield:</code>	135	floating-point dividing by zero	296
<code>ffourth</code>	73	floating-point numbers, input format	54
<code>field</code>	141	floating-point numbers, rounding or truncation.....	295
<code>field</code> usage	140	floating-point output.....	186
<code>field</code> usage in class definition	212	floating-point result out of range.....	295
<code>field:</code>	135	floating-point stack	72
file access methods used.....	293	floating-point stack in the standard	72
file exceptions	293	floating-point stack manipulation words.....	73
file input nesting, maximum depth	294	floating-point stack size.....	295
file line terminator	293	floating-point stack width.....	295
file name format.....	293	Floating-point unidentified fault.....	62
file search path	177	Floating-point unidentified fault (on integer division)	64
file words, ambiguous conditions	294	floating-point unidentified fault, <code>F>D</code>	296
file words, implementation-defined options.....	293	floating-point unidentified fault, <code>FACOS</code> , <code>FASIN</code> or <code>FATANH</code>	296
file words, system documentation	293	floating-point unidentified fault, <code>FACOSH</code>	296
<code>file-eof?</code>	175	floating-point unidentified fault, <code>FASINH</code> or <code>FSQRT</code>	296
file-handling.....	174	floating-point unidentified fault, <code>FLN</code> or <code>FLOG</code> ..	296
<code>file-position</code>	175	floating-point unidentified fault, <code>FLNP1</code>	296
<code>file-size</code>	175	floating-point unidentified fault, <code>FP</code> divide-by-zero	296
<code>file-status</code>	175	floating-point words, ambiguous conditions....	295
<code>file>fpath</code>	178	floating-point words, implementation-defined options	295
<code>file>path</code>	178	floating-point words, system documentation...	295
<code>FILE-STATUS</code> , returned information.....	294	<code>floating-stack</code>	170
<code>filename-match</code>	177		
filenames in <code>~~</code> output.....	244		
filenames in assertion output.....	246		
files.....	173		
files containing blocks.....	294		

floats.....	85
flog.....	70
FLOG, <i>float</i> ≤0.....	296
floor.....	69
floored division.....	62
FLOORED.....	170
flush.....	182
flush-file.....	175
flush-icache.....	262
fm/mod.....	63
fmax.....	69
fmin.....	69
fnegate.....	69
fnip.....	73
focus.....	324
FOR loops.....	100
foreign language interface.....	254
FORGET, deleting the compilation word list.....	297
FORGET, <i>name</i> can't be found.....	297
FORGET, removing a needed definition.....	298
forgetting words.....	243
FORK.....	235
form.....	189
format and range of floating point numbers.....	295
format of glossary entries.....	57
formatted numeric output.....	183
Forth.....	166
Forth - an introduction.....	43
Forth mode in Emacs.....	303
Forth source files.....	173
Forth Tutorial.....	14
forth-recognize.....	162
forth-recognizer.....	162
Forth-related information.....	331
forth-wordlist.....	165
forth.el.....	303
forward.....	106
FOR.....	101
fourth.....	72
fover.....	73
fp!.....	75
fp.....	186
fp@.....	75
fp0.....	75
FP output.....	186
FP tutorial.....	31
fpath.....	178
fpick.....	73
fr>.....	74
fr@.....	74
free.....	80
free-closure.....	230
free-mem-var.....	80
frequently asked questions.....	331
frot.....	73
fround.....	70
fs.....	186
fsin.....	70

fsincos.....	70
fsinh.....	71
fsqrt.....	70
FSQRT, <i>float</i> <0.....	296
fswap.....	73
ftan.....	71
FTAN on an argument <i>r1</i> where cos(<i>r1</i>) is zero.....	296
ftanh.....	71
fthird.....	73
ftrunc.....	70
ftuck.....	73
fully relocatable image files.....	308
functions, tutorial.....	18
fvalue.....	114
fvalue:.....	137
fvariable.....	113

G

g.....	239
gap.....	325
gdb disassembler.....	264
general control structures (case).....	103
general files.....	174
get.....	325
get-block-fid.....	181
get-current.....	165
get-dir.....	177
get-order.....	165
get-recognizers.....	162
get-stack.....	142
get-state.....	163
getenv.....	279
gforth.....	171
Gforth - leaving.....	9
Gforth engine.....	314
Gforth environment.....	4
Gforth extensions.....	299
Gforth files.....	11
Gforth locals.....	200
Gforth performance.....	319
Gforth stability.....	2
gforth-ditc.....	308
gforth-fast and backtraces.....	281
gforth-fast engine.....	314
gforth-fast, difference from gforth.....	281
gforth-itc engine.....	314
gforth.el.....	303
gforth.el, installation.....	303
gforth.fi, relocatability.....	308
GFORTH - environment variable.....	11, 308
GFORTH - environment variable.....	11, 308
GFORTH - environment variable.....	11
gforthmi.....	308
GFORTH - environment variable.....	11
GFORTH - environment variable.....	11
gg.....	240

giving a name to a library interface	257
glossary notation format	57
GNU C for the engine	312
goals of the Gforth project	2

H

h	325
h	182
halt	250
header fields	273
header methods	274
header space	165
heap allocation	80
heap memory	75
heap-new	219
heap-new discussion	212
heap-new usage	212
help	9
here	76
hex	157
hex	182
hglue	326
hglue@	326
hide	325
highlighting Forth code in Emacs	304
highlighting Forth code in Emacs	304
history file	10
hold	184
holds	184
hooks in the text interpreter	163
how:	224
hybrid direct/indirect threaded code	314

I

i	101
i'	101
I/O - blocks	179
I/O - file-handling	173
I/O - keyboard and display	182
I/O - see input	193
I/O exception in block transfer	292
id	147
IDE (integrated development environment)	238
if , tutorial	22
IF	104
IF control structure	96
iferror	109
image file	306
image file background	306
image file initialization sequence	310
image file invocation	309
image file loader	306
image file, data-relocatable	308
image file, executable	309

image file, fully relocatable	308
image file, non-relocatable	307
image file, stack and dictionary sizes	309
image file, turnkey applications	311
image license	306
immediate	143
immediate words	50, 143
immediate, tutorial	33
immediate?	276
implementation	219
implementation of locals	207
implementation usage	216
implementation-defined options, block words ..	292
implementation-defined options, core words ...	285
implementation-defined options, exception words	292
implementation-defined options, facility words ..	293
implementation-defined options, file words	293
implementation-defined options, floating-point words	295
implementation-defined options, locals words ..	296
implementation-defined options, memory-allocation words	297
implementation-defined options, programming-tools words	297
implementation-defined options, search-order words	298
in	165
in-colon-def?	153
in-wordlist	165
include	173
include search path	177
include , placement in files	303
include-file	173
include-locale	197
INCLUDE-FILE , <i>file-id</i> is invalid	294
INCLUDE-FILE , I/O exception reading or closing <i>file-id</i>	294
included	173
included-locale	197
included?	173
INCLUDED , I/O exception reading or closing <i>file-id</i>	294
INCLUDED , named file cannot be opened	294
including files	173
including files, stack effect	173
indentation of Forth code in Emacs	304
indirect threaded inner interpreter	313
inf	71
infile-execute	176
infile-id	176
infinity	71
info-color	190
inheritance	210
init-asm	261
init-buffer	81
init-object	219
init-object discussion	212

initialization of locals	201
initialization sequence of image file	310
initiate	249
inline:	115
inner interpreter implementation	313
inner interpreter optimization	313
inner interpreter, direct threaded	313
inner interpreter, indirect threaded	313
input buffer	154
input format for body-relative addresses	56
input format for characters/code points	54
input format for double-cell numbers	54
input format for environment variables	55
input format for execution tokens	56
input format for floating-point numbers	54
input format for name tokens	56
input format for single-cell numbers	54
input format for strings	55
input from pipes	11
input line size, maximum	294
input line terminator	286
Input Redirection	176
input sources	156
input stream	163
input, linewise from terminal	193
input, single-key	190
input-color	190
insert	91
inst-value	219
inst-value usage	214
inst-value visibility	215
inst-var	220
inst-var implementation	217
inst-var usage	214
inst-var visibility	215
instance variables	210
instruction pointer	313
insufficient data stack or return stack space ..	288
insufficient space for loop control parameters ..	288
insufficient space in the dictionary	289
INT-[I]	159
integer types, ranges	286
integrated development environment	238
interface	220
interface implementation	217
interface to C functions	254
interface usage	216
interfaces for objects	216
interpret	156
interpret state	154
Interpret/Compile states	157
interpret/compile:	143
interpretation semantics	50, 142
interpretation semantics tutorial	33
interpreter - outer	154
interpreter directives	158
interpreting	163
Interpreting a compile-only word	289
Interpreting a compile-only word, for a local ...	297
interpreting a word with undefined interpretation semantics	289
intsem:	144
invalid block number	292
Invalid memory address	288
Invalid memory address, stack overflow	288
Invalid name argument, TO	290, 297
invert	66
invoking a selector	210
invoking Gforth	4
invoking image files	309
ior type description	59
<i>ior</i> values and meaning	294, 297
is name semantics, changing them	125
IS	131
items on the stack after interpretation	282
iterate over array	99
 J	
j	101
JOIN	235
 K	
k	101
k-alt-mask	192
k-backspace	192
k-ctrl-mask	192
k-delete	192
k-down	191
k-end	191
k-enter	192
k-eof	192
k-f1	192
k-f10	192
k-f11	192
k-f12	192
k-f2	192
k-f3	192
k-f4	192
k-f5	192
k-f6	192
k-f7	192
k-f8	192
k-f9	192
k-home	191
k-insert	192
k-left	191
k-mute	192
k-next	192
k-pause	192
k-prior	191
k-right	191
k-sel	192

k-shift-mask	192
k-tab	192
k-up	191
k-voldown	192
k-volup	192
k-winch	192
kern*.fi , relocatability	308
kerneling	325
key	190
key-file	175
key-ior	190
key?	190
key?-file	175
keyboard events, encoding in EKEY	293
kill	250
kill-task	250
Kuehling, David	303

L

l	239
l!	83
l,	77
l>s	84
l@	83
L"	197
labels as values	313
lalign	86
laligned	86
LANG – environment variable	11
Language	197
last word was headerless	290
lastfit	326
late binding	213
latest	147
latestnt	147
latesttxt	117
lbe	83
LC_ALL – environment variable	11
LC_CTYPE – environment variable	11
LEAVE	101
leaving definitions, tutorial	27
leaving Gforth	9
leaving loops, tutorial	27
left	324
length of a line affected by \	292
lfield:	135
lib-error	259
lib-sym	259
Libraries in C interface	258
library interface names	257
license	10
license for images	306
lifetime of locals	206
light-mode	190
line input from terminal	193
line terminator on input	286

line-end-hook	163
list	181
list-size	208
LIST display format	292
Literal	149
literal tutorial	40
Literals	149
Literals (in source code)	54
literals for characters and strings	88
little-endian	82
ll	240
lle	83
load	182
load-cov	248
loader for image files	306
loading files at startup	9
loading Forth code, tutorial	17
local in interpretation state	297
local variables, tutorial	21
locale and case-sensitivity	285
locale!	197
locale-csv	197
locale-csv-out	198
locale-file	197
locale@	197
locals	200
locals and return stack	73
locals flavours	200
locals implementation	207
locals information on the control-flow stack	208
locals initialization	201
locals lifetime	206
locals programming style	206
locals stack	72, 207
locals types	200
locals visibility	203
locals words, ambiguous conditions	297
locals words, implementation-defined options	296
locals words, system documentation	296
locals, default type	201
locals, Gforth style	200
locals, maximum number in a definition	296
locals, Standard Forth style	209
locate	238
lock	252
log2	67
long long	312
loop control parameters not available	290
loops without count	97
loops, counted	97
loops, counted, tutorial	25
loops, endless	97
loops, indefinite, tutorial	24
LOOP	101
lp!	75, 207
lp+!	207
lp+n	207
lp@	75

lp0	75
lrol	67
lror	67
lshift	66
LSHIFT, large shift counts	291
LU"	197
lvalue:	137

M

m*	61
m*/	64
m+	61
m:	220
m: usage	214
Macros	150
macros	149
macros, advanced tutorial	40
macros-wordlist	198
magenta-input	190
make-latest	129
map-vocs	167
mapping block ranges to files	294
marker	243
max	61
max-float	170
MAX-CHAR	169
MAX-D	170
MAX-N	170
MAX-U	170
MAX-UD	170
MAX-XCHAR	170
maxalign	77
maxaligned	86
maxdepth-.s	243
maximum depth of file input nesting	294
maximum number of locals in a definition	296
maximum number of word lists in search order	298
maximum size of a counted string	286
maximum size of a definition name, in characters	286
maximum size of a parsed string	286
maximum size of input line	294
maximum string length for ENVIRONMENT?, in characters	286
mem+do	101
mem,	77
mem-do	101
memory access words	81
memory access/allocation tutorial	28
memory alignment tutorial	30
memory barrier	252
memory block words	87
memory overcommit for dictionary and stacks ...	5
memory words	75
memory-allocation word set	80

memory-allocation words, implementation-defined options	297
memory-allocation words, system documentation	297
message send	210
meta recognizer	56
metacompiler	309, 321
method	210, 220, 224
method conveniences	213
method map	216
method selector	210
method usage	221
methods	220
methods...end-methods	215
min	61
mini-oof	224
mini-oof example	225
mini-oof usage	224
mini-oof.fs, differences to other models	229
minimum search order	298
miscellaneous words	280
mixed precision arithmetic words	61
mkdir-parents	177
mod	62
modf	62
modf-stage2m	65
modifying >IN	49
Modifying a word defined earlier	129
modifying the contents of the input buffer or a string literal	289
mods	62
modulus	62
most recent definition does not have a name (IMMEDIATE)	290
motivation for object-oriented programming ...	209
move	87
ms	279
MS, repeatability to be expected	293
Multiple exits from begin	102
multitasker	248
Must now be used inside C-LIBRARY, see C interface doc	261
mux	66
mwords	167

N

n	239
n, stack item type	59
n/a	126
n>r	74
name	164
name dictionary	44
name field address	148
name lookup, case-sensitivity	285
name not defined by VALUE or (LOCAL) used by TO	297

name not defined by **VALUE** used by **TO** 290
 name not found 288
 name not found (', **POSTPONE**, ['], [**COMPILE**]) 290
 name space 75
 name token 146
name\$ 325
 name, maximum length 286
name>compile 147
name>interpret 147
name>link 147
name>string 147
 names for defined words 118
NaN 71
native@ 197
needs 174
negate 61
 negative increment for counted loops 98
 Neon model 228
 nested colon definitions 117
new 225
new-color: 327
newline 90
 newline character on input 286
newtask 249
newtask4 249
next-arg 199
next-case 104
next-section 79
NEXT 101
NEXT, direct threaded 313
NEXT, indirect threaded 313
nextname 118
NFA 148
nip 72
nocov [..... 247
 non-graphic characters and **EMIT** 285
 non-relocatable image files 307
noname 117
noname-from 129
noop 146
nosplit? 91
 notation of glossary entries 57
nothrow 108
nr> 74
ns 279
nt 240
nt (name token) 146
nt input format 56
nt token input format 56
nt, stack item type 59
NT Forth performance 319
ntime 279
 number conversion 157
 number conversion - traps for the unwary 157
 number of bits in one address unit 286
 number representation and arithmetic 286
 numeric comparison words 68
 numeric output - formatted 183

numeric output - simple/free-format 182
 numeric output, **FP** 186
nw 239

O

o> 227
object 210, 220, 224
 object allocation options 212
object class 212
 object creation 212
 object interfaces 216
 object models, comparison 228
object-' 223
object-: 223
object-:: 223
object-[] 223
object-asptr 223
object-bind 223
object-bound 223
object-class 222
object-class? 222
object-definitions 222
object-dispose 223
object-endwith 223
object-init 222
object-is 223
object-link 223
object-map discussion 216
object-new 223
object-new[] 223
 object-oriented programming 210, 221
 object-oriented programming motivation 209
 object-oriented programming style 212
 object-oriented terminology 210
object-postpone 223
object-ptr 223
object-self 223
object-super 223
object-with 223
objects 210
 objects, basic usage 211
objects.fs 210, 221
objects.fs Glossary 218
objects.fs implementation 216
objects.fs properties 211
obsolete? 147
of 104
off 60
on 60
once 244
Only 166
oof 221
oof.fs 210, 221
oof.fs base class 222
oof.fs properties 221
oof.fs usage 221

oof.fs, differences to other models.....	228
open-blocks.....	181
open-dir.....	176
open-file.....	174
open-lib.....	259
open-path-file.....	178
open-pipe.....	194
operating system - passing commands.....	279
operator's terminal facilities available.....	291
opt:.....	127
options on the command line.....	4
or.....	66
order.....	166
orig, control-flow stack item.....	104
os-class.....	171
os-type.....	171
OS command line arguments.....	199
other system documentation, block words.....	292
other system documentation, core words.....	291
out.....	188
outer interpreter.....	43, 45, 154
outfile-execute.....	176
outfile-id.....	176
output in pipes.....	12
Output Redirection.....	176
output to terminal.....	189
over.....	72
overcommit memory for dictionary and stacks... 5	
overflow of the pictured numeric output string. 289	
overrides.....	220
overrides usage.....	212

P

pad.....	87
PAD size.....	287
PAD use by nonstandard words.....	291
page.....	189
par-split.....	327
parameter stack.....	72
parameters are not of the same type (DO, ?DO, WITHIN).....	290
parent class.....	210
parent class binding.....	213
parent-w.....	325
parse.....	164
parse area.....	154
parse-name.....	164
parse-word.....	164
parsed string overflow.....	289
parsed string, maximum size.....	286
parsing words.....	49, 155
pass.....	249
patching threaded code.....	316
path for included.....	177
path+.....	178
path=.....	178

pause.....	250
pedigree of Gforth.....	330
perform.....	146
performance of some Forth interpreters.....	319
persistent form of dictionary.....	306
PFE performance.....	319
pi.....	71
pick.....	72
pictured numeric output.....	183
pictured numeric output buffer, size.....	287
pictured numeric output string, overflow.....	289
pipes, creating your own.....	194
pipes, Gforth as part of.....	11
place.....	95
postpone.....	150
postpone tutorial.....	39
postpone,.....	149
POSTPONE applied to [IF].....	298
POSTPONE or [COMPILE] applied to TO.....	291
postponing.....	163
Pountain's object-oriented model.....	228
pow2?.....	67
precision.....	186
precompiled Forth code.....	306
Preface.....	1
prefix `.....	145
prepend-where.....	240
preserve.....	132
previous.....	166
previous, search order empty.....	298
previous-section.....	79
primitive source format.....	317
primitive-centric threaded code.....	314
primitives, assembly code listing.....	319
primitives, automatic generation.....	317
primitives, implementation.....	317
primitives, keeping the TOS in a register.....	318
prims2x.fs.....	317
print.....	220
printdebugdata.....	244
private discussion.....	215
procedures, tutorial.....	18
process-option.....	311
program data space available.....	291
programming style, locals.....	206
programming style, object-oriented.....	212
programming tools.....	238
programming-tools words, ambiguous conditions.....	297
programming-tools words, implementation-defined options.....	297
programming-tools words, system documentation.....	297
prompt.....	287
pronunciation of words.....	57
protected.....	220
protected discussion.....	215
pthread.....	249

ptr 223
public 220

Q

query 156
quit 280
quotations 117

R

r'@ 74
r, stack item type 59
r/o 174
r/w 174
r> 74
r@ 74
raise 325
ranges for integer types 286
rdrop 74
re-color 327
re-emoji-color 328
re-fade-color 328
re-text-color 327
re-text-emoji-fade-color 328
read-csv 198
read-dir 176
read-file 174
read-line 174
read-only data space regions 287
reading from file positions not yet written 294
rec-body 161
rec-complex 161
rec-dtick 161
rec-env 161
rec-float 161
rec-meta 162
rec-moof2 227
rec-nt 161
rec-num 161
rec-scope 161
rec-string 161
rec-tick 161
rec-to 161
receiving object 210
reciprocal of integer 64
recognize 162
recognizer-sequence: 162
Recognizers normal usage 159
Recognizers, dealing with 161
recongizers 159
records 134
records tutorial 38
recover (old Gforth versions) 110
recurse 106
RECURSE appears after DOES> 290

recursion tutorial 26
recursive 106
recursive definitions 106
Redirection 176
refill 164
regexps 235
relocating loader 306
relocation at load-time 306
relocation at run-time 306
remainder 62
rename-file 174
repeatability to be expected from the execution of MS 293
REPEAT 105
replace-word 245
replacer: 198
replaces 198
Replication 314
report the words used in your program 282
reposition-file 175
REPOSITION-FILE, outside the file's boundaries 294
represent 187
REPRESENT, results when *float* is out of range 295
require 173
require, placement in files 303
required 173
reserving data space 76
resize 80
resize-file 175
resized 327
restart 250
restore 110
restore-input 156
RESTORE-INPUT, Argument type mismatch 290
restrict 143
result out of range 289
Result out of range 62
Result out of range (on integer division) 64
return stack 72
return stack and locals 73
return stack dump with *gforth-fast* 281
return stack manipulation words 73
return stack space available 291
return stack tutorial 27
return stack underflow 289
return-stack-cells 170
returning from a definition 106
reveal 129
reveal! 129
rol 67
roll 73
Root 167
ror 67
rot 72
rounding of floating-point numbers 295
rp! 75
rp@ 75
rp0 75

rpick	74
rshift	66
RSHIFT , large shift counts.....	291
run-time code generation, tutorial.....	40
running Gforth.....	4
running image files.....	309
Rydqvist, Goran.....	303

S

s+	92
s//	238
s>>	238
s>d	61
s>f	69
s>number?	193
s>unnumber?	193
s\"	89
S"	89
S" , number of string buffers.....	294
S" , size of string buffer.....	294
safe/string	91
save-buffer	182
save-buffers	182
save-cov	248
save-input	156
save-mem	80
save-mem-dict	77
savesystem	307
savesystem during gforthmi.....	308
scan	91
scan-back	91
scope	203
scope of locals.....	203
scoping and classes.....	215
scr	181
scrolled	324
scvalue:	137
seal	167
search	91
search order stack.....	165
search order, maximum depth.....	298
search order, minimum.....	298
search order, tutorial.....	41
search path control, source files.....	178
search path for files.....	177
search-order words, ambiguous conditions.....	298
search-order words, implementation-defined options.....	298
search-order words, system documentation.....	298
search-wordlist	167
sections and contiguous regions.....	78
see	240
see tutorial.....	18
see-code	241
see-code-range	241
SEE , source and format of output.....	297

select	60
selection control structures.....	96
selector.....	210, 220
selector implementation, class.....	216
selector invocation.....	210
selector invocation, restrictions.....	212, 222
selector usage.....	211
selectors and stack effects.....	212
selectors common to hardly-related classes.....	216
semantics tutorial.....	33
semantics, changing the to/+to/action-of/is name/addr semantics.....	125
semantics, interpretation and compilation.....	142
semaphore	251
send-event	253
set	325
set->comp	276
set->int	276
set-compsem	144
set-current	165
set-dir	177
set-does>	122
set-execute	275
set-forth-recognize	162
set-name>link	277
set-name>string	277
set-optimizer	127
set-order	165
set-precision	186
set-recognizers	162
set-stack	142
set-state	163
set-to	127
sf!	82
sf_ , stack item type.....	59
sf@	82
sf@ or sf! used with an address that is not single-float aligned.....	295
sfa!gn	77
sfa!gned	85
sf!field:	135
sf!float%	141
sf!float+	85
sf!float/	85
sf!floats	85
sf!value:	137
sh	279
sh-get	279
Shared libraries in C interface.....	258
shell commands.....	279
shift-args	199
short-where	240
show	325
show-you	325
sign	184
sign extension.....	82
silent exiting from Gforth.....	12
simple defining words.....	112

simple loops	97	stack overflow	288
simple-fkey-string	193	stack pointer manipulation words	75
simple-see	241	stack size default	309
simple-see-range	241	stack size, cache-friendly	309
single precision arithmetic words	60	stack space available	291
single-assignment style for locals	206	stack tutorial	15
single-cell numbers, input format	54	stack underflow	289
single-key input	190	stack, user-defined	142
singlestep Debugger	246	stack-cells	170
size of buffer at WORD	287	stack-effect comments, tutorial	18
size of the dictionary and the stacks	4	stack:	142
size of the keyboard terminal buffer	287	stack>	142
size of the pictured numeric output buffer	287	stacksize	249
size of the scratch area returned by PAD	287	stacksize4	249
size parameters for command-line options	4	staged/-divisor	66
skip	91	staged/-size	65
sleep	250	Standard conformance of Gforth	284
SLiteral	150	starting Gforth tutorial	14
slurp-fid	175	startup sequence for image file	310
slurp-file	175	Startup speed	12
slvalue:	137	state - effect on the text interpreter	49
sm/rem	63	state-smart words (are a bad idea)	144
source	156	STATE values	287
source code for exception	240	static	224
source code of a word	238	status-color	190
source location of error or debugging output in Emacs	303	stderr	175
source-id	156	stderr and pipes	12
SOURCE-ID, behaviour when BLK is non-zero ..	295	stdin	175
sourcefilename	174	stdout	175
sourceline#	174	stop	250
sp!	75	stop-dns	250
sp@	75	stop-ns	250
sp0	75	str<	91
space	188	str=	91
space delimiters	285	str=?	237
spaces	188	String input format	55
span	194	string larger than pictured numeric output area (f., fe., fs.)	296
spawn	254	string literals	88
spawn1	254	string longer than a counted string returned by WORD	291
spawn2	254	string words with \$	93
speed, startup	12	string,	95
split	326	string-parse	164
stability of Gforth	2	string-prefix?	91
stack	142	string-suffix?	91
stack depth changes during interpretation	282	strings - see character strings	88
stack effect	57	strings tutorial	29
Stack effect design, tutorial	21	struct	141
stack effect of DOES>-parts	120	struct usage	140
stack effect of included files	173	structs tutorial	38
stack effects of selectors	212	structure extension	139
stack empty	289	structure of Forth programs	51
stack item types	58	structures	134
stack manipulation tutorial	16	Structures in Forth200x	134
stack manipulation words	72	sub-list?	208
stack manipulation words, floating-point stack ..	73	substitute	198
stack manipulation words, return stack	73	success-color	190
stack manipulations words, data stack	72		

superclass binding	213
Superinstructions	314
swap	72
swvalue:	137
symmetric division	62
Synonym	133
synonyms	133
syntax tutorial	14
system	279
system dictionary space required, in address units	291
system documentation	284
system documentation, block words	291
system documentation, core words	285
system documentation, double words	292
system documentation, exception words	292
system documentation, facility words	293
system documentation, file words	293
system documentation, floating-point words	295
system documentation, locals words	296
system documentation, memory-allocation words	297
system documentation, programming-tools words	297
system documentation, search-order words	298
system prompt	287

T

table	166
TAGS file	303
target compiler	309, 321
task	249
task-local data	251
terminal buffer, size	287
terminal input buffer	154
terminal output	189
terminal size	189
terminology for object-oriented programming ..	210
text interpreter	43, 45, 154
text interpreter - effect of state	49
text interpreter - input sources	155, 156
text-color:	327
text-emoji-color:	327
text-emoji-fade-color:	327
THEN	105
third	72
this	220
this and catch	217
this implementation	217
this usage	214
ThisForth performance	319
thread-deadline	250
threaded code implementation	313
threading words	277
threading, direct or indirect?	314
threading-method	277

throw	107
THROW-codes used in the system	292
thru	182
tib	156
tick (')	145
TILE performance	319
time&date	279
time-related words	279
TMP, TEMP - environment variable	11
to <i>name</i> semantics, changing them	125
to-class:	126
to-table:	126
to-this	221
tokens for words	145
touchdown	324
touchup	324
toupper	88
T0	114
T0 on non-VALUES	290
T0 on non-VALUES and non-locals	297
TOS definition	45
TOS optimization for primitives	318
translate-dnum	162
translate-float	162
translate-method:	163
translate-nt	162
translate-num	162
translate:	162
traverse-wordlist	147
trigonometric operations	70
true	60
truncation of floating-point numbers	295
try	109
try-recognize	162
tt	240
tuck	72
turnkey image files	311
Tutorial	14
type	189
types of locals	200
types of stack items	58
types tutorial	20
typewhite	189

U

u*/	63
u*/mod	63
u, stack item type	59
u-[do	100
u	183
u.r	183
u/	62
u/-stage1m	65
u/-stage2m	65
u/mod	63
u/mod-stage2m	65

u<	68
u<=	68
u>	68
u>=	68
U+D0	100
U-D0	100
uallot	251
ud, stack item type	59
ud	183
ud.r	183
ud/mod	63
UDefer	251
ukeyed	324
um*	61
um/mod	63
umax	61
umin	61
umod	62
umod-stage2m	65
unaligned memory access	82
uncolored-mode	190
undefined word	288
undefined word, ', POSTPONE, ['], [COMPILE] ..	290
under+	61
unescape	198
unexpected end of the input buffer	290
unlock	252
unloop	101
unmapped block numbers	294
UNREACHABLE	203
UNTIL	105
UNTIL loop	97
unused	76
unused-words	240
unwind-protect	109
up@	251
update	181
UPDATE, no current block buffer	292
updated?	181
upper and lower case	59
use	181
User	251
user input device, method of selecting	286
user output device, method of selecting	286
user space	251
user variables	251
user'	251
user-defined defining words	118
Uses of a word	239
utime	279
UValue	251

V

v*	70
Value	114
value-flavoured locals	200
value-flavoured words	115
value:	137
value[]:	138
values	114
var	223, 224
Variable	113
variable-flavoured locals	200
variable-flavoured words	115
variables	112
variadic C functions	256
versions, invoking other versions of Gforth	9
vglue	326
vglue@	326
view (called locate in Gforth)	238
viewing the documentation of a word in Emacs	303
viewing the source of a word in Emacs	303
virtual function	210
virtual function table	216
virtual machine	312
virtual machine instructions, implementation ..	317
visibility of locals	203
vlist	167
Vocabularies, detailed explanation	168
Vocabulary	167
vocs	167
vocstack empty, previous	298
vocstack full, also	298
vp-bottom	328
vp-left	328
vp-needed	328
vp-reslide	328
vp-right	328
vp-top	328

W

w	325
w!	82
w,	77
w, stack item type	59
w-color	326
w/o	174
w>s	84
w@	82
W:	202
W^	202
wake	250
walign	86
waligned	86
warning-color	189
WARNING"	111
warnings	111

wbe	83
wfield:	135
where	239
where to go next.....	52
whereg	240
WHILE	105
WHILE loop.....	97
wid	165
wid , stack item type.....	59
widget	324
Win32Forth performance.....	319
wior type description.....	59
<i>wior</i> values and meaning.....	294
within	68
wle	83
word	44, 164
word glossary entry format.....	57
word list for defining locals.....	207
word lists.....	165
word lists - example.....	169
word lists - why use them?.....	168
word name too long.....	288
WORD buffer size.....	287
WORD , string overflow.....	291
wordlist	166
wordlist-words	167
wordlists	170
wordlists tutorial.....	41
words	57, 167
words used in your program.....	282
words, forgetting.....	243
wordset	58
wrap-xt	132
write-file	175
write-line	175
wrol	67
wror	67
WTF??	245
wvalue:	137
ww	239

X

x	325
x!	83
x,	77
x , stack item type.....	59
x-size	195
x-width	196
x>s	84
x@	83
x\string-	196
xalign	86

xaligned	86
xbe	83
xc!+	196
xc!+?	195
xc,	196
xc-size	195
xc-width	196
xc@	195
xc@+	195
xc@+?	195
xchar+	196
xchar-	196
XCHAR-ENCODING	170
XCHAR-MAXMEM	171
xd!	83
xd,	77
xd>s	84
xd@	83
xdbe	83
xdle	83
xemit	189
xfield:	135
xhold	196
xkey	196
xkey?	191
xle	83
xor	66
xt	44, 145
xt input format.....	56
xt , stack item type.....	59
xt-locate	238
xt-new	221
xt-see	240
xt-see-code	241
xt-simple-see	241
xt>name	147
XT tutorial.....	35
XT:	202
xywh	326
xywhd	326

Y

y	325
----------------	-----

Z

z:	202
zero-length string as a name.....	290
Zsoter's object-oriented model.....	228
zvalue:	137